








CENOVNIK HIKVISION VIDEO INTERFONA - NOVEMBAR 2020

NAZIV	ŠIFRA	OPIS	CENA	
			sa PDV	bez PDV
UNUTRAŠNJE JEDINICE - MONITORI				
DS-KH6210-L				
	4700	7-inch Colorful TFT LCD, Fizički tasteri, Rezolucija Monitora: 800 * 480 LAN: 10/100Mbps Ethernet 2X Alarmni ulaz Pasivni PoE 24V ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Dimenzije: 217 mm × 142 mm × 26 mm	106.80	89.00
HIKVISION				
DS-KH6310				
	4299	7" Touch-Screen Monitor 7-inch Colorful TFT LCD, Rezolucija Monitora: 800 * 480 LAN: 10/100Mbps Ethernet 8X Alarmni ulaz, 1X Relejni izlaz Pasivni PoE 24V ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Uređaj se može prijaviti na besplatan cloud servis Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 217 mm × 142 mm × 26 mm	156.00	130.00
HIKVISION				
DS-KH8300-T				
	4298	7" Touch-Screen Monitor 7-inch Colorful TFT LCD, Rezolucija Monitora: 1024 * 600 LAN: 10/100Mbps Ethernet 8X Alarmni ulaz Power Over Network Cable/ 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 217 mm × 142 mm × 26 mm	208.80	174.00
HIKVISION				
DS-KH6320-TE1				
	5931	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora: 1024 * 600 LAN: 10/100Mbps Ethernet 8X Alarmni ulaz 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm	122.40	102.00
HIKVISION				
DS-KH6320-WTE1				
	5764	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora: 1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm	133.20	111.00
HIKVISION				
DS-KH6320-WTE1				
	6457	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora: 1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm	133.20	111.00
HIKVISION				
DS-KH6320-WTE2				
	6221	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora: 1024 * 600 Dve žice za napajanje i mrežni pristup, 8X Alarmni ulaz 2X Izlaz Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm	133.20	106.00
HIKVISION				

DS-KH8301-WT



5148	7" Touch-Screen Monitor 7-inch Colorful TFT LCD, sa ugrađenom kamerom za pozivanje između jedinica Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet 8X Alarmni ulaz Power Over Network Cable/ 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 217 mm × 142 mm × 26 mm	270.00	225.00
------	--	--------	--------

HIKVISION

DS-KH8350-WTE1



5932	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 180 mm × 140 mm × 22.4 mm	278.40	232.00
------	--	--------	--------

HIKVISION

DS-KH9310-WTE1



6737	Android unutrašnja jedinica 7" Ekran: 7" TFT monitor osetljiv na dodir, rezolucije 1024 × 600 Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikrofoni, zvučnik, 8x alarmni ulaz, 2x alarmni izlaz (releji), 1x tamper, 1x debugging port Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 187 mm × 137 mm × 25.7 mm Težina: 419.3 g	300.00	250.00
------	---	--------	--------

HIKVISION

DS-KH8520-WTE1



5758	10.1" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 254 mm × 166 mm × 14.7 mm	300.00	250.00
------	---	--------	--------

HIKVISION

IP POZIVNE TABLE

DS-KB8113-IM



6736	2 MP Antivandal Spoljašnja jedinica sa jednim pozivom Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektivna 88° (horizontalno) 45° (vertikalno) Interfejsi: RJ45 10M/100M, mikrofoni, zvučnik, 1x alarmni ulaz, 1x relejni, 1x debugging port, uzemljenje Sertifikati zaštite: IP66, IK09 Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm	180.00	150.00
------	--	--------	--------

HIKVISION

DS-KV6113-WPE1



6391	2 MP HD Spoljašnja jedinica sa jednim pozivom Rezolucija kamere: 1080p@30fps ugao objektivna 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integrisan citac kartica Mifare 13.56Mhz Podržava konfigurisanje putem Web interfejsa 4X Alarmni ulaz, 1X relejni NO/NC izlaz, Zastita: IP65 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 161.9mm × 74.1mm × 53.2mm	138.00	115.00
------	--	--------	--------

HIKVISION

DS-KV8102-IP



4297	1.3 MP Spoljašnja jedinica sa jednim pozivom Plastična, Rezolucija kamere: HD720P, 25fps(P), WDR, ugao objektivna 120° LAN: 10M/100M Self-adaptive Ethernet, RS-485, Integrisan citac kartica Mifare 13.56Mhz 4X Alarmni ulaz, 1X relejni NO/NC izlaz, IP65, 12 VDC ili 24V pasivni PoE Dimenzije: 164x97x40.6 mm	144.00	120.00
------	--	--------	--------

HIKVISION

DS-KV8102-IM



4295	1.3 MP Spoljašnja jedinica sa jednim pozivom Aluminijum, Rezolucija kamere: HD720P, 25fps(P), WDR, ugao objektivna 120° 10M/100M Self-adaptive Ethernet, RS-485, integrisan citac kartica Mifare 13.56Mhz 4X alarmni ulaz, 1X relejni NO/NC izlaz, IP65, 12 VDC ili 24V pasivni PoE Dimenzije: 182x100x32.5 mm	193.20	161.00
------	---	--------	--------

HIKVISION

DS-KV8202-IM



4296	1.3 MP Spoljašnja jedinica sa jednim pozivom Aluminum, Rezolucija kamere: HD720P, 25fps(P), WDR, ugao objektivna 120° 10M/100M Self-adaptive Ethernet, RS-485, integrisan citac kartica Mifare 13,56Mhz 4X alarmni ulaz ,1X relejni NO/NC izlaz, IP65, 12 VDC ili 24V pasivni PoE Dimenzije: 182x100x32.5 mm	206.40	172.00
------	--	--------	--------

HIKVISION


DS-KV8402-IM



4523	1.3 MP Spoljašnja jedinica sa jednim pozivom Aluminum, Rezolucija kamere: HD720P, 25fps(P), WDR, ugao objektivna 120° 10M/100M Self-adaptive Ethernet, RS-485, integrisan citac kartica Mifare 13,56Mhz 4X alarmni ulaz ,1X relejni NO/NC izlaz, IP65, 12 VDC ili 24V pasivni PoE Dimenzije: 182x100x32.5 mm	204.00	170.00
------	--	--------	--------

HIKVISION

DS-KV8113-WME1



6430	2 MP HD Spoljašnja jedinica sa jednim pozivom Rezolucija kamere: 1080p@30fps ugao objektivna 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integrisan citac kartica Mifare 13,56Mhz Podržava konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 2X relejni NO/NC izlaz, Zastita: IP65, IK08 Napajanj: 12 VDC ili PoE Potrosnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 174 mm × 91 mm × 29 mm	180.00	150.00
------	--	--------	--------

HIKVISION


DS-KV8213-WME1



6390	2 MP HD Spoljašnja jedinica sa dva pozivna tastera Rezolucija kamere: 1080p@30fps ugao objektivna 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integrisan citac kartica Mifare 13,56Mhz Podržava konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 2X relejni NO/NC izlaz, Zastita: IP65, IK08 Napajanj: 12 VDC ili PoE Potrosnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 174 mm × 91 mm × 29 mm	198.00	165.00
------	---	--------	--------

HIKVISION

DS-KV8413-WME1



6429	2 MP HD Spoljašnja jedinica sa četiri pozivna tastera Rezolucija kamere: 1080p@30fps ugao objektivna 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integrisan citac kartica Mifare 13,56Mhz Podržava konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 2X relejni NO/NC izlaz, Zastita: IP65, IK08 Napajanj: 12 VDC ili PoE Potrosnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 174 mm × 91 mm × 29 mm	210.00	175.00
------	--	--------	--------

HIKVISION

DS-KD8102-V



4293	Pozivna jedinica 3.5" Capacitive Tasteri na dodir 1.3 MP Pozivna jedinica, 3.5-inch TFT LCD, Rezolucije: 480 * 320, Rezolucija Kamere: HD720P, 25fps(P)/30fps(N), LAN: 10M/100M/1000M Self-adaptive Ethernet, Wiegand i RS-485 komunikacija, citac kartica 8X Alarmni Ulaz, 4X Alarmni Izlaz, Led osvetljenje IP65, USB 2.0, 12 VDC Dimenzije: 418 mm × 145 mm × 61 mm	370.80	309.00
------	---	--------	--------

HIKVISION

DS-KD8002-VM



4294	Pozivna jedinica 3.5" Tasteri na pritisak 1.3 MP Pozivna jedinica Aluminijumska kućište 3.5-inch TFT LCD, Rezolucije: 480 * 320 Rezolucija Kamere: HD720P, 25fps(P)/30fps(N) LAN: 10M/100M/1000M Self-adaptive Ethernet Wiegand i RS-485 komunikacija, citac kartica 8X Alarni Ulaz 4X Alarmni Izlaz LED osvetljenje IP65, USB 2.0, 12 VDC Dimenzije: 418 mm × 145 mm × 61 mm	480.00	400.00
------	--	--------	--------

HIKVISION

DS-KB6403-WIP



5628	IP pozivno zvonce koje zove direktno Hik-Connect aplikaciju na telefonu Nije potrebna unutrašnja jedinica. Kamera: High performance CMOS, rezolucije do 2Mpx Ugao kamere: Ultra wide 180° (Horizontalno), 96° (Vertikalno) Dva strima, WDR, Nevidljivo IR svetlo 940 nm. Mreža: Wifi 2.4 Ghz Podržava funkcije: Motion Detection Prostor za SD karticu max 128 GB Ugrađen omnidirekcionni mikrofoni i zvučnik za dvosmernu komunikaciju Zaštita: IP54 Napajanje 12VDC Radna temperatura: -30° C to +50° C Dimenzije: 122.4 mm x 45.9 mm x 28.1 mm	142.80	119.00
------	--	--------	--------

HIKVISION



5257	<p>IP video interfonski kit, sastoji se od pozivne table sa jednim tasterom, monitora i distributera Pozivna jedinica (DS-KV8103-IME2): Kamera: Low Illumination 2 MP HD Colorful 155° Fisheye Camera Rezolucija: 1920 x 1080 Integrisan omnidirekcionni mikrofon Integrisan zvučnik Mrežni interfejs: 10/100 Mbps Self-Adaptive Ethernet Napajanje preko DS-KAD709 (uključen u komplet) Radna temperatura i zaštita: -30° C to +60° C, IP65 Dimenzije: 163 mm x 104 mm x 44 mm Monitor (DS-KHB340-TCE2): 7-Inch Colorful TFT LCD Rezolucija: 1024 x 600 Kapacitivni Touch Screen, Touch Key Funkcije: Interkom, daljinsko otvaranje vrata Napajanje preko DS-KAD709 (uključen u komplet) Montaža na zid, Dimenzije: 196 mm x 133 mm x 25.75 mm Audio/Video distributer (DS-KAD709) Služi za napajanje i kontrolu Monitora i Pozivne table Interfejsi: 1x RJ45 10/100M, 9ch 2 wire interfejsa Napajanje 24VDC</p>	427.20	356.00
------	---	--------	--------

HIKVISION

MODULARNI IP SISTEMI

DS-KD8003-IME1



5759	<p>Glavni pozivni modul sa integrisanom HD kamerom od 2 Mpx - Kamera: 2 MP HD IR - Main Stream: 1920 x 1080 Sub Stream 720 x 480 - Kompresija: H.264 - Ugrađen Omnidirekcionni mikrofon - Ugrađen zvučnik: 85dB do 20 cm - Interfejsi: RJ45 10/100 Mbps - Protokoli: TCP/IP, RTSP - IC za noćni režim - Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave - Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W IP zaštita: IP65, Radna temperatura -40° C - +60° C Dimenzije (Dužina x Širina x Visina): 98mm x 99.8mm x 43.9mm</p>	135.60	113.00
------	---	--------	--------

HIKVISION

DS-KD8003-IME2



6210	<p>Glavni pozivni modul (dve žice) sa integrisanom HD kamerom od 2 Mpx - Kamera: 2 MP HD IR - Main Stream: 1920 x 1080 Sub Stream 720 x 480 - Kompresija: H.264 - Dve žice za napajanje i mrežni pristup. - Ugrađen Omnidirekcionni mikrofon - Ugrađen zvučnik: 85dB do 20 cm - Protokoli: TCP/IP, RTSP - IC za noćni režim - Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave - Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W - Dimenzije (Dužina x Širina x Visina): 98mm x 99.8mm x 43.9mm - IP zaštita: IP65, Radna temperatura -40° C - +60° C</p>	135.60	113.00
------	---	--------	--------

HIKVISION

DS-KD-DIS



6319	<p>Modul sa 3,5" LCD ekranom i 4 fizička dugmeta sa osvetljenjem - Rezolucija ekrana 320 x 480px - Može se dodati do 500 kontakata - Poziva broj i zove unutrašnju stanicu putem tastature - Otključava vrata pomoću PIN koda putem tastature - MCU procesor, skladište memorije 64MB, flash memorija 8MB - Povezivanje modula 2 (1 ulaz i 1 izlaz) - Fizička 4 dugmeta (gore, dole, OK, nazad) - Potrošnja: ≈3 W - Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×34.2mm - IP zaštita: IP65 - Radna temperatura: -20° C - +60° C</p>	106.80	89.00
------	---	--------	-------

HIKVISION

DS-KD-KK



5760	<p>Modul sa 6 pozivnih tastera - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko glavne jedinice DS-KD8003-IME1 - Konekcije modula: 1 Ulaz 1 Izlaz - DIP switch: 8 - Potrošnja: ≈2 W IP zaštita: IP65 - Radna temperatura: -40° C - +60° C Dimenzije (Dužina x Širina x Visina): 98.21mm×100.21mm×33.7mm</p>	48.00	40.00
------	---	-------	-------

HIKVISION

DS-KD-M



5940	<p>Modul sa čitačem Mifare 13.56 Mhz kartica i tagova - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Ugrađen čitač Mifare kartica i tagova na 13.56 Mhz - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≈2 W - IP zaštita: IP65 Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×33.7mm</p>	64.80	54.00
------	---	-------	-------

HIKVISION

DS-KD-KP



5761	<p>Modul sa šifраторom za otvaranje vrata - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Mogućnost otvaranja vrata putom individualne šifre svakog od stanara - Mogućnost pozivanja stanara unošenjem broja stana - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≈2 W IP zaštita: IP65, IK7 Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×34.2mm</p>	104.40	87.00
------	--	--------	-------

HIKVISION

DS-KD-IN



5763	<p>Modul sa indikacijama: poziv, otvorena vrata i, razgovor - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≈2 W IP zaštita: IP65 Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×34.2mm</p>	39.60	33.00
------	--	-------	-------

HIKVISION

DS-KD-BK



5941	Modul za popunjavanje praznog mesta u sistemu - Dimenzije (Dužina x Širina): 98.5mm×100mm	24.00	20.00
------	---	-------	-------

HIKVISION**ANALOGNI VIDEO INTERFONSKI SISTEMI**

DS-KIS202



4821	Komplet analognog video interfona za jednu porodicu koji sadrži pozivnu jedinicu DS-KB2411-IM i video monitor DS-KH2220. Siva boja.	106.80	89.00
------	---	--------	-------

HIKVISION

DS-KIS203



4916	Komplet analognog video interfona za jednu porodicu koji sadrži pozivnu jedinicu DS-KB2421-IM i video monitor DS-KH2220. Siva boja.	126.00	105.00
------	---	--------	--------

HIKVISION

DS-KB2421-IM



5142	Antivandal pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom Rezolucija: 720x576 Fotosenzitivno osvetljenje, domet IR 2m Integrisan mikrofoni i zvučnik Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -) 1x Relejni izlaz Maksimalna potrošnja: 5W Materijal izrade: Zinc Alloy Radna Temperatura: -30° C to +60° C Dimenzije: 145 mm × 49.2 mm × 26.45 mm	73.20	61.00
------	---	-------	-------

HIKVISION

DS-KB2411-IM



4780	Pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom Rezolucija: 720x576 Fotosenzitivno osvetljenje, domet IR 2m Integrisan mikrofoni i zvučnik Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -) 1x Relejni izlaz Maksimalna potrošnja: 3W Materijal izrade: Plastika Radna Temperatura: -30° C to +60° C Dimenzije: 128 mm × 42 mm × 24.8 mm	49.20	41.00
------	---	-------	-------

HIKVISION

DS-KH2220



5123	LCD kolor monitor za analogne Hikvision interfone sisteme Mogućnost dodavanja do 3 monitora u jedan sistem Dijagonala 7", rezolucije 800x480 Integrisan mikrofoni i zvučnik Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -) Maksimalna potrošnja: ≈5 W Radna Temperatura: -10° C to + 55° C Dimenzije: 195.8 mm × 132.8 mm × 18.39 mm	79.20	66.00
------	---	-------	-------

HIKVISION**DODATNA OPREMA**

Mrežni

PoE Audio/Video Distributer

DS-KAD706



6253	Mrežni audio/video distributer za interfone sa dve žice. 1 x 100Mbps port (RJ45) 6 kanala za dvožično povezivanje i napajanje perifernih uređaja i 2kanala za kaskadno povezivanje Taster za reset Namijenjeno za montažu na DIN šinu Napajanje 24V DC Dimenzije: 176 mm × 91 mm × 32 mm	108.00	90.00
------	---	--------	-------

HIKVISION

Mrežni

PoE Audio/Video Distributer

DS-KAD706-S



6211	Mrežni audio/video distributer za interfone sa dve žice. 1 x 100Mbps port (RJ45) 6 kanala za dvožično povezivanje perifernih uređaja Taster za reset Namijenjeno za montažu na DIN šinu Napajanje 24V DC Dimenzije: 176 mm × 91 mm × 32 mm	108.00	90.00
------	--	--------	-------

HIKVISION

ADAPTER
DS-KAW60-2N



6212 Napajanje za distributere DS-KAD706 & DS-KAD706-S.
Izlaz: 24 VDC, 60W
Montaža za din šine.
Dimenzije: 52.5 mm x 90 mm x 54.5 mm
Radna temperatura: -30 °C to 70 °C

46.80 39.00

HIKVISION
DS-KIT801M



6389 Samostalna kontrola pristupa šifrom ili karticom Procesor: 32-bit processor Podržava do 3000 kartica i šifri Mifare kontrola na 13,56Mhz Ulazi: 1x Taster za izlaz, 1x Senzor za vrata Izlazi: 1x Zvonce, 1 Izlaz za bravu Napajanje: 12VDC Radna temperatura: -20°C do 65°C Dimezije: 126.5mm x 94.5mm x 24mm

43.20 36.00

HIKVISION
DS-KIT801M



5629 Samostalna kontrola pristupa šifrom ili karticom Procesor: 32-bit processor Podržava do 3000 kartica i šifri EM Card Ulazi: 1x Taster za izlaz, 1x Senzor za vrata Izlazi: 1x Zvonce, 1 Izlaz za bravu Napajanje: 12VDC Radna temperatura: -20°C do 65°C Dimezije: 126.5mm x 94.5mm x 24mm

43.20 36.00

HIKVISION

Sigurnosni modul DS-K2M060



5147 Sigurnosni modul za zaštitu brave u slučaju namernog presecanja kabla ili razbijanja Ulazni interfejs: Exit dugme, Magnetna brave i Wiegand Izlazni interfejs: Brava, Alarmni izlaz Komunikacija RS-485 Indikatori (Statusne LED lampice) za sve interfejse.

57.60 48.00

HIKVISION

Mrežni PoE Audio/Video
Distributer DS-KAD-606-P



6392 Mrežni PoE video distributer sa adapterom na 24V 8 x 100Mbps ports (6X PoE i 2-chcascading LAN interfaces) Idealno za napajanje unutrašnjih jedinica i spoljnih villa jedinica
Dimenzije: 176 mm x 91 mm x 32 mm

67.20 56.00

HIKVISION

Master Stanica DS-KM8301



4301 Master stanica, odnosno centralna jedinica za komplekse zgrada 7-inch Tuch Screen Rezolucije 1024*600, Podržava slušalicu i hand-free javljanje, Touch tastatura i Mehanički tasteri, Integrisana SIP funkcija Montaža na zid ili sto

763.20 636.00

HIKVISION

MIFARE KARTICA
13.56 Mhz



4153 MIFARE kartica 13.56Mhz

0.84 0.70

RF MIFARE
TAG 13,56 MHz



4591 Plastični tag elegantnog dizajna. Siva boja. Mifare 13.56 MHz

1.08 0.90

ELEKTROPRIHVATNIK

3877	Levi/Desni Elektromagnetni Prikvatnik (Metalna vrata) Sila držanja 4000N. Radna temperatura: -15°C / +40°C Dubina kućišta: 3mm Visina kućišta 9mm Radi na AC/DCAC: 5-12V DC:2-14V	27.00	22.50
------	--	-------	-------

Dozna za montažu

4782	Dozna za montažu unutrašnjih jedinica (monitora) i spoljašnje jedinice DS-KV8102-IP	2.40	2.00
------	---	------	------

HIKVISION**DS-KABV6113-RS**

6542	Nazidna kutija za pozivne jedinice DS-KV6103/6113 Materijal: Plastika Dimenzije: 149.78 mm × 76.59 mm × 48.63 mm	7.20	6.00
------	--	------	------

HIKVISION**DS-KABV8113-RS**

6543	Nazidna kutija za pozivne jedinice KV8113/8213/8413 Materijal: Nerđajući čelik Dimenzije: 188.69 mm × 97 mm × 48.63 mm	12.00	10.00
------	--	-------	-------

HIKVISION**DS-KABD8003-RS1**

6605	Nazidna kutija za pozivne jedinice DS-KD8003-IME1 ili DS-KD8003-IME2. Materijal: Nerđajući čelik Dimenzije: 122 × 116.4 × 58 mm	19.20	16.00
------	---	-------	-------

HIKVISION**DS-KABD8003-RS2**

6604	Nazidna kutija za pozivne jedinice za dva modula DS-KD8003-IME1 ili DS-KD8003-IME2 Materijal: Nerđajući čelik Dimenzije: 224 × 116.4 × 58 mm	24.00	20.00
------	---	-------	-------

HIKVISION**DS-KABD8003-RS3**

6592	Nazidna kutija za pozivne jedinice za 3 modula DS-KD8003-IME1 ili DS-KD8003-IME2 Materijal: Nerđajući čelik Dimenzije: 325.8 × 116.4 × 58 mm	30.00	25.00
------	---	-------	-------

HIKVISION**DS-KAB03-V**

5528	Nazidna kutija za pozivnu jedinicu DS-KV8102-IP Materijal: Nerđajući čelik Dimenzije: 172.3 mm × 100 mm × 71 mm	51.60	43.00
------	---	-------	-------

HIKVISION

DS-KAB10-D



5621 Nazidna kutija za pozivnu jedinicu DS-KD8102-V Materijal: Nerđajući čelik
Dimenzije: 489.6 mm × 171.88 mm × 105.41 mm 72.00 60.00

HIKVISION

DS-KAB01



5627 Nazidna kutija za aluminijumske pozivne jedinice DS-KV8x02-IM Materijal: Nerđajući čelik SUS201
Dimenzije: 212 mm × 115 mm × 80 mm 46.80 39.00

HIKVISION

DS-KAB02



5265 Nazidna kutija za aluminijumske pozivne jedinice DS-KV8x02-IM Materijal: Nerđajući čelik SUS201 Dimenzije: 193 mm × 106 mm × 80 mm 30.00 25.00

HIKVISION

DS-KD-ACW1



5768 Nazidna dozna sa ramom za instalaciju jednog modula - Materijal: Aluminijum
Dimenzije dozne: 117 x 107 × 32.7 mm - Dimenzije rama: 117 x 107 × 4 mm 48.00 40.00

HIKVISION

DS-KD-ACW2



5769 Nazidna dozna sa ramom za instalaciju dva modula - Materijal: Aluminijum
Dimenzije dozne: 219 x 107 × 32.7 mm - Dimenzije rama: 219 x 107 × 4 mm 67.20 56.00

HIKVISION

DS-KD-ACW3



5770 Nazidna dozna sa ramom za instalaciju tri modula - Materijal: Aluminijum
Dimenzije dozne: 320.8 x 107 × 32.7 mm - Dimenzije rama: 320.8 x 107 × 4 mm 112.80 94.00

HIKVISION

DS-KD-ACF1



5765 Uzidna dozna sa ramom za instalaciju jednog modula - Materijal: Aluminijumski ram, dozna plastika - Dimenzije dozne: 134 x 135 × 56 mm - Dimenzije rama: 134 x 124 × 4 mm 32.40 27.00

HIKVISION

DS-KD-ACF2



5766 Uzidna dozna sa ramom za instalaciju dva modula - Materijal: Aluminijumski ram, dozna plastika
Dimenzije dozne: 237 x 134 × 56 mm - Dimenzije rama: 236 x 124 × 4 mm 43.20 36.00

HIKVISION



5767	Uzidna dozna sa ramom za instalaciju tri modula - Materijal: Aluminijumski ram, dozna plastika Dimenzije dozne: 338.8 x 134 x 56 mm - Dimenzije rama: 337.8 x 124 x 4 mm	50.40	42.00
------	---	-------	-------

HIKVISION

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs