

CENOVNIK UNIVIEW VIDEO NADZORA - 08. Mart 2023.



NAZIV	ŠIFRA	OPIS	CENA	
-------	-------	------	------	--

SNIMAČI sa PDV bez PDV

4 KANALNI

XVR301-04G



7061	<p>4-CH Hybrid DVR Podrzan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal) 4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps Podrzan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6) Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF Video kompresija: H.265, H.264 Video/audio ulazi: 4ch BNC, 1ch audio, RCA Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio Ulazno/Izlazni saobraćaj: 24/48 Mbps Smart funkcije: Detekcija pokreta, tampering, video loss detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable Radna temperatura: -10 °C - +55 °C, Dimenzije: 260mm x240mmx 46mm (10.2" x 9.4"x1.8"), 1.1kg</p>	91,20	76,00
------	--	-------	-------



XVR301-04Q



6717	<p>4-CH Hybrid DVR Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava TVI,AHD, CVI,CVBS kamere do 8MP na kanalu 1 Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6) Video kompresija: H.265, H.264 Video/audio ulazi: 4ch BNC, 1ch audio Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio Ulazno/Izlazni saobraćaj: 48/60 Mbps Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk: 1 sata HDD do 6TB kapaciteta Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C - +55 °C, Dimenzije: 260mm x240mmx 46mm</p>	120,00	100,00
------	--	--------	--------



8 KANALNI**XVR301-08G**

uniview
Better Security. Better World.

7286	<p>8-CH Hybrid DVR Podržan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal) 4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps Podržan video ulaz IP kamere: do 4MP (4 IP kamere ili svih 12) Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF Video kompresija: H.265, H.264 Video/audio ulazi: 8ch BNC, 1ch audio, RCA Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio Ulazno/Izlazni saobraćaj: 40/60 Mbps Smart funkcije: Detekcija pokreta, tampering, video loss detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm ×240mm× 46mm (10.2" × 9.4"×1.8"),1.1kg</p>	132,00	110,00
------	---	--------	--------

XVR301-08Q

uniview
Better Security. Better World.

6716	<p>8-CH Hybrid DVR Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava TVI,AHD, CVI,CVBS kamere do 8MP na kanalu 1 i 2 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12) Video kompresija: H.265, H.264 Video/audio ulazi: 8ch BNC, 1ch audio Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio Ulazno/Izlazni saobraćaj: 56/64 Mbps Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk: 1 sata HDD do 6TB kapaciteta Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm ×240mm× 46mm</p>	186,00	155,00
------	--	--------	--------

16 KANALNI**XVR301-16G**

uniview
Better Security. Better World.

110684	<p>16-CH Hybrid DVR Podržan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal) 4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps Podržan video ulaz IP kamere: do 4MP (8 IP kamere ili svih 16) Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF Video kompresija: H.265, H.264 Video/audio ulazi: 16ch BNC, 1ch audio, RCA Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio Ulazno/Izlazni saobraćaj: 56/60 Mbps Smart funkcije: Detekcija pokreta, tampering, video loss detection Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm ×240mm× 46mm (10.2" × 9.4"×1.8")</p>	188,40	157,00
--------	---	--------	--------

XVR302-16Q3

uniview
Better Security. Better World.

8038	<p>16-CH Hybrid DVR Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF Podržava 8MP@15fps na prva 4 kanala Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx. Ulazno/Izlazni saobraćaj: 72/80 Mbps Video kompresija: H.265/H.264 video kompresija, Video/audio ulazi: 16ch BNC, 1ch RCA Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm ×315mm× 53mm, Težina 1.9Kg</p>	330,00	275,00
------	---	--------	--------

ANALOGNE KAMERE

UAC-T112-F28



2MP HD Fixed IR Turret Analog Camera

- 2MP high quality image
- TVI/AHD/CVI/CVBS
- IR-cut filter with auto switch (ICR)
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1004

32,40 27,00

UAC-B112-F28



2MP HD Fixed IR Mini Bullet Analog Camera

- 2MP high quality image
- TVI/AHD/CVI/CVBS
- IR-cut filter with auto switch (ICR)
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1000

32,40 27,00

UAC-T112-F28-W



2MP ColourHunter HD Fixed Turret Analog Camera

- 2MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 full-color imaging
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1006

46,80 39,00

UAC-B112-F28-W



2MP ColourHunter HD Fixed Mini Bullet Analog Camera

- 2MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 full-color imaging
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1001

49,20 41,00

UAC-T115-F28



5MP HD Fixed IR Turret Analog Camera

- 5MP high quality image
- TVI/AHD/CVI/CVBS
- IR-cut filter with auto switch (ICR)
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1005

51,60 43,00

UAC-B115-F28



5MP HD Fixed IR Mini Bullet Analog Camera

- 5MP high quality image
- TVI/AHD/CVI/CVBS
- IR-cut filter with auto switch (ICR)
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1002

52,80 44,00

UAC-T115-F28-W



5MP ColourHunter HD Fixed Turret Analog Camera

- 5MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 full-color imaging
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1007

58,80 49,00

UAC-B115-F28-W



5MP ColourHunter HD Fixed Mini Bullet Analog Camera

- 5MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 full-color imaging
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages

I1003

62,40 52,00

DOME IP KAMERE

IPC322LB-SF28-A



7059

2 MP IR Fiksna Dome Mrežna Kamera

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
 Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm@F2.0
 Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet
 Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP,
 HTTP Mrežni standardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection
 Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI.
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije Φ109 x 81mm težina: 0,35kg
 Kompatibilni nosači i pribor: TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UM06-EIN, TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

89,10

74,25

IPC3612LB-ADF28K



110357

2 MP HD WDR Fiksna Turret Mrežna Kamera

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
 Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm@F2.0
 Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet, Slot za MicroSD, do 128GB, Ugradjen Mikrofon
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
 Mrežni standardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering, Audio detection, human body detection.
 Ostale Karakteristike: 2D/3D DNR, WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI,
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 7W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 118 × 86.4 × 96mm, težina: 0.3kg
 Kompatibilni nosači i pribor: TR-JB03-I-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UP06-IN

90,00

75,00

IPC322LB-AF28WK-G



11008

2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera, WIFI

Rezolucija snimanja: 1080P (1920*1080), Max 20fps
 Čip: 1/2.9", progressive scan, 2.0 megapixel, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm @F2.0
 Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP.
 Mrežni standardi: ONVIF (Profile S, Profile G, Profile T), API, SDK
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering alarm
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (ΦxV): Φ109 x 83mm težina: 0,32kg
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

115,20

96,00

IPC322SB-DF28K-10



7291

2 MP Lighthunter Fiksna Anti Vandal Dome Mrežna Kamera

Rezolucija snimanja: 2MP (1920*1080)@30/25fps
 Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm @F1.6
 Osetljivost: Colour: 0.001Lux (F1.6, AGC ON) 0Lux sa IR, IR-cut filter, WDR:120db, IC domet do 30m
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 256GB, 1x Alarmni ulaz/izlaz,
 1x Audio ulaz/izlaz
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS,
 NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
 Mrežni standardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, tampering alarm, audio detection, Cross Line, Intrusion, Enter Area, Leave Area
 detection, Smart intrusion prevention
 Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (ΦxV): Φ108.7 x 81.1mm težina: 0,42kg
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

171,24

142,70

IPC324LB-SF28-A**11010****4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: ④4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps

Čip: 1/3", progressive scan, 4.0 megapixel, CMOS

Šater: Auto/Manual, 1 ~ 1/1000000s

Optika: 2.8mm @F2.0

Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS

Mrežni standardi: ONVIF (Profile S, Profile T), API, SDK

Kompresija: H.265, H.264,

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI,

Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

114,00 95,00**IPC322ER3-DUVPF28-C****6325****2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 30fps

Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/1000000s

Optika: 2.8mm @F1.6 Osetljivost: Color: 0.001Lux (F1.6, AGC ON) 0Lux with IR, IR-cut filter, WDR: 120db

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Audio Detection, Scene Change Detection, Defocus Detection, People counting, Face detection.

Ostale Karakteristike: Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 4W**

Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm težina: 0,35kg

142,38 118,65**IPC324LE-DSF28K-G****7055****4 MP IR AntiVandal Fiksna Dome Mrežna Kamera**

Rezolucija snimanja: 4MP (2688*1520), Max 30fps

Čip: 1/3", 4.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/1000000s

Osetljivost: 0.0003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering alarm, Cross line, Intrusion detection

Ostale Karakteristike: Digital Defog, 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod 9:16

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5,5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm, težina: 0,35kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

145,86 121,55**IPC3234LR3-VSPZ28-D****5595****4 MP IR Varifokalna Dome Mrežna Kamera**

Rezolucija snimanja: 4MP (2592*1520), Max 20fps;

Čip: 1/3", 4.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/1000000s

Optika: 2.8 ~ 12mm, motorizovani zoom

Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**

Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0,92kg

Kompatibilni nosači i pribor: TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB07/WM04-B-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

180,00 150,00

IPC325ER3-DUVPF28

5857

5 MP IR Fiksna Dome Mrežna Kamera

Rezolucija snimanja: 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF)

Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 - 1/100000s

Optika: 2.8mm @F1.6

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Slot za MicroSD do 256GB, 2x Audio ulaz, 1x Audio izlaz,

1x Alarm ulaz, 1x Alarmni izlaz

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,

UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.

Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.,

Statističke analize: Brojanje ljudi

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna Temperatura: -35°C - 60°C (-40°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ108.5 x 81mm, težina: 0.45kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN,

TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

180,00 150,00

**IPC328LE-ADF28KM-G**

11013

4K Antivandal Fiksna Dome Mrežna kamera

Rezolucija snimanja: 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps

Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 - 1/100000s

Optika: 2.8mm@1.6, Fixed-focal

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofoni, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line - intrusion detection (based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**

Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 83mm (Ø4.3" x 3.3") 0.37kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN,

TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

230,40 192,00

**IPC815SR-DVPPF14**

6451

5 MP Fisheye IP kamera

Čip: Image sensor 1/2.8", progressive scan, 5.0 megapixel, CMOS

Panoramic image: 360 stepeni

Optika: 1.4mm@F2.0

Rezolucija snimanja: 2592x1944 resolution, 30fps

Osetljivost: Colour: 0.01 Lux (F2.0, AGC ON) 0 Lux with IR, WDR 120db

Interfejsi: 1x RJ45, Slot za SD karticu do 256GB, Integriran mikrofoni.

Protokoli: Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS,

NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF

Smart funkcije: Motion detection, Tampering alarm, Heat map

Kompresija: H.265, H.264, MJPEG

IC osvetljenje: Domet IC dioda do 10m,

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna temperatura: -40°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije: Φ125 x 43.7 mm (Φ4.9" x 1.7")

Kompatibilni nosači i pribor: TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

300,00 250,00



BULLET KAMERE**IPC2122LB-SF40-A**

7056

2 MP IR Fiksna Bullet Mrežna Kamera

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
 Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 4.0mm@F2.0
 Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet
 Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP
 Mrežni stadardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection
 Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5,5W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 161 × 63 × 62mm težina: 0,27kg
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

82,80 69,00

**IPC2122LB-ADF40KM-G**

7113

2 MP HD WDR Fiksna Bullet Mrežna Kamera

Rezolucija snimanja: 1080P (1920*1080) 30/25fps,
 Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS,
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 4.0mm@F2.0
 Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP,
 FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP
 Mrežni stadardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering, Audio detection, Cross line, Intrusion
 Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16
 Integrisan mikrofon, Micro SD do 128 GB
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 7W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 165 × 63 × 62mm, 0,39kg
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

104,40 87,00

**IPC2122LB-AF28WK-G**

11009

2 MP IR Fiksna Bullet Mrežna WiFi Kamera

Rezolucija snimanja: 1080P (1920*1080), Max 20fps
 Čip: 1/2.9", progressive scan, 2.0 megapixel, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm @F2.0
 Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS,
 SMTP, SSL/TLS, SNMP.
 Mrežni stadardi: ONVIF (Profile S, Profile G, Profile T), API, SDK
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering alarm
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 172 × 76 × 72mm težina: 0,25kg
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

115,20 96,00

**IPC2124LB-SF28-A**

11011

4 MP Fiksna Bullet Mrežna Kamera

Rezolucija snimanja: ④4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps
 Čip: 1/3", progressive scan, 4.0 megapixel, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm @F2.0
 Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS,
 SMTP, QoS, SSL/TLS
 Mrežni stadardi: ONVIF (Profile S, Profile T), API, SDK
 Kompresija: H.265, H.264,
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI,
 Corridor mod
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 172 × 76 × 72mm težina: 0,25kg
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR -JB06-A-IN

114,00 95,00



IPC2124LR5-DUPF40M-F

4 MP WDR EASYSTAR Fiksna Bullet Mrežna Kamera

Rezolucija snimanja: 4MP (2688*1520)@ 30/25fps
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 - 1/100000s
 Optika: 4mm@F1.6
 Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR
 IC domet: do 50m
 Interfejsi: 10/100M Base-TX Ethernet
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
 Mrežni stadardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering, human body detection.
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI, Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**
 Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 191.3×72.6×70.9mm (7.5"×2.9"×2.8") 0.5kg
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN



110691

136,80 114,00



IPC2124LE-ADF28KM-G



4 MP Mini IR Fiksna Bullet Mrežna Kamera

Rezolucija snimanja: 4MP (2688*1520)@ 30/25fps
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 - 1/100000s
 Optika: 2.8mm@F1.6
 Osetljivost: Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 50m
 Interfejsi: 10/100M Base-TX Ethernet, Micro SD do 256GB
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP
 Mrežni stadardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering detection, Audio detection, Cross line, Intrusion detection
 Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI., Integrisan mikrofoni, Corridor mode 9:16
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**
 Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 190×73×71mm težina: 0,45kg
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN



7178

153,36 127,80



IPC2322LBR3-SPZ28-D



2 MP IR Varifokalna bullet Mrežna Kamera

Rezolucija snimanja: : 1080P (1920*1080), Max 30fps
 Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 - 1/100000s
 Optika: 2.8 - 12mm, motorizovani zoom
 Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet, Slot za MicroSD, do 256GB
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
 Mrežni stadardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.
 Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**
 Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 240.3 × 86.4 × 75.6mm, težina: 1kg
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR -JB06-AIN



5592

165,00 137,50



IPC2324LB-ADZK-G



4 MP HD IR Varifokalna Bullet Mrežna Kamera

Rezolucija snimanja: 4MP (2688*1520)@ 30/25fps
 Čip: 1/2.7", 4.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 - 1/100000s
 Optika: 2.8 - 12mm,
 Osetljivost: Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR on
 IC domet: do 50m
 Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofoni, Reset dugme
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
 Mrežni stadardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection (based on human body detection).
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 8.5W**
 Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (DxŠxV): 206 × 74 × 74mm (8.1" × 2.9" × 2.9"), 0.55kg
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN



7181

210,00 175,00



IPC2325LB-ADZK-G

110425

5 MP HD IR Varifokalna Bullet Mrežna Kamera

Rezolucija snimanja: 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@30/25fps

Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens

Osetljivost: Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection (based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 8.5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 206 × 74 × 74mm (8.1" × 2.9" × 2.9"), 0.55kg

Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

212,40 177,00

**IPC2128LE-ADF28KM-G**

11012

4K Mini Fiksna Bullet Mrežna kamera

Rezolucija snimanja: 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps

Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 4mm@1.6, Fixed-focal

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection (based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 190×73×71mm (7.5"×2.9"×2.8"), 0.45kg

Kompatibilni nosači i pribor: TR-JB05-B-IN, TR-UP06-C-IN, TR-A01-IN

230,40 192,00

**PTZ KAMERE****IPC6312LFW-AX4C-VG**

7655

2 MP Outdoor PTZ kamera sa integrisanom sirenom, dolazi sa nosacem

Rezolucija snimanja: 1080P (1920*1080), Max 30fps

Čip: 1/2.8", progressive scan, 2.0 megapixel, CMOS

Shutter: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom

PTZ komande: 255 preseta, Home pozicija, 16 patrola

Osetljivost: 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 50m i toplo svetlo do 10m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, Reset dugme, Ugradjen mikrofon i zvcnik

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL

Mrežni stadardi: ONVIF (Profile S, Profile G, Profile T), API

PTZ funkcije: Preset patrol, Route patrol (255 preseta)

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Deep Learning, Smart Intrusion Prevention (Cross Line, Enter Area, Leave Area, Intrusion), People counting (Deep Learning), People Flow Counting (Deep Learning), Crowd Density Monitoring

(Deep Learning), Face Capture, Auto Tracking (Deep Learning)

Kamera poseduje integrisanu sirenu od 52db, kao i mikrofon i zvcnik sa mogucnoscu da se izabere jedna od 10

poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno podrucje

(moguće ubaciti jednu poruku na srpskom ili nekom drugom jeziku)

Zaštita: IP66

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE802.3 at), 15W**

Radna Temperatura: -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije: Φ133mm*269.4mm (Φ5.2"x 10.6"), 0.87kg

Kompatibilni nosači i pribor: TR-JB07-D-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN

324,00 270,00



IPC6412LR-X5P



5873	<p>2MP unutrašnja Mini PTZ kamera Rezolucija snimanja: : 2MP (1920*1080), Max 30fps Čip: 1/2.9" progressive scan, 2.0 megapixel, CMOS Šater: Auto/Manual, 1s ~ 1/1000000 s Optika: 2.7-13.5mm, Automatski fokus i motorizovani zoom Osetljivost: Colour: 0.03 lux (F1.2,AGC ON) 0 lux with IR IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL Mrežni stadardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 12W Radna Temperatura: -10°C ~ 50°C (-14°F ~ 122°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 129 × 143 mm, težina: 0,75kg Kompatibilni nosači i pribor: TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN</p>	<p>168,00 140,00</p>
-------------	---	-----------------------------

IPC6322SR-X22P-D



6761	<p>2 MP Speed Dome PTZ kamera sa 22x optičkim zoom-om Rezolucija snimanja: 2MP (1920*1080), Max 30fps Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS, Blenda: F1.5 ~ F3.8 Šater: Auto/Manual, 1 ~ 1/1000000s Optika: 5.2 ~ 114.4mm, AF automatski fokus sa motorizovanim zoom-om Osetljivost: 0.003Lux (F1.5, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db IR domet: do 150 m Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 1x Alarmni ulaz, 1x Alarmni izlaz PTZ komande: Preset Patrol, 1024 preseta, Home pozicija. Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS. Mrežni stadardi: ONVIF (Profile G, Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Cross line, intrusion, object removed, object left behind, master-slave linkage, face detection, people counting, auto tracking Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS Zaštita: IP66 Napajanje: DC 12V±10%, PoE (PSE potreban) Radna Temperatura: -40°C ~ 65°C (-40°F ~ 149°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije: (ΦxV):Φ220 × 369mm, težina: 3,4kg Kompatibilni nosači i pribor: TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-IN, TR-WE45-A-IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP08-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-IN</p>	<p>720,00 600,00</p>
-------------	---	-----------------------------

NVR UREDJAJI

4 KANALNI

NVR301-04S3



7283	<p>4-ch NVR Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p Ulazno/Izlazni saobraćaj: 64/48Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD), Smart Funkcije:Face detection, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg</p>	<p>114,00 95,00</p>
-------------	---	----------------------------

NVR301-04S2



5864	<p>4-ch NVR Rezolucija snimanja: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 40/40 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI/VGA (FULL HD), Smart Funkcije:Detekcija Lica, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0., Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 48V DC, Potrošnja 10W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg</p>	<p>96,00 80,00</p>
-------------	---	---------------------------

NVR301-08S3

7284	<p>8-ch NVR Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 64/48 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0., Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 48V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C – +55 °C, Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg</p>	144,00	120,00
------	--	--------	--------

**NVR301-16S3**

110353	<p>16-ch NVR Rezolucija snimanja: 8MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 64/48 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection Smart Intrusion Prevention (SIP) by Camera 4-ch(supports channel 1-4; Alarm only, no image) Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0., Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 48V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C – +55 °C, Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg</p>	141,60	118,00
--------	--	--------	--------

**NVR301-16E**

6454	<p>16-ch NVR Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 80/80 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking Pretraga snimka po smart funkcijama: Face search, Behavior search Statističke analize: Brojanje ljudi ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 3xUSB 2.0 interfejs, 4x Alarmni ulaz, 1x Alarmni izlaz Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 10TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Radna temperatura: -10 °C – +55 °C, Dimenzije: 260mm×240mm×44mm, Težina 1,12Kg</p>	224,40	187,00
------	---	--------	--------

**NVR302-16S2**

7109	<p>16-ch NVR Rezolucija snimanja: 8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/ D1/ 2CIF/ CIF Ulazno/Izlazni saobraćaj: 160/64 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K) / HD, VGA Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed, Face search, Behavior search Statističke analize: People counting ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura: -10 °C – +55 °C, Dimenzije: 380mm × 315mm × 53mm, Težina 0,98Kg</p>	290,40	242,00
------	---	--------	--------

**NVR302-16E2**

110422	<p>16-ch NVR Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p Ulazno/Izlazni saobraćaj: 320/320 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA Smart Funkcije: Smart intrusion prevention, Face recognition, LPR, People counting, Heatmap Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search Statističke analize: People counting, Vehicle search ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: 2xRJ45 mrežni ulaz, Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0 1 x USB3.0 8x Alarmni ulaz, 2x Alarmni izlaz, RS485, Audio IN, Audio Out Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS Hard disk prostor: 2 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD, Radna temperatura: -10 °C – +55 °C, Dimenzije: 380mm × 315mm × 53mm (15.0" × 12.4" × 2.1"), 1,8kg</p>	336,00	280,00
--------	--	--------	--------



NVR304-32E2

110678

32-ch NVR
 Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p
 Ulazno/Izlazni saobraćaj: 320/320 Mbps
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,
 Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA
 Smart Funkcije: Smart intrusion prevention, Face recognition, LPR, People counting, Heatmap
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search
 Statističke analize: People counting, Vehicle search
 ONVIF conformance: Profile S, Profile G, Profile T
 Dodatni ulazi: 2xRJ45 mrežni ulaz, Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0 1 x USB3.0
 8x Alarmni ulaz, 2x Alarmni izlaz, RS485, Audio IN, Audio Out
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS
 Hard disk prostor: 4 sata HDD do 6TB kapaciteta, podrzava RAID
 Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,
 Radna temperatura: -10 °C – +55 °C,
 Dimenzije: 380mm × 315mm × 53mm (15.0" × 12.4" × 2.1"), 1.8kg

501,60 418,00

**HARD DISKOVI****WD GREEN 320 GB**

Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 500 GB

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 1 TB

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

SEAGATE 1 TB

SEAGATE, 1TB , 7200RPM, SATA III, 32MB

KONTAKT

**HIKVISION WD10PURX-7B
PURPLE 1 TB**

3861 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

85,20 71,00

**HIKVISION WD20PURX-7B
PURPLE 2 TB**

4091 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

116,40 97,00

**HIKVISION WD30PURX-7B
PURPLE 3TB**

3523 Western Digital, 3TB Purple, IntelliPower, SATA III, 64MB

138,00 115,00

**HIKVISION WD40PURX-7B
PURPLE 4 TB**

4195 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB

163,20 136,00

HIKVISION WD60PURX-7B
PURPLE 6 TB



3844 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB

276,00 230,00

HIKVISION WD81PURX-7B
PURPLE 8 TB



6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB

396,00 330,00

DS-UTF64G-H1 SD KARTICA
64GB



3911 Brzina čitanja do 25MB/s.
Brzina upisa do 20MB/s.
Dimenzije: 14.99 mm × 10.92 mm × 1.02 mm

22,80 19,00

Uniview POE SVIČEVI

NSW2010-6T-POE-IN



6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava:
IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode);Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 65W Maksimalna snaga porta: 30W Dimenzije: 160mm x 93mm x 32mm

6232 68,40 57,00

NSW2010-10T-POE-IN



10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava:
IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode);Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 120W Maksimalna snaga porta: 30W Dimenzije: 220mm x 150mm x 44mm Moguća rek montaža 19" , dolazi uz switch

6235 140,40 117,00

NSW2010-16T2GC-POE-IN



16×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode);Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga porta: 250W Dimenzije: 440mm x 207mm x 45mm Moguća rek montaža 19" , dolazi uz switch

6334 336,00 280,00

NSW2020-24T16T16C-PO



24PoE+16P+26C Switch
• 24×100Mbps PoE ports (RJ45) +
1×1000Mbps Gigaethernet ports +
1×1000Mbps Combo ports
• Switching kapacitet: 8.8Gbps
• Performanse prosleđivanja: 6.55Mpps
• Packet Buffer: 4M bit
• Maks. PoE Power: 370W
• Višestruki režimi rada koji zadovoljavaju vaše poslovne potrebe: podrazumevano (normalan režim), VLAN (bezbedni režim), EKSTEND (režim nadzora)
• Podržava port traffic kontrolu
• Podrška za bezbedni režim, svi portovi za downlink mogu da komuniciraju samo sa uplink port
• Udaljenost prenosa do 250m u režimu nadzora
• Podržava optimizaciju bafera
• Potpuno metalno kucište, sigurno i pouzdano
• Dimenzije: 440*244,8*44mm
• Tezina: 2.93KG

110682 510,00 425,00

KUĆIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633	Razvodna kutija za spoljašnju montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00
------	---	------	------

DOZNA ZA KAMERE BA-02



5634	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	2,16	1,80
------	--	------	------

KONEKTORI

BNC NA LEMLJENJE SA ŠRAFOM



3299	BNC konektor muški sa šraфом. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

BNC NA LEMLJENJE



2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,54	0,45
------	--	------	------

BNC KONEKTOR



30020	BNC konektor muški na šraf.	0,50	0,42
-------	-----------------------------	------	------

BNC NA KRIMP RG59



2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,60	0,50
------	---	------	------

BNC MUŠKI- F ŽENSKI



1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,60	0,50
------	--	------	------

BNC NASTAVAK



4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

F KONEKTOR na krimp RG6



2559	F konektor za RG6 kabl. Pakovanje 100 kom.	0,14	0,12
------	---	------	------

F KONEKTOR na krimp RG59



1796	F konektor za RG59 kabl. Pakovanje 100 kom.	0,14	0,12
------	--	------	------

RF METALNI G MUŠKI



4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,35	0,29
------	--	------	------

RCA MUŠKI-F ŽENSKI

4446 RCA muški - F ženski konektor
Pakovanje 100 kom.

0,53 0,44

F NASTAVAK

3300 F nastavak ženski - ženski
Pakovanje 100 kom

0,22 0,18

**F KONEKTOR
KOMPRESIONI RG6 XL**

1625 Profesionalni PPC F konektor za RG6 kabl.
Pakovanje 50 kom.

0,44 0,37

**F KONEKTOR
KOMPRESIONI RG11 XL**

1627 Profesionalni PPC F konektor za RG11 kabl.

2,96 2,47

**F KONEKTOR
KOMPRESIONI RG59 XL**

1624 Profesionalni PPC F konektor za RG59 kabl.
Pakovanje 50 kom.

0,47 0,39

DC KABL-MUŠKI

1387 DC utikač-muški

0,48 0,40

DC KABL-ŽENSKI

5044 DC utikač-ženski

0,48 0,40

DC KONEKTOR MUŠKI

3425 DC konektor Muški

0,83 0,69

DC KONEKTOR ŽENSKI

4197 DC konektor ženski.

0,83 0,69

DC RAZDELNIK 1-4

1388 1 DC utičnica - 4 DC utikača

1,99 1,66

DC RAZDELNIK 1-8












1389 1 DC utičnica - 8 DC utikača

3,97 3,31

CAT7 RJ45

Mrežni konektor RJ45 kategorija 7

0,50 0,42

CAT5 RJ45				
	0067	Mrežni konektor RJ45	0,05	0,04
Telefonski konektor RJ11				
	0068	Telefonski konektor RJ11	0,02	0,02
DODATNA OPREMA				
ŠTAMPAČ P-TOUCH E100				
	4663	Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu	106,56	88,80
MIKROFON LY-501C				
	2584	Audio modul sa izvedenim konektorima. Napajanje 12 V DC	3,97	3,31
MIKROFON LY-502B				
	2583	Audio modul plastični sa trimrom. Napajanje 12 V DC	6,00	5,00
MIKROFON LY-506				
	1937	Audio modul metalni sa trimrom. Napajanje 12 V DC	10,00	8,33
DS-2FP2020				
	5222	Viisoko osetljivi omnidirekcionni mikrofon. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).	36,00	30,00
DH-PFM800-4K (par)				
	3632	One (1) Channel Balun Real-time Transmission over UTP CAT5E/6 Cable Compatible with HDCVI, TVI, AHD, and CVBS Video Formats Transmission Distance at 4K: 200 m (656 ft) External Power Supply not Required	6,90	5,75
06 razvodna kutija 100x100				
	00091	Razvodna kutija 100x100	1,80	1,50
06 razvodna kutija 80x80				
	00092	Razvodna kutija 80x80	1,10	0,92
ALAT ZA KRIMP RG6, RG11, RG59				
	3302	Alat za krimpovanje RG6, RG11, RG59 konektora	48,00	40,00

STRIPER ZA KABLOVE RG59,RG6



3301 Alat za stripovanje RG59,RG6 kablova

20,40 17,00

ALAT KOMPRESIONI
ZA RG59, RG6

1629 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake.

37,92 31,60

ALAT KOMPRESIONI, ZA
RG6,RG11,RG59

3796 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6,RG11,RG59 XL oznake.

54,34 45,28

KLEŠTA ZA KRIMPOVANJE
KOMPLET

5790 Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečićom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)

26,40 22,00

NAPAJANJA

XED-1212S



Ulaz: 90V-264V
Izlaz: 12V , 1A
Snaga: 12W
Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm
Dužina izlaznog kablova: 110cm, 10.5x5,5x2mm konektor

1633 6,00 5,00

XED-2012S



Ulaz: 90V-264V
Izlaz: 12V , 2A
Snaga: 24W
Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm
Dužina izlaznog kablova: 110cm, 10.5x5,5x2mm konektor

1382 7,20 6,00

XED-3013S



Ulaz: 90V-264V
Izlaz: 12V , 3A
Snaga: 36W
Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm
Dužina izlaznog kablova: 110cm, 10.5x5,5x2mm konektor

1383 11,16 9,30

XED-5013S



Ulaz: 100V-240V
Izlaz: 12V , 5A
Snaga: 60W
Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm
Dužina izlaznog kablova: 110cm, 10.5x5,5x2mm konektor

1384 16,20 13,50

XED-6013B



Ulaz: 100V-240V
Izlaz: 12V , 6A
Snaga: 72W
Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm
Dužina izlaznog kablova: 110cm, 10.5x5,5x2mm konektor

3509 20,40 17,00

9-KANALNO NAPAJANJE
XED-10A12VX-9L

Snaga: 120W
Ulaz: 100~240V 50~60Hz
Izlaz: 12V 10A 9 kanala
Dimenzije: 237*213*70mm
Neto težina: 1800g
Napomena: Sadrži AC kabl

5435 79,20 66,00

18-KANALNO NAPAJANJE
XED-15A12VX-18L

Snaga: 180W
Ulaz: 100~240V 50~60Hz
Izlaz: 12V 15A 18 kanala
Dimenzije: 240*218*70mm
Neto težina: 2300g
Napomena: Sadrži AC kabl

5114 91,20 76,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs