

## CENOVNIK UNIVIEW VIDEO NADZORA – 22. Maj 2023.



NAZIV	ŠIFRA	OPIS	CENA	
SNIMAČI			sa PDV	bez PDV
4 KANALNI				

**XVR301-0463**



8037	<p>4-CH Hybrid DVR                      Podržan video ulaz: 5MP @ 20fps ( Prvi kanal 20fps, ostali 12fps ) 5MP @ 12fps, 4MP @ 30fps ( Prvi kanal )                      4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps                      Podržan video ulaz IP kamere: do 4MP ( 2 IP kamere ili svih 6 )                      Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF                      Video kompresija: H.265, H.264                      Video/audio ulazi: 4ch BNC, 1ch audio, RCA                      Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio                      Ulazno/Izlazni saobraćaj: 16/48 Mbps                      Smart funkcije: Detekcija pokreta, video loss detection                      Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs                      Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE                      Hard disk prostor: 1 sata HDD do 8TB kapaciteta                      Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable                      Radna temperatura: -10 °C – +55 °C,                      Dimenzije: 260mm × 226mm × 47mm (10.2" × 8.9" × 1.8"), 1.1kg</p>	87,60	73,00
------	---	-------	-------



**XVR301-04Q**



6717	<p>4-CH Hybrid DVR                      Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF                      Podržava TVI,AHD, CVI,CVBS kamere do 8MP na kanalu 1                      Rezolucija snimanja IP kamera: do 8mp ( 2 IP kamere ili svih 6 )                      Video kompresija: H.265, H.264                      Video/audio ulazi: 4ch BNC, 1ch audio                      Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio                      Ulazno/Izlazni saobraćaj: 48/60 Mbps                      Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection                      Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485                      Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE                      Hard disk: 1 sata HDD do 6TB kapaciteta                      Napajanje 12V DC, Potrošnja 8W bez HDD,                      Radna temperatura: -10 °C – +55 °C,                      Dimenzije: 260mm × 240mm × 46mm</p>	104,40	87,00
------	--	--------	-------



**XVR301-04Q3**

4-CH Hybrid DVR  
 Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF  
 Podržava TVI,AHD, CVI,CVBS  
 Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6)  
 Video kompresija: H.265, H.264  
 Video/audio ulazi: 4ch BNC, 1ch audio  
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio  
 Ulazno/Izlazni saobraćaj: 48/60 Mbps  
 Smart funkcije: Motion detection, video loss detection, audio detection,  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485  
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP  
 Hard disk: 1 sata HDD do 8TB kapaciteta  
 Napajanje 12V DC, Potrošnja 10W bez HDD,  
 Radna temperatura: -10 °C ~ +55 °C,  
 Dimenzije: 260mm ×226mm× 47mm

8036

123,60 103,00



**uniview**  
 Better Security. Better World.

**8 KANALNI****XVR301-08G**

8-CH Hybrid DVR  
 Podržan video ulaz: 5MP@ 20fps ( Prvi kanal 20fps, ostali 12fps) 5MP@ 12fps, 4MP@ 30fps ( Prvi kanal )  
 4MP Lite @ 15fps,1080P @ 30fps, 720P @ 60fps  
 Podržan video ulaz IP kamere: do 4MP (4 IP kamere ili svih 12)  
 Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF  
 Video kompresija: H.265, H.264  
 Video/audio ulazi: 8ch BNC, 1ch audio, RCA  
 Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio  
 Ulazno/Izlazni saobraćaj: 40/60 Mbps  
 Smart funkcije: Detekcija pokreta, tampering, video loss detection  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable  
 Radna temperatura: -10 °C ~ +55 °C,  
 Dimenzije: 260mm ×240mm× 46mm (10.2" × 9.4"×1.8"),1.1kg

7286

132,00 110,00

**uniview**  
 Better Security. Better World.

**XVR301-08Q**

8-CH Hybrid DVR  
 Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF  
 Podržava TVI,AHD, CVI,CVBS kamere do 8MP na kanalu 1 i 2  
 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)  
 Video kompresija: H.265, H.264  
 Video/audio ulazi: 8ch BNC, 1ch audio  
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio  
 Ulazno/Izlazni saobraćaj: 56/64 Mbps  
 Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line  
 detection, audio detection, defocus detection, scene change detection  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk: 1 sata HDD do 6TB kapaciteta  
 Napajanje 12V DC,  
 Potrošnja 8W bez HDD,  
 Radna temperatura: -10 °C ~ +55 °C,  
 Dimenzije: 260mm ×240mm× 46mm

6716

174,00 145,00



**uniview**  
 Better Security. Better World.

**XVR301-08Q3**

8-CH Hybrid DVR  
 Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF  
 Podržava TVI,AHD, CVI,CVBS  
 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)  
 Video kompresija: H.265, H.264  
 Video/audio ulazi: 8ch BNC, 1ch audio  
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio  
 Ulazno/Izlazni saobraćaj: 40/64 Mbps  
 Smart funkcije: Motion detection, video loss detection, audio detection,  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1  
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP  
 Hard disk: 1 sata HDD do 8TB kapaciteta  
 Napajanje 12V DC,  
 Potrošnja 10W bez HDD,  
 Radna temperatura: -10 °C ~ +55 °C,  
 Dimenzije: 260mm ×226mm× 47mm

8029

192,00 160,00



**uniview**  
 Better Security. Better World.

## 16 KANALNI

### XVR301-16G



110684	<p>16-CH Hybrid DVR                  Podrzan video ulaz: 5MP Lite @ 20fps ( Prvi kanal 20fps, ostali 12fps) 5MP Lite @ 12fps, 4MP Lite @ 30fps ( Prvi kanal )                  4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps                  Podrzan video ulaz IP kamere: do 4MP (8 IP kamere ili svih 16)                  Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF                  Video kompresija: H.265, H.264                  Video/audio ulazi: 16ch BNC, 1ch audio, RCA                  Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio                  Ulazno/Izlazni saobraćaj: 56/60 Mbps                  Smart funkcije: Detekcija pokreta, tampering, video loss detection                  Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs                  Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE                  Hard disk prostor: 1 sata HDD do 6TB kapaciteta                  Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable                  Radna temperatura: -10 °C ~ +55 °C,                  Dimenzije: 260mm ×240mm× 46mm (10.2" × 9.4"×1.8")</p>	188,40	157,00
--------	--	--------	--------



### XVR302-16Q3



8038	<p>16-CH Hybrid DVR                  Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF                  Podržava 8MP@15fps na prva 4 kanala                  Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.                  Ulazno/Izlazni saobraćaj: 72/80 Mbps                  Video kompresija: H.265/H.264 video kompresija,                  Video/audio ulazi: 16ch BNC, 1ch RCA                  Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA                  Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection                  Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485                  Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE                  Hard disk prostor: 2 sata HDD do 6TB kapaciteta                  Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,                  Radna temperatura: -10 °C ~ +55 °C,                  Dimenzije: 380mm ×315mm× 53mm, Težina 1.9Kg</p>	306,00	255,00
------	---	--------	--------



## ANALOGNE KAMERE

### UAC-T112-F28



11004	<p><b>2MP HD Fixed IR Turret Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 2MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• IR-cut filter with auto switch (ICR)</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	30,00	25,00
-------	---	-------	-------

### UAC-B112-F28



11000	<p><b>2MP HD Fixed IR Mini Bullet Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 2MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• IR-cut filter with auto switch (ICR)</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	30,00	25,00
-------	--	-------	-------

### UAC-T112-F28-W



11006	<p><b>2MP ColourHunter HD Fixed Turret Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 2MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• Supports white light illumination, 24/7 full-color imaging</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	38,40	32,00
-------	---	-------	-------

### UAC-B112-F28-W



11001	<p><b>2MP ColourHunter HD Fixed Mini Bullet Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 2MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• Supports white light illumination, 24/7 full-color imaging</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	39,60	33,00
-------	--	-------	-------

**UAC-T115-F28**

<b>11005</b>	<p><b>5MP HD Fixed IR Turret Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 5MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• IR-cut filter with auto switch (ICR)</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	<b>46,80</b>	<b>39,00</b>
--------------	---	--------------	--------------

**UAC-B115-F28**

<b>11002</b>	<p><b>5MP HD Fixed IR Mini Bullet Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 5MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• IR-cut filter with auto switch (ICR)</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	<b>46,80</b>	<b>39,00</b>
--------------	--	--------------	--------------

**UAC-T115-F28-W**

<b>11007</b>	<p><b>5MP ColourHunter HD Fixed Turret Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 5MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• Supports white light illumination, 24/7 full-color imaging</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	<b>50,40</b>	<b>42,00</b>
--------------	---	--------------	--------------

**UAC-B115-F28-W**

<b>11003</b>	<p><b>5MP ColourHunter HD Fixed Mini Bullet Analog Camera</b></p> <ul style="list-style-type: none"> <li>• 5MP high quality image</li> <li>• TVI/AHD/CVI/CVBS</li> <li>• Supports white light illumination, 24/7 full-color imaging</li> <li>• Supports 180° horizontal flip, 180° vertical flip</li> <li>• OSD configuration menu, easy to operate</li> <li>• IP67 waterproof and dustproof design, high reliability</li> <li>• OSD configuration menu in 11 languages</li> </ul>	<b>52,80</b>	<b>44,00</b>
--------------	--	--------------	--------------

**DOME IP KAMERE****IPC322LB-SF28-A**

<b>7059</b>	<p><b>2 MP IR Fiksna Dome Mrežna Kamera</b></p> <p>Rezolucija snimanja: 1080P (1920*1080), Max 30fps          Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,          Šater: Auto/Manual, 1 - 1/100000s          Optika: 2.8mm@F2.0          Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter          IC domet: do 30m          Interfejsi: 10/100M Base-TX Ethernet          Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP,          HTTP Mrežni standardi: ONVIF (Profile S, Profile T), API          Kompresija: Ultra 265, H.265, H.264, MJPEG          Smart funkcije: Motion detection          Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI.          Zaštita: IP67, IK10          Napajanje i potrošnja: <b>DC 12V±25%, PoE (IEEE 802.3af), max 5W</b>          Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)          Dimenzije Φ109 x 81mm težina: 0,35kg          Kompatibilni nosači i pribor: TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UM06-EIN, TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN</p>	<b>89,10</b>	<b>74,25</b>
-------------	--	--------------	--------------

**IPC3612LB-ADF28K**

<b>110357</b>	<p><b>2 MP HD WDR Fiksna Turret Mrežna Kamera</b></p> <p>Rezolucija snimanja: 1080P (1920*1080), Max 30fps          Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS          Šater: Auto/Manual, 1 - 1/100000s          Optika: 2.8mm@F2.0          Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter          IC domet: do 30m          Interfejsi: 10/100M Base-TX Ethernet, Slot za microSD, do 128GB, Ugradjen Mikrofon          Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.          Mrežni standardi: ONVIF (Profile S, Profile T), API          Kompresija: Ultra 265, H.265, H.264, MJPEG          Smart funkcije: Motion detection, Tampering, Audio detection, human body detection.          Ostale Karakteristike: 2D/3D DNR, WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI,          Zaštita: IP67          Napajanje i potrošnja: <b>DC 12V±25%, PoE (IEEE 802.3af), max 7W</b>          Radna Temperatura: -30°C - 60°C (-22°F - 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)          Dimenzije (DxŠxV): 118 x 86.4 x 96mm, težina: 0.3kg          Kompatibilni nosači i pribor: TR-JB03-I-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UP06-IN</p>	<b>90,00</b>	<b>75,00</b>
---------------	--	--------------	--------------

IPC322LB-AF28WK-G



11008

**2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera, WIFI**

Rezolucija snimanja: 1080P (1920\*1080), Max 20fps  
 Čip: 1/2.9", progressive scan , 2.0 megapixel, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8mm @F2.0  
 Osetljivost: 0.01Lux ( F2.0, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB  
 Protokoli:IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP.  
 Mrežni stadardi: ONVIF (Profile S, Profile G, Profile T), API, SDK  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection,Tampering alarm  
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR. HLC, BLC, OSD, Privacy mask, ROI  
 Zaštita: IP67, IK10  
 Napajanje i potrošnja: **DC 12V±25%**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (ΦxV): Φ109 x 83mm težina: 0,32kg  
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

90,00 75,00

IPC322SB-DF28K-10



7291

**2 MP Lighthunter Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: 2MP (1920\*1080)@30/25fps  
 Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8mm @F1.6  
 Osetljivost: Colour: 0.001Lux (F1.6, AGC ON)0Lux sa IR, IR-cut filter, WDR:120db, IC domet do 30m  
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 256GB, 1x Alarmni ulaz/izlaz, 1x Audio ulaz/izlaz  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, tampering alarm, audio detection, Cross Line, Intrusion, Enter Area, Leave Area detection, Smart intrusion prevention  
 Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16  
 Zaštita: IP67, IK10  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (ΦxV): Φ108.7 x 81.1mm težina: 0,42kg  
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

168,00 140,00

IPC324LB-SF28-A



11010

**4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: ④4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@25/20fps; 2MP (1920\*1080)@30/25fps  
 Čip: 1/3", progressive scan , 4.0 megapixel, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8mm @F2.0  
 Osetljivost: 0.01Lux ( F2.0, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,QoS,SSL/TLS  
 Mrežni stadardi: ONVIF (Profile S, Profile T),API,SDK  
 Kompresija: H.265, H.264,  
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR. HLC, BLC, OSD, Privacy mask, ROI, Corridor mod  
 Zaštita: IP67, IK10  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg  
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

96,00 80,00

IPC322ER3-DUVPF28-C



6325

**2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: 1080P (1920\*1080), Max 30fps  
 Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8mm @F1.6 Osetljivost: Color: 0.001Lux (F1.6, AGC ON)0Lux with IR, IR-cut filter, WDR: 120db  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 256GB  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection,Tampering alarm, Audio Detection, Scene Change Detection, Defocus Detection, People counting, Face detection.  
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod  
 Zaštita: IP67, IK10  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 4W**  
 Radna Temperatura: -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (ΦxV): Φ109 x 81mm težina: 0,35kg

142,38 118,65

## IPC324LE-DSF28K-G

**4 MP IR AntiVandal Fiksna Dome Mrežna Kamera**

Rezolucija snimanja: 4MP (2688\*1520), Max 30fps

Čip: 1/3", 4.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Osetljivost: 0.0003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP

7055 Mrežni standardi: ONVIF (Profile S, Profile T), API

147,60 123,00

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering alarm, Cross line, Intrusion detection

Ostale Karakteristike: Digital Defog, 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod 9:16

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5,5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm, težina: 0.35kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

## IPC3234LR3-VSPZ28-D

**4 MP IR Varifokalna Dome Mrežna Kamera**

Rezolucija snimanja: 4MP (2592\*1520), Max 20fps;

Čip: 1/3", 4.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8 ~ 12mm, motorizovani zoom

Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

5595 Mrežni standardi: ONVIF (Profile S, Profile T), API

168,00 140,00

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**

Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0.92kg

Kompatibilni nosači i pribor: TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB07/WM04-B-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

## IPC325ER3-DUVPF28

**5 MP IR Fiksna Dome Mrežna Kamera**

Rezolucija snimanja: 5MP (2592\*1944), Max 20fps; 5MP (2592\*1944), Max 25fps (WDR OFF)

Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm @F1.6

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Slot za MicroSD do 256GB, 2x Audio ulaz, 1x Audio izlaz,

1x Alarm ulaz, 1x Alarmni izlaz

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

5857 Mrežni standardi: ONVIF (Profile S, Profile T), API

174,00 145,00

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.

Inteligentne identifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat,

Statističke analize: Brojanje ljudi

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna Temperatura: -35°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ108.5 x 81mm, težina: 0.45kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN



**IPC328LE-ADF28KM-G**

11013

**4K Antivandal Fiksna Dome Mrežna kamera**

Rezolucija snimanja: 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080) @30/25fps

Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm@1.6, Fixed-focal

Osetljivost: 0.005Lux ( F1.6, AGC ON) 0Lux with IR on

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni stadardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line intrusion detection (based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 83mm (Ø4.3" x 3.3") 0.37kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

216,00 180,00

**IPC815SR-DVPPF14**

6451

**5 MP Fisheye IP kamera**

Čip: Image sensor 1/2.8", progressive scan, 5.0 megapixel, CMOS

Panoramic image: 360 stepeni

Optika: 1.4mm@F2.0

Rezolucija snimanja: 2592x1944 resolution, 30fps

Osetljivost: Colour: 0.01 Lux (F2.0, AGC ON) 0 Lux with IR, WDR 120db

Interfejsi: 1x RJ45, Slot za SD karticu do 256GB, Integrisan mikrofon.

Protokoli: Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF

Smart funkcije: Motion detection, Tampering alarm, Heat map

Kompresija: H.265, H.264, MJPEG

IC osvetljenje: Domet IC dioda do 10m,

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna temperatura: -40°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije: Φ125 × 43.7 mm (Φ4.9" × 1.7")

Kompatibilni nosači i pribor: TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

300,00 250,00

**BULLET KAMERE****IPC2122LB-SF40-A**

7056

**2 MP IR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 1080P (1920\*1080), Max 30fps

Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 4.0mm@F2.0

Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP

Mrežni stadardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection

Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5.5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 161 × 63 × 62mm težina: 0,27kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

79,20 66,00

**IPC2122LB-ADF40KM-G**

7113

**2 MP HD WDR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 1080P (1920\*1080) 30/25fps,

Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS,

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 4.0mm@F2.0

Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP,

FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP

Mrežni stadardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross line, Intrusion

Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16

Integrisan mikrofon, Micro SD do 128 GB

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 7W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 165 × 63 × 62mm, 0,39kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

102,00 85,00

## IPC2122LB-AF28WK-G

**2 MP IR Fiksna Bullet Mrežna WIFI Kamera**

Rezolucija snimanja: 1080P (1920\*1080), Max 20fps  
 Čip: 1/2.9", progressive scan , 2.0 megapixel, CMOS  
 Šater: Auto/Manual, 1 ~ 1/1000000s  
 Optika: 2.8mm @F2.0  
 Osetljivost: 0.01Lux ( F2.0, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP.  
 Mrežni stadardi: ONVIF (Profile S, Profile G, Profile T), API, SDK  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering alarm  
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR. HLC, BLC, OSD, Privacy mask, ROI  
 Zaštita: IP67, IK10  
 Napajanje i potrošnja: **DC 12V±25%**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 172 × 76 × 72mm težina: 0,25kg  
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

11009

90,00 75,00

## IPC2124LB-SF28-A

**4 MP Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: ④4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@25/20fps; 2MP (1920\*1080)@30/25fps  
 Čip: 1/3", progressive scan , 4.0 megapixel, CMOS  
 Šater: Auto/Manual, 1 ~ 1/1000000s  
 Optika: 2.8mm @F2.0  
 Osetljivost: 0.01Lux ( F2.0, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API, SDK  
 Kompresija: H.265, H.264,  
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR. HLC, BLC, OSD, Privacy mask, ROI, Corridor mod  
 Zaštita: IP67, IK10  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 172 × 76 × 72mm težina: 0,25kg  
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR -JB06-AIN

11011

96,00 80,00

## IPC2124LR5-DUPF40M-F

**4 MP WDR EASYSTAR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 4MP (2688\*1520)@ 30/25fps  
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/1000000s  
 Optika: 4mm@F1.6  
 Osetljivost: 0.005Lux ( F1.6, AGC ON) 0Lux with IR  
 IC domet: do 50m  
 Interfejsi: 10/100M Base-TX Ethernet  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering, human body detection.  
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,  
 Zaštita: IP67  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 191.3\*72.6\*70.9mm (7.5"\*2.9"\*2.8") 0.5kg  
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

110691

136,80 114,00

## IPC2124LE-ADF28KM-G

**4 MP Mini IR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 4MP (2688\*1520)@ 30/25fps  
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/1000000s  
 Optika: 2.8mm@F1.6  
 Osetljivost: Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 50m  
 Interfejsi: 10/100M Base-TX Ethernet, Micro SD do 256GB  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering detection, Audio detection, Cross line, Intrusion detection  
 Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI., Integrisan mikrofon, Corridor mode 9:16  
 Zaštita: IP67  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 190\*73\*71mm težina: 0,45kg  
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

7178

147,60 123,00



## IPC2322LBR3-SPZ28-D



5592

**2 MP IR Varifokalna bullet Mrežna Kamera**

Rezolucija snimanja: : 1080P (1920\*1080), Max 30fps  
 Čip: 1/2.7", 2.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8 ~ 12mm, motorizovani zoom  
 Osetljivost:0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet, Slot za MicroSD, do 256Gb  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.  
 Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.  
 Zaštita: IP67  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 240,3 × 86,4 × 75,6mm, težina: 1kg  
 Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR-JB06-AIN

150,00 125,00



## IPC2324LB-ADZK-G



7181

**4 MP HD IR Varifokalna Bullet Mrežna Kamera**

Rezolucija snimanja: 4MP (2688\*1520)@ 30/25fps  
 Čip: 1/2.7", 4.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8 - 12mm,  
 Osetljivost: Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR on  
 IC domet: do 50m  
 Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection (based on human body detection).  
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,  
 Zaštita: IP67  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 8.5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 206 × 74 × 74mm (8.1" × 2.9" × 2.9"), 0.55kg  
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

186,00 155,00



## IPC2325LB-ADZK-G



110425

**5 MP HD IR Varifokalna Bullet Mrežna Kamera**

Rezolucija snimanja: 5MP (2880\*1620)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296)@ 30/25fps; 2MP (1920\*1080)@30/25fps  
 Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens  
 Osetljivost: Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR on  
 IC domet: do 50m  
 Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection (based on human body detection).  
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,  
 Zaštita: IP67  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 8.5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 206 × 74 × 74mm (8.1" × 2.9" × 2.9"), 0.55kg  
 Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

212,40 177,00



## IPC2128LE-ADF28KM-G



11012

**4K Mini Fiksna Bullet Mrežna kamera**

Rezolucija snimanja: 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080) @30/25fps  
 Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS  
 Šater: Auto/Manual, 1 ~ 1/100000s  
 Optika: 4mm@1.6, Fixed-focal  
 Osetljivost: 0.005Lux ( F1.6, AGC ON) 0Lux with IR on  
 IC domet: do 50m  
 Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection (based on human body detection).  
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,  
 Zaštita: IP67  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**  
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 190\*73\*71mm (7.5"\*2.9"\*2.8"), 0.45kg  
 Kompatibilni nosači i pribor: TR-JB05-B-IN, TR-UP06-C-IN, TR-A01-IN

211,20 176,00



PTZ KAMERE

IPC6312LFW-AX4C-VG



7655

**2 MP Outdoor PTZ kamera sa integrisanom sirenom, dolazi sa nosacem**

Rezolucija snimanja: 1080P (1920\*1080), Max 30fps  
 Čip: 1/2.8", progressive scan, 2.0 megapixel, CMOS  
 Shutter: Auto/Manual, 1 - 1/100000s  
 Optika: 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom  
 PTZ komande: 255 preseta, Home pozicija, 16 patrola  
 Osetljivost: 0.001Lux ( F1.6, AGC ON) 0Lux with IR on, IR-cut filter  
 IC domet: do 50m i toplo svetlo do 10m  
 Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, Reset dugme, Ugradjen mikrofon i zvcnik  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL  
 Mrežni stadardi: ONVIF(Profile S, Profile G, Profile T), API  
 PTZ funkcije: Preset patrol, Route patrol (256 preseta)  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Motion detection, Tampering, Audio detection, Deep Learning, Smart Intrusion Prevention(Cross Line, Enter Area, Leave Area, Intrusion), People counting ( Deep Learning ), People Flow Counting (Deep Learning), Crowd Density Monitoring  
 (Deep Learning), Face Capture, Auto Tracking (Deep Learning)  
 Kamera poseduje integrisanu sirenu od 52db, kao i mikrofon i zvcnik sa mogucnoscu da se izabere jedna od 10 poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno podrucje (moguće ubaciti jednu poruku na srpskom ili nekom drugom jeziku)  
 Zaštita: IP66  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE802.3 at), 15W**  
 Radna Temperatura: -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije: Φ133mm\*269.4mm (Φ5.2"x 10.6"), 0.87kg  
 Kompatibilni nosači i pribor: TR-JB07-D-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN

324,00 270,00

IPC6412LR-X5P



5873

**2MP unutrašnja Mini PTZ kamera**

Rezolucija snimanja: : 2MP (1920\*1080), Max 30fps  
 Čip: 1/2.9" progressive scan, 2.0 megapixel, CMOS  
 Šater: Auto/Manual, 1 s - 1/100000 s  
 Optika: 2.7-13.5mm, Automatski fokus i motorizovani zoom  
 Osetljivost: Colour: 0.03 lux (F1.2, AGC ON) 0 lux with IR  
 IC domet: do 30m  
 Interfejsi: 10/100M Base-TX Ethernet  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL  
 Mrežni stadardi: ONVIF (Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection  
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 12W**  
 Radna Temperatura: -10°C ~ 50°C (-14°F ~ 122°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije (DxŠxV): 129 × 143 mm, težina: 0,75kg  
 Kompatibilni nosači i pribor: TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN

168,00 140,00

IPC6612SR-X25-VG



6761

2 MP Speed Dome PTZ kamera sa 25x optičkim zoom-om  
 Rezolucija snimanja: 2MP (1920\*1080), Max 30fps  
 Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS, Blenda: F1.5 - F3.0  
 Šater: Auto/Manual, 1 - 1/100000s  
 Optika: 5 - 125mm, AF automatski fokus sa motorizovanim zoom-om  
 Osetljivost: 0.001Lux (F1.5, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db  
 IR domet: do 150 m  
 Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 2x Alarmni ulaz, 1x Alarmni izlaz, 1x RS485  
 PTZ komande: Preset Patrol, 1024 preseta, Home pozicija.  
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.  
 Mrežni stadardi: ONVIF (Profile G, Profile S, Profile T), API  
 Kompresija: Ultra 265, H.265, H.264, MJPEG  
 Smart funkcije: Moution detevtion, audio detection, tampering alarm, Smart intrusion prevention, auto tracking  
 Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS  
 Zaštita: IP66  
 Napajanje: **DC 12V±10%, PoE+ (IEEE802.3at)**  
 Radna Temperatura: -40°C ~ 65°C (-40°F ~ 149°F), Vlažnost: ≤95% RH (ne kondenzujuće)  
 Dimenzije: (ΦxV):Φ220 × 369mm, težina: 3,3kg  
 Kompatibilni nosači i pribor: TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-IN, TR-WE45-A-IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP08-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-IN

720,00 600,00

**NVR UREDJAJI**

**4 KANALNI**

**NVR301-04S3**



7283

4-ch NVR  
 Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p  
 Ulazno/Izlazni saobraćaj: 64/48Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),  
 Smart Funkcije:Face detection, Intrusion detection, Cross line detection, Audio detection  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search  
 Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

108,00 90,00



**NVR301-04S2**



5864

4-ch NVR  
 Rezolucija snimanja: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 Ulazno/Izlazni saobraćaj: 40/40 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: HDMI/VGA (FULL HD),  
 Smart Funkcije:Detekcija Lica, Intrusion detection, Cross line detection, Audio detection  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Pretraga snimka po smart funkcijama: Face search, Behavior search  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 10TB kapaciteta  
 Opšte: Napajanje 48V DC, Potrošnja 10W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

96,00 80,00



**NVR301-08S3**



7284

8-ch NVR  
 Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 Ulazno/Izlazni saobraćaj: 64/48 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije  
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection  
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,  
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 48V DC, Potrošnja 5W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

126,00 105,00



**NVR301-16S3**



110353

16-ch NVR  
 Rezolucija snimanja: 8MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 Ulazno/Izlazni saobraćaj: 64/48 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije  
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection  
 Smart Intrusion Prevention (SIP) by Camera  
 4-ch(supports channel 1-4; Alarm only, no image)  
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,  
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 48V DC, Potrošnja 5W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

141,60 118,00



**NVR301-16E**



6454

16-ch NVR  
 Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 Ulazno/Izlazni saobraćaj: 80/80 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA  
 Smart Funkcije:Detekcija Lica, Intrusion detection, Cross line detection, Audio detection, Defocus  
 detection, Scene change detection, Auto tracking  
 Pretraga snimka po smart funkcijama: Face search, Behavior search  
 Statističke analize: Brojanje ljudi  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: RJ45 mrežni ulaz, 3xUSB 2.0 interfejs, 4x Alarmni ulaz, 1x Alarmni izlaz  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 10TB kapaciteta  
 Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 260mm×240mm×44mm, Težina 1.12Kg

200,40 167,00



**NVR302-16S2**

16-ch NVR  
 Rezolucija snimanja: 8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/ D1/ 2CIF/ CIF  
 Ulazno/Izlazni saobraćaj: 160/64 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: HDMI (4K) / HD, VGA  
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed, Face search, Behavior search  
 Statistické analize: People counting  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0  
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 2 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 380mm × 315mm × 53mm, Težina 0,98Kg



7109

276,00 230,00

**uniview**  
 Better Security. Better World.

**NVR302-16E2**

16-ch NVR  
 Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p  
 Ulazno/Izlazni saobraćaj: 320/320 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA  
 Smart Funkcije: Smart intrusion prevention, Face recognition, LPR, People counting, Heatmap  
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search  
 Statistické analize: People counting, Vehicle search  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: 2xRJ45 mrežni ulaz, Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0 1 x USB3.0  
 8x Alarmni ulaz, 2x Alarmni izlaz, RS485, Audio IN, Audio Out  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS  
 Hard disk prostor: 2 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 380mm × 315mm × 53mm (15.0" × 12.4" × 2.1"), 1,8kg



110422

336,00 280,00

**uniview**  
 Better Security. Better World.

**NVR304-32E2**

32-ch NVR  
 Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p  
 Ulazno/Izlazni saobraćaj: 320/320 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: HDMI (4K), VGA (FULL HD), 1ch RCA  
 Smart Funkcije: Smart intrusion prevention, Face recognition, LPR, People counting, Heatmap  
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search  
 Statistické analize: People counting, Vehicle search  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: 2xRJ45 mrežni ulaz, Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0 1 x USB3.0  
 8x Alarmni ulaz, 2x Alarmni izlaz, RS485, Audio IN, Audio Out  
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS  
 Hard disk prostor: 4 sata HDD do 6TB kapaciteta, podržava RAID  
 Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,  
 Radna temperatura: -10 °C – +55 °C,  
 Dimenzije: 380mm × 315mm × 53mm (15.0" × 12.4" × 2.1"), 1,8kg



110678

501,60 418,00

**uniview**  
 Better Security. Better World.

**HARD DISKOVI****WD GREEN 320 GB**

Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

**WD GREEN 500 GB**

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

**WD GREEN 1 TB**

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

**SEAGATE 1 TB**

SEAGATE, 1TB, 7200RPM, SATA III, 32MB

KONTAKT

HIKVISION WD10PURX-7B  
PURPLE 1 TB



3861 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

82,80 69,00

HIKVISION WD20PURX-7B  
PURPLE 2 TB



4091 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

114,00 95,00

HIKVISION WD30PURX-7B  
PURPLE 3TB



3523 Western Digital, 3TB Purple, IntelliPower, SATA III, 64MB

138,00 115,00

HIKVISION WD40PURX-7B  
PURPLE 4 TB



4195 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB

163,20 136,00

HIKVISION WD60PURX-7B  
PURPLE 6 TB



3844 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB

228,00 190,00

HIKVISION WD81PURX-7B  
PURPLE 8 TB



6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB

396,00 330,00

DS-UTF64G-H1 SD KARTICA  
64GB



3911 Brzina čitanja do 25MB/s.  
Brzina upisa do 20MB/s.  
Dimenzije: 14.99 mm × 10.92 mm × 1.02 mm

22,80 19,00

Uniview POE SVIČEVI

NSW2010-6T-POE-IN



6232 6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava:  
IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):Svi  
portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu  
10Mb/s. 6kV zaštita od prenapona PoE Budžet: 65W Maksimalna snaga porta: 30W Dimenzije: 160mm x 93mm x  
32mm

68,40 57,00

NSW2010-10T-POE-IN



6235 10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava:  
IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):Svi  
portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu  
10Mb/s. VLAN(Secure mode): 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od  
prenapona PoE Budžet: 120W Maksimalna snaga porta: 30W Dimenzije: 220mm x 150mm x 44mm Moguća rek  
montaža 19" , dolazi uz switch

140,40 117,00

## NSW2010-16T2GC-POE-IN



6334	<p>16x100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta                  Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at                  Modovi rada: Default(Normal mode);Svi portovi komuniciraju normalno međusobno                  EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s.                  VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima.                  6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga porta: 250W                  Dimenzije: 440mm x 207mm x 45mm Moguća rek montaža 19" , dolazi uz switch</p>	336,00	280,00
------	---	--------	--------

## NSW2020-24T16T16C-PO



110682	<p>24PoE+16P+26C Switch                  • 24x100Mbps PoE ports (RJ45) +                  1x1000Mbps Gigaethernet ports +                  1x1000Mbps Combo ports                  • Switching kapacitet: 8.8Gbps                  • Performanse prosleđivanja: 6.55Mpps                  • Packet Buffer: 4M bit                  • Maks. PoE Power: 370W                  • Višestruki režimi rada koji zadovoljavaju vaše poslovne potrebe: podrazumevano (normalan režim), VLAN (bezbedni režim), EKSTEND (režim nadzora)                  • Podržava port traffic kontrolu                  • Podrška za bezbedni režim, svi portovi za downlink mogu da komuniciraju samo sa uplink port                  • Udaljenost prenosa do 250m u režimu nadzora                  • Podržava optimizaciju bafera                  • Potpuno metalno kucište, sigurno i pouzdano                  • Dimenzije: 440*244.8*44mm                  • Tezina: 2.93KG</p>	510,00	425,00
--------	---	--------	--------

## KUĆIŠTA I NOSAČI

### DOZNA ZA KAMERE BA-01



5633	Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00
------	--	------	------

### DOZNA ZA KAMERE BA-02



5634	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	2,16	1,80
------	--	------	------

## KONEKTORI

### BNC NA LEMLJENJE SA ŠRAFOM



3299	BNC konektor muški sa šrafom. Pakovanje 100 kom.	0,54	0,45
------	--	------	------

### BNC NA LEMLJENJE



2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

### BNC KONEKTOR



30020	BNC konektor muški na šraf.	0,50	0,42
-------	-----------------------------	------	------



---

**BNC NA KRIMP RG59**

2534 BNC konektor za RG59 kabl na krimp.  
Pakovanje 100 kom.

0,60 0,50

---

**BNC MUŠKI- F ŽENSKI**

1795 BNC konektor muški F ženski.  
Pakovanje 100 kom.

0,60 0,50

---

**BNC NASTAVAK**

4447 BNC konektor. Nastavak ženski-ženski.  
Pakovanje 100 kom.

0,54 0,45

---

**F KONEKTOR na krimp  
RG6**

2559 F konektor za RG6 kabl.  
Pakovanje 100 kom.

0,14 0,12

---

**F KONEKTOR na krimp RG59**

1796 F konektor za RG59 kabl.  
Pakovanje 100 kom.

0,14 0,12

---

**RF METALNI G MUŠKI**

4448 RF metalni G muški (UGAONI) konektor  
Pakovanje 100 kom.

0,35 0,29

---

**RCA MUŠKI-F ŽENSKI**

4446 RCA muški - F ženski konektor  
Pakovanje 100 kom.

0,53 0,44

---

**F NASTAVAK**

3300 F nastavak ženski - ženski  
Pakovanje 100 kom

0,22 0,18

---

**F KONEKTOR  
KOMPRESIONI RG6 XL**

1625 Profesionalni PPC F konektor za RG6 kabl.  
Pakovanje 50 kom.

0,44 0,37

---

**F KONEKTOR  
KOMPRESIONI RG11 XL**

1627 Profesionalni PPC F konektor za RG11 kabl.

2,96 2,47

---

**F KONEKTOR  
KOMPRESIONI RG59 XL**

1624 Profesionalni PPC F konektor za RG59 kabl.  
Pakovanje 50 kom.

0,47 0,39

---

**DC KABL-MUŠKI**

1387 DC utikač-muški

0,48 0,40

---

**DC KABL-ŽENSKI**

5044 DC utikač-ženski

0,48 0,40

---

## DC KONEKTOR MUŠKI



3425 DC konektor Muški

0,83 0,69

## DC KONEKTOR ŽENSKI



4197 DC konektor ženski.

0,83 0,69

## DC RAZDELNIK 1-4



1388 1 DC utičnica - 4 DC utikača

1,99 1,66

## DC RAZDELNIK 1-8



1389 1 DC utičnica - 8 DC utikača

3,97 3,31

## CAT7 RJ45



Mrežni konektor RJ45 kategorija 7

0,50 0,42

## CAT5 RJ45



0067 Mrežni konektor RJ45

0,05 0,04

## Telefonski konektor RJ11



0068 Telefonski konektor RJ11

0,02 0,02

## DODATNA OPREMA

## ŠTAMPAČ P-TOUCH E100



Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija \*dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu

4663

106,56 88,80

## MIKROFON LY-501C

2584 Audio modul sa izvedenim konektorima.  
Napajanje 12 V DC

3,97 3,31

## MIKROFON LY-502B

2583 Audio modul plastični sa trimerom.  
Napajanje 12 V DC

6,00 5,00

## MIKROFON LY-506

1937 Audio modul metalni sa trimerom.  
Napajanje 12 V DC

10,00 8,33

## DS-2FP2020



Viisoko osetljivi omnidirekcionni mikrofon. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).

5222

36,00 30,00

DH-PFM800-4K (par)



3632	<p>One (1) Channel Balun                  Real-time Transmission over UTP CAT5E/6 Cable                  Compatible with HDCVI, TVI, AHD, and CVBS Video Formats                  Transmission Distance at 4K: 200 m (656 ft)                  External Power Supply not Required</p>	6,90	5,75
------	---	------	------

OG razvodna kutija 100x100



00091	Razvodna kutija 100x100	1,80	1,50
-------	-------------------------	------	------

OG razvodna kutija 80x80



00092	Razvodna kutija 80x80	1,10	0,92
-------	-----------------------	------	------

ALAT ZA KRIMP  
 RG6, RG11, RG59



3302	Alat za krimpovanje RG6, RG11, RG59 konektora	48,00	40,00
------	---	-------	-------

STRIPER ZA KABLOVE RG59, RG6



3301	Alat za stripovanje RG59, RG6 kablova	20,40	17,00
------	---------------------------------------	-------	-------

ALAT KOMPRESIONI  
 ZA RG59, RG6



1629	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59, RG6 XL oznake.	37,92	31,60
------	---	-------	-------

ALAT KOMPRESIONI, ZA  
 RG6, RG11, RG59



3796	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6, RG11, RG59 XL oznake.	54,34	45,28
------	---	-------	-------

KLEŠTA ZA KRIMPOVANJE  
 KOMPLET



5790	Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečicom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)	26,40	22,00
------	---	-------	-------

NAPAJANJA

XED-1212S



1633	<p>Ulaz: 90V-264V                  Izlaz: 12V , 1A                  Snaga: 12W                  Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm                  Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor</p>	6,00	5,00
------	---	------	------

XED-2012S



1382	<p>Ulaz: 90V-264V                  Izlaz: 12V , 2A                  Snaga: 24W                  Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm                  Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor</p>	7,20	6,00
------	---	------	------

XED-3013S



1383	<p>Ulaz: 90V-264V                  Izlaz: 12V , 3A                  Snaga: 36W                  Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm                  Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor</p>	11,16	9,30
------	---	-------	------

XED-5013S



1384	<p>Ulaz: 100V-240V                  Izlaz: 12V , 5A                  Snaga: 60W                  Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm                  Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor</p>	16,20	13,50
------	---	-------	-------

XED-6013B		3509	Ulaz: 100V-240V Izlaz: 12V , 6A Snaga: 72W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabl: 110cm, 10.5x5,5x2mm konektor	20,40	17,00
9-KANALNO NAPAJANJE XED-10A12VX-9L		5435	Snaga: 120W Ulaz: 100~240V 50~60Hz Izlaz: 12V 10A 9 kanala Dimenzije: 237*213*70mm Neto težina: 1800g Napomena: Sadrži AC kabl	79,20	66,00
18-KANALNO NAPAJANJE XED-15A12VX-18L		5114	Snaga: 180W Ulaz: 100~240V 50~60Hz Izlaz: 12V 15A 18 kanala Dimenzije: 240*218*70mm Neto težina: 2300g Napomena: Sadrži AC kabl	91,20	76,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite [www.isec.rs](http://www.isec.rs)