

CENOVNIK HIKVISION INTERFONSKIH SISTEMA

INTERFONSKI KOMPLETI

DS-KIS202



4821 Komplet analognog video interfona za jednu porodicu koji sadrži pozivnu jedinicu DS-KB2411-IM i video monitor DS-KH2220. Siva boja

115.2

96

KIS203



4916 Komplet analognog video interfona za jednu porodicu koji sadrži pozivnu jedinicu DS-KB2421-IM i video monitor DS-KH2220. Siva boja.

134.4

112

DS-KIS101-P



2-žični analogni komplet za interfon
Primite video poziv i otključajte ga putem unutrašnje stanice

Spoljna jedinica:

Pozivanje jednim dodirnom na oznaku imena

2MP HD kamera sa WDR podrškom, "belim" osvetljenjem i uglovima horizontalni: 100°,

Vertikalni: 69°, 4 alarmna ulaza, dve žice, tamper, 2 exit dugmeta, 2 kontrole zaključavanja, 2 vratna

kontakta ulaza, napajanje zaključavanja 12V 1A

Sertifikati zaštite IP65, IK7 Radna temperatura -30 ° C do +60 ° C

Dimenzije 150 mm × 82 mm × 23.5 mm , Napajanje 48 VDC, 0.5 A, potrošnja ≤ 12 W

7075

207.6

173

Unutrašnja jedinica:

7" ekran u boji sa rezolucijom 1024 × 600, 6 tastera na dodir

2 žice x 3

Napajanje 48 VDC

Radna temperatura -10 ° C do +50 ° C

Dimenzije 187 mm × 137 mm × 25,4 mm

Potrošnja ≤ 5 W

DS-KB2421-IM



Antivandal pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom

Rezolucija: 720x576

Fotosenzitivno osvetljenje, doomet IR 2m

Integriran mikrofoni i zvučnik

Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -)

5142

1x Relejni izlaz

Maksimalna potrošnja: 5W

85.2

71

Materijal izrade: Zinc Alloy

Radna Temperatura: -30° C to +60° C

Dimenzije: 145 mm × 49.2 mm × 26.45 mm

DS-KB2411-IM



Pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom

Rezolucija: 720x576

Fotosenzitivno osvetljenje, doomet IR 2m

Integriran mikrofoni i zvučnik

Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -)

4780

1x Relejni izlaz

Maksimalna potrošnja: 3W

Materijal izrade: Plastika

Radna Temperatura: -30° C to +60° C

Dimenzije: 128 mm × 42 mm × 24.8 mm

57.6

48

DS-KH2220-S



6965	<p>4 žice analogna unutrašnja stanica Podržava nadgledanje vrata i spoljašnjih analogna kamera Integriran omnidirekcionni mikrofoni sa funkcijom suzbijanja buke i poništavanje eho Integriran zvučnik Podržava reprodukciju snimljenih slika-200 slika Daljinsko otključavanje Napajanje 12 VDC Potrošnja ≤5 W Radna temperatura -10° C do + 55° Dimenzije 195.8 mm × 132.8 mm × 18.39 mm</p>	130.8	109
------	---	-------	-----

UNUTRAŠNJE JEDINICE - MONITORI

DS-KH6320-WTE1



5764	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom		
Crni	<p>Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz ,2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara, Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm</p>	164.4	137
6457	Beli		

DS-KH6320-WTE2



6221	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom		
Crni	<p>Rezolucija Monitora:1024 * 600 Dve žice za napajanje i mrežni pristup. 8X Alarmni ulaz , 2X Izlaz Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara, Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm</p>	164.4	137
6575	Beli		

DS-KH8350-WTE1



5932	7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom		
	<p>Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz , 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara. Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 180 mm × 140 mm × 22.4 mm</p>	310.8	259

DS-KH8520-WTE1



5758	10.1" Unutrašnja Touch screen jedinica sa IPS LCD monitorom		
	<p>Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz , 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara. Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 254 mm × 166 mm × 14.7 mm</p>	368.4	307

DS-KH9310-WTE1



6737	Android unutrašnja jedinica 7"		
	<p>Ekran: 7" TFT monitor osetljiv na dodir, rezolucije 1024 × 600 Interna memorija skladištenja 4 GB Emmc Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikrofoni, zvučnik, 8x alarmni ulaz, 2x alarmni izlaz (releji), 1x tamper, 1x debugging port Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 187 mm × 137 mm × 25.7 mm Težina: 419.3 g</p>	345.6	288

DS-KH9510-WTE1



6780	Android unutrašnja jedinica 10.1"		
	<p>Ekran: 10.1" TFT monitor osetljiv na dodir, rezolucije 1024 × 600 Interna memorija skladištenja 8 GB Emmc Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikrofoni, zvučnik, 8x alarmni ulaz, 2x alarmni izlaz (releji), 1x tamper, 1x debugging port Napajanje: 12 VDC ili PoE Radna Temperatura: -10° C to +50° C Dimenzije: 254 mm × 166 mm × 26.65 mm Težina: 875 g</p>	404.4	337

IP POZIVNE JEDINICE

DS-KB8113-IME1



6736	<p>2 MP Antivandal Spoljašnja jedinica sa jednim pozivom Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektiva 88° (horizontalno) 45° (vertikalno) Interfejsi: RJ45 10M/100M, mikrofoni, zvučnik, 1x alarmin ulaz, 1x relejni, 1x debugging port, uzemljenje Sertifikati zaštite: IP66, IK09 Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm</p>	151.2	126
------	--	-------	-----

DS-KV6113-WPE1



6391	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom Rezolucija kamere: 1080p@30fps ugao objektiva 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integriran citac kartica Mifare 13,56Mhz Podrška konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 1X relejni NO/NC izlaz, Zastita: IP65 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 161.9mm × 74.1mm × 53.2mm</p>	157.2	131
------	---	-------	-----

DS-KV8113-WME1



6430	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom Rezolucija kamere: 1080p@30fps ugao objektiva 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integriran citac kartica Mifare 13,56Mhz Podrška konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 2X relejni NO/NC izlaz, Zastita: IP65, IK08 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 174 mm × 91 mm × 29 mm</p>	208.8	174
------	--	-------	-----

DS-KV8213-WME1



6390	<p>2 MP HD Spoljašnja jedinica sa dva pozivna tastera Rezolucija kamere: 1080p@30fps ugao objektiva 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integriran citac kartica Mifare 13,56Mhz Podrška konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 2X relejni NO/NC izlaz, Zastita: IP65, IK08 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 174 mm × 91 mm × 29 mm</p>	226.8	189
------	---	-------	-----

DS-KV8413-WME1



6429	<p>2 MP HD Spoljašnja jedinica sa četiri pozivna tastera Rezolucija kamere: 1080p@30fps ugao objektiva 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integriran citac kartica Mifare 13,56Mhz Podrška konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 2X relejni NO/NC izlaz, Zastita: IP65, IK08 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 174 mm × 91 mm × 29 mm</p>	243.6	203
------	--	-------	-----

DS-KD8103-E6



7071	<p>2 MP Antivandal Spoljašnja jedinica sa jednim pozivom Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektiva 88° (horizontalno) 45° (vertikalno) Interfejsi: RJ45 10M/100M, mikrofoni, zvučnik, 1x alarmin ulaz, 1x relejni, 1x debugging port, uzemljenje Sertifikati zaštite: IP66, IK09 Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm</p>	340.8	284
------	--	-------	-----

DS-KD8023-E6



7074	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom Rezolucija kamere: 1080p@30fps ugao objekтива 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integriran citac kartica Mifare 13,56Mhz Podrška konfigurisanje putem Web interfejsa 4X Alarmin ulaz,1X relejni NO/NC izlaz, Zastita: IP65 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 161.9mm × 74.1mm × 53.2mm</p>	392.4	327
------	--	-------	-----

DS-KD9203-E6



7126	<p>Pozivna jedinica sa funkcijom prepoznavanja lica i ekranom od 4,3" Sistem: Linux operativni sistem, RAM 1 GB, ROM 4 GB. Ekran: 4,3" rezolucije 800x480. Mreža: 10/100/1000 Mbps, protokoli TCP/IP, RTSP. Kamera: 2 x 2 MP HD (1080p@30fps) sa WDR-om. Ugao posmatranja 120°. Kompresija H.264. Audio: integriran omnidirekcionni mikrofoni i zvučnik sa funkcijom suzbijanja buke i poništavanje odjeka. Kontrola pristupa: Mifare kartica, ulazi/izlazi 4, 2 x RS-485, kontrola vrata, Debugging port. Kapacitet kartice Max. 25.000, kapacitet korisnika Max. 10.000, Kapacitet zapamćenih lica 5.000. Protokoli ISAPI, RTSP, SNMPv1,v2,v3. Otključavanje: prislanjanjem kartice, očitavanjem lica (distanca 2m, brzinom 0.2s), preko klijentovog softvera, preko unutrašnje centrale. Opšte: napajanje 12 VDC, potrošnja ≤ 13 W, radna temperatura -30 °C to +60 °C, radna vlažnost 10% to 90%, težina 0.995kg, IP65 zaštita.</p>	482.4	402
------	---	-------	-----

DS-KB6403-WIP



5628	<p>P pozivno zvonce koje zove direktno Hik-Connect aplikaciju na telefonu Nije potrebna unutrašnja jedinica. Kamera: High performance CMOS, rezolucije do 2Mpx Ugao kamere: Ultra wide 180° (Horizontalno), 96° (Vertikalno) Dva strima, WDR, Nevidljivo IR svetlo 940 nm. Mreža: Wifi 2.4 Ghz Podrška funkcije: Motion Detection Prostor za SD karticu max 128 GB Ugrađen omnidirekcionni mikrofoni i zvučnik za dvosmernu komunikaciju Zaštita: IP54 Napajanje 12VDC Radna temperatura: -30° C to +50° C Dimenzije: 122.4 mm x 45.9 mm x 28.1 mm</p>	114	95
------	--	-----	----

MODULARNI IP SISTEMI

DS-KD8003-IME1



5759	<p>Glavni pozivni modul sa integriranom HD kamerom od 2 Mpx - Kamera: 2 MP HD IR - Main Stream: 1920 × 1080 Sub Stream: 720 × 480 - Kompresija: H.264 - Ugrađen Omnidirekcionni mikrofoni - Ugrađen zvučnik: 85dB do 20 cm - Interfejsi: RJ45 10/100 Mbps - Protokoli: TCP/IP, RTSP - IC za noćni režim - Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave - Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W - Dimenzije (Dužina x Širina x Visina): 98mm × 99.8mm × 43.9mm - IP zaštita: IP65, Radna temperatura -40° C - +60° C</p>	157.2	131
------	---	-------	-----

DS-KD8003-IME2



6210	<p>Glavni pozivni modul (dve žice) sa integriranom HD kamerom od 2 Mpx - Kamera: 2 MP HD IR - Main Stream: 1920 × 1080 Sub Stream: 720 × 480 - Kompresija: H.264 - Dve žice za napajanje i mrežni pristup. - Ugrađen Omnidirekcionni mikrofoni - Ugrađen zvučnik: 85dB do 20 cm - Protokoli: TCP/IP, RTSP - IC za noćni režim - Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave - Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W - Dimenzije (Dužina x Širina x Visina): 98mm × 99.8mm × 43.9mm - IP zaštita: IP65, Radna temperatura -40° C - +60° C</p>	157.2	131
------	---	-------	-----

DS-KD-KK



5760	<p>Modul sa 6 pozivnih tastera</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko glavne jedinice DS-KD8003-IME1 - Konekcije modula: 1 Ulaz 1 Izlaz - DIP switch: 8 - Potrošnja: ≤ 2 W - Dimenzije (Dužina x Širina x Visina): 98,21mm×100,21mm×33,7mm - IP zaštita: IP65 - Radna temperatura: -40° C - +60° C 	51,6	43
------	---	------	----

DS-KD-DIS



6319	<p>Modul sa 3,5" LCD ekranom i 4 fizička dugmeta sa osvetljenjem</p> <ul style="list-style-type: none"> - Rezolucija ekrana 320 × 480px - Može se dodati do 500 kontakata - Poziva broj i zove unutrašnju stanicu putem tastature - Otključava vrata pomoću PIN koda putem tastature - MCU procesor, skladište memorije 64MB, flash memorija 8MB - Povezivanje modula 2 (1 ulaz i 1 izlaz) - Fizička 4 dugmeta (gore, dole, OK, nazad) - Potrošnja: ≤ 3 W - Dimenzije (Dužina x Širina x Visina): 98,5mm×100mm×34,2mm - IP zaštita: IP65 - Radna temperatura: -20° C - +60° C 	114	95
------	--	-----	----

DS-KD-M



5940	<p>Modul sa čitačem Mifare 13,56 Mhz kartica i tagova</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Ugrađen čitač Mifare kartica i tagova na 13,56 Mhz - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤ 2 W - IP zaštita: IP65 - Dimenzije (Dužina x Širina x Visina): 98,5mm×100mm×33,7mm 	68,4	57
------	--	------	----

DS-KD-E



5762	<p>Modul sa čitačem EM kartica i tagova</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤ 2 W - IP zaštita: IP65 - Dimenzije (Dužina x Širina x Visina): 98,5mm×100mm×33,7mm 	68,4	57
------	--	------	----

DS-KD-KP



5761	<p>Modul sa šifраторom za otvaranje vrata</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Mogućnost otvaranja vrata putom individualne šifre svakog od stanara - Mogućnost pozivanja stanara unošenjem broja stana - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤ 2 W - IP zaštita: IP65, IK7 - Dimenzije (Dužina x Širina x Visina): 98,5mm×100mm×34,2mm 	111,6	93
------	--	-------	----

DS-KD-IN



5763	<p>Modul sa indikacijama: poziv, otvorena vrata i, razgovor</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤ 2 W - IP zaštita: IP65 - Dimenzije (Dužina x Širina x Visina): 98,5mm×100mm×34,2mm 	43,2	36
------	--	------	----

DS-KD-BK



5941 Modul za popunjavanje praznog mesta u sistemu
- Dimenzije (Dužina x Širina): 98.5mm×100mm 25.2 21

DODATNA OPREMA ZA DVOIŽIČNE SISTEME

Mrežni PoE

Audio/Video Distributer

DS-KAD706



6253 Mrežni audio/video distributer za interfone sa dve žice.
1 x 100Mbps port (RJ45)
6 kanala za dvožično povezivanje i napajanje perifernih uređaja i 2kanala za kaskadno povezivanje
Taster za reset
Namenjeno za montažu na DIN šinu
Napajanje 24V DC
Dimenzije: 176 mm × 91 mm × 32 mm 126 105

Mrežni

Audio/Video Distributer

DS-KAD706-S



6211 Mrežni audio/video distributer za interfone sa dve žice.
1 x 100Mbps port (RJ45)
6 kanala za dvožično povezivanje perifernih uređaja
Taster za reset
Namenjeno za montažu na DIN šinu
Napajanje 24V DC
Dimenzije: 176 mm × 91 mm × 32 mm 126 105

ADAPTER

DS-KAW60-2N



6212 Napajanje za distributere DS-KAD706 & DS-KAD706-S.
Izlaz: 24 VDC, 60W
Montaža za din šine.
Dimenzije: 52.5 mm × 90 mm × 54.5 mm
Radna temperatura: -30 °C to 70 °C 54 45

DOZNE

DS-KABV6113-RS



6542 Nazidna kutija za pozivne jedinice DS-KV6103/6113
Materijal: Plastika
Dimenzije: 149.78 mm × 76,59 mm × 48,63 mm 8.4 7

DS-KABV8113-RS



6543 Nazidna kutija za pozivne jedinice KV8113/8213/8413
Materijal: Nerđajući čelik
Dimenzije: 188.69 mm × 97 mm × 48.63 mm 14.4 12

DS-KABD8003-RS1



6605	Nazidna kutija za pozivne jedinice DS-KD8003-IME1 ili DS-KD8003-IME2. Materijal: Nerđajući čelik Dimenzije: 122 × 116,4 × 58 mm	22,8	19
------	---	------	----

DS-KABD8003-RS2



6604	Nazidna kutija za pozivne jedinice za dva modula DS-KD8003-IME1 ili DS-KD8003-IME2 Materijal: Nerđajući čelik Dimenzije: 224x 116,4x58 mm	28,8	24
------	--	------	----

DS-KABD8003-RS3



6592	Nazidna kutija za pozivne jedinice za 3 modula DS-KD8003-IME1 ili DS-KD8003-IME2 Materijal: Nerđajući čelik Dimenzije: 325,8 × 116,4 × 58 mm	34,8	29
------	---	------	----

DS-KD-ACW1



5768	Nazidna dozna sa ramom za instalaciju jednog modula - Materijal: Aluminijum - Dimenzije dozne: 117 x 107 × 32,7 mm - Dimenzije rama: 117 x 107 × 4 mm	51,6	43
------	--	------	----

DS-KD-ACW2



5769	Nazidna dozna sa ramom za instalaciju dva modula - Materijal: Aluminijum - Dimenzije dozne: 219 x 107 × 32,7 mm - Dimenzije rama: 219 x 107 × 4 mm	70,8	59
------	---	------	----

DS-KD-ACW3



5770	Nazidna dozna sa ramom za instalaciju tri modula - Materijal: Aluminijum - Dimenzije dozne: 320,8 x 107 × 32,7 mm - Dimenzije rama: 320,8 x 107 × 4 mm	120	100
------	---	-----	-----

DS-KAB10-D



5621 Nazidna kutija za pozivnu jedinicu DS-KD8102-V
Materijal: Nerđajući čelik
Dimenzije: 489.6 mm × 171.88 mm × 105.41 mm

103.2

86

DS-KAB11-D



6703 Nazidna kutija za pozivnu jedinicu DS-KD8102-V
Materijal: Nerđajući čelik

108

90

DS-KD-ACF1



5765 Uzidna dozna sa ramom za instalaciju jednog modula
- Materijal: Aluminijumski ram, dozna plastika
- Dimenzije dozne: 134 x 135 × 56 mm
- Dimenzije rama: 134 x 124 × 4 mm

34.8

29

DS-KD-ACF2



5766 Uzidna dozna sa ramom za instalaciju dva modula
- Materijal: Aluminijumski ram, dozna plastika
- Dimenzije dozne: 237 x 134 × 56 mm
- Dimenzije rama: 236 x 124 × 4 mm

45.6

38

DS-KD-ACF3



5767 Uzidna dozna sa ramom za instalaciju tri modula
- Materijal: Aluminijumski ram, dozna plastika
- Dimenzije dozne: 338.8 x 134 × 56 mm
- Dimenzije rama: 337.8 x 124 × 4 mm

57.6

48

DS-KAB86



4782 Dozna za montažu unutrašnjih jedinica (monitora) i spoljašnje jedinice DS-KV8102-IP

2.4

2

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs