

CENOVNIK HIKVISION INTERFONSKIH SISTEMA

APRIL 2022.

INTERFONSKI KOMPLETI

DS-KIS202



4821	Komplet analognog video interfona za jednu porodicu koji sadrži pozivnu jedinicu DS-KB2411-IM i video monitor DS-KH2220. Siva boja	115,2	96
------	--	-------	----

DS-KIS202T



7195	Komplet analognog video interfona za vilu ili kuću koji sadrži pozivnu jedinicu DS-KB2411T-IM i video monitor DS-KH2220. DS-KB2411T-IM Pozivna jedinica sa jednim tasterom sa pinhole kamerom 1920 x 1080 @ 25 fps DS-KH2220 7" LCD ekran sa fizičkim tasterima rezolucije 800 x 480	171,6	143
------	--	-------	-----

KIS203T



7196	Vodootporan analogni komplet video interfona za vilu ili kuću. Komplet sadrži pozivnu jedinicu DS-KB2421T-IM i video monitor DS-KH2220. DS-KB2421T-IM Vodootporna pozivna jedinica sa pinhole kamerom 1920 x 1080 @ 25 fps DS-KH2220 7" LCD ekran sa fizičkim tasterima rezolucije 800 x 480	192	160
------	--	-----	-----

DS-KIS101-P



7075	<p>2-žični analogni komplet za interfon Primate video poziv i otključajte ga putem unutrašnje stanice</p> <p>Spoljna jedinica: Pozivanje jednim dodirom na oznaku imena 2MP HD kamera sa WDR podrškom, "belim" osvetljenjem i uglovima horizontalni: 100°, Vertikalni: 69°, 4 alarmna ulaza, dve žice, tamper, 2 exit dugmeta, 2 kontrole zaključavanja, 2 vratna kontakta ulaza, napajanje zaključavanja 12V 1A Sertifikati zaštite IP65, IK7 Radna temperatura -30 ° C do +60 ° C Dimenzije 150 mm × 82 mm × 23,5 mm , Napajanje 48 VDC, 0,5 A, potrošnja ≤ 12 W</p> <p>Unutrašnja jedinica: 7" ekran u boji sa rezolucijom 1024 × 600, 6 tastera na dodir 2 žice x 3 Napajanje 48 VDC Radna temperatura -10 ° C do +50 ° C Dimenzije 187 mm × 137 mm × 25,4 mm Potrošnja ≤ 5 W</p>	258	215
------	---	-----	-----

DS-KB2421-IM



5142	<p>Antivandal pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom Rezolucija: 720x576 Fotosenzitivno osvetljenje, doomet IR 2m Integrisan mikrofoni i zvučnik Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -) 1x Relejni izlaz Maksimalna potrošnja: 5W</p> <p>Materijal izrade: Zinc Alloy Radna Temperatura: -30° C to +60° C Dimenzije: 145 mm × 49,2 mm × 26,45 mm</p>	97,2	81
------	--	------	----

DS-KB2411-IM



4780	<p>Pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom Rezolucija: 720x576 Fotosenzitivno osvetljenje, doomet IR 2m Integrisan mikroskop i zvučnik Ožičenje od četiri žice (Video ulaz, Audio in/out, +, -) 1x Relejni izlaz Maksimalna potrošnja: 3W Materijal izrade: Plastika Radna Temperatura: -30° C to +60° C Dimenzije: 128 mm × 42 mm × 24.8 mm</p>	64,8	54
------	--	------	----

DS-KH2220-S



6965	<p>4 Žice analogna unutrašnja stanica Podržava nadgledanje vrata i spoljašnjih analogna kamera Integrisan omnidirekcionni mikroskop sa funkcijom suzbijanja buke i poništavanje eho Integrisan zvučnik Podržava reprodukciju snimljenih slika-200 slika Daljinsko otključavanje Napajanje 12 VDC Potrošnja ≤5 W Radna temperatura -10° C do + 55° Dimenzije 195.8 mm × 132.8 mm × 18.39 mm</p>	153,6	128
------	---	-------	-----

UNUTRAŠNJE JEDINICE – MONITORI

DS-KH6320-WTE1



5764 Crni	<p>7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz ,2X Izlaz Napajanje: Standard PoE ili 12 VDC</p>	205,2	171
6457 Beli	<p>Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara, Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm</p>		

DS-KH6320-WTE2



6221 Crni	<p>7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora:1024 * 600 Dve žice za napajanje i mrežni pristup. 8X Alarmni ulaz , 2X Izlaz Mogućnost dodavanja IP kamera sa mreže</p>	205,2	171
6575 Beli	<p>Pozivanje između monitora, odnosno stanara, Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 200 mm × 140 mm × 15.1 mm</p>		

DS-KH8350-WTE1



5932	<p>7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz , 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara. Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 180 mm × 140 mm × 22.4 mm</p>	363,6	303
------	---	-------	-----

DS-KH8520-WTE1



5758	<p>10.1" Unutrašnja Touch screen jedinica sa IPS LCD monitorom Rezolucija Monitora:1024 * 600 LAN: 10/100Mbps Ethernet / WiFi 8X Alarmni ulaz , 2X Izlaz Napajanje: Standard PoE ili 12 VDC Mogućnost dodavanja IP kamera sa mreže Pozivanje između monitora, odnosno stanara. Screenshot funkcija Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice Dimenzije: 254 mm × 166 mm × 14.7 mm</p>	430,8	359
------	--	-------	-----

DS-KH9310-WTE1



6737	<p>Android unutrašnja jedinica 7" Ekran: 7" TFT monitor osetljiv na dodir, rezolucije 1024 × 600 Interna memorija skladištenja 4 GB Emmc Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikroskop, zvučnik, 8x alarmin ulaz, 2x alarmni izlaz (relej), 1x tamper, 1x debugging port Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 187 mm × 137 mm × 25.7 mm Težina: 419.3 g</p>	436,8	364
------	--	-------	-----

DS-KH9510-WTE1



6780	<p>Android unutrašnja jedinica 10.1"</p> <p>Ekran: 10.1" TFT monitor osetljiv na dodir, rezolucije 1024 × 600</p> <p>Interna memorija skladištenja 8 GB Emmc</p> <p>Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikrofon, zvučnik, 8x alarmin ulaz, 2x alarmni izlaz (releji), 1x tamper, 1x debugging port</p> <p>Napajanje: 12 VDC ili PoE</p> <p>Radna Temperatura: -10° C to +50° C</p> <p>Dimenzije: 254 mm × 166 mm × 26.65 mm</p> <p>Težina: 875 g</p>	510	425
------	---	-----	-----

IP POZIVNE JEDINICE

DS-KB8113-IME1



6736	<p>2 MP Antivandal Spoljašnja jedinica sa jednim pozivom</p> <p>Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektivna 88° (horizontalno) 45° (vertikalno)</p> <p>Interfejsi: RJ45 10M/100M, mikrofon, zvučnik, 1x alarmin ulaz, 1x relejni, 1x debugging port, uzemljenje</p> <p>Sertifikati zaštite: IP66, IK09</p> <p>Napajanje: 12 VDC ili PoE</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm</p>	174	145
------	--	-----	-----

DS-KV6113-WPE1



6391	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 1X relejni NO/NC izlaz,</p> <p>Zastita: IP65</p> <p>Napajanje: 12 VDC ili PoE Potrošnja: <10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 161.9mm × 74.1mm × 53.2mm</p>	183,6	153
------	--	-------	-----

DS-KV8113-WME1



6430	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 2X relejni NO/NC izlaz,</p> <p>Zastita: IP65, IK08</p> <p>Napajanje: 12 VDC ili PoE Potrošnja: <10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 174 mm × 91 mm × 29 mm</p>	243,6	203
------	---	-------	-----

DS-KV8213-WME1



6390	<p>2 MP HD Spoljašnja jedinica sa dva pozivna tastera</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 2X relejni NO/NC izlaz,</p> <p>Zastita: IP65, IK08</p> <p>Napajanje: 12 VDC ili PoE Potrošnja: <10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 174 mm × 91 mm × 29 mm</p>	264	220
------	--	-----	-----

DS-KV8413-WME1



6429	<p>2 MP HD Spoljašnja jedinica sa četiri pozivna tastera</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 2X relejni NO/NC izlaz,</p> <p>Zastita: IP65, IK08</p> <p>Napajanje: 12 VDC ili PoE Potrošnja: <10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 174 mm × 91 mm × 29 mm</p>	284,4	237
------	---	-------	-----

DS-KD8103-E6



7071	<p>2 MP Antivandal Spoljašnja jedinica sa jednim pozivom Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektivna 88° (horizontalno) 45° (vertikalno) Interfejsi: RJ45 10M/100M, mikrofon, zvučnik, 1x alarmin ulaz, 1x relejni, 1x debugging port, uzemljenje Sertifikati zaštite: IP66, IK09 Napajanje: 12 VDC ili PoE Radna Temperatura: -30° C to +50° C Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm</p>	398,4	332
------	--	-------	-----

DS-KD8023-E6



7074	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom Rezolucija kamere: 1080p@30fps ugao objektivna 129° (horizontalno) 75° (vertikalno) True WDR, DNR, BLC LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi Integrisan citac kartica Mifare 13,56Mhz Podrška konfigurisanje putem Web interfejsa 4X Alarmin ulaz, 1X relejni NO/NC izlaz, Zastita: IP65 Napajanje: 12 VDC ili PoE Potrošnja: <10W Radna Temperatura: -30° C to +50° C Dimenzije: 161.9mm × 74.1mm × 53.2mm</p>	464,4	387
------	--	-------	-----

DS-KD9203-E6



7126	<p>Pozivna jedinica sa funkcijom prepoznavanja lica i ekranom od 4,3" Sistem: Linux operativni sistem, RAM 1 GB, ROM 4 GB. Ekran: 4.3" rezolucije 800x480. Mreža: 10/100/1000 Mbps, protokoli TCP/IP, RTSP. Kamera: 2 x 2 MP HD (1080p@30fps) sa WDR-om. Ugao posmatranja 120°. Kompresija H.264. Audio: integrisan omnidirekcionni mikrofon i zvučnik sa funkcijom suzbijanja buke i poništavanje odjeka. Kontrola pristupa: Mifare kartica, ulazi/izlazi 4, 2 x RS-485, kontrola vrata, Debugging port. Kapacitet kartice Max. 25.000, kapacitet korisnika Max. 10.000, Kapacitet zapamćenih lica 5.000. Protokoli ISAPI, RTSP, SNMPv1,v2,v3. Otključavanje: prisanjanjem kartice, očitavanjem lica (distanca 2m, brzinom 0.2s), preko klijentovog softvera, preko unutrašnje centrale. Opšte: napajanje 12 VDC, potrošnja ≤ 13 W, radna temperatura -30 °C to +60 °C, radna vlažnost 10% to 90%, težina 0,995kg, IP65 zaštita.</p>	553,2	461
------	---	-------	-----

IP STANICA DS-KM9503



7271	<p>10 -inčna Android IP stanica na dodir. Video interfon i funkcije kontrole pristupa. 10,1-inčni IPS ekran osetljiv na dodir sa rezolucijom: 1280 × 800. Na uređaj se može dodati do 128 mrežnih kamera. Ugrađeni SIP privatni server, može se dodati do 10000 video interfon uređaja. 2 mrežna ulaza 10/100/1000 M, 2 alarmna ulaza, HDMI, RS-485, 3 USB, podržava SD kartice do 128GB, 2 relejna izlaza. Video parametri: rezolucija 2 MP, video kompresija H.264 Podrška više od 2 zvučnika i mikrofona: Povezuje se sa spoljnim slušalicama (3,5 mm). Spoljni mikrofonom sa dužim vratom. Napajanje: standardni PoE i 12 VDC</p>	1167,6	973
------	--	--------	-----

DS-KB6403-WIP



5628	<p>P pozivno zvonce koje zove direktno Hik-Connect aplikaciju na telefonu Nije potrebna unutrašnja jedinica. Kamera: High performance CMOS, rezolucije do 2Mpx Ugao kamere: Ultra wide 180° (Horizontalno), 96° (Vertikalno) Dva strima, WDR, Nevidljivo IR svetlo 940 nm. Mreža: Wifi 2.4 Ghz Podrška funkcije: Motion Detection Prostor za SD karticu max 128 GB Ugrađen omnidirekcionni mikrofon i zvučnik za dvosmernu komunikaciju Zaštita: IP54 Napajanje 12VDC Radna temperatura: -30° C to +50° C Dimenzije: 122.4 mm x 45.9 mm x 28.1 mm</p>	114	95
------	---	-----	----

MODULARNI IP SISTEMI

DS-KD8003-IME1




5759	<p>Glavni pozivni modul sa integrisanom HD kamerom od 2 Mpx</p> <ul style="list-style-type: none"> - Kamera: 2 MP HD IR - Main Stream: 1920 × 1080 Sub Stream: 720 × 480 - Kompresija: H.264 - Ugrađen Omnidirekcionni mikrofoni - Ugrađen zvučnik: 85dB do 20 cm - Interfejsi: RJ45 10/100 Mbps - Protokoli: TCP/IP, RTSP - IC za noćni režim - Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave - Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W - Dimenzije (Dužina x Širina x Visina): 98mm × 99.8mm × 43.9mm - IP zaštita: IP65, Radna temperatura -40° C - +60° C 	183,6	153
------	--	-------	-----

DS-KD8003-IME2



6210	<p>Glavni pozivni modul (dve žice) sa integrisanom HD kamerom od 2 Mpx</p> <ul style="list-style-type: none"> - Kamera: 2 MP HD IR - Main Stream: 1920 × 1080 Sub Stream: 720 × 480 - Kompresija: H.264 - Dve žice za napajanje i mrežni pristup. - Ugrađen Omnidirekcionni mikrofoni - Ugrađen zvučnik: 85dB do 20 cm - Protokoli: TCP/IP, RTSP - IC za noćni režim - Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave - Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W - Dimenzije (Dužina x Širina x Visina): 98mm × 99.8mm × 43.9mm - IP zaštita: IP65, Radna temperatura -40° C - +60° C 	183,6	153
------	--	-------	-----

DS-KD-KK



5760	<p>Modul sa 6 pozivnih tastera</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko glavne jedinice DS-KD8003-IME1 - Konekcije modula: 1 Ulaz 1 Izlaz - DIP switch: 8 - Potrošnja: ≤2 W - Dimenzije (Dužina x Širina x Visina): 98.21mm×100.21mm×33.7mm - IP zaštita: IP65 - Radna temperatura: -40° C - +60° C 	60	50
------	--	----	----

DS-KD-DIS



6319	<p>Modul sa 3,5" LCD ekranom i 4 fizička dugmeta sa osvetljenjem</p> <ul style="list-style-type: none"> - Rezolucija ekrana 320 × 480px - Može se dodati do 500 kontakata - Poziva broj i zove unutrašnju stanicu putem tastature - Otključava vrata pomoću PIN koda putem tastature - MCU procesor, skladište memorije 64MB, flash memorija 8MB - Povezivanje modula 2 (1 ulaz i 1 izlaz) - Fizička 4 dugmeta (gore, dole, OK, nazad) - Potrošnja: ≤3 W - Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×34.2mm - IP zaštita: IP65 - Radna temperatura: -20° C - +60° C 	133,2	111
------	---	-------	-----

DS-KD-M



5940	<p>Modul sa čitačem Mifare 13,56 Mhz kartica i tagova</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Ugrađen čitač Mifare kartica i tagova na 13,56 Mhz - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤2 W - IP zaštita: IP65 - Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×33.7mm 	80,4	67
------	---	------	----

DS-KD-E



5762	<p>Modul sa čitačem EM kartica i tagova</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤2 W - IP zaštita: IP65 - Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×33.7mm 	80,4	67
------	---	------	----

DS-KD-KP



5761	<p>Modul sa šifratorem za otvaranje vrata</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Mogućnost otvaranja vrata putom individualne šifre svakog od stanara - Mogućnost pozivanja stanara unošenjem broja stana - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤2 W - IP zaštita: IP65, IK7 - Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×34.2mm 	129,6	108
------	---	-------	-----

DS-KD-IN



5763	<p>Modul sa indikacijama: poziv, otvorena vrata i, razgovor</p> <ul style="list-style-type: none"> - Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu - Napaja se preko modula koji je iznad njega - DIP switch: 8 - Potrošnja: ≤2 W - IP zaštita: IP65 - Dimenzije (Dužina x Širina x Visina): 98.5mm×100mm×34.2mm 	50,4	42
------	---	------	----

DS-KD-BK



5941	<p>Modul za popunjavanje praznog mesta u sistemu</p> <ul style="list-style-type: none"> - Dimenzije (Dužina x Širina): 98.5mm×100mm 	30	25
------	--	----	----

DODATNA OPREMA ZA DVOŽIČNE SISTEME

Mrežni PoE

Audio/Video Distributer
DS-KAD706

6253	<p>Mrežni audio/video distributer za interfone sa dve žice.</p> <ul style="list-style-type: none"> 1 x 100Mbps port (RJ45) 6 kanala za dvožično povezivanje i napajanje perifernih uređaja i 2kanala za kaskadno povezivanje Taster za reset Namenjeno za montažu na DIN šinu Napajanje 24V DC Dimenzije: 176 mm × 91 mm × 32 mm 	146,4	122
------	--	-------	-----

Mrežni

Audio/Video Distributer
DS-KAD706-S

6211	<p>Mrežni audio/video distributer za interfone sa dve žice.</p> <ul style="list-style-type: none"> 1 x 100Mbps port (RJ45) 6 kanala za dvožično povezivanje perifernih uređaja Taster za reset Namenjeno za montažu na DIN šinu Napajanje 24V DC Dimenzije: 176 mm × 91 mm × 32 mm 	146,4	122
------	--	-------	-----

ADAPTER

DS-KAW60-2N



6212	<p>Napajanje za distributere DS-KAD706 & DS-KAD706-S.</p> <ul style="list-style-type: none"> Izlaz: 24 VDC, 60W Montaža za din šine. Dimenzije: 52.5 mm × 90 mm × 54.5 mm Radna temperatura: -30 °C to 70 °C 	63,6	53
------	--	------	----

DOZNE

DS-KABV6113-RS



6542 Nazidna kutija za pozivne jedinice DS-KV6103/6113
Materijal: Plastika
Dimenzije: 149,78 mm × 76,59 mm × 48,63 mm

9,6

8

DS-KABV8113-RS



6543 Nazidna kutija za pozivne jedinice KV8113/8213/8413
Materijal: Nerđajući čelik
Dimenzije: 188,69 mm × 97 mm × 48,63 mm

16,8

14

DS-KABD8003-RS1



6605 Nazidna kutija za pozivne jedinice DS-KD8003-IME1 ili DS-KD8003-IME2.
Materijal: Nerđajući čelik
Dimenzije: 122 × 116,4 × 58 mm

26,4

22

DS-KABD8003-RS2



6604 Nazidna kutija za pozivne jedinice za dva modula
DS-KD8003-IME1 ili DS-KD8003-IME2
Materijal: Nerđajući čelik
Dimenzije: 224 × 116,4 × 58 mm

33,6

28

DS-KABD8003-RS3



6592 Nazidna kutija za pozivne jedinice za 3 modula
DS-KD8003-IME1 ili DS-KD8003-IME2
Materijal: Nerđajući čelik
Dimenzije: 325,8 × 116,4 × 58 mm

39,6

33

DS-KD-ACW1



5768 Nazidna dozna sa ramom za instalaciju jednog modula
- Materijal: Aluminijum
- Dimenzije dozne: 117 x 107 × 32,7 mm
- Dimenzije rama: 117 x 107 × 4 mm

60

50

DS-KD-ACW2



5769	<p>Nazidna dozna sa ramom za instalaciju dva modula</p> <ul style="list-style-type: none"> - Materijal: Aluminijum - Dimenzije dozne: 219 x 107 x 32.7 mm - Dimenzije rama: 219 x 107 x 4 mm 	84	70
------	---	----	----

DS-KD-ACW3



5770	<p>Nazidna dozna sa ramom za instalaciju tri modula</p> <ul style="list-style-type: none"> - Materijal: Aluminijum - Dimenzije dozne: 320.8 x 107 x 32.7 mm - Dimenzije rama: 320.8 x 107 x 4 mm 	140,4	117
------	---	-------	-----

DS-KAB10-D



5621	<p>Nazidna kutija za pozivnu jedinicu DS-KD8102-V</p> <p>Materijal: Nerđajući čelik</p> <p>Dimenzije: 489.6 mm x 171.88 mm x 105.41 mm</p>	120	100
------	--	-----	-----

DS-KAB11-D




6703	<p>Nazidna kutija za pozivnu jedinicu DS-KD8102-V</p> <p>Materijal: Nerđajući čelik</p>	127,2	106
------	---	-------	-----

DS-KD-ACF1



5765	<p>Uzidna dozna sa ramom za instalaciju jednog modula</p> <ul style="list-style-type: none"> - Materijal: Aluminijumski ram, dozna plastika - Dimenzije dozne: 134 x 135 x 56 mm - Dimenzije rama: 134 x 124 x 4 mm 	39,6	33
------	--	------	----

DS-KD-ACF2



5766	<p>Uzidna dozna sa ramom za instalaciju dva modula</p> <ul style="list-style-type: none"> - Materijal: Aluminijumski ram, dozna plastika - Dimenzije dozne: 237 x 134 x 56 mm - Dimenzije rama: 236 x 124 x 4 mm 	54	45
------	---	----	----

DS-KD-ACF3



5767	Uzidna dozna sa ramom za instalaciju tri modula - Materijal: Aluminijski ram, dozna plastika - Dimenzije dozne: 338.8 x 134 x 56 mm - Dimenzije rama: 337.8 x 124 x 4 mm	67,2	56
------	---	------	----

DS-KAB86



4782	Dozna za montažu unutrašnjih jedinica (monitora) i spoljašnje jedinice DS-KV8102-IP	3,6	3
------	---	-----	---

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs