

## CENOVNIK HIKVISION INTERFONSKIH SISTEMA

JANUAR 2023.

### INTERFONSKI KOMPLETI

#### DS-KIS202



4821 Komplet analognog video interfona za jednu porodicu koji sadrži pozivnu jedinicu DS-KB2411-IM i video monitor DS-KH2220. Siva boja

115,2

96

#### DS-KIS202T



7195 Komplet analognog video interfona za vilu ili kuću koji sadrži pozivnu jedinicu DS-KB2411T-IM i video monitor DS-KH2220. DS-KB2411T-IM Pozivna jedinica sa jednim tasterom sa pinhole kamerom 1920 x 1080 @ 25 fps DS-KH2220 7" LCD ekran sa fizičkim tasterima rezolucije 800 x 480

174

145

#### KIS203T



7196 Vodootporan analogni komplet video interfona za vilu ili kuću. Komplet sadrži pozivnu jedinicu DS-KB2421T-IM i video monitor DS-KH2220. DS-KB2421T-IM Vodootporna pozivna jedinica sa pinhole kamerom 1920 x 1080 @ 25 fps DS-KH2220 7" LCD ekran sa fizičkim tasterima rezolucije 800 x 480

195,6

163

#### DS-KIS101-P

2-žični analogni komplet za interfon  
Primite video poziv i otključajte ga putem unutrašnje stanice

Spoljna jedinica:

Pozivanje jednim dodirom na oznaku imena

2MP HD kamera sa WDR podrškom, "belim" osvetljenjem i uglovima horizontalni: 100°,

Vertikalni: 69°, 4 alarmna ulaza, dve žice, tamper, 2 exit dugmeta, 2 kontrole zaključavanja, 2 vratna

kontakta ulaza, napajanje zaključavanja 12V 1A

Sertifikati zaštite IP65, IK7 Radna temperatura -30 ° C do +60 ° C

7075 Dimenzije 150 mm × 82 mm × 23,5 mm , Napajanje 48 VDC, 0,5 A, potrošnja ≤ 12 W

249,6

208

Unutrašnja jedinica:

7" ekran u boji sa rezolucijom 1024 × 600, 6 tastera na dodir

2 žice x 3

Napajanje 48 VDC

Radna temperatura -10 ° C do +50 ° C

Dimenzije 187 mm × 137 mm × 25,4 mm

Potrošnja ≤ 5 W

#### DS-KB2421-IM



Antivandal pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom

Rezolucija: 720x576

Fotosenzitivno osvetljenje, doomet IR 2m

Integrisan mikrofoni i zvučnik

Ožičenje od četiri žice ( Video ulaz, Audio in/out, +, - )

5142 1x Relejni izlaz

Maksimalna potrošnja: 5W

97,2

81

Materijal izrade: Zinc Alloy

Radna Temperatura: -30° C to +60° C

Dimenzije: 145 mm × 49,2 mm × 26,45 mm

DS-KB2411-IM



4780	<p>Pozivna jedinica sa jednim tasterom i ugrađenom pin hole kamerom          Rezolucija: 720x576          Fotosenzitivno osvetljenje, doomet IR 2m          Integrisan mikroskop i zvučnik          Ožičenje od četiri žice ( Video ulaz, Audio in/out, +, - )          1x Relejni izlaz          Maksimalna potrošnja: 3W          Materijal izrade: Plastika          Radna Temperatura: -30° C to +60° C          Dimenzije: 128 mm × 42 mm × 24.8 mm</p>	64,8	54
------	--	------	----

DS-KH2220-S



6965	<p>4 Žice analogna unutrašnja stanica          Podržava nadgledanje vrata i spoljašnjih analogna kamera          Integrisan omnidirekcionni mikroskop sa funkcijom suzbijanja buke i poništavanje eho          Integrisan zvučnik          Podržava reprodukciju snimljenih slika-200 slika          Daljinsko otključavanje          Napajanje 12 VDC          Potrošnja ≤5 W          Radna temperatura -10° C do + 55°          Dimenzije 195.8 mm × 132.8 mm × 18.39 mm</p>	153,6	128
------	---	-------	-----

## UNUTRAŠNJE JEDINICE – MONITORI

DS-KH6320-WTE1




5764 Crni	<p>7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom          Rezolucija Monitora:1024 * 600          LAN: 10/100Mbps Ethernet / WiFi          8X Alarmni ulaz ,2X Izlaz          Napajanje: Standard PoE ili 12 VDC</p>	208,8	174
6457 Beli	<p>Mogućnost dodavanja IP kamera sa mreže          Pozivanje između monitora, odnosno stanara, Screenshot funkcija          Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice          Dimenzije: 200 mm × 140 mm × 15.1 mm</p>		

DS-KH6320-WTE2



6221 Crni	<p>7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom          Rezolucija Monitora:1024 * 600          Dve žice za napajanje i mrežni pristup.          8X Alarmni ulaz , 2X Izlaz          Mogućnost dodavanja IP kamera sa mreže</p>	208,8	174
6575 Beli	<p>Pozivanje između monitora, odnosno stanara, Screenshot funkcija          Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice          Dimenzije: 200 mm × 140 mm × 15.1 mm</p>		

DS-KH8350-WTE1



5932	<p>7" Unutrašnja Touch screen jedinica sa IPS LCD monitorom          Rezolucija Monitora:1024 * 600          LAN: 10/100Mbps Ethernet / WiFi          8X Alarmni ulaz, 2X Izlaz          Napajanje: Standard PoE ili 12 VDC          Mogućnost dodavanja IP kamera sa mreže          Pozivanje između monitora, odnosno stanara. Screenshot funkcija          Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice          Dimenzije: 180 mm × 140 mm × 22.4 mm</p>	369,6	308
------	--	-------	-----

DS-KH8520-WTE1



5758	<p>10.1" Unutrašnja Touch screen jedinica sa IPS LCD monitorom          Rezolucija Monitora:1024 * 600          LAN: 10/100Mbps Ethernet / WiFi          8X Alarmni ulaz , 2X Izlaz          Napajanje: Standard PoE ili 12 VDC          Mogućnost dodavanja IP kamera sa mreže          Pozivanje između monitora, odnosno stanara. Screenshot funkcija          Mogućnost pozivanja na mobilni telefon pri pozivanju sa spoljne jedinice          Dimenzije: 254 mm × 166 mm × 14.7 mm</p>	438	365
------	--	-----	-----

DS-KH9310-WTE1



6737	<p>Android unutrašnja jedinica 7"          Ekran: 7" TFT monitor osetljiv na dodir, rezolucije 1024 × 600          Interna memorija skladištenja 4 GB Emmc          Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikroskop, zvučnik, 8x alarmin ulaz, 2x alarmni izlaz (relej), 1x tamper, 1x debugging port          Napajanje: 12 VDC ili PoE          Radna Temperatura: -30° C to +50° C          Dimenzije: 187 mm × 137 mm × 25.7 mm          Težina: 419.3 g</p>	404,4	337
------	--	-------	-----

DS-KH9510-WTE1



6780	<p>Android unutrašnja jedinica 10.1"</p> <p>Ekran: 10.1" TFT monitor osetljiv na dodir, rezolucije 1024 × 600</p> <p>Interna memorija skladištenja 8 GB Emmc</p> <p>Interfejsi: RJ45 10M/100M, Wi-Fi, RS-485, mikrofon, zvučnik, 8x alarmin ulaz, 2x alarmni izlaz (releji), 1x tamper, 1x debugging port</p> <p>Napajanje: 12 VDC ili PoE</p> <p>Radna Temperatura: -10° C to +50° C</p> <p>Dimenzije: 254 mm × 166 mm × 26.65 mm</p> <p>Težina: 875 g</p>	492	410
------	---	-----	-----

## IP POZIVNE JEDINICE

DS-KB8113-IME1



6736	<p>2 MP Antivandal Spoljašnja jedinica sa jednim pozivom</p> <p>Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektivna 88° (horizontalno) 45° (vertikalno)</p> <p>Interfejsi: RJ45 10M/100M, mikrofon, zvučnik, 1x alarmin ulaz, 1x relejni, 1x debugging port, uzemljenje</p> <p>Sertifikati zaštite: IP66, IK09</p> <p>Napajanje: 12 VDC ili PoE</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm</p>	177,6	148
------	--	-------	-----

DS-KV6113-WPE1



6391	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 1X relejni NO/NC izlaz,</p> <p>Zastita: IP65</p> <p>Napajanje: 12 VDC ili PoE Potrosnja: &lt;10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 161.9mm × 74.1mm × 53.2mm</p>	187,2	156
------	--	-------	-----

DS-KV8113-WME1



6430	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 2X relejni NO/NC izlaz,</p> <p>Zastita: IP65, IK08</p> <p>Napajanj: 12 VDC ili PoE Potrosnja: &lt;10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 174 mm × 91 mm × 29 mm</p>	248,4	207
------	--	-------	-----

DS-KV8213-WME1



6390	<p>2 MP HD Spoljašnja jedinica sa dva pozivna tastera</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 2X relejni NO/NC izlaz,</p> <p>Zastita: IP65, IK08</p> <p>Napajanj: 12 VDC ili PoE Potrosnja: &lt;10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 174 mm × 91 mm × 29 mm</p>	268,8	224
------	---	-------	-----

DS-KV8413-WME1



6429	<p>2 MP HD Spoljašnja jedinica sa četiri pozivna tastera</p> <p>Rezolucija kamere: 1080p@30fps</p> <p>ugao objektivna 129° (horizontalno) 75° (vertikalno)</p> <p>True WDR, DNR, BLC</p> <p>LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi</p> <p>Integriran citac kartica Mifare 13,56Mhz</p> <p>Podrška konfigurisanje putem Web interfejsa</p> <p>4X Alarmin ulaz, 2X relejni NO/NC izlaz,</p> <p>Zastita: IP65, IK08</p> <p>Napajanj: 12 VDC ili PoE Potrosnja: &lt;10W</p> <p>Radna Temperatura: -30° C to +50° C</p> <p>Dimenzije: 174 mm × 91 mm × 29 mm</p>	289,2	241
------	--	-------	-----

## DS-KD8103-E6



7071	<p>2 MP Antivandal Spoljašnja jedinica sa jednim pozivom          Kamera: rezolucija 1080p @30fps, Motion detection, True WDR, ugao objektivna 88° (horizontalno) 45° (vertikalno)          Interfejsi: RJ45 10M/100M, mikrofoni, zvučnik, 1x alarmin ulaz, 1x relejni, 1x debugging port, uzemljenje          Sertifikati zaštite: IP66, IK09          Napajanje: 12 VDC ili PoE          Radna Temperatura: -30° C to +50° C          Dimenzije: 161.85 mm × 24.13 mm × 53.2 mm</p>	404,4	337
------	---	-------	-----

## DS-KD8023-E6



7074	<p>2 MP HD Spoljašnja jedinica sa jednim pozivom          Rezolucija kamere: 1080p@30fps          ugao objektivna 129° (horizontalno) 75° (vertikalno)          True WDR, DNR, BLC          LAN: 10M/100M Ethernet, mogućnost povezivanja na WiFi          Integrisan čitač kartica Mifare 13,56Mhz          Podrška konfigurisanje putem Web interfejsa          4X Alarmin ulaz, 1X relejni NO/NC izlaz,          Zastita: IP65          Napajanje: 12 VDC ili PoE Potrošnja: &lt;10W          Radna Temperatura: -30° C to +50° C          Dimenzije: 161.9mm × 74.1mm × 53.2mm</p>	472,8	394
------	--	-------	-----

## DS-KD9203-E6



7126	<p>Pozivna jedinica sa funkcijom prepoznavanja lica i ekranom od 4,3"          Sistem: Linux operativni sistem, RAM 1 GB, ROM 4 GB.          Ekran: 4.3" rezolucije 800x480.          Mreža: 10/100/1000 Mbps, protokoli TCP/IP, RTSP.          Kamera: 2 x 2 MP HD (1080p@30fps) sa WDR-om. Ugao posmatranja 120°. Kompresija H.264. Audio: integrisan omnidirekcionni mikrofoni i zvučnik sa funkcijom suzbijanja buke i poništavanje odjeka.          Kontrola pristupa: Mifare kartica, ulazi/izlazi 4, 2 x RS-485, kontrola vrata, Debugging port.          Kapacitet kartice Max. 25.000, kapacitet korisnika Max. 10.000, Kapacitet zapamćenih lica 5.000. Protokoli ISAPI, RTSP, SNMPv1,v2,v3.          Otključavanje: prisanjanjem kartice, očitavanjem lica (distanca 2m, brzinom 0.2s), preko klijentovog softvera, preko unutrašnje centrale.          Opšte: napajanje 12 VDC, potrošnja ≤ 13 W, radna temperatura -30 °C to +60 °C, radna vlažnost 10% to 90%, težina 0,995kg, IP65 zaštita.</p>	506,4	422
------	--	-------	-----

## IP STANICA DS-KM9503



7271	<p>10 -inčna Android IP stanica na dodir.          Video interfon i funkcije kontrole pristupa.          10,1-inčni IPS ekran osetljiv na dodir sa rezolucijom: 1280 × 800.          Na uređaj se može dodati do 128 mrežnih kamera.          Ugrađeni SIP privatni server, može se dodati do 10000 video interfon uređaja.          2 mrežna ulaza 10/100/1000 M, 2 alarmna ulaza, HDMI, RS-485, 3 USB, podrška SD kartice do 128GB, 2 relejna izlaza.          Video parametri: rezolucija 2 MP, video kompresija H.264          Podrška više od 2 zvučnika i mikrofona: Povezuje se sa spoljnim slušalicama (3,5 mm).          Spoljni mikrofonom sa dužim vratom.          Napajanje: standardni PoE i 12 VDC</p>	1185,6	988
------	---	--------	-----

## DS-KB6403-WIP



5628	<p>P pozivno zvonice koje zove direktno Hik-Connect aplikaciju na telefonu          Nije potrebna unutrašnja jedinica.          Kamera: High performance CMOS, rezolucije do 2Mpx          Ugao kamere: Ultra wide 180° (Horizontalno), 96° (Vertikalno)          Dva strima, WDR, Nevidljivo IR svetlo 940 nm.          Mreža: Wifi 2.4 Ghz          Podrška funkcije: Motion Detection          Prostor za SD karticu max 128 GB          Ugrađen omnidirekcionni mikrofoni i zvučnik za dvosmernu komunikaciju          Zaštita: IP54          Napajanje 12VDC          Radna temperatura: -30° C to +50° C          Dimenzije: 122.4 mm x 45.9 mm x 28.1 mm</p>	114	95
------	---	-----	----

## MODULARNI IP SISTEMI

## DS-KD8003-IME1



5759	<p>Glavni pozivni modul sa integrisanom HD kamerom od 2 Mpx</p> <ul style="list-style-type: none"> <li>- Kamera: 2 MP HD IR</li> <li>- Main Stream: 1920 × 1080 Sub Stream: 720 × 480</li> <li>- Kompresija: H.264</li> <li>- Ugrađen Omnidirekcionni mikrofoni</li> <li>- Ugrađen zvučnik: 85dB do 20 cm</li> <li>- Interfejsi: RJ45 10/100 Mbps</li> <li>- Protokoli: TCP/IP, RTSP</li> <li>- IC za noćni režim</li> <li>- Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave</li> <li>- Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98mm × 99.8mm × 43.9mm</li> <li>- IP zaštita: IP65, Radna temperatura -40° C - +60° C</li> </ul>	187,2	156
------	--	-------	-----

## DS-KD8003-IME2



6210	<p>Glavni pozivni modul (dve žice) sa integrisanom HD kamerom od 2 Mpx</p> <ul style="list-style-type: none"> <li>- Kamera: 2 MP HD IR</li> <li>- Main Stream: 1920 × 1080 Sub Stream: 720 × 480</li> <li>- Kompresija: H.264</li> <li>- Dve žice za napajanje i mrežni pristup.</li> <li>- Ugrađen Omnidirekcionni mikrofoni</li> <li>- Ugrađen zvučnik: 85dB do 20 cm</li> <li>- Protokoli: TCP/IP, RTSP</li> <li>- IC za noćni režim</li> <li>- Alarmni ulazi / izlazi: 4/4, mogućnost otvaranja 2 brave</li> <li>- Napajanje: PoE ili 12VDC/1A, Potrošnja: ≤10 W</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98mm × 99.8mm × 43.9mm</li> <li>- IP zaštita: IP65, Radna temperatura -40° C - +60° C</li> </ul>	187,2	156
------	--	-------	-----

## DS-KD-KK



5760	<p>Modul sa 6 pozivnih tastera</p> <ul style="list-style-type: none"> <li>- Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu</li> <li>- Napaja se preko glavne jedinice DS-KD8003-IME1</li> <li>- Konekcije modula: 1 Ulaz 1 Izlaz</li> <li>- DIP switch: 8</li> <li>- Potrošnja: ≤2 W</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98.21mm×100.21mm×33.7mm</li> <li>- IP zaštita: IP65</li> <li>- Radna temperatura: -40° C - +60° C</li> </ul>	61,2	51
------	--	------	----

## DS-KD-DIS



6319	<p>Modul sa 3,5" LCD ekranom i 4 fizička dugmeta sa osvetljenjem</p> <ul style="list-style-type: none"> <li>- Rezolucija ekrana 320 × 480px</li> <li>- Može se dodati do 500 kontakata</li> <li>- Poziva broj i zove unutrašnju stanicu putem tastature</li> <li>- Otključava vrata pomoću PIN koda putem tastature</li> <li>- MCU procesor, skladište memorije 64MB, flash memorija 8MB</li> <li>- Povezivanje modula 2 (1 ulaz i 1 izlaz)</li> <li>- Fizička 4 dugmeta (gore, dole, OK, nazad)</li> <li>- Potrošnja: ≤3 W</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98.5mm×100mm×34.2mm</li> <li>- IP zaštita: IP65</li> <li>- Radna temperatura: -20° C - +60° C</li> </ul>	118,8	99
------	---	-------	----

## DS-KD-M



5940	<p>Modul sa čitačem Mifare 13,56 Mhz kartica i tagova</p> <ul style="list-style-type: none"> <li>- Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu</li> <li>- Ugrađen čitač Mifare kartica i tagova na 13,56 Mhz</li> <li>- Napaja se preko modula koji je iznad njega</li> <li>- DIP switch: 8</li> <li>- Potrošnja: ≤2 W</li> <li>- IP zaštita: IP65</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98.5mm×100mm×33.7mm</li> </ul>	81,6	68
------	---	------	----

## DS-KD-E



5762	<p>Modul sa čitačem EM kartica i tagova</p> <ul style="list-style-type: none"> <li>- Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu</li> <li>- Napaja se preko modula koji je iznad njega</li> <li>- DIP switch: 8</li> <li>- Potrošnja: ≤2 W</li> <li>- IP zaštita: IP65</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98.5mm×100mm×33.7mm</li> </ul>	81,6	68
------	---	------	----

## DS-KD-KP



5761	<p>Modul sa šifratom za otvaranje vrata</p> <ul style="list-style-type: none"> <li>- Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu</li> <li>- Mogućnost otvaranja vrata putom individualne šifre svakog od stanara</li> <li>- Mogućnost pozivanja stanara unošenjem broja stana</li> <li>- Napaja se preko modula koji je iznad njega</li> <li>- DIP switch: 8</li> <li>- Potrošnja: ≤2 W</li> <li>- IP zaštita: IP65, IK7</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98.5mm×100mm×34.2mm</li> </ul>	133,2	111
------	---	-------	-----

## DS-KD-IN



5763	<p>Modul sa indikacijama: poziv, otvorena vrata i, razgovor</p> <ul style="list-style-type: none"> <li>- Vezuje redno na glavnu jedinicu ili jedinicu iznad po RS 485 protokolu</li> <li>- Napaja se preko modula koji je iznad njega</li> <li>- DIP switch: 8</li> <li>- Potrošnja: ≤2 W</li> <li>- IP zaštita: IP65</li> <li>- Dimenzije ( Dužina x Širina x Visina ): 98.5mm×100mm×34.2mm</li> </ul>	51,6	43
------	---	------	----

## DS-KD-BK



5941	<p>Modul za popunjavanje praznog mesta u sistemu</p> <ul style="list-style-type: none"> <li>- Dimenzije ( Dužina x Širina ): 98.5mm×100mm</li> </ul>	31,2	26
------	--	------	----

## DODATNA OPREMA ZA DVOŽIČNE SISTEME

## Mrežni PoE

Audio/Video Distributer  
DS-KAD706

6253	<p>Mrežni audio/video distributer za interfone sa dve žice.</p> <ul style="list-style-type: none"> <li>1 x 100Mbps port (RJ45)</li> <li>6 kanala za dvožično povezivanje i napajanje perifernih uređaja i 2kanala za kaskadno povezivanje</li> <li>Taster za reset</li> <li>Namenjeno za montažu na DIN šinu</li> <li>Napajanje 24V DC</li> <li>Dimenzije: 176 mm × 91 mm × 32 mm</li> </ul>	153,6	128
------	--	-------	-----

## Mrežni

Audio/Video Distributer  
DS-KAD706-S

6211	<p>Mrežni audio/video distributer za interfone sa dve žice.</p> <ul style="list-style-type: none"> <li>1 x 100Mbps port (RJ45)</li> <li>6 kanala za dvožično povezivanje perifernih uređaja</li> <li>Taster za reset</li> <li>Namenjeno za montažu na DIN šinu</li> <li>Napajanje 24V DC</li> <li>Dimenzije: 176 mm × 91 mm × 32 mm</li> </ul>	153,6	128
------	--	-------	-----

## ADAPTER

## DS-KAW60-2N



6212	<p>Napajanje za distributere DS-KAD706 &amp; DS-KAD706-S.</p> <ul style="list-style-type: none"> <li>Izlaz: 24 VDC, 60W</li> <li>Montaža za din šine.</li> <li>Dimenzije: 52.5 mm × 90 mm × 54.5 mm</li> <li>Radna temperatura: -30 °C to 70 °C</li> </ul>	64,8	54
------	--	------	----

## DOZNE

## DS-KABV6113-RS



6542 Nazidna kutija za pozivne jedinice DS-KV6103/6113  
Materijal: Plastika  
Dimenzije: 149,78 mm × 76,59 mm × 48,63 mm

10,8

9

## DS-KABV8113-RS



6543 Nazidna kutija za pozivne jedinice KV8113/8213/8413  
Materijal: Nerđajući čelik  
Dimenzije: 188,69 mm × 97 mm × 48,63 mm

18

15

## DS-KABD8003-RS1



6605 Nazidna kutija za pozivne jedinice DS-KD8003-IME1 ili DS-KD8003-IME2.  
Materijal: Nerđajući čelik  
Dimenzije: 122 × 116,4 × 58 mm

27,6

23

## DS-KABD8003-RS2



6604 Nazidna kutija za pozivne jedinice za dva modula  
DS-KD8003-IME1 ili DS-KD8003-IME2  
Materijal: Nerđajući čelik  
Dimenzije: 224 × 116,4 × 58 mm

34,8

29

## DS-KABD8003-RS3



6592 Nazidna kutija za pozivne jedinice za 3 modula  
DS-KD8003-IME1 ili DS-KD8003-IME2  
Materijal: Nerđajući čelik  
Dimenzije: 325,8 × 116,4 × 58 mm

40,8

34

## DS-KD-ACW1



5768 Nazidna dozna sa ramom za instalaciju jednog modula  
- Materijal: Aluminijum  
- Dimenzije dozne: 117 x 107 × 32,7 mm  
- Dimenzije rama: 117 x 107 × 4 mm

61,2

51

## DS-KD-ACW2



5769	<p>Nazidna dozna sa ramom za instalaciju dva modula</p> <ul style="list-style-type: none"> <li>- Materijal: Aluminijum</li> <li>- Dimenzije dozne: 219 x 107 x 32.7 mm</li> <li>- Dimenzije rama: 219 x 107 x 4 mm</li> </ul>	85,2	71
------	---	------	----

## DS-KD-ACW3



5770	<p>Nazidna dozna sa ramom za instalaciju tri modula</p> <ul style="list-style-type: none"> <li>- Materijal: Aluminijum</li> <li>- Dimenzije dozne: 320.8 x 107 x 32.7 mm</li> <li>- Dimenzije rama: 320.8 x 107 x 4 mm</li> </ul>	142,8	119
------	---	-------	-----

## DS-KAB10-D



5621	<p>Nazidna kutija za pozivnu jedinicu DS-KD8102-V</p> <p>Materijal: Nerđajući čelik</p> <p>Dimenzije: 489.6 mm x 171.88 mm x 105.41 mm</p>	122,4	102
------	--	-------	-----

## DS-KAB11-D




6703	<p>Nazidna kutija za pozivnu jedinicu DS-KD8102-V</p> <p>Materijal: Nerđajući čelik</p>	129,6	108
------	---	-------	-----

## DS-KD-ACF1



5765	<p>Uzidna dozna sa ramom za instalaciju jednog modula</p> <ul style="list-style-type: none"> <li>- Materijal: Aluminijumski ram, dozna plastika</li> <li>- Dimenzije dozne: 134 x 135 x 56 mm</li> <li>- Dimenzije rama: 134 x 124 x 4 mm</li> </ul>	40,8	34
------	--	------	----

## DS-KD-ACF2



5766	<p>Uzidna dozna sa ramom za instalaciju dva modula</p> <ul style="list-style-type: none"> <li>- Materijal: Aluminijumski ram, dozna plastika</li> <li>- Dimenzije dozne: 237 x 134 x 56 mm</li> <li>- Dimenzije rama: 236 x 124 x 4 mm</li> </ul>	55,2	46
------	---	------	----



DS-KD-ACF3



5767	Uzidna dozna sa ramom za instalaciju tri modula - Materijal: Aluminijski ram, dozna plastika - Dimenzije dozne: 338.8 x 134 x 56 mm - Dimenzije rama: 337.8 x 124 x 4 mm	68,4	57
------	---	------	----

DS-KAB86



4782	Dozna za montažu unutrašnjih jedinica ( monitora ) i spoljašnje jedinice DS-KV8102-IP	3,6	3
------	---	-----	---

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite [www.isec.rs](http://www.isec.rs)