

CENOVNIK KONTROLE PRISTUPA HIKVISION



ACCESS CONTROL

HIKVISION



www.hikvision.com

A SAFE ENVIRONMENT
THROUGH SECURED ACCESS

NAZIV

ŠIFRA

OPIS

CENA

KONTROLERI

sa PDV

bez PDV

DS-K2601T



6595

Processor: 32-bit
Capacity: 16M
Uplink interfejs: TCP/IP, RS-485
Downlink interfejs: RS-485, Wiegand (W26/W34)
Skladištenje: 100.000 kartica, proširivo do 200.000; access control događaja 300.000, proširivo do 600.000
Led indikator: za napajanje, za komunikacije, za radni status
Ugrađen sat: da
Interfejsi za čitače kartica: 2 interfejsa RS485 i 2 interfejsa Wiegand
Ulazni interfejsi: 4 x alarmni, 1 x senzor vrata, 1 x exit dugme, 2 x case ulaza, 1 x tamper alarm
Izlazni interfejsi: 1 x relej zaključavanja, 2 x Alarmni Relej
Radna temperatura: 20°C to +65°C
Vlažnost: 10% to 90% nekondenzujuće
Dimenzije: 370mm x 345mm x 90 mm
Napajanje: DC 12V/1A
Potrošnja: ≤4W do ≤50W

260.40

217.00

DS-K2602T



6611

Processor: 32-bit
Capacity: 16M
Uplink interfejs: TCP/IP, RS-485
Downlink interfejs: RS-485, Wiegand (W26/W34)
Skladištenje: 100.000 kartica, proširivo do 200.000; access control događaja 300.000, proširivo do 600.000
Led indikator: za napajanje, za komunikacije, za radni status
Ugrađen sat: da
Interfejsi za čitače kartica: 4 interfejsa RS485 i 4 interfejsa Wiegand
Ulazni interfejsi: 4 x alarmni, 2 x senzor vrata, 2 x exit dugme, 4 x case ulaza, 1 x tamper alarm
Izlazni interfejsi: 2 x relej vrata, 4 x Alarmni Relej
Radna temperatura: 20°C to +65°C
Vlažnost: 10% to 90% nekondenzujuće
Dimenzije: 370mm x 345mm x 90 mm
Napajanje: DC 12V/1A
Potrošnja: ≤4W do ≤100W

295.20

246.00



6596	<p>Processor: 32-bit Capacity: 16M Uplink interfejs: TCP/IP, RS-485 Downlink interfejs: RS-485, Wiegand (W26/W34) Skladištenje: 100.000 kartica, proširivo do 200.000; access control događaja 300.000, proširivo do 600.000 Led indikator: za napajanje, za komunikacije, za radni status Ugrađen sat: da Interfejsi za čitače kartica: 8 interfejsa RS485 i 4 interfejsa Wiegand Ulazni interfejsi: 4 x alarmni, 4 x senzor vrata, 4 x exit dugme, 8 x case ulaza, 1 x tamper alarm Izlazni interfejsi: 4 x relej vrata, 4 x Alarmni Relej Radna temperatura: 20°C to +65°C Vlažnost: 10% to 90% nekondenzujuće Dimenzije: 370mm x 345mm x 90 mm Napajanje: DC 12V/1A Potrošnja: ≤4W do ≤100W</p>	367.20	306.00
------	---	--------	--------

ČITAČI

DS-K1107E



Čitač Kartica Za Kontrolu Pristupa - EM card 125Khz			
6598	<p>Procesor: high-speed 32-bit Domet čitača: ≤50mm (≤1.97") ID poševanja: preko DIP Switch Komunikacioni interfejs: RS-485/Wiegand (podesiv preko DIP Switch) Audio upozorenje: Beeper LED Indikator: napanjanje i status Tamper alarm: podržava Zaštita: IP65 sertifikat Instalacija: Zidna instalacija Napajanje i potrošnja: 12V DC, ≤2W Dimenzije: 115mm x 44mm x 22mm Radna temperatura: 20°C to +65°C Radna vlažnost: 10% to 90%</p>	38.40	32.00

DS-K1107M



Čitač Kartica Za Kontrolu Pristupa - Mifare 13,56Mhz			
6597	<p>Procesor: high-speed 32-bit Domet čitača: ≤50mm (≤1.97") ID poševanja: preko DIP Switch Komunikacioni interfejs: RS-485/Wiegand (podesiv preko DIP Switch) Audio upozorenje: Beeper LED Indikator: napanjanje i status Tamper alarm: podržava Zaštita: IP65 sertifikat Instalacija: Zidna instalacija Napajanje i potrošnja: 12V DC, ≤2W Dimenzije: 115mm x 44mm x 22mm Radna temperatura: 20°C to +65°C Radna vlažnost: 10% to 90%</p>	38.40	32.00

Čitač Kartica Za Kontrolu Pristupa - EM card 125Khz



6516	<p>Domet čitača: ≤50mm (≤1.97")</p> <p>ID poševanja: preko DIP Switch</p> <p>Komunikacioni interfejs: RS-485/Wiegand (podesiv preko DIP Switch)</p> <p>Tastatura: 12 dugmiča (0~9, *, #)</p> <p>Audio upozorenje: Beeper</p> <p>LED Indikator: napanjanje i status</p> <p>Tamper alarm: podržava</p> <p>Zaštita: IP65 sertifikat</p> <p>Instalacija: Zidna instalacija</p> <p>Napajanje i potrošnja: 12V DC, ≤2W</p> <p>Dimenzije: 115mm × 44mm × 22mm</p> <p>Radna temperatura: 20°C to +65°C</p> <p>Radna vlažnost: 10% to 90%</p>	48.00	40.00
------	--	-------	-------

DS-K1107MK

Čitač Kartica Za Kontrolu Pristupa - Mifare 13,56Mhz



6515	<p>Domet čitača: ≤50mm (≤1.97")</p> <p>ID poševanja: preko DIP Switch</p> <p>Komunikacioni interfejs: RS-485/Wiegand (podesiv preko DIP Switch)</p> <p>Tastatura: 12 dugmiča (0~9, *, #)</p> <p>Audio upozorenje: Beeper</p> <p>LED Indikator: napanjanje i status</p> <p>Tamper alarm: podržava</p> <p>Zaštita: IP65 sertifikat</p> <p>Instalacija: Zidna instalacija</p> <p>Napajanje i potrošnja: 12V DC, ≤2W</p> <p>Dimenzije: 115mm × 44mm × 22mm</p> <p>Radna temperatura: 20°C to +65°C</p> <p>Radna vlažnost: 10% to 90%</p>	48.00	40.00
------	--	-------	-------

TERMINALI ZA PREPOZNAVANJE LICA

DS-K1T331W



6606	<p>Terminal Za Prepoznavanje Lica</p> <p>Operativni sistem: Linux</p> <p>Ekran: na dodir, dijagonale 3.97-inča</p> <p>Kapacitet kartice: 1.500 kad se konektuje eksterni čitač</p> <p>Kapacitet događaja: 150.000</p> <p>Kapacitet zapamćenih lica: 300</p> <p>Distanca prepoznavanja: 0.3 m do 1.5 m</p> <p>Brzina prepoznavanja: < 0.2 s</p> <p>Mrežni interfejs: 10/100 Mbps</p> <p>Kamera: 2 MP sa dvostrukim objektivom i širokim dinamičkim opsegom</p> <p>Komunikacija: TCP/IP, Wi-Fi</p> <p>Interfejs: USB × 1, električna brava × 1, kontakt vrata × 1, tamper × 1, exit dugme × 1, RS-485 × 1</p> <p>Napajanje: 12 V, 1.5 A, 18 W</p> <p>Radna temperatura: -10 °C to +50 °C</p> <p>Radna vlažnost: 10 to 90% (bez kondenzacije)</p> <p>Dimenzije: 120 mm × 110 mm × 23 mm</p> <p>Predviđeno za unutrašnju upotrebu.</p>	242.40	202.00
------	---	--------	--------



6607

Terminal Za Prepoznavanje Lica
 Operativni sistem: Linux
 Ekran: na dodir, dijagonale 7-inča, rezolucije 1024 × 600
 Prepoznavanje: lice i otisak prsta
 Kapacitet kartice: 6.000
 Kapacitet događaja: 50.000
 Kapacitet zapamćenih lica: 5.000
 Kapacitet otiska prstiju: 5000
 Distanca prepoznavanja lica: 0.3 m do 3 m
 Brzina prepoznavanja: < 0.2 s
 Mrežni interfejs: 10/100/1000 Mbps
 Kamera: 2 MP sa dvostrukim objektivom, WDR
 Komunikacija: TCP/IP
 Interfejs: mrežni × 1, RS-485 × 1, Wiegand × 1, USB × 1, alarm izlaz × 1, alarm ulaz × 2, brava × 1, kontakt vrata × 1, exit dugme × 1, tamper × 1
 Tip kartice: M1 card
 Napajanje: 12 VDC/2 A
 Radna temperatura: -30 °C to +60 °C
 Radna vlažnost: 0 to 90% (bez kondenzacije)
 Dimenzije: 290 mm × 116,5 mm × 33 mm

59.28

494.00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD.

Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs