






CENOVNIK AKTIVNE MREŽNE OPREME – Februar 2023

HIKVISION
PoE SWITCHES



Tenda

cudy

NAZIV	ŠIFRA	OPIS	CENA	
			sa PDV	bez PDV
RUTERI I AP				
Tenda router N301				
	G3135	Standard i protokol: IEEE 802.3/3U IEEE 802.11n/g/b 1*10/100Mbps WAN Port / 3*10/100Mbps LAN Ports Mod rada: Universal Repeater, AP, WISP, WDS Bridge 2 fixed 5dbi Omni Directional antenas	22,56	18,80
Tenda router F300				
	G3283	Standard i protokol: IEEE 802.3/3U IEEE 802.11n/g/b 1*10/100Mbps WAN Port / 4*10/100Mbps LAN Ports Mod rada: AP, WISP, WDS Bridge 2 fixed 5dbi Omni Directional antennas	25,61	21,34
Tenda router F3				
	G3864	Standard i protokol: IEEE 802.3/3U IEEE 802.11n/g/b 1*10/100M auto-negotiation WAN port / 3*10/100M auto-negotiation LAN ports Mod rada: Universal Repeater, WISP 3x 5dBi external undetachable antennas	17,96	14,97
Tenda Router F6				
	G7427	Standard i protokol: IEEE802.3, IEEE802.3u, IEEE802.3ab 1*10/100M auto-negotiation WAN port / 3*10/100M auto-negotiation LAN ports Mod rada: Wireless Router Mode, Universal Repeater, WISP, AP Mode 4x 5dBi external undetachable antennas	29,48	24,57
Cudy WR1200				
	G7721	Standard&Protocol: IEEE 802.11ac/n/a 5 GHz, IEEE 802.11n/b/g 2.4 GHz Interfejs: 1*10/100Mbps WAN port / 4*10/100Mbps LAN ports Antenna: 4 x Fixed Omni-Directional Antennas Napajanje: DC 12V 1A Frequency 2.4GHz & 5GHz Wireless Security WEP, WPA/WPA2, WPA-PSK/WPA2-PSK Internet Connection Type PPPoE, Dynamic IP, Static IP Operating Mode Wireless Router Mode Mod rada: AP Mode / Universal Repeater mode / WISP Mode / DHCP / DHCP Server / DHCP Client List / DHCP Reservation / Virtual Server / Port Forwarding / DMZ Host / UPnP Certification: CE, FCC, CCC, SRRC	34,15	28,46

SVIČEVI

Cudy FS105D



G3073	Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3x standards, 5 x 10/100Mbps Auto-Negotiation RJ45 ports, Supports IEEE802.3x flow control for Full-duplex	9,74	8,12
-------	---	------	------

TENDA S108



G3073	Standard i protokol: IEEE 802.3, IEEE 802.3u, IEEE 802.3x 8*10/100M auto-negotiation RJ 45 ports (Auto MDI/MDIX)	10,48	8,73
-------	---	-------	------

HikVision DS-3E0508D-E



6731	Standard i protokol: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, 8*10/100/1000 Mbps RJ45 ports, Store-and-forward switching, Store-and-forward switching 16Gbps	31,20	26,00
------	--	-------	-------

HikVision DS-3E0516-E(B)



6769	16 x 1000M Ethernet ports, Supports IEEE 802.3, IEEE 802.3u and IEEE 802.3x, Wire-speed forwarding and non-blocking design, Store-and-forward switching	87,60	73,00
------	---	-------	-------

HikVision DS-3E0524-E(B)



6772	24 x 1000M Ethernet ports, Supports IEEE 802.3, IEEE 802.3u and IEEE 802.3x, Wire-speed forwarding and non-blocking design, Store-and-forward switching	120,00	100,00
------	---	--------	--------

POE SVIČEVI

Cuby FS1006P



G7734	6-Port 10/100M PoE+ Switch FS1006P, Complies with IEEE802.3af/at Standard, Supports PoE power up to 32W for each PoE port, Auto detect non PoE device and PoE device, CCTV/VLAN mode switch, remote power and data up to 250m, PoE Total 60W	31,94	26,62
-------	--	-------	-------

Cuby FS1010P





G7736	8-Port 10/100M PoE+ Switch with 2 Uplink Ports, Complies with IEEE802.3af/at Standard, Supports PoE power up to 32W for each PoE port, Auto detect non PoE device and PoE device, CCTV/VLAN mode switch, remote power and data up to 250m, PoE Total 120W	45,50	37,92
-------	---	-------	-------

HikVision DS-3E0106P-E/M



7375	4 Port Fast Ethernet Unmanaged POE Switch, 4 x 10/100Mbps PoE ports, and 2 x 10/100Mbps RJ45 ports, IEEE 802.3at/af standard for PoE ports (Max. 35 W PoE output), IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard, 6 KV surge protection for PoE ports, Up to 300 m long-range transmission, Max. Port Power 30 W, PoE Power Budget 35 W	50,40	42,00
------	---	-------	-------

HikVision 3E0106HP-E/M	DS-		6683	4 Port Fast Ethernet Unmanaged POE Switch, Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime, Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters, 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables, PoE Power Budget 60 W	61,20	51,00
HikVision 3E0109P-E/M	DS-		5834	8 Port Fast Ethernet Unmanaged POE Switch, Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime, Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters, 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables, PoE Power Budget 60 W	81,60	68,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD.

Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs