

CENOVNIK UNIVIEW VIDEO NADZORA - 04.04.2024.



NAZIV	ŠIFRA	OPIS	CENA
SNIMACI			sa PDV bez PDV
4 KANALNI			
XVR301-04G3			



Unlimited New View



4-CH Hybrid DVR

Podržan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal)

4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podržan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6)

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulažno/Izlazni saobraćaj: 16/48 Mbps

87,60 73,00

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x 226mm x 47mm (10.2" x 8.9" x 1.8"), 1.1kg



I1031



XVR301-04Q3

4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamere: do 8mp (2 IP kamere ili svih 6)

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

123,60 103,00

Ulažno/Izlazni saobraćaj: 48/60 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x 226mm x 47mm



8 KANALNI

XVR301-08G3



8-CH Hybrid DVR

Podržava: TVI,AHD, CVI, CVBS

Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF

Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)

Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio

I1025

Ulažno/Izlazni saobraćaj: 32/64 Mbps

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB

Napajanje 12V DC, Potrošnja 8W bez HDD

Radna temperatura: -10 °C ~ +55 °C

Dimenzije: 260mm ×226mm× 47mm

126,00 105,00



XVR301-08Q3



8-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)

Video kompresija: H.265, H.264

Video/audio ulazi: 8ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

I1033

Ulažno/Izlazni saobraćaj: 40/64 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC,

Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm ×226mm× 47mm

192,00 160,00



16 KANALNI

XVR301-16G3



16-CH Hybrid DVR

Podržava: TVI, AHD, CVI, CVBS, IP cameras

Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF

IP kamere: do 8 IP kamere ili svih 16

Video/audio ulazi: 16-ch BNC / 1-ch RCA

Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio

I1026

Ulažno/Izlazni saobraćaj: 40/64 Mbps

Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 SATA HDD do 8TB

Napajanje 12V DC, Potrošnja 10W bez HDD

Radna temperatura: -10 °C ~ +55 °C

Dimenzije: 260mm ×226mm× 47mm

204,00 170,00



XVR302-16Q3



16-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava 8MP@15fps na prva 4 kanala

Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.

Ulažno/Izlazni saobraćaj: 72/80 Mbps

Video kompresija: H.265/H.264 video kompresija,

Video/audio ulazi: 16ch BNC, 1ch RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA

I1034

Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line

detection, audio detection, defocus detection, scene change detection

Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 2 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 380mm ×315mm× 53mm, Težina 1.9Kg

306,00 255,00



ANALOGNE KAMERE

UAC-T112-F28



I1004

2MP HD Fixed IR Turret Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

28,80 24,00

UAC-B112-F28



I1000

2MP HD Fixed IR Mini Bullet Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

28,80 24,00

UAC-T112-F28-W



I1005

2MP ColourHunter HD Fixed Turret Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

NEMA NA STANJU

31,20 26,00

UAC-B112-F28-W



I1001

2MP ColourHunter HD Fixed Mini Bullet Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

31,20 26,00

UAC-D122-AF28M



I1017

2MP LightHunter HD IR Fixed Dome Analog Camera

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal/vertical flip
OSD configuration menu, easy to operate
Water and dust resistant (IP67) and vandal-resistant (IK10)
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal base and metal housing
3-Axis

46,80 39,00

UAC-T122-AF28LM



I1054

2MP LightHunter HD IR Fixed Turret Analog Camera

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
3-Axis

49,20 41,00

UAC-B122-AF28LM**2MP LightHunter HD IR Fixed Mini Bullet Analog Camera**

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog

49,20 41,00

I1053

**UAC-T122-AF28M-W****2MP ColorHunter HD Fixed Turret Analog Camera**

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing
3-Axis

52,80 44,00

I1016

**UAC-B122-AF28M-W****2MP ColorHunter HD Fixed Mini Bullet Analog Camera**

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing

52,80 44,00

I1014

**UAC-B122-AF40M-W****2MP ColorHunter HD Fixed Mini Bullet Analog Camera**

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing

52,80 44,00

I1015

**UAC-T115-F28****5MP HD Fixed IR Turret Analog Camera**

5MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

43,20 36,00

NEMA NA STANJU

I1005

**UAC-B115-F28****5MP HD Fixed IR Mini Bullet Analog Camera**

5MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

43,20 36,00

I1002



UAC-T115-F28-W

unv

UAC-B115-F28-W

unv

UAC-T125-AF28LM

unv

UAC-B125-AF28LM

unv

UAC-T125-AF28M-W

unv

UAC-T125-AF28M-W-Black

unv

5MP ColourHunter HD Fixed Turret Analog Camera

5MP high quality image

TVI/AHD/CVI/CVBS

- I1007 Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

45,60 38,00

5MP ColourHunter HD Fixed Mini Bullet Analog Camera

5MP high quality image

TVI/AHD/CVI/CVBS

- I1003 Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

45,60 38,00

5MP LightHunter HD IR Fixed Turret Analog Camera

High quality imaging with 5MP resolution

TVI/AHD/CVI/CVBS

- I1056 Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
3-Axis

58,80 49,00

5MP LightHunter HD IR Fixed Mini Bullet Analog Camera

High quality imaging with 5MP resolution

TVI/AHD/CVI/CVBS

- I1055 Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

58,80 49,00

5MP ColorHunter HD Fixed Turret Analog Camera

5MP high quality imaging

TVI/AHD/CVI/CVBS

- I1020 Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing
3-Axis

NEMA NA STANJU

62,40 52,00

5MP ColorHunter HD Fixed Turret Analog Camera

5MP high quality imaging

TVI/AHD/CVI/CVBS

- I1057 Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing
3-Axis

62,40 52,00

UAC-B125-AF28M-W**UAC-B125-AF40M-W****5MP ColorHunter HD Fixed Mini Bullet Analog Camera**

5MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing

62,40 52,00

I1018

DOME IP KAMERE**IPC322LB-SF28-A****2 MP IR Fiksna Dome Mrežna Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,
Šater: Auto/Manual, 1 ~ 1/10000s
Optika: 2.8mm@F2.0
Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet
Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP,
7059 HTTP Mrežni standardi: ONVIF (Profile S, Profile T), API
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: Motion detection
Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI.
Zaštitna IP67, IK10
Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5W
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije: Ø109 x 81mm težina: 0,35kg
Kompatibilni nosači i pribor: TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UM06-EIN, TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

81,60 68,00

I1019

IPC322LB-AF28WK-G**2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera, WiFi**

Rezolucija snimanja: 1080P (1920*1080), Max 20fps
Čip: 1/2.9", progressive scan, 2.0 megapixel, CMOS
Šater: Auto/Manual, 1 ~ 1/10000s
Optika: 2.8mm @F2.0
Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP.
Mrežni standardi: ONVIF (Profile S, Profile G, Profile T), API, SDK
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: Motion detection, Tampering alarm
Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI
Zaštitna IP67, IK10
Napajanje i potrošnja: DC 12V±25%
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije (ØxV): Ø109 x 83mm težina: 0,32kg
Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

93,60 78,00

I1008

IPC3612LB-ADF28K-G**2MP HD IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.7"CMOS sensor

2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Smart IR, up to 30m (98ft) IR distance

Built-in Mic

Supports 128 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

90,00 75,00

I1042

IPC3612LE-ADF28KMC-WL**BLACK****2MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.8"CMOS sensor

2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Built-in Mic & Speaker

Smart IR, up to 30m (98ft) IR distance

White Light, up to 30m (98ft) white light distance

Supports 128 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

96,00 80,00

I1039

IPC3612LE-ADF28KC-WL**2MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.8"CMOS sensor

2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Built-in Mic & Speaker

Smart IR, up to 30m (98ft) IR distance

White Light, up to 30m (98ft) white light distance

Supports 128 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

99,00 82,50

I1038

IPC3614LB-SF28-A**4MP Fixed Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor

4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps

Ultra 265, H.265, H.264, MJPEG

Smart IR, up to 30m (98ft) IR distance

Supports 128 G Micro SD card

Support PoE power supply

3-Axis

84,00 70,00

I1030

IPC3614LE-ADF28KC-WL**4MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 4MP, 1/3"CMOS sensor

4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;

3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Built-in Mic & Speaker

Smart IR, up to 30m (98ft) IR distance

White Light, up to 30m (98ft) white light distance

Supports 128 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

150,00 125,00

I1040

IPC324LB-SF28-A

4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera
 Rezolucija snimanja: ④4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps;
 2MP (1920*1080)@30/25fps
 Čip: 1/3", progressive scan , 4.0 megapixel, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm @F2.0
 Osetljivost: 0.01Lux (F2.0, AGC ON) OLux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS,
 DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS
 Mrežni standardi: ONVIF (Profile S, Profile T), API, SDK
 Kompresija: H.265, H.264,
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD,
 Privacy mask, ROI, Corridor mod
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH
 (ne kondenzujuće)
 Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN,
 TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

NEMA NA STANJU

84,00 70,00

IPC3234LR3-VSPZ28-D

4 MP IR Varifokalna Dome Mrežna Kamera
 Rezolucija snimanja: 4MP (2592*1520), Max 20fps;
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8 ~ 12mm, motorizovani zoom
 Osetljivost: 0.01Lux (F1.6, AGC ON) OLux with IR on, IR-cut filter
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
 Mrežni standardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.
 Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.
 Zaštita: IP67, IK10
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**
 Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
 Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0.92kg
 Kompatibilni nosači i pribor: TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB07/WM04-B-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

168,00 140,00

IPC328LE-ADF28KM-G

4K 8MP Antivandal Fiksna Dome Mrežna kamera
 Rezolucija snimanja: 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 ~ 1/100000s
 Optika: 2.8mm @@1.6, Fixed-focal
 Osetljivost: 0.005Lux (F1.6, AGC ON) OLux with IR on
 IC domet: do 30m
 Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb,
 Ugradjen mikrofon, Reset dugme
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP,
 RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
 Mrežni standardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG
 Smart funkcije: Motion detection, Tampering, Audio detection,
 Cross Line, intrusion detection(based on human body detection).
 Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,
 Zaštita: IP67
 Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**
 Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH
 (ne kondenzujuće)
 Dimenzije (ΦxV): Φ109 x 83mm (Φ4.3" x 3.3") 0.37kg
 Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN,
 TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN,
 TR-CM24-IN

NEMA NA STANJU

216,00 180,00



IPC328SB-ADF28K-I0**8MP HD Intelligent IR Fixed Dome Network Camera**

High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG

Intelligent perimeter protection, include cross line, intrusion,
enter area, leave area detection

Based on target classification, smart intrusion prevention significantly
reduce false alarm caused by leaves, birds and lights etc., accurately
focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Alarm:1 in/1 out, Audio: 1 in/1 out
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 256 G Micro SD card
IK10 vandal resistant and IP67 protection

229,20 191,00

**BULLET IP KAMERE****IPC2122LB-SF40-A****2 MP IR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,
Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 4.0mm@F2.0
Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, ICMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP

81,60 68,00

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection

Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5,5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 161 × 63 ×62mm težina: 0,27kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

**IPC2122LB-SF28-A 2MP****2 MP IR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,
Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm@F2.0
Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, ICMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP,

81,60 68,00

UPnP, HTTP

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection

Ostale karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5,5W**

Radna temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 161 × 63 ×62mm težina: 0,27kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

**IPC2122LB-AF28WK-G****2 MP IR Fiksna Bullet Mrežna WiFi Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 20fps
Čip: 1/2.9", progressive scan , 2.0 megapixel, CMOS
Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm @F2.0
Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB

Protokoli:IPv4, ICMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS,

93,60 78,00

SMTP, SSL/TLS, SNMP.

Mrežni standardi: ONVIF (Profile S, Profile G, Profile T), API, SDK

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection,Tampering alarm

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 172 × 76 × 72mm težina: 0,25kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN



IPC2122LB-AF28K-WL
2MP HD ColorHunter Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.9"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra H.265,H.265, H.264
 Built-in Mic
 i1050 Warm Light, up to 30m (98ft) warm light distance
 2D/3D DNR (Digital Noise Reduction)
 Support 128GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

96,00 80,00

IPC2122LE-ADF28KMC-WL
2MP HD ColorHunter Mini IR Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8"CMOS sensor
 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 i1028 Built-in Mic & Speaker
 Smart IR, up to 30m (98ft) IR distance
 White Light, up to 30m (98ft) white light distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

102,00 85,00

IPC2123LB-AF28KM-G
3MP HD Fixed IR Bullet Network Camera

High quality image with 3MP, 1/2.7"CMOS sensor
 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Support 9:16 Corridor Mode
 i1037 Built-in Mic
 Smart IR, up to 30m (99ft) IR distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

84,00 70,00

IPC2124LB-SF28-A
High quality image with 4MP, 1/3.0"CMOS sensor

4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 i1011 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

84,00 70,00

IPC2124LB-SF28KM-G
4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/3"CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 i1036 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 IP67 protection
 3-Axis

88,80 74,00

IPC2124LE-ADF28KM-G**4 MP Mini IR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 4MP (2688*1520)@ 30/25fps
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 ~ 1/10000s
 Optika: 2.8mm@F1.6
 Osetljivost: Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD do 256GB
 Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP
 Mrežni standardi: ONVIF (Profile S, Profile T), API
 Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering detection, Audio detection, Cross line, Intrusion detection

Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Integriran mikrofon, Corridor mode 9:16

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 190×73×71mm težina: 0.45kg

Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

NEMA NA STANJU

147,60 123,00

I1027

**IPC2314LE-ADF28KM-WL****4MP HD ColorHunter Fixed Bullet Network Camera**

High quality image with 4MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG

Colorhunter technology ensures 24-hour full-color images

120dB true WDR technology enables clear image in strong light scene

I1029 Support 9:16 Corridor Mode

159,60 133,00

Built-in Mic

White Light, up to 30m white light distance

Supports 128 GB Micro SD card

IP67 protection

Support PoE power supply

3-Axis

**IPC2324LBR3-SPZ28-D****4 MP IR Varifokalna Bullet Mrežna Kamera**

Rezolucija snimanja: 4MP (2592*1520), Max 20fps;
 Čip: 1/3", 4.0 megapixel, progressive scan, CMOS
 Šater: Auto/Manual, 1 ~ 1/10000s
 Optika: 2.8 ~ 12mm, motorizovani zoom
 Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

156,00 130,00

5865

Smart funkcije: **Intrusion Detection, Motion detection, Tampering alarm.**

Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask,

ROI.

Zaštita: IP67

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**

Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 240.3 × 86.4 × 75.6mm, težina: 1kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR-JB06-A-IN

**IPC2125LE-ADF28KM-G****5MP HD Mini IR Fixed Bullet Network Camera**

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG

IC domet: do 50m

EasyStar technology ensures high image quality in low illumination environment

I1041

120dB true WDR technology enables clear image in strong light scene

159,60 133,00

Support 9:16 Corridor Mode

Built-in Mic

Smart IR, up to 50m (164ft) IR distance

Supports 256 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis



IPC2325LB-ADZK-G

i1035

5 MP HD IR Varifokalna Bullet Mrežna Kamera

Rezolucija snimanja: 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps; 2MP

(1920*1080)@30/25fps

Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS

Šator: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens

Osetljivost: Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,

SSL, QoS.

180,00 150,00

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection(based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 8.5W

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 206 × 74 × 74mm (8.1" × 2.9" × 2.9"), 0.55kg

Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

IPC2128LE-ADF28KM-G

i1012

4K 8MP Mini Flksna Bullet Mrežna kamera

Rezolucija snimanja: 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps

Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS

Šator: Auto/Manual, 1 ~ 1/100000s

Optika: 4mm@1.6, Fixed-focal

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,

SSL, QoS.

211,20 176,00

Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection(based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6.5W

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 190×73×71mm (7.5"×2.9"×2.8"), 0.45kg

Kompatibilni nosači i pribor: TR-JB05-B-IN, TR-UP06-C-IN, TR-A01-IN



PTZ KAMERE

IPC6312LFW-AX4C-VG



7655

2 MP Outdoor PTZ kamera sa integriranom sirenom, dolazi sa nosacem

Rezolucija snimanja: 1080P (1920*1080), Max 30fps

Čip: 1/2.8", progressive scan , 2.0 megapixel, CMOS

Shutter: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom

PTZ komande: 255 presesta, Home pozicija, 16 patrola

Osetljivost: 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 50m i toplu svetlo do 10m

Interfejsi: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, Reset dugme, Ugradjen mikrofon i zvucnik

Protokoli: IPv4, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS,

SMTP , 802.1x , SNMP, SSL

Mrežni standardi: ONVIF(Profile S, Profile G, Profile T), API

PTZ funkcije: Preset patrol, Route patrol (256 presesta)

Kompresija: Ultra 265, H.265, H.264, MJPEG

324,00 270,00

Smart funkcije: Motion detection, Tampering, Audio detection,Deep Learning, Smart Intrusion Prevention(Cross Line, Enter Area, Leave Area, Intrusion), People counting (Deep Learning), People Flow Counting (Deep Learning), Crowd Density Monitoring

(Deep Learning),Face Capture,Auto Tracking (Deep Learning)

Kamera poseduje integriranu sirenu od 52db, kao i mikrofon i zvucnik sa mogucnoscu da se izabere jedna od 10 poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno područje

(moguce ubaciti jednu poruku na srpskom ili nekom drugom jeziku)

Zaštita: IP66

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE802.3 at), 15W

Radna Temperatura: -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≈95% RH (ne kondenzujuće)

Dimenzije: Φ133mm*269.4mm (Φ5.2"x 10.6"), 0.87kg

Kompatibilni nosači i pribor: TR-JB07-D-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN



UNIARCH

Uho-S2-M3



i1051

High quality image with 3MP, 1/3"CMOS sensor

3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720) @30/25/fps

Ultra 265, H.265, H.264

45,00 37,50

Built-in Mic & Speaker, support two-way audio, offer better interaction

IR night vision, up to 10m (33ft) IR distance

Support 256 G Micro SD card

Wi-Fi connection and easy installation



Uho-P1A-M3F4D



i1052

High quality image with 3MP, 1/2.8"CMOS sensor

2304*1296@20fps in the main stream

Ultra 265, H.265, H.264

110,00 91,67

Support digital WDR (Wide Dynamic Range)

Built-in Mic & Speaker, support two-way audio, offer better interaction

Support sound and light warning, makes warning and alarming more noticeable

Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, suitable for more scenes

Self-contained bracket, support two kinds of mounting

Supports 256 GB Micro SD card

Wi-Fi connection and easy installation

IP66 ingress protection

The front face is made of grapheme, which has better heat dissipation and more

Environmental protection



NVR UREDJAJI

4 KANALNI

NVR301-04S3

4-ch NVR

Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Ulažno/Izlazni saobraćaj: 64/48Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection

ONVIF conformance: Profile S, Profile G, Profile T

108,00 90,00

i1049

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

NVR301-08S3**8-ch NVR**

Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulažno/Izlazni saobraćaj: 64/48 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0..

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 48V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x 240mm x 46mm, Težina 1Kg

126,00 105,00

**NVR501-16B****16-ch NVR**

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulažno/Izlazni saobraćaj: 80/64 Mbps

Video kompresija: Ultra 265/H.265/H.264

Video/audio izlazi: HDMI (4K) / HD, VGA

Smart Funkcije: Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, UMD(Ultra Motion Detection)

Statisticke analize: People counting

Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP

Hard disk prostor: 2 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x 222mm x 47mm, Težina 0,98Kg

252,00 210,00

**NVR304-32X****32-ch NVR**

32-KANALNI MREŽNI SNIMAČ

Rezolucija snimanja:

12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulažno/Izlazni saobraćaj: 384/384 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed, Face search, Behavior search

Statisticke analize: People counting

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1x RS485, 1x

RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5

Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 442mm x426mmx 89mm, Težina 5,7Kg

768,00 640,00

**HARD DISKOVI**

Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 500 GB

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 1 TB

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

SEAGATE 1 TB

SEAGATE, 1TB , 7200RPM, SATA III, 32MB

[KONTAKT](#)

**HIKVISION WD10PURX-78
PURPLE 1 TB**

3861 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

90,00 75,00

**HIKVISION WD20PURX-78
PURPLE 2 TB**

4091 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

116,40 97,00

**HIKVISION WD30PURX-78
PURPLE 3TB**

3523 Western Digital, 3TB Purple, IntelliPower, SATA III, 64MB

157,20 131,00

**HIKVISION WD40PURX-78
PURPLE 4 TB**

4195 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB

181,20 151,00

**HIKVISION WD60PURX-78
PURPLE 6 TB**

3844 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB

252,00 210,00

**HIKVISION WD81PURX-78
PURPLE 8 TB**

6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB

378,00 315,00

TF-64G-T-L

Uniview memorijска kartica

Kapacitet: 64GB

I1021 Maksimalna brzina čitanja: 90MB/s
Maksimalna brzina pisanja: 65MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g

10,80 9,00



TF-128G-T-L

Uniview memorijска kartica

Kapacitet: 128GB

I1022 Maksimalna brzina čitanja: 100MB/s
Maksimalna brzina pisanja: 80MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g

19,20 16,00



Uniview POE SVIĆEV

NSW2020-6T-POE-IN



I1023	6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava: IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm	81,60	68,00
-------	---	-------	-------

NSW2020-10T-POE-IN



I1024	10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava: IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm	144,00	120,00
-------	--	--------	--------

NSW2010-16T2GC-POE-IN



I6334	16×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta Podržava: IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga porta: 250W Dimenzije: 440mm x 207mm x 45mm Moguća rekonstrukcija 19", dolazi uz switch	432,00	360,00
-------	--	--------	--------


NSW2020-24T1GT1GC-PO



I110682	24PoE+1GP+2GC Switch • 24×100Mbps PoE ports (RJ45) + 1×1000Mbps Gigabit Ethernet ports + 1×1000Mbps Combo ports • Switching kapacitet: 8.8Gbps • Performanse prosledivanja: 6.55Mpps • Packet Buffer: 4M bit • Maks. PoE Power: 370W • Višestruki režimi rada koji zadovoljavaju vaše poslovne potrebe: predstavljeno (normalan režim), VLAN (bezbedni režim), EKSTEND (režim nadzora) • Podržava port traffic kontrolu • Podrška za bezbedni režim, svi portovi za downlink mogu da komuniciraju samo sa uplink port • Udaljenost prenosa do 250m u režimu nadzora • Podržava optimizaciju bafera • Potpuno metalno kucište, sigurno i pouzdano • Dimenzije: 440×244.8×44mm • Težina: 2.93KG	684,00	570,00
---------	--	--------	--------

KABLOVI

UNV Cat6 (UTP), CCA




CAB-LC3100B-CCA-IN

Conductor material: CCA(Copper content: 27%)
 Insulation material: HDPE
 Packing length: 305±1 m
 Sheath material: PVC

i1044

0,30 0,250

UNV Cat5e (UTP), BC




CAB-LC2100A-E2-ECA-IN

Conductor material: OFC (Oxygen free copper)
 Insulation material: HDPE
 Packing length: 305±1 m
 Sheath material: PVC (complies RoHS/REACH)

i1045

0,54 0,450

UNV Cat6 (UTP), BC



CAB-LC3100A-EC-ECA-IN

Conductor material: OFC (Oxygen free copper)
 Insulation material: HDPE
 Packing length: 305±1 m
 Sheath material: PVC (complies RoHS/REACH)

i1046

0,78 0,650

KUĆIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633

Razvodna kutija za spoljašnju montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.

3,60 3,00

DOZNA ZA KAMERE G153



8644

Razvodna kutija za spoljašnju montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.

3,20 2,67

DOZNA ZA KAMERE BA-02



8645

Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.

3,00 2,50

TR-JB05-B-IN



5861

Nosač za Dome kamere serije IPC21XX
 Dimenzijs: Ø104.4mm*54.5mm
 Težina: 0.36kg
 Materijal: Aluminijum

16,80 14,00



5879	Nosač za Dome kamere serije IPC32x i IPC31x Dimenzije: φ106,6mm*36mm Težina: 0,2kg Materijal: Aluminijum	12,00	10,00
------	---	-------	-------

KONEKTORI**BNC NA LEMLJENJE
SA ŠRAFOM**

3299	BNC konektor muški sa šrafom. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

BNC NA LEMLJENJE

2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,54	0,45
------	--	------	------

BNC KONEKTOR

30020	BNC konektor muški na šraf.	0,50	0,42
-------	-----------------------------	------	------

BNC NA KRIMP RG59

2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,60	0,50
------	---	------	------

BNC MUŠKI- F ŽENSKI

1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,60	0,50
------	--	------	------

BNC NASTAVAK

4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

**F KONEKTOR na krimp
RG6**

2559	F konektor za RG6 kabl. Pakovanje 100 kom.	0,14	0,12
------	---	------	------

F KONEKTOR na krimp RG59

1796	F konektor za RG59 kabl. Pakovanje 100 kom.	0,14	0,12
------	--	------	------

RF METALNI G MUŠKI

4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,35	0,29
------	--	------	------

RCA MUŠKI-F ŽENSKI

4446	RCA muški - F ženski konektor Pakovanje 100 kom.	0,53	0,44
------	---	------	------

F NASTAVAK

3300	F nastavak Ženski - Ženski Pakovanje 100 kom.	0,22	0,18
------	--	------	------

**F KONEKTOR
KOMPRESIONI RG6 XL**

1625	Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.	0,44	0,37
------	--	------	------

**F KONEKTOR
KOMPRESIONI RG11 XL**

1627	Profesionalni PPC F konektor za RG11 kabl.	2,96	2,47
------	--	------	------

**F KONEKTOR
KOMPRESIONI RG59 XL**

1624	Profesionalni PPC F konektor za RG59 kabl. Pakovanje 50 kom.	0,47	0,39
------	---	------	------

DC KABL-MUŠKI

1387	DC utikač-muški	0,48	0,40
------	-----------------	------	------

DC KABL-ŽENSKI

5044	DC utikač-ženski	0,48	0,40
------	------------------	------	------

DC KONEKTOR MUŠKI

3425	DC konektor Muški	0,83	0,69
------	-------------------	------	------

DC KONEKTOR ŽENSKI

4197	DC konektor ženski.	0,83	0,69
------	---------------------	------	------

DC RAZDELNIK 1-4

1388	1 DC utičnica - 4 DC utikača	1,99	1,66
------	------------------------------	------	------

DC RAZDELNIK 1-8

1389	1 DC utičnica - 8 DC utikača	3,97	3,31
------	------------------------------	------	------

CAT7 RJ45

	Mrežni konektor RJ45 kategorija 7	0,50	0,42
--	-----------------------------------	------	------

CAT5 RJ45

0067	Mrežni konektor RJ45	0,05	0,04
------	----------------------	------	------

Telefonski konektor RJ11



0068	Telefonski konektor RJ11	0,02	0,02
------	--------------------------	------	------

DODATNA OPREMA

ŠTAMPAČ P-TOUCH E100



4663	Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manualni sekaci Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu	106,56	88,80
------	--	--------	-------

MIKROFON LY-501C



2584	Audio modul sa izvedenim konektorima. Napajanje 12 V DC	3,97	3,31
------	--	------	------

MIKROFON LY-502B



2583	Audio modul plastični sa trimerom. Napajanje 12 V DC	6,00	5,00
------	---	------	------

MIKROFON LY-506



1937	Audio modul metalni sa trimerom. Napajanje 12 V DC	10,00	8,33
------	---	-------	------

PoE Extender



9995	Model: LN-POEPL03S PoE In: 44-57V/30W PoE Out (1-3) : 44-57V/25W Support: 10/100 Mbps IEEE802.3af/at	30,00	25,00
------	---	-------	-------

DS-2FP2020



5222	Vrlo osetljivi omnidirekcioni mikrofon. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).	36,00	30,00
------	---	-------	-------

DH-PFM800-4K (par)



3632	One (1) Channel Balun Real-time Transmission over UTP CAT5E/6 Cable Compatible with HDCVI, TVI, AHD, and CVBS Video Formats Transmission Distance at 4K: 200 m (656 ft) External Power Supply not Required	6,90	5,75
------	--	------	------

OG razvodna kutija 100x100



00091	Razvodna kutija 100x100	1,80	1,50
-------	-------------------------	------	------

OG razvodna kutija 80x80



00092	Razvodna kutija 80x80	1,10	0,92
-------	-----------------------	------	------

OG razvodna kutija 160x100x74



00093	Razvodna kutija 160x100x74	3,00	2,50
-------	----------------------------	------	------

06 razvodna kutija 160x100x48

00094 Razvodna kutija 160x100x48

2,64 2,20

**ALAT ZA KRIMP
RG6, RG11,RG59**

3302 Alat za krimpovanje RG6, RG11,RG59 konektora

48,00 40,00

STRIPER ZA KABLOVE RG59,RG6

3301 Alat za stripovanje RG59,RG6 kablova

20,40 17,00

**ALAT KOMPRESIONI
ZA RG59, RG6**

1629 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake.

37,92 31,60

**ALAT KOMPRESIONI, ZA
RG6,RG11,RG59**

3796 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6,RG11,RG59 XL oznake.

54,34 45,28

**KLEŠTA ZA KRIMPOVANJE
KOMPLET**

5790 Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečicom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)

28,68 23,90

NAPAJANJA**XED-1212S**

Ulag: 90V-264V

Izlag: 12V , 1A

Snaga: 12W

Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm

Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

6,00 5,00

XED-2012S

Ulag: 90V-264V

Izlag: 12V , 2A

Snaga: 24W

Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm

Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

8,04 6,70

XED-3013S

Ulag: 90V-264V

Izlag: 12V , 3A

Snaga: 36W

Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm

Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

12,60 10,50

XED-5013S

Ulag: 100V-240V

Izlag: 12V , 5A

Snaga: 60W

Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm

Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

16,20 13,50

XED-6013B

Ulag: 100V-240V

Izlag: 12V , 6A

Snaga: 72W

Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm

Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

20,40 17,00

9-KANALNO NAPAJANJE**XED-10A12VX-9L**

Snaga: 120W

Ulag: 100-240V 50-60Hz

Izlag: 12V 10A 9 kanala

Dimenzije: 237*213*70mm

Neto težina: 1800g

Napomena: Sadrži AC kabl

82,80 69,00

18-KANALNO NAPAJANJE
XED-15A12VX-18L



5114	Snaga: 180W Ulaz: 100-240V 50-60Hz Izlaz: 12V 15A 18 kanala Dimenziije: 240*218*70mm Neto težina: 2300g Napomena: Sadrži AC kabl	94,80	79,00
------	---	-------	-------

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD.
Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cenu bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs