

CENOVNIK UNIVIEW VIDEO NADZORA - 15.05.2024.



NAZIV	ŠIFRA	OPIS	CENA
SNIMACI			sa PDV bez PDV
4 KANALNI			
XVR301-04G3			



4-CH Hybrid DVR

Podržan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal) 4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podržan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6)

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulažno/Izlazni saobraćaj: 16/48 Mbps

87,60 73,00

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x 226mm x 47mm (10.2" x 8.9" x 1.8"), 1.1kg



XVR301-04Q3



4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamere: do 8mp (2 IP kamere ili svih 6)

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

I1032 Ulažno/Izlazni saobraćaj: 48/60 Mbps

123,60 103,00

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x 226mm x 47mm



8 KANALNI

XVR301-08G3



8-CH Hybrid DVR

Podržava: TVI,AHD, CVI, CVBS

Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF

Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)

Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio

I1025	Ulažno/Izlazni saobraćaj: 32/64 Mbps Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP Hard disk: 1 sata HDD do 8TB Napajanje 12V DC, Potrošnja 8W bez HDD Radna temperatura: -10 °C ~ +55 °C Dimenzije: 260mm x226mmx 47mm	126,00	105,00
-------	--	--------	--------



XVR301-08Q3



8-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP / 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)

Video kompresija: H.265, H.264

Video/audio ulazi: 8ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

I1033	Ulažno/Izlazni saobraćaj: 40/64 Mbps Smart funkcije: Motion detection, video loss detection, audio detection, Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP Hard disk: 1 sata HDD do 8TB kapaciteta Napajanje 12V DC, Potrošnja 10W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm x226mmx 47mm	192,00	160,00
-------	--	--------	--------



16 KANALNI

XVR301-16G3



16-CH Hybrid DVR

Podržava: TVI, AHD, CVI, CVBS, IP cameras

Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF

IP kamere: do 8 IP kamere ili svih 16

Video/audio ulazi: 16-ch BNC / 1-ch RCA

Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio

I1026	Ulažno/Izlazni saobraćaj: 40/64 Mbps Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP Hard disk: 1 SATA HDD do 8TB Napajanje 12V DC, Potrošnja 10W bez HDD Radna temperatura: -10 °C ~ +55 °C Dimenzije: 260mm x226mmx 47mm	204,00	170,00
-------	--	--------	--------



XVR302-16Q3



16-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava 8MP@15fps na prva 4 kanala

Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.

Ulažno/Izlazni saobraćaj: 72/80 Mbps

Video kompresija: H.265/H.264 video kompresija,

Video/audio ulazi: 16ch BNC, 1ch RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA

I1034	Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 2 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 380mm x315mmx 53mm, Težina 1.9Kg	306,00	255,00
-------	---	--------	--------



ANALOGNE KAMERE

UAC-T112-F28



I1004

2MP HD Fixed IR Turret Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

28,80 24,00

UAC-B112-F28



I1000

2MP HD Fixed IR Mini Bullet Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

28,80 24,00

UAC-T112-F28-W



I1005

2MP ColourHunter HD Fixed Turret Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

NEMA NA STANJU

31,20 26,00

UAC-B112-F28-W



I1001

2MP ColourHunter HD Fixed Mini Bullet Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

31,20 26,00

UAC-D122-AF28M



I1017

2MP LightHunter HD IR Fixed Dome Analog Camera

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal/vertical flip
OSD configuration menu, easy to operate
Water and dust resistant (IP67) and vandal-resistant (IK10)
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal base and metal housing
3-Axis

46,80 39,00

UAC-T122-AF28LM



I1054

2MP LightHunter HD IR Fixed Turret Analog Camera

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
3-Axis

49,20 41,00

UAC-B122-AF28LM**2MP LightHunter HD IR Fixed Mini Bullet Analog Camera**

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog

49,20 41,00

I1053

**UAC-T122-AF28M-W****2MP ColorHunter HD Fixed Turret Analog Camera**

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing
3-Axis

52,80 44,00

I1016

**UAC-B122-AF28M-W****2MP ColorHunter HD Fixed Mini Bullet Analog Camera**

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing

52,80 44,00

I1014

**UAC-B122-AF40M-W****2MP ColorHunter HD Fixed Mini Bullet Analog Camera**

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing

52,80 44,00

I1015

**UAC-T115-F28****5MP HD Fixed IR Turret Analog Camera**

5MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

43,20 36,00

NEMA NA STANJU

I1005

**UAC-B115-F28****5MP HD Fixed IR Mini Bullet Analog Camera**

5MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

43,20 36,00

I1002



UAC-T115-F28-W

UNV

UAC-B115-F28-W

UNV

UAC-T125-AF28LM

UNV

UAC-B125-AF28LM

UNV

UAC-T125-AF28M-W

UNV

UAC-T125-AF28M-W-Black

UNV

5MP ColourHunter HD Fixed Turret Analog Camera

5MP high quality image

TVI/AHD/CVI/CVBS

- I1007 Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

45,60 38,00

5MP ColourHunter HD Fixed Mini Bullet Analog Camera

5MP high quality image

TVI/AHD/CVI/CVBS

- I1003 Supports white light illumination, 24/7 full-color imaging
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

45,60 38,00

5MP LightHunter HD IR Fixed Turret Analog Camera

High quality imaging with 5MP resolution

TVI/AHD/CVI/CVBS

- I1056 Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
3-Axis

58,80 49,00

5MP LightHunter HD IR Fixed Mini Bullet Analog Camera

High quality imaging with 5MP resolution

TVI/AHD/CVI/CVBS

- I1055 Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

58,80 49,00

5MP ColorHunter HD Fixed Turret Analog Camera

5MP high quality imaging

TVI/AHD/CVI/CVBS

- I1020 Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing
3-Axis

NEMA NA STANJU

62,40 52,00

5MP ColorHunter HD Fixed Turret Analog Camera

5MP high quality imaging

TVI/AHD/CVI/CVBS

- I1057 Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing
3-Axis

62,40 52,00

UAC-B125-AF28M-W**5MP ColorHunter HD Fixed Mini Bullet Analog Camera**

5MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing

62,40 52,00

UAC-B125-AF40M-W
**5MP ColorHunter HD Fixed Mini Bullet Analog Camera**

5MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing

62,40 52,00

DOME IP KAMERE**IPC322LB-SF28-A****2 MP IR Fiksna Dome Mrežna Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 30fps
Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8mm@F2.0
Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet
Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP,
7059 HTTP Mrežni standardi: ONVIF (Profile S, Profile T), API
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: Motion detection
Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI.
Zaštitna IP67, IK10
Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5W
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije Φ109 x 81mm težina: 0,35kg
Kompatibilni nosači i pribor: TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UM06-EIN, TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

81,60 68,00

IPC322LB-AF28WK-G**2 MP IR Fiksna Anti Vandal Dome Mrežna Kamera, WiFi**

Rezolucija snimanja: 1080P (1920*1080), Max 20fps
Čip: 1/2.9", progressive scan , 2.0 megapixel, CMOS
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8mm @F2.0
Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP.
Mrežni standardi: ONVIF (Profile S, Profile G, Profile T), API, SDK
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: Motion detection,Tampering alarm
Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI
Zaštitna IP67, IK10
Napajanje i potrošnja: DC 12V±25%
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije (ΦxV): Φ109 x 83mm težina: 0,32kg
Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

93,60 78,00



IPC3612LB-ADF28K-G**2MP HD IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.7"CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Smart IR, up to 30m (98ft) IR distance
Built-in Mic
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1042

90,00 75,00

IPC3612LE-ADF28KMC-WL**BLACK****2MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.8"CMOS sensor
2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic & Speaker
Smart IR, up to 30m (98ft) IR distance
White Light, up to 30m (98ft) white light distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1039

96,00 80,00

IPC3612LE-ADF28KC-WL**2MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.8"CMOS sensor
2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic & Speaker
Smart IR, up to 30m (98ft) IR distance
White Light, up to 30m (98ft) white light distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1038

99,00 82,50

IPC3614LB-SF28-A**4MP Fixed Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
Support PoE power supply
3-Axis

I1030

84,00 70,00

IPC3614LE-ADF28KC-WL**4MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 4MP, 1/3"CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic & Speaker
Smart IR, up to 30m (98ft) IR distance
White Light, up to 30m (98ft) white light distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1040

150,00 125,00

IPC324LB-SF28-A**4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: ④4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps;

2MP (1920*1080)@30/25fps

Čip: 1/3", progressive scan , 4.0 megapixel, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm @F2.0

Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS,

DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS

Mrežni standardi: ONVIF (Profile S, Profile T), API, SDK

Kompresija: H.265, H.264,

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD,

Privacy mask, ROI, Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH

(ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN,

TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

NEMA NA STANJU

84,00 70,00



I1010

IPC324LE-DSF28K-G**4MP HD Vandal-resistant IR Fixed Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor

4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;

Ultra 265, H.265, H.264, MJPEG

Easystar technology ensures high image quality in low illumination environment

120dB true WDR technology enables clear image in strong light scene

7055A Support 9:16 Corridor Mode

132,00 110,00

Smart IR, up to 30m (98ft) IR distance

Supports 256 G Micro SD card

IK10 vandal resistant

IP67 protection

Support PoE power supply

3-Axis

IPC3234LR3-VSPZ28-D**4 MP IR Varifokalna Dome Mrežna Kamera**

Rezolucija snimanja: 4MP (2592*1520), Max 20fps;

Čip: 1/3", 4.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8 ~ 12mm, motorizovani zoom

Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

5595 Mrežni standardi: ONVIF (Profile S, Profile T), API

168,00 140,00

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6W**

Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ148 x 111.3mm, težina: 0.92kg

Kompatibilni nosači i pribor: TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-

JB07/WM04-B-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN



IPC328LE-ADF28KM-G**4K 8MP Antivandal Fiksna Dome Mrežna kamera**

Rezolucija snimanja: 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;

4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps

Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm@F1.6, Fixed-focal

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb,

Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP,

RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.

I1013 Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection,

Cross Line, intrusion detection(based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6.5W

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH

(ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 83mm (04.3" x 3.3") 0.37kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN,

TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN,

TR-CM24-IN

NEMA NA STANJU

216,00 180,00

IPC328SB-ADF28K-I0**8MP HD Intelligent IR Fixed Dome Network Camera**

High quality image with 8MP, 1/2.7"CMOS sensor

8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;

4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps

Ultra 265, H.265, H.264, MJPEG

Intelligent perimeter protection, include cross line, intrusion,

enter area, leave area detection

I1043 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle

Intelligent People Flow Counting and Crowd Density Monitoring

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Alarm:1 in/1 out, Audio: 1 in/1 out

Built-in Mic

Smart IR, up to 30m (98ft) IR distance

Supports 256 G Micro SD card

IK10 vandal resistant and IP67 protection

229,20 191,00

BULLET IP KAMERE**IPC2122LB-SF40-A****2 MP IR Fiksna Bullet Mrežna Kamera**

Rezolucija snimanja: 1080P (1920*1080), Max 30fps

Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS,

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 4.0mm@F2.0

Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

7056 Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP

Mrežni standardi: ONVIF (Profile S, Profile T), API

Komprezija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection

Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5,5W

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 161 × 63 ×62mm težina: 0,27kg

Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN

81,60 68,00



IPC2122LB-SF28-A 2MP

8031  2 MP IR Fiksna Bullet Mrežna Kamera Rezolucija snimanja: 1080P (1920*1080), Max 30fps Čip: 1/2.8", 2.0 megapixel, progressive scan, CMOS, Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm@F2.0 Osetljivost: Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet Protokoli: IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP Mrežni standardi: ONVIF (Profile S, Profile T), API Kompresija: Ultra 265, H.265, H.264, MJPEG Smart funkcije: Motion detection Ostale karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI. Zaštita: IP67 Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5,5W Radna temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće) Dimenzije (DxŠxV): 161 × 63 × 62mm težina: 0,27kg Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN	81,60 68,00
--	---------------------------

IPC2122LB-AF28WK-G

i1009  2 MP IR Fiksna Bullet Mrežna WiFi Kamera Rezolucija snimanja: 1080P (1920*1080), Max 20fps Čip: 1/2.9", progressive scan, 2.0 megapixel, CMOS Šater: Auto/Manual, 1 ~ 1/100000s Optika: 2.8mm @F2.0 Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter IC domet: do 30m Interfejsi: 10/100M Base-TX Ethernet, Slot za Micro SD slot do 128GB Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP	93,60 78,00
---	---------------------------

IPC2122LB-AF28K-WL

i1050  2MP HD ColorHunter Mini Fixed Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps Ultra 265, H.265, H.264, MJPEG Built-in Mic & Speaker Warm Light, up to 30m (98ft) warm light distance 2D/3D DNR (Digital Noise Reduction) Support 128GB Micro SD card IP67 protection Support PoE power supply 3-Axis	96,00 80,00
--	---------------------------

IPC2122LE-ADF28KMC-WL

i1028  2MP HD ColorHunter Mini IR Fixed Bullet Network Camera High quality image with 2MP, 1/2.8"CMOS sensor 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps; Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic & Speaker Smart IR, up to 30m (98ft) IR distance White Light, up to 30m (98ft) white light distance Supports 128 G Micro SD card IP67 protection Support PoE power supply 3-Axis	102,00 85,00
---	----------------------------

IPC2123LB-AF28KM-G

i1037  3MP HD Fixed IR Bullet Network Camera High quality image with 3MP, 1/2.7"CMOS sensor 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; Ultra 265, H.265, H.264, MJPEG Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card IP67 protection Support PoE power supply 3-Axis	84,00 70,00
---	---------------------------

IPC2124LB-SF28-A

High quality image with 4MP, 1/3.0"CMOS sensor	
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps	
H.265, H.264	
I1011	Smart IR, up to 30m (98ft) IR distance
	Day/night functionality
	2D/3D DNR (Digital Noise Reduction)
	IP67 protection
	DC12V or PoE(IEEE 802.3af) power supply
	3-Axis
	84,00 70,00



IPC2124LB-SF28KM-G

4MP Mini Fixed Bullet Network Camera	
High quality image with 4MP, 1/3"CMOS sensor	
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps	
I1036	Ultra 265, H.265, H.264, MJPEG
	Smart IR, up to 30m (98ft) IR distance
	Supports 128 G Micro SD card
	Support PoE power supply
	IP67 protection
	3-Axis
	88,80 74,00



IPC2124LE-ADF28KM-G

4 MP Mini IR Flksna Bullet Mrežna Kamera	
Rezolucija snimanja: 4MP (2688*1520)@ 30/25fps	
Čip: 1/3", 4.0 megapixel, progressive scan, CMOS	
Šater: Auto/Manual, 1 ~ 1/100000s	
Optika: 2.8mm@F1.6	
Osetljivost: Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter	
IC domet: do 50m	
Interfejsi: 10/100M Base-TX Ethernet, Micro SD do 256GB	
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP	
Mrežni standardi: ONVIF (Profile S, Profile T), API	
Kompresija: Ultra 265, H.265, H.264, MJPEG	
Smart funkcije: Motion detection, Tampering detection, Audio detection, Cross line, Intrusion detection	
Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Integriran mikrofon, Corridor mode 9:16	
Zaštita: IP67	
Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6W	
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)	
Dimenzije (DxŠxV): 190x73x71mm težina: 0,45kg	
Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN	
NEMA NA STANJU	
	147,60 123,00



IPC2314LE-ADF28KM-WL

4MP HD ColorHunter Fixed Bullet Network Camera	
High quality image with 4MP, 1/1.8"CMOS sensor and F1.0 large aperture lens	
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;	
I1029	Ultra 265, H.265, H.264, MJPEG
	Colorhunter technology ensures 24-hour full-color images
	120dB true WDR technology enables clear image in strong light scene
	Support 9:16 Corridor Mode
	Built-in Mic
	White Light, up to 30m white light distance
	Supports 128 GB Micro SD card
	IP67 protection
	Support PoE power supply
	3-Axis
	159,60 133,00



IPC2324LBR3-SPZ28-D

5865

4 MP IR Varifokalna Bullet Mrežna Kamera

Rezolucija snimanja: 4MP (2592*1520), Max 20fps;
Čip: 1/3", 4.0 megapixel, progressive scan, CMOS
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8 ~ 12mm, motorizovani zoom
Osetljivost: 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet, MicroSD, do 256GB
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
Mrežni standardi: ONVIF (Profile S, Profile T), API
Kompresija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: **Intrusion Detection, Motion detection, Tampering alarm.**
Ostale Karakteristike: **2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.**
Zaštita: IP67
Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 6.5W**
Radna Temperatura: -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije (DxŠxV): 240.3 × 86.4 × 75.6mm, težina: 1kg
Kompatibilni nosači i pribor: TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR-JB06-A-IN

156,00

130,00



IPC2125LE-ADF28KM-G

I1041

5MP HD Mini IR Fixed Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
IC domet: do 50m
EasyStar technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

159,60

133,00



IPC2325LB-ADZK-G

i1035

5 MP HD IR Varifokalna Bullet Mrežna Kamera

Rezolucija snimanja: 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@ 30/25fps
Čip: 1/2.7", 5.0 megapixel, progressive scan, CMOS
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens
Osetljivost: Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR on
IC domet: do 50m
Interfejsi: 10/100M Base-TX Ethernet, SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
Mrežni standardi: ONVIF (Profile S, Profile T), API
Komprimacija: Ultra 265, H.265, H.264, MJPEG
Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection(based on human body detection).
Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,
Zaštita: IP67
Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 8.5W**
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije (DxŠxV): 206 × 74 × 74mm (8.1" × 2.9" × 2.9"), 0.55kg
Kompatibilni nosači i pribor: TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN

180,00

150,00



**4K 8MP Mini Flksna Bullet Mrežna kamera**

Rezolucija snimanja:8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP

(1920*1080) @30/25fps

Čip: 1/2.7", 8.0 megapixel, progressive scan, CMOS

Šater: Auto/Manual, 1 ~ 1/10000s

Optika: 4mm@@1.6, Fixed-focal

Osetljivost: 0.005Lux (F1.6, AGC ON) 0Lux with IR on

IC domet: do 50m

Interfejsi: 10/100M Base-TX Ethernet,SD Card up to 256Gb, Ugradjen mikrofon, Reset dugme

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,

I1012 SSL, QoS.

211,20 176,00



Mrežni standardi: ONVIF (Profile S, Profile T), API

Kompresija: Ultra 265, H.265, H.264, MJPEG

Smart funkcije: Motion detection, Tampering, Audio detection, Cross Line, intrusion detection(based on human body detection).

Ostale Karakteristike: 2D/3D DNR, 120db WDR, HLC, BLC, OSD, Privacy mask, ROI,

Zaštita: IP67

Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 6.5W

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (DxŠxV): 190×73×71mm (7.5"×2.9"×2.8"), 0.45kg

Kompatibilni nosači i pribor: TR-JB05-B-IN, TR-UP06-C-IN, TR-A01-IN



PTZ KAMERE

**5MP LightHunter Active Deterrence Mini PTZ Camera**

High quality image with 5MP, 1/2.7"CMOS sensor

Ultra 265, H.265, H.264, MJPEG

LightHunter technology ensures ultra-high image quality in low illumination environment

I6800 Up to 120 dB Optical WDR (Wide Dynamic Range)

210,00 175,00

Built-in Mic & Speaker

Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance

Micro SD, up to 256GB

IP66 protection

DC12V or PoE (IEEE 802.3af) power supply

**2*2MP Lighthunter Dual-lens Network PTZ camera**

Fixed camera and PTZ camera integration, dual channels with one IP, look at overall situation and consider details at the same time

High quality image with 2MP,1/2.8" CMOS sensor

1920*1080@25fps in the main stream

I7504 Ultra 265, H.265, H.264, MJPEG

243,60 203,00

4X optical zoom of PTZ channel allows for closer viewing of subjects

Lighthunter technology ensures ultra-high image quality in low illumination environment

Up to 120 dB Optical WDR (Wide Dynamic Range)

Built-in 2*mic & high-power speaker, support two-way audio, has better sound performance

Support ceiling mount and wall mount



UNIARCH



High quality image with 3MP, 1/3"CMOS sensor

3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720) @30/25/fps

Ultra 265, H.265, H.264

I1051 Built-in Mic & Speaker, support two-way audio, offer better interaction

45,00 37,50

IR night vision, up to 10m (33ft) IR distance

Support 256 G Micro SD card

Wi-Fi connection and easy installation





High quality image with 3MP, 1/2.8"CMOS sensor
2304*1296@20fps in the main stream

Ultra 265, H.265, H.264

Support digital WDR (Wide Dynamic Range)

Built-in Mic & Speaker, support two-way audio, offer better interaction

Support sound and light warning, makes warning and alarming more noticeable

i1052 Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance,suitable for more scenes

110,00 91,67

Self-contained bracket, support two kinds of mounting

Supports 256 GB Micro SD card

Wi-Fi connection and easy installation

IP66 ingress protection

The front face is made of grapheme, which has better heat dissipation and more

Environmental protection

NVR UREDJAJI

4 KANALNI

NVR301-04S3

4-ch NVR

Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Ulažno/Izlazni saobraćaj: 64/48Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),

Smart Funkcije:Face detection, Intrusion detection, Cross line detection, Audio detection

ONVIF conformance: Profile S, Profile G, Profile T



i1049 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

108,00 90,00

Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

NVR301-08S3

8-ch NVR

Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulažno/Izlazni saobraćaj: 64/48 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection



i1048 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

126,00 105,00

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 48V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

NVR501-16B

16-ch NVR

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulažno/Izlazni saobraćaj: 80/64 Mbps

Video kompresija: Ultra 265/H.265/H.264

Video/audio izlazi: HDMI (4K) / HD, VGA

Smart Funkcije: Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change



i1047 Detection, Object Left Behind, Object Removed, Auto Tracking, UMD(Ultra Motion Detection)

252,00 210,00

Statisticke analize: People counting

Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP

Hard disk prostor: 2 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 222mm × 47mm, Težina 0,98Kg

NVR304-32X

32-ch NVR
32-KANALNI MREŽNI SNIMAČ
 Rezolucija snimanja:
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Ulazno/Izlazni saobraćaj: 384/384 Mbps
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,
 Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio
 detection, Defocus detection, Scene change detection, Auto tracking, Object left
 behind, Object removed, Face search, Behavior search
 Statisticke analize: People counting
 ONVIF conformance: Profile S, Profile G, Profile T
 Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1x RS485, 1 x
 RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE
 Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5
 Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 442mm x426mmx 89mm, Težina 5,7Kg

768,00 640,00

**HARD DISKOVI****WD GREEN 320 GB**

Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

[KONTAKT](#)**WD GREEN 500 GB**

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

[KONTAKT](#)**WD GREEN 1 TB**

Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

[KONTAKT](#)**SEAGATE 1 TB**

SEAGATE, 1TB , 7200RPM, SATA III, 32MB

[KONTAKT](#)**HIKVISION WD10PURX-78****PURPLE 1 TB**

3861 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

90,00 75,00

HIKVISION WD20PURX-78**PURPLE 2 TB**

4091 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

116,40 97,00

HIKVISION WD30PURX-78**PURPLE 3TB**

3523 Western Digital, 3TB Purple, IntelliPower, SATA III, 64MB

157,20 131,00

HIKVISION WD40PURX-78
PURPLE 4 TB



4195 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB 181,20 151,00

HIKVISION WD60PURX-78
PURPLE 6 TB



3844 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB 252,00 210,00

HIKVISION WD81PURX-78
PURPLE 8 TB



6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB 378,00 315,00

TF-64G-T-L

Uniview memorjska kartica

Kapacitet: 64GB

I1021 Maksimalna brzina čitanja: 90MB/s
Maksimalna brzina pisanja: 65MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g 10,80 9,00

TF-128G-T-L

Uniview memorjska kartica

Kapacitet: 128GB

I1022 Maksimalna brzina čitanja: 100MB/s
Maksimalna brzina pisanja: 80MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g 19,20 16,00

Uniview POE SVIĆEV

NSW2020-6T-POE-IN



I1023 6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava:
IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm 81,60 68,00

NSW2020-10T-POE-IN



I1024 10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava:
IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm 144,00 120,00

NSW2010-16T2GC-POE-IN



6334 16×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta Podržava: IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga porta: 250W Dimenzije: 440mm x 207mm x 45mm Moguća rekonstrukcija 19", dolazi uz switch 432,00 360,00

24PoE+1GP+2GC Switch


- 24×100Mbps PoE ports (RJ45) +
- 1×1000Mbps Gigaethernet ports +
- 1×1000Mbps Combo ports
- Switching kapacitet: 8.8Gbps
- Performanse prosljedivanja: 6.55Mpps
- Packet Buffer: 4M bit
- Maks. PoE Power: 370W
- Višestruki režimi rada koji zadovoljavaju vaše poslovne potrebe: podrazumevano (normalan režim), VLAN (bezbedni režim), EKSTEND (režim nadzora)
- Podržava port traffic kontrolu
- podrška za bezbedni režim, svi portovi za downlink mogu da komuniciraju samo sa uplink port
- Udaljenost prenosa do 250m u režimu nadzora
- Podržava optimizaciju bafera
- Potpuno metalno kucište, sigurno i pouzdano
- Dimenzije: 440×244.8×44mm
- Tezina: 2.93KG



i10682	poslovne potrebe: podrazumevano (normalan režim), VLAN (bezbedni režim), EKSTEND (režim nadzora)	684,00	570,00
	• Podržava port traffic kontrolu		
	• podrška za bezbedni režim, svi portovi za downlink mogu da komuniciraju samo sa uplink port		
	• Udaljenost prenosa do 250m u režimu nadzora		
	• Podržava optimizaciju bafera		
	• Potpuno metalno kucište, sigurno i pouzdano		
	• Dimenzije: 440×244.8×44mm		
	• Tezina: 2.93KG		


KABLOVI

UNV Cat6 (UTP), CCA




i1044	CAB-LC3100B-CCA-IN Conductor material: CCA(Copper content: 27%) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC	0,30	0,250
-------	--	------	-------

UNV Cat5e (UTP), BC



i1045	CAB-LC2100A-E2-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,54	0,450
-------	---	------	-------

UNV Cat6 (UTP), BC



i1046	CAB-LC3100A-EC-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,78	0,650
-------	---	------	-------

KUĆIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633	Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00
------	--	------	------

DOZNA ZA KAMERE G153



8644	Razvodna kutija za spoljašnu montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,20	2,67
------	--	------	------

DOZNA ZA KAMERE BA-02

8645	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,00	2,50
------	--	------	------

TR-JB05-B-IN

5861	Nosač za Dome kamere serije IPC21XX Dimenzije: Ø104,4mm*54,5mm Težina: 0,36kg Materijal: Aluminijum	16,80	14,00
------	--	-------	-------

TR-JB03-G-IN

5879	Nosač za Dome kamere serije IPC32x i IPC31x Dimenzije: Ø106,6mm*36mm Težina: 0,2kg Materijal: Aluminijum	12,00	10,00
------	---	-------	-------

KONEKTORI**BNC NA LEMLJENJE
SA ŠRAFOM**

3299	BNC konektor muški sa šrafom. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

BNC NA LEMLJENJE

2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,54	0,45
------	--	------	------

BNC KONEKTOR

30020	BNC konektor muški na šraf.	0,50	0,42
-------	-----------------------------	------	------

BNC NA KRIMP RG59

2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,60	0,50
------	---	------	------

BNC MUŠKI- F ŽENSKI

1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,60	0,50
------	--	------	------

BNC NASTAVAK

4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

**F KONEKTOR na krimp
RG6**

2559	F konektor za RG6 kabl. Pakovanje 100 kom.	0,14	0,12
------	---	------	------

F KONEKTOR na krimp RG59

1796	F konektor za RG59 kabl. Pakovanje 100 kom.	0,14	0,12
------	--	------	------

RF METALNI G MUŠKI

4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,35	0,29
------	--	------	------

RCA MUŠKI-F ŽENSKI

4446	RCA muški - F ženski konektor Pakovanje 100 kom.	0,53	0,44
------	---	------	------

F NASTAVAK

3300	F nastavak Ženski - Ženski Pakovanje 100 kom	0,22	0,18
------	---	------	------

**F KONEKTOR
KOMPRESIONI RG6 XL**

1625	Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.	0,44	0,37
------	--	------	------

**F KONEKTOR
KOMPRESIONI RG11 XL**

1627	Profesionalni PPC F konektor za RG11 kabl.	2,96	2,47
------	--	------	------

**F KONEKTOR
KOMPRESIONI RG59 XL**

1624	Profesionalni PPC F konektor za RG59 kabl. Pakovanje 50 kom.	0,47	0,39
------	---	------	------

DC KABL-MUŠKI

1387	DC utikač-muški	0,48	0,40
------	-----------------	------	------

DC KABL-ŽENSKI

5044	DC utikač-ženski	0,48	0,40
------	------------------	------	------

DC KONEKTOR MUŠKI

3425	DC konektor Muški	0,83	0,69
------	-------------------	------	------

DC KONEKTOR ŽENSKI

4197	DC konektor ženski.	0,83	0,69
------	---------------------	------	------

DC RAZDELNIK 1-4

1388	1 DC utičnica - 4 DC utikača	1,99	1,66
------	------------------------------	------	------

DC RAZDELNIK 1-8

1389	1 DC utičnica - 8 DC utikača	3,97	3,31
------	------------------------------	------	------

CAT7 RJ45

Mrežni konektor RJ45 kategorija 7

0,50 0,42

CAT5 RJ45

0067 Mrežni konektor RJ45

0,05 0,04

Telefonski konektor RJ11

0068 Telefonski konektor RJ11

0,02 0,02

DODATNA OPREMA**ŠTAMPAČ P-TOUCH E100**

- Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9
4663 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu 106,56 88,80

MIKROFON LY-501C

- 2584 Audio modul sa izvedenim konektorima.
Napajanje 12 V DC

3,97 3,31

MIKROFON LY-502B

- 2583 Audio modul plastični sa trimerom.
Napajanje 12 V DC

6,00 5,00

MIKROFON LY-506

- 1937 Audio modul metalni sa trimerom.
Napajanje 12 V DC

10,00 8,33

PoE Extender

- Model: LN-POEPL03S
PoE In: 44-57V/30W
PoE Out (1-3) : 44-57V/25W
Support: 10/100 Mbps IEEE802.3af/at

30,00 25,00

DS-2FP2020

- 5222 Viisoko osetljivi omnidirekcioni mikrofon. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).

36,00 30,00

DH-PFM800-4K (par)

- One (1) Channel Balun
Real-time Transmission over UTP CAT5E/6 Cable
3632 Compatible with HDCVI, TVI, AHD, and CVBS Video Formats
Transmission Distance at 4K: 200 m (656 ft)
External Power Supply not Required

6,90 5,75

DG razvodna kutija 100x100

00091 Razvodna kutija 100x100

1,80 1,50

**OG razvodna kutija
80x80**



00092 Razvodna kutija 80x80 1,10 0,92

OG razvodna kutija 160x100x74



00093 Razvodna kutija 160x100x74 3,00 2,50

OG razvodna kutija 160x100x48



00094 Razvodna kutija 160x100x48 2,64 2,20

**ALAT ZA KRIMP
RG6, RG11,RG59**




3302 Alat za krimpovanje RG6, RG11,RG59 konektora 48,00 40,00

STRIPER ZA KABLOVE RG59,RG6



3301 Alat za stripovanje RG59,RG6 kablova 20,40 17,00

**ALAT KOMPRESIONI
ZA RG59, RG6**



1629 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake. 37,92 31,60

**ALAT KOMPRESIONI, ZA
RG6,RG11,RG59**



3796 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6,RG11,RG59 XL oznake. 54,34 45,28

**KLEŠTA ZA KRIMPOVANJE
KOMPLET**



5790 Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečicom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell) 28,68 23,90

NAPAJANJA

XED-1212S



Ulaž: 90V-264V
Izlaz: 12V , 1A
Snaga: 12W
Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor 6,00 5,00

XED-2012S



Ulaž: 90V-264V
Izlaz: 12V , 2A
Snaga: 24W
Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor 8,04 6,70

XED-3013S



Ulaž: 90V-264V
Izlaz: 12V , 3A
Snaga: 36W
Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor 12,60 10,50

XED-5013S



Ulaž: 100V-240V
Izlaz: 12V , 5A
Snaga: 60W
Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor 16,20 13,50

XED-6013B



Ulag: 100V-240V

Izlag: 12V , 6A

3509 Snaga: 72W

Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm

Duzina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

20,40 17,00

9-KANALNO NAPAJANJE

XED-10A12VX-9L



Snaga: 120W

Ulag: 100~240V 50~60Hz

5435 Izlag: 12V 10A 9 kanala

Dimenzije: 237*213*70mm

Neto težina: 1800g

Napomena: Sadrži AC kabl

82,80 69,00

18-KANALNO NAPAJANJE

XED-15A12VX-18L



Snaga: 180W

Ulag: 100~240V 50~60Hz

5114 Izlag: 12V 15A 18 kanala

Dimenzije: 240*218*70mm

Neto težina: 2300g

Napomena: Sadrži AC kabl

94,80 79,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD.
Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cene bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs