

CENOVNIK UNIVIEW VIDEO NADZORA - 20.04.2026.



NAZIV	ŠIFRA	OPIS	CENA	
-------	-------	------	------	--

DVR UREDJAJI sa PDV bez PDV

4 KANALNI

XVR301-04G3



4-CH Hybrid DVR

Podrzan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal)
4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podrzan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6)

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulazno/Izlazni saobraćaj: 16/48 Mbps

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x226mmx 47mm (10.2" x 8.9"x1.8"), 1.1kg

11031

69,60 58,00



XVR301-04Q3



4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6)

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

Ulazno/Izlazni saobraćaj: 48/60 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x226mmx 47mm

11032

96,00 80,00

XVR301-04U3**4-ch 1U Digital Video Recorder**

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
 Support Ultra 265/H.265/H.264 video formats
 Support audio over coaxial cable (TVI cameras)
 Control the dual-light of UNV analog cameras under TVI
 Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
 Support 1-ch CVBS output, 1-ch VGA output,
 1-ch HDMI output at up to 4K (3840 x 2160)
 HDMI and VGA simultaneous output
 Long transmission distance over coaxial cable
 Support mainstream cameras of ONVIF and RTSP protocols
 1HDD Up to 16 TB

I1129

144,00 120,00

8 KANALNI**XVR301-08G****8-Ch Digital Video Recorder**

Support H.265/H.264 video formats
 Recording Resolution: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF
 Support audio over coaxial cable (only for TVI cameras)
 Control the dual-light of UNV analog cameras under TVI
 Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
 4/8/16-channel BNC input
 Support 1-ch HDMI output, 1-ch VGA output at up to 1920*1080
 HDMI and VGA simultaneous output
 Long transmission distance over coaxial cable
 Support mainstream cameras of ONVIF and RTSP protocols
 1 SATA interface up to 6 TB

I1176

84,00 70,00

**XVR301-08G3****8-CH Hybrid DVR**

Podrška: TVI,AHD, CVI, CVBS
 Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF
 Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)
 Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio
 Ulazno/Izlazni saobraćaj: 32/64 Mbps
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
 Hard disk: 1 sata HDD do 8TB
 Napajanje 12V DC, Potrošnja 8W bez HDD
 Radna temperatura: -10 °C ~ +55 °C
 Dimenzije: 260mm x226mmx 47mm

I1025

91,20 75,00

**XVR301-08Q3****8-CH Hybrid DVR**

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
 Podrška TVI,AHD, CVI,CVBS
 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)
 Video kompresija: H.265, H.264
 Video/audio ulazi: 8ch BNC, 1ch audio
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio
 Ulazno/Izlazni saobraćaj: 40/64 Mbps
 Smart funkcije: Motion detection, video loss detection, audio detection,
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
 Hard disk: 1 sata HDD do 8TB kapaciteta
 Napajanje 12V DC,
 Potrošnja 10W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 260mm x226mmx 47mm

I1033

138,00 115,00



XVR301-08U3

uniview
Better Security. Better World.

8-Ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
8-channel BNC input
Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols

11080 **222,00** **185,00**

16 KANALNI**XVR301-16G3**

uniview
Better Security. Better World.

16-CH Hybrid DVR

Podržava: TVI, AHD, CVI, CVBS, IP cameras
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF
IP kamere: do 8 IP kamere ili svih 16
Video/audio ulazi: 16-ch BNC / 1-ch RCA
Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio
Ulazno/Izlazni saobraćaj: 40/64 Mbps
Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 SATA HDD do 8TB
Napajanje 12V DC, Potrošnja 10W bez HDD
Radna temperatura: -10 °C ~ +55 °C
Dimenzije: 260mm x226mmx 47mm

11026 **148,80** **124,00**

XVR302-16Q3

uniview
Better Security. Better World.

16-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
Podržava 8MP@15fps na prva 4 kanala
Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.
Ulazno/Izlazni saobraćaj: 72/80 Mbps
Video kompresija: H.265/H.264 video kompresija,
Video/audio ulazi: 16ch BNC, 1ch RCA
Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA
Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection
Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485
Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
Hard disk prostor: 2 sata HDD do 6TB kapaciteta
Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,
Radna temperatura: -10 °C ~ +55 °C,
Dimenzije: 380mm x315mmx 53mm, Težina 1.9Kg

11034 **288,00** **240,00**

KIT/XVR 301-04G3/4*UAC-T112-F28**UNV KIT/XVR 301-04G3/4*UAC-T112-F28**

Kompet sadrži:
1x XVR 04G3
4x UAC-T112-F28
1x Napajanje 2A
4x 20m Koaksijalni kabl + napajanje (sa konektorima)
1x Razdelnik 1 / 4

11065 **180,00** **150,00**

ANALOGNE DOME KAMERE 2MP**UAC-T112-AF28****2MP HD Fixed IR Turret Analog Camera**

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Built-in microphone
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

11066 **24,00** **20,00**

UAC-T112-F28-W

	2MP ColourHunter HD Fixed Turret Analog Camera		
	2MP high quality image TVI/AHD/CVI/CVBS		
11006	Supports white light illumination, 24/7 full-color imaging Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	28,80	24,00

UAC-T122-AF28LM

	2MP LightHunter HD IR Fixed Turret Analog Camera		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11054	Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	36,00	30,00

UAC-T122-AF40LM

	2MP LightHunter HD IR Fixed Turret Analog Camera		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11099	Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	36,00	30,00

UAC-T122-AF28M-W

	2MP ColorHunter HD Fixed Turret Analog Camera		
	2MP high quality imaging TVI/AHD/CVI/CVBS		
11016	Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing 3-Axis		

NEMA NA STANJU**UAC-T142-AF28LM-DL**

	2MP ColorHunter Fixed Dual-light Turret Analog Camera		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11077	Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	43,20	36,00

ANALOGNE BULLET KAMERE 2MP**UAC-B112-F28**

	2MP HD Fixed IR Mini Bullet Analog Camera		
	2MP high quality image TVI/AHD/CVI/CVBS		
11000	IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	25,20	21,00

UAC-B112-AF28

1121	<p>2MP Fixed IR Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	26,40	22,00
------	---	-------	-------

UAC-B112-F28-W

11001	<p>2MP ColourHunter HD Fixed Mini Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 full-color imaging Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages</p>	27,60	23,00
-------	---	-------	-------

UAC-B122-AF28LM

11053	<p>2MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog</p>	36,00	30,00
-------	--	-------	-------

UAC-B122-AF40LM

11098	<p>2MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog</p>		
-------	--	--	--

NEMA NA STANJU

UAC-B122-AF28M-W

11014	<p>2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability SD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing</p>	36,00	30,00
-------	---	-------	-------

UAC-B122-AF28M-W-Black

11214	<p>2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability SD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing</p>	36,00	30,00
-------	---	-------	-------

UAC-B122-AF40M-W



11015	<p>2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing</p>	37,20	31,00
-------	--	-------	-------

UAC-B142-AF28LM-DL



11076	<p>2MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	46,80	39,00
-------	--	-------	-------

UAC-B142-AF40LM-DL



11122	<p>2MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	46,80	39,00
-------	--	-------	-------

ANALOGNE DOME KAMERE 5MP

UAC-T115-AF28



11126	<p>5MP Fixed IR Turret Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	30,00	25,00
-------	--	-------	-------

UAC-T125-AF28LM



11056	<p>5MP LightHunter HD IR Fixed Turret Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables 3-Axis</p>	46,80	39,00
-------	--	-------	-------

UAC-T125-AF28M-W



11020	<p>5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis</p>		
-------	---	--	--

NEMA NA STANJU

UAC-T125-AF28M-W-Black

	<p>5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis</p>			
11057			48,00	40,00

UAC-T145-AF28LM-DL

	<p>5MP ColorHunter Fixed Dual-light Turret Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11079				

NEMA NA STANJU**ANALOGNE BULLET KAMERE 5MP****UAC-B115-F28**

	<p>5MP HD Fixed IR Mini Bullet Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages</p>			
11002			30,00	25,00

UAC-B115-AF28

	<p>5MP Fixed IR Bullet Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11125			30,00	25,00

UAC-B125-AF28LM

	<p>5MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11055			44,40	37,00

UAC-B125-AF40LM

	<p>5MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11124			44,40	37,00

UAC-B125-AF28M-W

11018	<p>5MP ColorHunter HD Fixed Mini Bullet Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing</p>	48,00	40,00
-------	--	-------	-------

UAC-B125-AF40M-W

11019	<p>5MP ColorHunter HD Fixed Mini Bullet Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing</p>	49,20	41,00
-------	--	-------	-------

UAC-B145-AF28LM-DL

11078	<p>5MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	54,00	45,00
-------	---	-------	-------

UAC-B315-ADZLM

11079	<p>5MP LightHunter VARIFOCAI IR Bullet Analog Camera High quality imaging with 5MP resolution 2.8mm-12mm motorized lens TVI/AHD/CVI/CVBS Illumination Distance: 50m Supports IR cut filter with auto switch (ICR) LightHunter monitoring with high sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built in microphone for high quality audio transmission via coaxial cables</p>	54,00	45,00
-------	---	-------	-------

*U DOLASKU***NVR UREDJAJI****NVR301-04S3**

11049	<p>4-ch NVR Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p Ulazno/izlazni saobraćaj: 64/48Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD), Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8"), 1kg</p>	54,00	45,00
-------	---	-------	-------

NEMA NA STANJU

NVR301-04B-IQ**NOVO****EASY**

I1115

4-ch NVR

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Support Ultra 265/H.265/H.264 video formats

Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1x HDD, up to 10TB

132,00

110,00

NVR501-04B-IQ**NOVO****PRIME**

I1150

4-ch NVR

Decoding Capability:

Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30

Smart On: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30

Support Ultra H.265/H.265/H.264 video formats

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

150,00

125,00

NVR301-04LS2-P4**NOVO****EASY**

I1149

4-ch PoE NVR

Support Ultra 265/H.265/H.264 video formats

4-channel input

Recording Resolution: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Capability: 1 x 6MP@20, 1 x 5MP@30, 2 x 4MP@25, 2 x 3MP @30,

4 x 1080p@25, 8 x 960p@25, 8 x 720p@30

Third-party IP cameras supported with ONVIF conformance:

Profile S, Profile G, Profile T

Support 1-ch HDMI, 1-ch VGA

HDMI and VGA simultaneous output

Up to 6MP resolution recording

1 SATA HDD up to 6 TB

Support cloud upgrade

Power Supply: 48V DC

120,00

100,00

NVR301-08S3**EASY**

I1048

8-ch NVR

Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 64/48 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0,.

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

120,00

100,00

NVR301-08B-IQ**NOVO****EASY**

I1117

8-ch NVR

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Support Ultra 265/H.265/H.264 video formats

4/8/16 channel input

Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1x HDD, up to 10TB

150,00

125,00

NVR501-08B-IQ**NOVO****PRIME****8-ch NVR**

Decoding Capability: Smart Off: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30

11118

Support Ultra H.265/H.265/H.264 video formats
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
 Support HDMI and VGA simultaneous output
 Up to 16 Megapixels resolution recording
 ANR technology to enhance the storage reliability
 When the network is disconnected
 Support cloud upgrade
 1 SATA Interface, up to 16 TB

138,00 140,00

NVR301-16S3**NOVO****EASY****16-ch NVR**

Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p
 Ulazno/Izlazni saobraćaj: 64/48Mbps
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,
 Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),
 Smart Funkcije:Face detection, Intrusion detection, Cross line detection, Audio detection
 ONVIF conformance: Profile S, Profile G, Profile T
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search
 Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta
 Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

11116

138,00 115,00

NVR301-16B-IQ**NOVO****EASY****16-ch NVR**

Decoding Capability - Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 10 x 1080P@30, 16 x 720P@30
 Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30, 16 x 720P@30
 Support Ultra 265/H.265/H.264 video formats
 Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support HDMI and VGA simultaneous output
 Up to 12 Megapixels resolution recording
 ANR technology to enhance the storage reliability when the network is disconnected
 Support cloud upgrade

11151

210,00 175,00

NVR501-16B**PRIME****16-ch NVR**

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Ulazno/Izlazni saobraćaj: 80/64 Mbps
 Video kompresija: Ultra 265/H.265/H.264
 Video/audio izlazi: HDMI (4K) / HD, VGA
 Smart Funkcije: Intrusion Detection, Cross Line Detection,Enter Area, Leave Area, Defocus Detection,Scene Change Detection, Object Left Behind, Object Removed,Auto Tracking, UMD(Ultra Motion Detection)
 Statisticke analize: People counting
 Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP,HTTPS, DNS, DDNS, SNMP, SMTP
 Hard disk prostor: 1 sata HDD do 8TB kapaciteta
 Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 260mm × 222mm × 47mm, Težina 0,98Kg

11047

215,00 180,00

uniview
Better Security. Better World.

NVR501-16B-IQ

11119

16-ch NVR

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30
 Support Ultra H.265/H.265/H.264 video formats
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
 Support HDMI and VGA simultaneous output
 Up to 16 Megapixels resolution recording
 ANR technology to enhance the storage reliability
 When the network is disconnected
 Support cloud upgrade
 1 SATA Interface, up to 16 TB

228,00 190,00

NVR502-16B-IQ

11119

16-ch NVR

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30
 Support Ultra H.265/H.265/H.264 video formats
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
 Support HDMI and VGA simultaneous output
 Up to 16 Megapixels resolution recording
 ANR technology to enhance the storage reliability
 When the network is disconnected
 Support cloud upgrade
 2 SATA Interface, up to 16 TB per HDD

U DOLASKU

NVR304-32X

11154

32-ch NVR

32-KANALNI MREŽNI SNIMAČ
 Rezolucija snimanja:
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Ulazno/izlazni saobraćaj: 384/384 Mbps
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,
 Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed, Face search, Behavior search
 Statisticke analize: People counting
 ONVIF conformance: Profile S, Profile G, Profile T
 Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1 x RS485, 1 x RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE
 Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5
 Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,
 Radna temperatura: -10 °C – +55 °C,
 Dimenzije: 442mm x426mmx 89mm, Težina 5,7Kg

600,00 500,00

DOVE IP KAMERE 2MPX**IPC3612LB-SF28-A**

11144

2MP Fixed IR Turret Network Camera

High quality image with 1080P, 1/2.8" CMOS sensor
 1080P (1920 x 1080)@30/25 fps; 720P (1280 x 720)@30/25 fps
 Ultra 265, H.265, H.264
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 Supports PoE power supply
 3-axis

66,00 55,00

2MP



Ultra H.265

Smart Search



IPC322LB-SF28-A



2MP Vandal-resistant Network IR Fixed Dome Camera

High quality image with 2MP, 1/2.8" CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 IK10 vandal resistant
 Support PoE power supply
 2-Axis

11174

56,40 47,00

IPC322LB-AF28WK-G



2MP WIFI Fixed Dome Network Camera

High quality image with 2MP, 1/2.9" CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 3-Axis

11008

86,40 72,00

IPC322LB-DSF28K-G




High quality image with 2MP, 1/2.7" CMOS sensor

2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply

11177

72,00 60,00

IPC3622LE-ADF28K-WP




2MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera

High quality image with 2MP, 1/2.7" CMOS sensor and F1.0 large aperture lens
 2MP (1920 * 1080)@30/25 fps; 720P (1280 * 720)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, Detail, and smear effects in extremely low-light scenes
 120 dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30 m (98 ft) warm light distance
 Supports up to 512 GB Micro SD Card
 IP67 protection
 Support PoE power supply
 3-Axis

11112

104,40 87,00

IPC3612LE-ADF28KC-WL



2MP HD ColorHunter IR Fixed Eyeball Network Camera

High quality image with 2MP, 1/2.8" CMOS sensor
 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic & Speaker
 Smart IR, up to 30m (98ft) IR distance
 White Light, up to 30m (98ft) white light distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11038

110,40 92,00

IPC3532LB-ADZK-G-BLACK

EASY



2MP HD IR VF (2.8 ~ 12mm) Dome Network Camera

High quality image with 2MP, 1/2.7" CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 40m (131ft) IR distance
Supports 128 G Micro SD card
IK10 vandal resistant
IP67 protection
Support PoE power supply
3-Axis

I1092

156,00 130,00

BULLET IP KAMERA 2MPX

IPC2122LB-SF28-A

EASY



2MP Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8" CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
IP67 protection
Support PoE power supply
3-Axis

I1143

55,20 46,00

IPC2122LB-SF40-A

EASY



2MP Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8" CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
IP67 protection
Support PoE power supply
3-Axis

I1173

55,20 46,00

IPC2122LB-AF28WK-G

EASY



2MP HD WIFI Bullet Network Camera

High quality image with 2MP, 1/2.9" CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
IP67 protection
3-Axis

I1009

78,00 65,00

IPC2122LB-AF40WK-G BLACK



2MP HD WIFI Bullet Network Camera

High quality image with 2MP, 1/2.9"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG

I1093 Built-in Mic 78,00 65,00
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IP67 protection
 3-Axis

IPC2122LB-ADF40KM-G



2MP HD WDR Fixed IR Bullet Network Camera

High quality image with 2MP, 1/2.7"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene

I1175 Support 9:16 Corridor Mode 72,00 60,00
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 3-Axis

IPC2122LB-AF28K-WL



2MP HD ColorHunter Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.9"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra H.265,H.265, H.264
 Built-in Mic

I1050 Warm Light, up to 30m (98ft) warm light distance 99,00 82,50
 2D/3D DNR (Digital Noise Reduction)
 Support 128GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

IPC2312LE-ADF28KM-WP



2MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 2MP, 1/2.7"CMOS sensor and F1.0 large aperture lens
 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG

I1111 Colorhunter with Wise-ISP technology ensures 24-hour full-color images 104,40 87,00
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

IPC2122LE-ADF28KMC-WL



2MP HD ColorHunter Mini IR Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8"CMOS sensor
 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene

I1028 Support 9:16 Corridor Mode 110,40 92,00
 Built-in Mic & Speaker
 Smart IR, up to 30m (98ft) IR distance
 White Light, up to 30m (98ft) white light distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

BULLET IP KAMERE 3MPX

IPC2123LB-AF28KM-G

EASY



3MP HD Fixed IR Bullet Network Camera

High quality image with 3MP, 1/2.7"CMOS sensor
3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
Ultra 265, H.265, H.264, MJPEG
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

11037

86,40 72,00

DOME IP KAMERE 4MPX

IPC3614LB-SF28-A

EASY

NOVO



4MP Fixed Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Support PoE power supply
3-Axis

11030

81,60 68,00

IPC324LB-SF28-A

EASY

NOVO



4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera

Rezolucija snimanja: ④4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps
Čip: 1/3", progressive scan, 4.0 megapixel, CMOS
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8mm @F2.0
Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP,
DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,Qos,SSL/TLS
Mrežni standardi: ONVIF (Profile S, Profile T),API,SDK
Kompresija: H.265, H.264,
Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI,
Corridor mod
Zaštita: IP67, IK10
Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)
Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg
Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

11010

81,60 68,00

IPC3614LB-ASF28K-A

EASY

NOVO



4MP Fixed Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
Support PoE power supply
Built-in Mic
3-Axis

11114

86,40 72,00

IPC3614LB-AF28K-A2



4MP IR Eyeball Network Camera
 High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Supports accurate human body detection 2.0
 Ultra 265, H.265, H.264
 Built-in mic
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 MicroSD, up to 512 GB
 DC 12 V, PoE (IEEE 802.3af) power supply
 IP67 protection
 3-axis

U DOLASKU

IPC324LB-ASF28K-A



4MP Fixed IR Dome Network Camera
 High quality image with 4MP, 1/3" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 Support Micro SD card
 IP67 protection
 IK10 vandal resistant
 DC12V or PoE(IEEE 802.3af) power supply
 2-Axis

NEMA NA STANJU

IPC3624LE-ADF28K-WP



4MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera
 High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@25/20fps; 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, And smear effects in extremely low-light scenes
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m (98ft) warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11086 128,40 107,00

IPC3514LE-ADF28K-WP



4MP ColorHunter Wise-ISP Fixed Dome Network Camera
 High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@25/20fps; 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Supports 512 GB Micro SD card
 IP67 protection
 IK10 protection
 Support PoE power supply
 3-Axis

11084 128,40 107,00

IPC3614LE-ADF28K-H



4MP EasyStar Fixed IR Turret Network Camera
 High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688 × 1520)@25/20 fps; 4MP (2560 × 1440)@25/20 fps; 3MP (2304 × 1296)@30/25 fps; 2MP (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Easystar technology ensures high image quality in low illumination environment
 120 dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30 m (98 ft) IR distance
 Supports up to 512 GB Micro SD Card
 IP67 protection
 Support PoE power supply
 3-Axis

11137 147,60 123,00

IPC3614LE-ADF28KC-WL



i1040

4MP HD ColorHunter IR Fixed Eyeball Network Camera

High quality image with 4MP, 1/3"CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic & Speaker
 Smart IR, up to 30m (98ft) IR distance
 White Light, up to 30m (98ft) white light distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

150,00 125,00

IPC3614SB-ADF28KMC-I0




i1194

4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage.When Smart intrusion prevention is triggered
 The camera links sound alarm and light linkage.
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

156,00 130,00

IPC3614SB-ADF40KMC-I0



i1094

4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage.When Smart intrusion prevention is triggered , the camera links sound alarm and light linkage.
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

156,00 130,00

IPC354SB-ADNF28K-I0



i1087

4MP LightHunter Fixed IR Dome Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, Motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30m (98 ft) IR distance
 Supports 512 G Micro SD card
 Cable-free
 Support PoE power supply

180,00 150,00

IPC3534LB-ADZK-G



4MP HD IR VF (2.8 – 12mm) Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps;2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 256 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply
 3-Axis

11166

180,00 150,00

BULLET IP KAMERE 4MPX

IPC2124LB-SF28-A



4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

11011

81,60 68,00

IPC2124LB-SF40-A




4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

11081

84,00 70,00

IPC2124LB-AF28K-A2



4MP Fixed IR Bullet Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Supports accurate human body detection 2.0
 Ultra 265, H.265, H.264
 Built-in mic
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 MicroSD, up to 512 GB
 DC 12 V, PoE (IEEE 802.3af) power supply
 IP67 protection
 3-axis

11155

86,40 72,00

IPC2124LB-ASF28K-A




4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra H.265,H.265, H.264
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 Supports Micro SD card
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

11071

86,40 72,00

IPC2124LB-ADF28KM-H



4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/2.9" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps;
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG

11068 Built-in Mic 114,00 95,00
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 120dB WDR
 3-Axis

IPC2124LB-ADF40KM-H



4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/2.9" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps;
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Built-in Mic

11075 Ultra 265, H.265, H.264, MJPEG 116,40 97,00
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 120dB WDR
 3-Axis

IPC2314LE-ADF28KM-WP



4MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)
 @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG

11085 Colorhunter with Wise-ISP technology ensures 24-hour full-color images 128,40 107,00
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

IPC2124LE-ADF28KMC-WL



4MP ColorHunter Fixed Dual-light Bullet Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps;
 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 120 dB true WDR technology enables clear image in strong light scene

11148 Supports 9:16 corridor mode 132,00 110,00
 Built-in mic and speaker
 Smart IR, up to 30 m (98.4 ft) IR distance
 White light, up to 30 m (98.4 ft) white light distance
 MicroSD, up to 512 GB
 IP67 protection
 Supports PoE power supply
 3-axis

IPC2124LE-ADF28KM-G



4MP HD Mini IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP
 (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG

11027 Easystar technology ensures high image quality in low illumination environment 147,60 123,00
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

IPC2314LE-ADF28KM-WL

EASYSSTAR



4MP HD ColorHunter Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Colorhunter technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m white light distance
 Supports 128 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11029

159,60 133,00

IPC2124SB-ADF28KM-I0

PRIME



4MP HD Intelligent LightHunter IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

11088

162,00 135,00

IPC2324LB-ADZK-G

EASY



4MP HD IR VF (2.8 - 12mm) Bullet Network Camera


High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 IK10 vandal resistant
 Support PoE power supply
 3-Axis

9999

180,00 150,00

IPC2314SB-ADF60KM-I0

PRIME



4MP HD Intelligent 80m IR Fixed Bullet Network Camera

High quality image with 4MP, 1/2.7" CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle And non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in 2 Mic
 Smart IR, up to 80m (262 ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection

11097

192,00 160,00

PRIME

**4MP LightHunter** Fixed IR Bullet Network Camera

High quality image with 4MP, 1/2.7" CMOS sensor

4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps

Ultra 265, H.265, H.264, MJPEG

Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection

I1157 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle 192,00 160,00

Intelligent People Flow Counting and Crowd Density Monitoring

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Built-in 2 Mic

Smart IR, up to 80m (262 ft) IR distance

Supports 512 G Micro SD card

IP67 protection

PRIME

NOVO

**4MP Tri-Guard** Fixed Dual-light Bullet Network Camera

High quality image with 4 MP, 1/2.7" CMOS sensor

4 MP (2688 × 1520)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps

Ultra 265, H.265, H.264, MJPEG

Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection

I1159 Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles 215,88 179,90

Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage

120 dB true WDR technology enables clear image in strong light scene

Supports 9:16 corridor mode

Built-in mic and speaker

Smart IR, up to 30 m (98.4 ft) IR distance

MicroSD, up to 512 GB

IP67 protection

4MP Recognition Of Vehicle License Plate Bullet IP Camera (2.8 ~ 12mm)

Features

Optics

Built-in lens supports motorized zoom to adapt to different scenes and allows for easy installation.

Automatic gain control, white balance, and WDR for various light conditions.

Compression

Supports triple streams.

Advanced H.265 encoding technology improves compression efficiency.

Custom OSD allows various vehicle information to be overlaid on the video image.

Functions

Built-in vehicle and license plate recognition algorithm can recognize standard license plates of multiple countries.

Supports capturing vehicle head only.

Supports plate allowlist and blacklist configuration.

Supports vehicle access control when connected to a barrier.

Supports Micro SD cards of up to 256GB.

Automatic network replenishment (ANR) allows to automatically

store video to SD card in case of network disconnection.

Supports audio collection and intercom.

I1120

Network 840,00 700,00

Network auto-adaptability ensures smooth live video in relatively bad network conditions such as packet loss.

Supports SNMP.

Supports UNP for NAT traversal between public and private networks.

Supports integration with the third party via SDK or HTTP.

Network Security

Supports authorized user access by password. Weak password detection and account lock-up when failed login attempts reach the Upper limit enhance password security.

Supports Web access via HTTPS.

RTSP authentication prevents unauthorized video stream requests.

IP address filtering prevents illegal access from untrusted IP addresses.

Gateway ARP protection prevents MAC address spoofing.

Structure


Supports DC 12V and PoE (802.3at) power supplies.

Cast aluminum body offers excellent heat dissipation.

3-axis mounting bracket for various installation scenarios.

A junction box on the mounting bracket is convenient for storing tail cables.

IP67 and IK10 protection.



DOME IP KAMERE 5MPX

IPC3615LB-SF28-A



EASY

5MP Fixed IR Turret Network Camera

High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 DC 12 V, PoE (IEEE 802.3af) power supply
 3-axis

11147 86,40 72,00

IPC3635LB-ADZK-G



EASY

5MP HD IR VF Eyeball Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11139 192,00 160,00

IPC3615SS-ADF28K-11



PRIME

5MP HD Intelligent LightHunter IR Fixed Turret Dome Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25(default)fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 Auto Scene Match (ASM) (WDR only)
 LightHunter technology ensures ultra-high image quality in low illumination environment
 130dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection

11105 192,00 160,00

IPC3615SE-ADF28KM-WL-10



PRIME

5MP HD Intelligent ColorHunter Fixed Eyeball Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@30/25fps; 4MP (2560*1440)@30/25fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce False alarm caused by leaves,
 Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 Colorhunter technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 corridor Mode
 Support built-in Mic
 Support 256 G Micro SD card
 IP67 protection
 Support PoE power supply

11161 258,36 215,30

BULLET IP KAMERE 5MPX

IPC2125LB-SF28-A

NOVO **EASY**



5MP **POE** **H.265** **MIC**

Smart IR **Smart Search** **IP 67**

5MP Fixed IR Bullet Network Camera
 High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG

I1145 **Smart IR, up to 30 m (98.4 ft) IR distance** **86,40** **72,00**
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 DC 12 V, PoE (IEEE 802.3af) power supply
 3-axis

IPC2125LB-SF40-A

NOVO **EASY**



5MP **POE** **H.265** **MIC**

Smart IR **Smart Search** **IP 67**

5MP Fixed IR Bullet Network Camera
 High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG

I1146 **Smart IR, up to 30 m (98.4 ft) IR distance** **86,40** **72,00**
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 DC 12 V, PoE (IEEE 802.3af) power supply
 3-axis

IPC2125LE-ADF28KM-G

EASYSSTAR



5MP **Built-in Mic** **Edge Storage** **Encrypt**

Intrusion Detection **Open Site detection** **IP 67** **WDR**

5MP HD Mini IR Fixed Bullet Network Camera
 High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 IC domet: do 50m
 Easystar technology ensures high image quality in low
 illumination environment
I1041 **120dB true WDR technology enables clear image in strong light scene** **159,60** **133,00**
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

IPC2125SB-ADF40KMC-10

NOVO **PRIME**



5MP **Edge Storage** **Built-in Mic** **WDR**

Active deterrence **Corridor Mode** **IP 67**

5MP HD Intelligent Light and Audible Warning Fixed Bullet Network Camera
 High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296)
 @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area
 detection
 Based on target classification, smart intrusion prevention significantly reduce
 false alarm caused by leaves, birds and lights etc., accurately focus on human and,
I1095 **motor vehicle and non-motor vehicle** **168,00** **140,00**
 Supports sound and light alarm linkage. When Smart intrusion prevention
 is triggered, The camera links sound alarm and light linkage.
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

IPC2125SB-ADF28KM-IO




5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

1110

168,00 140,00

IPC2125SB-ADF28KM-IO BLACK



5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

1106

168,00 140,00

IPC2125SB-ADF28KMC-IO



5MP Tri-Guard Fixed Dual-light Bullet Network Camera

High quality image with 5 MP, 1/2.7" CMOS sensor
 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection
 Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles
 Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage
 120 dB true WDR technology enables clear image in strong light scene
 Supports 9:16 corridor mode
 Built-in mic and speaker
 Smart IR, up to 30 m (98.4 ft) IR distance
 MicroSD, up to 512 GB
 IP67 protection
 Supports PoE power supply

11156

168,00 140,00

IPC2325LB-ADZK-H



5MP HD IR VF (2.8 – 12mm) Bullet Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Built-in Mic
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11069

192,00 160,00

IPC2315SB-ADF40K-10




11096

5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor Vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in 2 Mic
 Smart IR, up to 80m (262 ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection

198,00 165,00

IPC2225SE-DF40K-WL-10



11158


5MP ColorHunter Fixed Warm Light Bullet Network Camera

High quality image with 5 MP, 1/2.7" CMOS sensor
 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, including cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduces false alarm caused by leaves, birds and lights, accurately focusing on human, motor vehicle and non-motor vehicle
 Intelligent people flow counting and crowd density monitoring
 ColorHunter technology ensures 24-hour full-color images
 120 dB true WDR technology enables clear image in strong light scene
 Supports 9:16 corridor mode
 Alarm I/O: 1/1, audio I/O: 1/1
 MicroSD, up to 512 GB
 IK10 vandal resistant and IP67 protection
 Supports PoE power supply

261,60 218,00

DOME IP KAMERE 8MPX

IPC328SB-ADF28K-10



11043

8MP HD Intelligent IR Fixed Dome Network Camera

High quality image with 8MP, 1/2.7" CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Alarm:1 in/1 out, Audio: 1 in/1 out
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IK10 vandal resistant and IP67 protection

229,20 191,00

IPC3618LE-ADF28K-G



11162

4K HD IR Fixed Eyeball Network Camera

High quality image with 8MP, 1/2.7" CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Easystar technology ensures high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

216,00 180,00

BULLET IP KAMERE 8MPX

IPC2318LE-ADF28KM-WP



8MP ColorHunter Wise-ISP Warm Light Bullet Network Camera

High quality image with 8MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Colorhunter with Wise-ISP technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11113

210,00 175,00

IPC2128LE-ADF28KM-G




4K 8MP Mini Fixed Bullet Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Easystar technology ensures high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11012

211,20 176,00

IPC2128SB-ADF28KMC-IO



8MP Tri-Guard Fixed Dual-light Bullet Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Built-in Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection

11090

246,00 205,00

IPC2328SB-DZK-IO



8MP HD Intelligent LighterHunter IR VF (2.8 ~ 12mm) Bullet Network Camera

High quality image with 8MP, 1/2.8"CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image
 Quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Alarm:1 in/1 out, Audio: 1 in/1 out
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply


11138

264,00 220,00

Uho-S2



High quality image with 2MP, 1/3" CMOS sensor
 2MP (1920*1080)@25/20fps; 720P (1280*720) @25/20fps
 Ultra 265, H.265, H.264
I1091 Built-in Mic & Speaker, support two-way audio, offer better interaction
 IR night vision, up to 10m (33ft) IR distance
 Support 256 G Micro SD card
 Wi-Fi connection and easy installation



Uho-S3E-M3



High quality image with 3MP, 1/3" CMOS sensor
 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720) @30/25/fps
 Ultra 265, H.265, H.264
I1051 Built-in Mic & Speaker, support two-way audio, offer better interaction
 IR night vision, up to 10m (33ft) IR distance
 Support 256 G Micro SD card
 Wi-Fi connection and easy installation



IPC-B122-APF28




High quality image with 1080P, 1/2.9" CMOS sensor
 1080P (1920 × 1080)@25/20 fps; 720P (1280 × 720)@25/20 fps
 Ultra 265, H.265, H.264
 2D/3D DNR (digital noise reduction)
 ROI (region of interest) ensures image quality in areas of interest
I1140 With low bandwidth
 Smart IR, up to 30 m (98.4 ft.) IR distance
 Built-in mic
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
 DC 12 V, PoE (IEEE 802.3af) power supply



IPC-T122-APF28



High quality image with 1080P, 1/2.8" CMOS sensor
 1080P (1920 × 1080)@25 fps; 720P (1280 × 720)@25 fps
 Ultra 265, H.265, H.264
 2D/3D DNR (digital noise reduction)
 ROI (region of interest) ensures image quality in areas of interest with low bandwidth
I1141 Smart IR, up to 30 m (98.4 ft.) IR distance
 Built-in mic
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
 DC 12 V, PoE (IEEE 802.3af) power supply



Uho-B1R-M2F3



High quality image with 2MP, 1/2.9" CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
I1127 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IP67 protection
 3-Axis



IPC-B125-APF28



High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps; 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30 fps; 720P (1280 × 720)@30 fps; D1 (720 × 576)@30 fps
 Ultra 265, H.265, H.264
 2D/3D DNR (digital noise reduction)
 ROI (region of interest) ensures image quality in areas of interest with low bandwidth
 Smart IR, up to 30 m (98.4 ft.) IR distance
 Built-in mic
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
 DC 12 V, PoE (IEEE 802.3af) power supply

I1142

60,00 50,00

Uho-P1A-M3F4D




High quality image with 3MP, 1/2.8" CMOS sensor
 2304*1296@20fps in the main stream
 Ultra 265, H.265, H.264
 Support digital WDR (Wide Dynamic Range)
 Built-in Mic & Speaker, support two-way audio, offer better interaction
 Support sound and light warning, makes warning and alarming more noticeable
 Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes
 Self-contained bracket, support two kinds of mounting
 Supports 256 GB Micro SD card
 Wi-Fi connection and easy installation
 IP66 ingress protection
 The front face is made of grapheme, which has better heat dissipation and more Environmental protection

I1052

NEMA NA STANJU

Uho-P2S-M33F34




Fixed camera and PTZ camera integration, dual channels with one IP, Look at overall situation and consider details at the same time
 Ultra 265, H.265, H.264
 Support digital WDR (Wide Dynamic Range)
 Built in Mic Speaker, support two way audio, offer better interaction
 Support sound and light warning, makes warning and alarming more noticeable
 Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes
 IR warm light illumination to deal with different scenes and achieve full color illumination
 Supports 512 GB Micro SD card
 Wi Fi connection and easy installation
 IP66 ingress protection

I1128

NEMA NA STANJU

PTZ IP KAMERE

IPC6312LR-AX4W-VG



2MP LightHunter WIFI IR Network PTZ Camera
 High quality image with 2MP, 1/2.7" CMOS sensor
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
 People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Up to 120 dB Optical WDR (Wide Dynamic Range)
 Wi-Fi connection and easy installation
 Built-in Mic & Speaker
 Smart IR, Up to 50 m (164 ft) IR distance
 Micro SD, up to 256GB
 IP66 protection

I1160

NEMA NA STANJU

IPC6312LR-AX4-VG



2MP LightHunter IR Network PTZ Camera

High quality image with 2MP, 1/2.7" CMOS sensor
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
 People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in Low illumination environment
 Up to 120 dB Optical WDR (Wide Dynamic Range)
 Built-in Mic & Speaker
 Smart IR, Up to 50 m (164 ft) IR distance
 Micro SD, up to 256GB
 IP66 protection
 DC12V or PoE (IEEE 802.3af) power supply

11073

255,00 212,50

IPC675LFW-AX4DUPKC-VG



5MP LightHunter Active Deterrence Mini PTZ Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 Ultra 265, H.265, H.264, MJPEG
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Up to 120 dB Optical WDR (Wide Dynamic Range)
 Built-in Mic & Speaker
 Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance
 Micro SD, up to 256GB
 IP66 protection
 DC12V or PoE (IEEE 802.3af) power supply

11109

270,00 225,00

IPC6412LR-X5UPW-VG



2MP 5X LightHunter Wi-Fi IR Network Mini PTZ Camera

High quality image with 1080P, 1/2.7" CMOS sensor
 1920 × 1080@30 fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 5X optical zoom allows for closer viewing of subjects
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
 automatic selection of best snapshots
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Up to 120 dB optical WDR (wide dynamic range)
 Wi-Fi connection and easy installation
 Built-in mic and speaker, supports two-way audio
 Alarm I/O: 1/1
 Smart IR, up to 30 m (98.4 ft) IR distance

11157

228,00 190,00

IPC6412LR-X16-VG



2MP 16x LightHunter Network PTZ Dome Camera

High quality image with 2MP, 1/2.8" CMOS sensor
 1920*1080@30fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 16X optical zoom allows for closer viewing of subjects
 LightHunter technology ensures ultra-high image quality
 In low illumination environment
 Smart IR, up to 100m (328ft) IR distance
 Micro SD, up to 256GB
 DC 12V±25% or PoE+ (IEEE 802.3at)
 IP66 ingress protection

11074

396,00 330,00

IPC6424SR-X25-B



4MP 25x LightHunter IR Network PTZ Camera
 High quality image with 4 MP, 1/2.8" CMOS sensor
 2688 × 1520@30 fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 25X optical zoom
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
 automatic selection of best snapshots, supports face detection masked area
 People counting, supports people flow counting and crowd density monitoring, suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Smart IR, up to 100 m (328 ft) IR distance
 DC 12 V±25%, PoE+ (IEEE 802.3at)
 Alarm I/O: 2/1, audio I/O: 1/1
 IP67 ingress protection
 IK10 vandal resistant

11152 635,00 530,00

IPC6612SR-X33-VG




2MP 33x Lighthunter Network PTZ Dome Camera
 High quality image with 2MP,1/2.8" CMOS sensor
 1920*1080@30fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 33X optical zoom allows for closer viewing of subjects
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
 LightHunter technology ensures ultra-high image quality in Low illumination environment
 Up to 120 dB Optical WDR (Wide Dynamic Range)
 DC12V or PoE+(IEEE 802.3at) power supply
 Audio 1 in and 1 out, Alarm 2 in and 1 out
 Micro SD, up to 256GB
 Smart IR, up to 150m (492 ft) IR distance
 IP66 ingress protection

11083

NEMA NA STANJU

IPC6634S-X33-VF



4MP 33X LightHunter IR Network PTZ Camera
 High quality image with 4 MP, 1/2.8" CMOS sensor
 2688 × 1520@30 fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 33X optical zoom
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
 automatic selection of best snapshots, supports face detection masked area
 People counting, supports people flow counting and crowd density monitoring, Suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in low illumination environment
 AC 24 V±25%, DC 24 V±25%, PoE+ (IEEE802.3 at)
 Alarm I/O: 7/2, audio I/O: 1/1
 IP67 ingress protection
 IK10 vandal resistant

11153 1320,00 1100,00

VIDEO INTERFONI

OEU-2018-HMK-W



Outdoor Station
 Front panel: Plastic cement
 Supports batch configuration
 Supports intercom calls to associated indoor units or APPS
 Support monitoring function, security alarm, tamper alarm
 Support Wi-Fi
 Built-in IC card reader
 Card Capacity 2000
 IP65(Apply silica gel to gaps between the device and the wall)

11201 216,00 180,00

OEU-2025-HMK2



Outdoor Station
 Front panel: Metal
 Vandal-resistant: IK08
 Supports batch configuration
 WDR: Digital
 Built-in IC card reader
 Card Capacity 10000
 IP65(Apply silica gel to gaps between the device and the wall)

11202 252,00 210,00

OEU-202S-HMK4



11204	<p>Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)</p>	276,00	230,00
-------	--	--------	--------



OEU-301S-HMKA



11301	<p>Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 Alarm Output: 2 IP65(Apply silica gel to gaps between the device and the wall)</p>	420,00	350,00
-------	---	--------	--------



EP-CS201



11203	<p>Wall Mount Sunshield Compatible with OEU-201B-HMK-W, OEU-201B-HMK-W-NB, OEU-201S-HMK-W, And OEU-201S-HMK-W-NB villa door stations</p>	18,00	15,00
-------	--	-------	-------



OEI-372S-H-W



11372	<p>Indoor Station Rugged ABS casing and glass panel. 1024*600 HD touch screen. Batch configuration transfer. Remote opening of linked door stations, one-key opening. Network camera monitoring, security alarm</p>	192,00	160,00
-------	--	--------	--------



KIT/201S/372S/NSW2020



11205	<p>OEU-201S-HMK-W Metal casing. Supports call and intercom with the connected indoor station and app. Supports security protection alarm and tamper alarm triggered by door magnet, infrared, etc. Supports Wi-Fi. Built-in IC card reader.</p> <p>OEI-372S-H-W ABS casing and glass panel, solid and durable. Supports Wi-Fi. Supports touchscreen operation. 1024 x 600 HD screen. Supports remote door opening by sending signal to the door station. Allows to view live video of connected door stations and network cameras.</p> <p>NSW2020-6T-POE-IN Allows to switch operating modes, including Default, VLAN, and Extend. Supports VLAN isolation. All PoE ports are isolated from each other and only able to communicate with uplink ports. Supports network extension. With a high-quality network cable and IPC, the network transmission distance can reach up to 250 meters by lowering the network port rate to 10Mbps. Supports port priority. Packets from high-priority ports will be forwarded first. Supports flow control. When there is data congestion in the uplink ports, the switch will actively send flow control frames to PoE ports. Plug-and-play, simple and convenient. All metal casing, secure and reliable.</p>	360,00	300,00
-------	--	--------	--------

HARD DISKOVI

WD GREEN 320 GB



Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 500 GB



Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 1 TB



Western Digital, 1 TB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

HDD 1TB WD11PURZ-85C5HYO



I1100 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

104,40 87,00

HDD 2TB WD23PURZ-85C5HYO



I1200 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

144,00 120,00

HDD 4TB WD44PURZ-85CPDYO



I1400 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB

192,00 160,00

HDD 6TB WD64PURZ-74BWUYO



I1600 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB

275,00 230,00

HDD 8TB WD64PURZ-85BWUYO



6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB

372,00 310,00

TF-64G-T-L



Uniview memorijska kartica
Kapacitet: 64GB
Maksimalna brzina čitanja: 90MB/s
Maksimalna brzina pisanja: 65MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g

14,40 12,00

TF-128G-T-L



Uniview memorijska kartica
Kapacitet: 128GB
Maksimalna brzina čitanja: 100MB/s
Maksimalna brzina pisanja: 80MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g

22,80 19,00

TF-256G-T-L

NOVO



11123	<p>Uniview memorijska kartica Kapacitet: 256GB Maksimalna brzina čitanja: 90MB/s Maksimalna brzina pisanja: 65MB/s Dimenzije: 11mm x 15mm x 1mm Težina: 0,33g</p>	43,20	36,00
-------	--	-------	-------

Uniview SVIČEVI

NSW1010-5T-IN

NOVO



11130	<p>5-Port 100 Megabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.</p>	8,40	7,00
-------	--	------	------

NSW1010-8T-IN

NOVO



11131	<p>8-Port 100 Megabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.</p>	12,00	10,00
-------	--	-------	-------

NSW1010-5GT-IN

NOVO



11132	<p>5-Port Gigabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode</p>	14,40	12,00
-------	---	-------	-------

NSW1010-8GT-IN

NOVO



11133	<p>8-Port Gigabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.</p>	24,00	20,00
-------	--	-------	-------

Uniview POE SVIČEVI

NSW2020-6T-POE-IN



11023	<p>6x100Mbps network ports (RJ45), od toga 4 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm</p>	NEMA NA STANJU	
-------	--	-----------------------	--

NSW2010-5GT-POE-IN



11059	<p>4 Port GigabitPoE Switch 1 Port Gigabit Uplink PoE Power up to 30W Each Port Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD) Auto Detect Power Device Power Port Supply prioritization, guarantees the continuous power supply of key nodes IEEE802.3 X full duplex flow control and Backpressure half duplex flow control Line Speed Forwarding, intelligent identification Up to 250m transmission distance on surveillance mode</p>	78,00	65,00
-------	--	-------	-------

NSW2020-10T-POE-IN



I1024	<p>10x100Mbps network ports (RJ45), od toga 8 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode); 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm</p>	90,00	75,00
-------	--	-------	-------

NSW2010-10GT-POE-IN



I1060	<p>8 Port Gigabit PoE Switch 2 Port Gigabit Uplink PoE Power up to 30W Each Port Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD) Auto Detect Power Device Power Port Supply prioritization, guarantees the continuous power supply of key nodes IEEE802.3 X full duplex flow control and Backpressure half duplex flow control Line Speed Forwarding, intelligent identification Up to 250m transmission distance on surveillance mode</p>		NEMA NA STANJU
-------	---	--	-----------------------

NSW2100-9GT16P-LPOE-IN



I1060	<p>8 Port Gigabits PoE Switch Ports Type: 8x 10/100/1000Mbps PoE port (RJ45) 1 x 10/100/1000Mbps port (RJ45) 1 x Gigabit SFP Supports Web login, and device configuration and management on the Web interface. Supports visiting the cloud by scanning the QR code. Allows to view the device status in real time on the app, and remotely restart the PoE power supply. Supports PoE power supply ; allows to enable or disable PoE power supply for the powered device; allows up to 250m power supply using a standard network cable. Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate. Supports port priority. The priority port will be powered first when the PoE power supply is full. All metal casing, secure and reliable.</p>		U DOLASKU
-------	--	--	------------------

NSW3000-8T2GT-POE-IN



I1134	<p>Cloud Managed Ethernet Switch(PoE) 8 x 10/100Mbps POE port (RJ45) ,2 x Gigabit port (RJ45) Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software. Supports Web login, and device configuration and management on the Web interface; supports visiting the cloud by scanning the QR code. Allows to view the device status and network topology in real time on the app, and remotely restart the PoE power supply. Allows up to 250m power supply using a standard network cable. Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate. Allows to report port abnormal alarms to the software for realtime monitoring. Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full. All metal casing, secure and reliable. Maximum total power: 120W Maximum PoE power for single port: 30W</p>	96,00	80,00
-------	--	-------	-------

NSW2020-16T2GC-POE-IN



I1067	<p>16x100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az, IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga: 250W Maksimalna PoE snaga porta: 30W Dimenzije: 440mm x 207mm x 45mm Moguća rek montaža 19" , dolazi uz switch</p>	216,00	180,00
-------	---	--------	--------

NSW3000-16T1G1GC-LPOE-IN



	<p>Cloud Management Switch 16 x 10/100Mbps POE port (RJ45) + 1 x Gigabit port (RJ45)+ 1 x Gigabit Combo Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software. Supports Web login, and device configuration and management on the Web interface in real time on the app, and remotely restart the PoE power supply. Supports PoE power supply and allows to view the power; allows to enable or disable PoE power supply for the powered device; Allows up to 250m power supply using a standard network cable. Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate. Allows to report port abnormal alarms to the software for realtime monitoring. Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full. All metal casing, secure and reliable. Maximum total power: 150W Maximum PoE power for single port: 30W</p>	150,00	125,00
--	--	--------	--------

NSW2020-24T1G1GC-POE-IN



	<p>Unmanaged Ethernet Switch(PoE) 24×100Mbps PoE ports (RJ45) + 1×1000Mbps Gigaethernet ports +1×1000Mbps Combo ports Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode) Support port traffic control Support for secure mode, all downlink ports can communicate only with uplink ports Up to 250m transmission distance on surveillance mode Support buffer optimization All metal housing, safe and reliable Max capacity:370W Max capacity for single port: 30W</p>	232,20	193,50
--	---	--------	--------

NSW2010-24T2GC-PoE-IN



	<p>Ethernet Switch(PoE) 24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode) Support port traffic control Support for secure mode, all downlink ports can communicate Only with uplink ports Up to 250m transmission distance on surveillance mode Support buffer optimization All metal housing, safe and reliable Max power: 390W</p>	288,00	240,00
--	---	--------	--------

MONITORI

MW3224-V



	<p>UNV 24" LED Monitor Resolution 1920 × 1080 Color Support: 16.7 M Refresh Rate: 60 Hz Operation Hour: 24/7</p>	120,00	100,00
--	--	--------	--------

DODATNA OPREMA

GCB01-B7



	<p>UNV-Link Pro Connect Box Network: 4 x RJ45 10M/100M Base-TX EthernetNetwork Port 1 Support POE (IEEE802.3af) OutputNetwork Port 4 Support PSE Voltage Test Wi-Fi 2.4G Wi-Fi Battery: 7500mAH Power Input: 1 x DC 5V/2A max, type-c Power Output: 1 x DC 12V/1A output; 1 x DC 5V/1A output, type-A</p>	78,00	65,00
--	--	-------	-------

PoE Extender



Model: LN-POEPL03S
9995 PoE In: 44-57V/30W
PoE Out (1-3) : 44-57V/25W
Support: 10/100 Mbps IEEE802.3af/at

NEMA NA STANJU

3 Ports POE Injector




PoE extender, repeater, switch 1 na 2
Usklađenost sa IEEE 802. af/at
2255 Power over Ethernet(10/100M podržano)
Proširite domet Porta za dodatnih 100 metara

25,00 20,83

KABLOVI


UNV Cat6 (UTP), CCA



i1044 CAB-LC3100B-CCA-IN
Conductor material: CCA(Copper content: 27%)
Insulation material: HDPE
Packing length: 305±1 m
Sheath material: PVC

NEMA NA STANJU


UNV Cat5e (UTP), BC



i1045 CAB-LC2100A-E2-ECA-IN
Conductor material: OFC (Oxygen free copper)
Insulation material:HDPE
Packing length: 305±1 m
Sheath material: PVC (complies RoHS/REACH)

0,54 0,450

UNV Cat6 (UTP), BC




i1046 CAB-LC3100A-EC-ECA-IN
Conductor material: OFC (Oxygen free copper)
Insulation material: HDPE
Packing length: 305±1 m
Sheath material: PVC (complies RoHS/REACH)

0,78 0,650

CAB-LC3110B-E-IN

NOVO



Cat6 305m Outdoor UTP Network Cable (OFC 0.5mm Black)
Packing length: 305±1m
Material: Solid-Bare Copper
Insulation material: HDPE
Sheath material(IN Jacket): PVC(complies RoHS/REACH)
Sheath material (OUT Jacket): LDPE
Color: Black

U DOLASKU


KUĆIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633 Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje. 3,60 3,00

DOZNA ZA KAMERE G153



8644 Razvodna kutija za spoljašnu montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje. 3,20 2,67

DOZNA ZA KAMERE BA-02



8645 Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje. 3,00 2,50

TR-JB05-B-IN



11062 Nosač za Dome kamere serije IPC21XX
Dimenzije: $\Phi 104,4\text{mm} \times 54,5\text{mm}$
Težina: 0.36kg
Materijal: Aluminijum 19,20 16,00

TR-JB05-A-IN



11061 Nosač za kamere
Dimenzije: $\Phi 93 \times 93 \times 39\text{mm}$
Težina: 0.2kg
Materijal: Aluminijum 15,60 13,00

TR-JB03-G-IN



11064 Nosač za Dome kamere serije IPC32x i IPC31x
Dimenzije: $\phi 106,6\text{mm} \times 36\text{mm}$
Težina: 0.2kg
Materijal: Aluminijum 13,20 11,00

TR-JB03-I-IN



11063 Nosač za Dome kamere serije IPC36XXL i IPCT1XX
Dimenzije: $\emptyset 117,8 \times 36\text{mm}$
Težina: 0.2kg
Materijal: Aluminijum 15,60 13,00

TR-JB03-H-IN



11171 Nosač za Dome kamere serije IPC363X, IPC36XXS/E i 4MP fisheye
Dimenzije: $\Phi 126\text{mm} \times 36\text{mm}$ (4.96" x 1.42")
Težina: 0.24kg
Materijal: Aluminijum legura 14,40 12,00

TR-JB04-C-IN

NOVO



Nosač za Dome kamere serije 323
 Dimenzije: $\Phi 144.8$ mm \times 42.5 mm (5.7" \times 1.7")
 Težina: 0.3kg
 Materijal: Aluminijum legura

15,60 13,00

TR-JB07-D-IN

NOVO



11170 Bullet Junction Box(Support wiring from behind)

30,00 25,00

TR-JB07/WM03-G-IN

NOVO



11165 Wall Mounting Assembling Bracket For 32 Fix-dome
 &Mini Fix-dome&Plastic Turret Camera

36,00 30,00

TR-WM07P-B

NOVO



Dome Wall Mounting Plastic Bracket
 Application: IPC32X Series, IPC361XX Series (Plastic)
 Bracket Weight: 0,10kg

U DOLASKU

UNV TR-UP06-C-IN



11169 Pole Mounting Bracket for Bullet Junction Box Only
 Application: Outdoor, pole or rail installation for
 Bullet camera of IPC23XX OEM IPC23XX/22X、IPC74X and IPC252/26X series
 Bracket Dimensions: 136.0 mm \times 127.0 mm \times 63.6 mm (5.4" \times 5.0" \times 2.5")
 Bracket Weight: 0.34kg
 Bracket Material: Aluminum alloy

NEMA NA STANJU

KONEKTORI

BNC NA LEMLJENJE
SA ŠRAFOM

3299 BNC konektor muški sa šrafom.
 Pakovanje 100 kom.

0,54 0,45

BNC NA LEMLJENJE



2560 BNC konektor muški na lemljenje.
 Pakovanje 100 kom.

0,54 0,45

BNC KONEKTOR



30020 BNC konektor muški na šraf.

0,50 0,42

BNC NA KRIMP RG59



2534 BNC konektor za RG59 kabl na krimp.
 Pakovanje 100 kom.

0,60 0,50

BNC MUŠKI- F ŽENSKI1795 BNC konektor muški F ženski.
Pakovanje 100 kom.

0,70 0,58

BNC NASTAVAK4447 BNC konektor. Nastavak ženski-ženski.
Pakovanje 100 kom.

0,54 0,45

**F KONEKTOR na krímp
RG6**2559 F konektor za RG6 kabl.
Pakovanje 100 kom.

0,14 0,12

F KONEKTOR na krímp RG591796 F konektor za RG59 kabl.
Pakovanje 100 kom.

0,14 0,12

RF METALNI G MUŠKI4448 RF metalni G muški (UGAONI) konektor
Pakovanje 100 kom.

0,35 0,29

RCA MUŠKI-F ŽENSKI4446 RCA muški - F ženski konektor
Pakovanje 100 kom.

0,53 0,44

F NASTAVAK3300 F nastavak ženski - ženski
Pakovanje 100 kom

0,22 0,18

**F KONEKTOR
KOMPRESIONI RG6 XL**1625 Profesionalni PPC F konektor za RG6 kabl.
Pakovanje 50 kom.

0,44 0,37

**F KONEKTOR
KOMPRESIONI RG11 XL**

1627 Profesionalni PPC F konektor za RG11 kabl.

2,96 2,47

**F KONEKTOR
KOMPRESIONI RG59 XL**1624 Profesionalni PPC F konektor za RG59 kabl.
Pakovanje 50 kom.

0,47 0,39

DC KABL-MUŠKI

1387 DC utikač-muški

0,47 0,39

DC KABL-ŽENSKI

1391 DC utikač-ženski

0,47 0,39

DC KONEKTOR MUŠKI

3425 DC konektor Muški

0,37 0,31

DC KONEKTOR ŽENSKI



4197 DC konektor ženski.

0,38 0,32

DC RAZDELNIK 1-4



1388 1 DC utičnica - 4 DC utikača

1,99 1,66

DC RAZDELNIK 1-8



1389 1 DC utičnica - 8 DC utikača

3,97 3,31

CAT7 RJ45



Mrežni konektor RJ45 kategorija 7

0,50 0,42

CAT6 UNV RJ45 GC-RJ6-IN

NOVO



Cat6 Unshielded Crystal Head
 3μ inches gold-plated for excellent contact performance
 Stable data transmission with up to 750 plugs and unplugs
 Highly transparent PC material support RoHS standards,
 Wear-resistant and durable
 8 pins × 8 conductors, support 1000Bas-T Ethernet

U DOLASKU

CAT5 RJ45



0067 Mrežni konektor RJ45

0,05 0,04

Telefonski konektor RJ11



0066 Telefonski konektor RJ11

0,02 0,02

DODATNA OPREMA

ŠTAMPAČ P-TOUCH E100



Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu

106,56 88,80

MIKROFON LY-501C

2584 Audio modul sa izvedenim konektorima.
Napajanje 12 V DC

3,97 3,31

MIKROFON LY-502B












2583 Audio modul plastični sa trimerom.
Napajanje 12 V DC

6,00 5,00








MIKROFON LY-506

1937 Audio modul metalni sa trimerom.
Napajanje 12 V DC

10,00 8,33

DS-2FP2020		5222	Viisoko osetljivi omnidirekcionni mikrofon. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).	36,00	30,00
DH-PFM800-4K (par)		3632	One (1) Channel Balun Real-time Transmission over UTP CAT5E/6 Cable Compatible with HDCVI, TVI, AHD, and CVBS Video Formats Transmission Distance at 4K: 200 m (656 ft) External Power Supply not Required	6,90	5,75
OG razvodna kutija 100x100		00091	Razvodna kutija 100x100	1,80	1,50
OG razvodna kutija 80x80		00092	Razvodna kutija 80x80	1,10	0,92
OG razvodna kutija 160x100x74		00093	Razvodna kutija 160x100x74	3,00	2,50
OG razvodna kutija 160x100x48		00094	Razvodna kutija 160x100x48	2,64	2,20
ALAT ZA KRIMP RG6, RG11, RG59		3302	Alat za krimpovanje RG6, RG11, RG59 konektora	48,00	40,00
STRIPER ZA KABLOVE RG59, RG6		3301	Alat za stripovanje RG59, RG6 kablova	20,40	17,00
ALAT KOMPRESIONI ZA RG59, RG6		1629	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59, RG6 XL oznake.	37,92	31,60
ALAT KOMPRESIONI, ZA RG6, RG11, RG59		3796	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6, RG11, RG59 XL oznake.	54,34	45,28
KLEŠTA ZA KRIMPOVANJE KOMPLET		5790	Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sećicom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)	28,68	23,90

NAPAJANJA

XED-1212S		1633	Ulaz: 90V-264V Izlaz: 12V , 1A Snaga: 12W Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	6,00	5,00
XED-2012S		1382	Ulaz: 90V-264V Izlaz: 12V , 2A Snaga: 24W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	8,04	6,70
XED-3013S		1383	Ulaz: 90V-264V Izlaz: 12V , 3A Snaga: 36W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	12,60	10,50
XED-5013S		1384	Ulaz: 100V-240V Izlaz: 12V , 5A Snaga: 60W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	16,20	13,50
XED-6013B		3509	Ulaz: 100V-240V Izlaz: 12V , 6A Snaga: 72W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	20,40	17,00
9-KANALNO NAPAJANJE XED-10A12VX-9L		5435	Snaga: 120W Ulaz: 100-240V 50-60Hz Izlaz: 12V 10A 9 kanala Dimenzije: 237*213*70mm Neto težina: 1800g Napomena: Sadrži AC kabl	82,80	69,00
18-KANALNO NAPAJANJE XED-15A12VX-18L		5114	Snaga: 180W Ulaz: 100-240V 50-60Hz Izlaz: 12V 15A 18 kanala Dimenzije: 240*218*70mm Neto težina: 2300g Napomena: Sadrži AC kabl	94,80	79,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs