

## CENOVNIK UNIVIEW VIDEO NADZORA - 24.03.2026.



NAZIV	ŠIFRA	OPIS	CENA	
-------	-------	------	------	--

### DVR UREDJAJI

sa PDV bez PDV

#### 4 KANALNI

##### XVR301-04G3



#### 4-CH Hybrid DVR

Podrzan video ulaz: 5MP @ 20fps ( Prvi kanal 20fps, ostali 12fps ) 5MP @ 12fps, 4MP @ 30fps ( Prvi kanal )

4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podrzan video ulaz IP kamere: do 4MP ( 2 IP kamere ili svih 6 )

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulazno/Izlazni saobraćaj: 16/48 Mbps

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x226mm x 47mm (10.2" x 8.9"x1.8"), 1.1kg

11031

69,60 58,00



##### XVR301-04Q3



#### 4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp ( 2 IP kamere ili svih 6 )

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

Ulazno/Izlazni saobraćaj: 48/60 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x226mm x 47mm

11032

96,00 80,00

**XVR301-04U3****4-ch 1U Digital Video Recorder**

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1  
 Support Ultra 265/H.265/H.264 video formats  
 Support audio over coaxial cable (TVI cameras)  
 Control the dual-light of UNV analog cameras under TVI  
 Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access  
 Support 1-ch CVBS output, 1-ch VGA output,  
 1-ch HDMI output at up to 4K (3840 x 2160)  
 HDMI and VGA simultaneous output  
 Long transmission distance over coaxial cable  
 Support mainstream cameras of ONVIF and RTSP protocols  
 1HDD Up to 16 TB

I1129

144,00 120,00

**8 KANALNI****XVR301-08G****8-Ch Digital Video Recorder**

Support H.265/H.264 video formats  
 Recording Resolution: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF  
 Support audio over coaxial cable (only for TVI cameras)  
 Control the dual-light of UNV analog cameras under TVI  
 Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access  
 4/8/16-channel BNC input  
 Support 1-ch HDMI output, 1-ch VGA output at up to 1920\*1080  
 HDMI and VGA simultaneous output  
 Long transmission distance over coaxial cable  
 Support mainstream cameras of ONVIF and RTSP protocols  
 1 SATA interface up to 6 TB

I1176

84,00 70,00

**XVR301-08G3****8-CH Hybrid DVR**

Podrška: TVI,AHD, CVI, CVBS  
 Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF  
 Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)  
 Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)  
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio  
 Ulazno/Izlazni saobraćaj: 32/64 Mbps  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs  
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP  
 Hard disk: 1 sata HDD do 8TB  
 Napajanje 12V DC, Potrošnja 8W bez HDD  
 Radna temperatura: -10 °C ~ +55 °C  
 Dimenzije: 260mm x226mmx 47mm

I1025

91,20 75,00

**XVR301-08Q3****8-CH Hybrid DVR**

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF  
 Podrška TVI,AHD, CVI,CVBS  
 Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)  
 Video kompresija: H.265, H.264  
 Video/audio ulazi: 8ch BNC, 1ch audio  
 Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio  
 Ulazno/Izlazni saobraćaj: 40/64 Mbps  
 Smart funkcije: Motion detection, video loss detection, audio detection,  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1  
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP  
 Hard disk: 1 sata HDD do 8TB kapaciteta  
 Napajanje 12V DC,  
 Potrošnja 10W bez HDD,  
 Radna temperatura: -10 °C ~ +55 °C,  
 Dimenzije: 260mm x226mmx 47mm

I1033

138,00 115,00



**XVR301-08U3**

**uniview**  
Better Security. Better World.

**8-Ch 1U Digital Video Recorder**

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1  
Support Ultra 265/H.265/H.264 video formats  
Support audio over coaxial cable (TVI cameras)  
Control the dual-light of UNV analog cameras under TVI  
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access  
8-channel BNC input  
Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K (3840 x 2160)  
HDMI and VGA simultaneous output  
Long transmission distance over coaxial cable  
Support mainstream cameras of ONVIF and RTSP protocols

**11080** **222,00** **185,00**

**16 KANALNI****XVR301-16G3**

**uniview**  
Better Security. Better World.

**16-CH Hybrid DVR**

Podržava: TVI, AHD, CVI, CVBS, IP cameras  
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF  
IP kamere: do 8 IP kamere ili svih 16  
Video/audio ulazi: 16-ch BNC / 1-ch RCA  
Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio  
Ulazno/izlazni saobraćaj: 40/64 Mbps  
Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485  
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP  
Hard disk: 1 SATA HDD do 8TB  
Napajanje 12V DC, Potrošnja 10W bez HDD  
Radna temperatura: -10 °C ~ +55 °C  
Dimenzije: 260mm x226mmx 47mm

**11026** **148,80** **124,00**

**XVR302-16Q3**

**uniview**  
Better Security. Better World.

**16-CH Hybrid DVR**

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF  
Podržava 8MP@15fps na prva 4 kanala  
Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.  
Ulazno/izlazni saobraćaj: 72/80 Mbps  
Video kompresija: H.265/H.264 video kompresija,  
Video/audio ulazi: 16ch BNC, 1ch RCA  
Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA  
Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection  
Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485  
Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  
Hard disk prostor: 2 sata HDD do 6TB kapaciteta  
Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,  
Radna temperatura: -10 °C ~ +55 °C,  
Dimenzije: 380mm x315mmx 53mm, Težina 1.9Kg

**11034** **288,00** **240,00**

**KIT/XVR 301-04G3/4\*UAC-T112-F28****UNV KIT/XVR 301-04G3/4\*UAC-T112-F28**

Kompet sadrži:  
1x XVR 04G3  
4x UAC-T112-F28  
1x Napajanje 2A  
4x 20m Koaksijalni kabl + napajanje (sa konektorima)  
1x Razdelnik 1 / 4

**11065** **180,00** **150,00**

**ANALOGNE DOME KAMERE 2MP****UAC-T112-AF28****2MP HD Fixed IR Turret Analog Camera**

2MP high quality image  
TVI/AHD/CVI/CVBS  
IR-cut filter with auto switch (ICR)  
Built-in microphone  
Supports 180° horizontal flip, 180° vertical flip  
OSD configuration menu, easy to operate  
IP67 waterproof and dustproof design, high reliability  
OSD configuration menu in 11 languages

**11066** **24,00** **20,00**

**UNV**

**UAC-T112-F28-W**

	<b>2MP ColourHunter HD Fixed Turret Analog Camera</b>		
	2MP high quality image TVI/AHD/CVI/CVBS		
11006	Supports white light illumination, 24/7 full-color imaging Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	28,80	24,00

**UAC-T122-AF28LM**

	<b>2MP LightHunter HD IR Fixed Turret Analog Camera</b>		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11054	Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	36,00	30,00

**UAC-T122-AF40LM**

	<b>2MP LightHunter HD IR Fixed Turret Analog Camera</b>		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11099	Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	36,00	30,00

**UAC-T122-AF28M-W**

	<b>2MP ColorHunter HD Fixed Turret Analog Camera</b>		
	2MP high quality imaging TVI/AHD/CVI/CVBS		
11016	Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing 3-Axis		

NEMA NA STANJU

**UAC-T142-AF28LM-DL**

	<b>2MP ColorHunter Fixed Dual-light Turret Analog Camera</b>		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11077	Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	43,20	36,00

**ANALOGNE BULLET KAMERE 2MP****UAC-B112-F28**

	<b>2MP HD Fixed IR Mini Bullet Analog Camera</b>		
	2MP high quality image TVI/AHD/CVI/CVBS		
11000	IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	25,20	21,00

**UAC-B112-AF28**

1121	<p><b>2MP Fixed IR Bullet Analog Camera</b>          2MP high quality image          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          3D noise reduction technology delivers clean and sharp images          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables</p>	26,40	22,00
------	---	-------	-------

**UAC-B112-F28-W**

11001	<p><b>2MP ColourHunter HD Fixed Mini Bullet Analog Camera</b>          2MP high quality image          TVI/AHD/CVI/CVBS          Supports white light illumination, 24/7 full-color imaging          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages</p>	27,60	23,00
-------	---	-------	-------

**UAC-B122-AF28LM**

11053	<p><b>2MP LightHunter HD IR Fixed Mini Bullet Analog Camera</b>          High quality imaging with 2MP resolution          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          LightHunter monitoring with high-sensitivity sensor          3D noise reduction technology delivers clean and sharp images          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables          Supports digital defog</p>	36,00	30,00
-------	--	-------	-------

**UAC-B122-AF40LM**

11098	<p><b>2MP LightHunter HD IR Fixed Mini Bullet Analog Camera</b>          High quality imaging with 2MP resolution          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          LightHunter monitoring with high-sensitivity sensor          3D noise reduction technology delivers clean and sharp images          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables          Supports digital defog</p>	36,00	30,00
-------	--	-------	-------

*NEMA NA STANJU***UAC-B122-AF28M-W**

11014	<p><b>2MP ColorHunter HD Fixed Mini Bullet Analog Camera</b>          2MP high quality imaging          TVI/AHD/CVI/CVBS          Supports white light illumination, 24/7 color images          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          SD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables          Supports digital defog          Metal front face and housing</p>	36,00	30,00
-------	---	-------	-------

**UAC-B122-AF28M-W-Black**

11214	<p><b>2MP ColorHunter HD Fixed Mini Bullet Analog Camera</b>          2MP high quality imaging          TVI/AHD/CVI/CVBS          Supports white light illumination, 24/7 color images          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          SD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables          Supports digital defog          Metal front face and housing</p>	36,00	30,00
-------	---	-------	-------

## UAC-B122-AF40M-W



11015	<b>2MP ColorHunter HD Fixed Mini Bullet Analog Camera</b> 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing	37,20	31,00
-------	---	-------	-------

## UAC-B142-AF28LM-DL



11076	<b>2MP ColorHunter Fixed Dual-light Bullet Analog Camera</b> High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	46,80	39,00
-------	---	-------	-------

## UAC-B142-AF40LM-DL



11122	<b>2MP ColorHunter Fixed Dual-light Bullet Analog Camera</b> High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	46,80	39,00
-------	---	-------	-------

## ANALOGNE DOME KAMERE 5MP

### UAC-T115-AF28



11126	<b>5MP Fixed IR Turret Analog Camera</b> 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	30,00	25,00
-------	---	-------	-------

### UAC-T125-AF28LM



11056	<b>5MP LightHunter HD IR Fixed Turret Analog Camera</b> High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables 3-Axis	46,80	39,00
-------	---	-------	-------

### UAC-T125-AF28M-W



11020	<b>5MP ColorHunter HD Fixed Turret Analog Camera</b> 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis		
-------	--	--	--

NEMA NA STANJU

UAC-T125-AF28M-W-Black



	<p><b>5MP ColorHunter HD Fixed Turret Analog Camera</b>          5MP high quality imaging          TVI/AHD/CVI/CVBS          Supports white light illumination, 24/7 color images          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables          Metal front face and housing          3-Axis</p>	48,00	40,00
--	---	-------	-------

UAC-T145-AF28LM-DL



	<p><b>5MP ColorHunter Fixed Dual-light Turret Analog Camera</b>          High quality imaging with 5MP resolution          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          Smart Dual Light (only TVI)          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables</p>		
--	---	--	--

NEMA NA STANJU

ANALOGNE BULLET KAMERE 5MP

UAC-B115-F28



	<p><b>5MP HD Fixed IR Mini Bullet Analog Camera</b>          5MP high quality image          TVI/AHD/CVI/CVBS          IR-cut filter with auto switch (ICR)          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages</p>	30,00	25,00
--	---	-------	-------

UAC-B115-AF28



	<p><b>5MP Fixed IR Bullet Analog Camera</b>          5MP high quality image          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables</p>	30,00	25,00
--	--	-------	-------

UAC-B125-AF28LM



	<p><b>5MP LightHunter HD IR Fixed Mini Bullet Analog Camera</b>          High quality imaging with 5MP resolution          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          LightHunter monitoring with high-sensitivity sensor          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables</p>	44,40	37,00
--	---	-------	-------

UAC-B125-AF40LM



	<p><b>5MP LightHunter HD IR Fixed Mini Bullet Analog Camera</b>          High quality imaging with 5MP resolution          TVI/AHD/CVI/CVBS          Supports IR-cut filter with auto-switch (ICR)          LightHunter monitoring with high-sensitivity sensor          Supports 180° horizontal flip, 180° vertical flip          OSD configuration menu, easy to operate          IP67 waterproof and dustproof design, high reliability          OSD configuration menu in 11 languages          Built-in microphone for high quality audio transmission via coaxial cables</p>	44,40	37,00
--	---	-------	-------

**UAC-B125-AF28M-W**

11018	<p><b>5MP ColorHunter HD Fixed Mini Bullet Analog Camera</b>            5MP high quality imaging            TVI/AHD/CVI/CVBS            Supports white light illumination, 24/7 color images            Supports 180° horizontal flip, 180° vertical flip            OSD configuration menu, easy to operate            IP67 waterproof and dustproof design, high reliability            OSD configuration menu in 11 languages            Built-in microphone for high quality audio transmission via coaxial cables            Metal front face and housing</p>	48,00	40,00
-------	--	-------	-------

**UAC-B125-AF40M-W**

11019	<p><b>5MP ColorHunter HD Fixed Mini Bullet Analog Camera</b>            5MP high quality imaging            TVI/AHD/CVI/CVBS            Supports white light illumination, 24/7 color images            Supports 180° horizontal flip, 180° vertical flip            OSD configuration menu, easy to operate            IP67 waterproof and dustproof design, high reliability            OSD configuration menu in 11 languages            Built-in microphone for high quality audio transmission via coaxial cables            Metal front face and housing</p>	49,20	41,00
-------	--	-------	-------

**UAC-B145-AF28LM-DL**

11078	<p><b>5MP ColorHunter Fixed Dual-light Bullet Analog Camera</b>            High quality imaging with 5MP resolution            TVI/AHD/CVI/CVBS            Supports IR-cut filter with auto-switch (ICR)            Smart Dual Light (only TVI)            Supports 180° horizontal flip, 180° vertical flip            OSD configuration menu, easy to operate            IP67 waterproof and dustproof design, high reliability            OSD configuration menu in 11 languages            Built-in microphone for high quality audio transmission via coaxial cables</p>	54,00	45,00
-------	---	-------	-------

**NVR UREDJAJI****NVR301-04S3**

11049	<p><b>4-ch NVR</b>            Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p            Ulazno/Izlazni saobračaj: 64/48Mbps            Video kompresija: Ultra 265, H.265, H.264 video kompresija,            Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),            Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection            ONVIF conformance: Profile S, Profile G, Profile T            Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search            Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm            Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE            Hard disk prostor: 1 sata HDD do 6TB kapaciteta            Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,            Radna temperatura: -10 °C ~ +55 °C,            Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg</p>	108,00	90,00
-------	--	--------	-------

**NVR301-04B-IQ**

11115	<p><b>4-ch NVR</b>            Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30            Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30            Support Ultra 265/H.265/H.264 video formats            Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T ) and RTSP protocols            Support HDMI and VGA simultaneous output            Up to 12 Megapixels resolution recording            ANR technology to enhance the storage reliability when the network is disconnected            Support cloud upgrade            1x HDD, up to 10TB</p>	132,00	110,00
-------	---	--------	--------

**NVR501-04B-IQ****NOVO****PRIME**

I1150

**4-ch NVR**

Decoding Capability:  
 Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30  
 Smart On: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30  
 Support Ultra H.265/H.265/H.264 video formats  
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution  
 Support HDMI and VGA simultaneous output  
 Up to 16 Megapixels resolution recording  
 ANR technology to enhance the storage reliability when the network is disconnected  
 Support cloud upgrade  
 1 SATA Interface, up to 16 TB

150,00 125,00

**NVR301-04LS2-P4****NOVO****EASY**

I1149

**4-ch PoE NVR**

Support Ultra 265/H.265/H.264 video formats  
 4-channel input  
 Recording Resolution: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 Capability: 1 x 6MP@20, 1 x 5MP@30, 2 x 4MP@25, 2 x 3MP @30,  
 4 x 1080p@25, 8 x 960p@25,8 x 720p@30  
 Third-party IP cameras supported with ONVIF conformance:  
 Profile S, Profile G, Profile T  
 Support 1-ch HDMI, 1-ch VGA  
 HDMI and VGA simultaneous output  
 Up to 6MP resolution recording  
 1 SATA HDD up to 6 TB  
 Support cloud upgrade  
 Power Supply: 48V DC

120,00 100,00

**NVR301-08S3****EASY**

I1048

**8-ch NVR**

Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
 Ulazno/Izlazni saobraćaj: 64/48 Mbps  
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,  
 Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije  
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection  
 Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search  
 ONVIF conformance: Profile S, Profile G, Profile T  
 Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,  
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE  
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta  
 Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,  
 Radna temperatura: -10 °C ~ +55 °C,  
 Dimenzije: 260mm x 240mm x 46mm, Težina 1Kg

120,00 100,00

**NVR301-08B-IQ****NOVO****EASY**

I1117

**8-ch NVR**

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30  
 Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30  
 Support Ultra 265/H.265/H.264 video formats  
 4/8/16 channel input  
 Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T ) and RTSP protocols  
 Support HDMI and VGA simultaneous output  
 Up to 12 Megapixels resolution recording  
 ANR technology to enhance the storage reliability when the network is disconnected  
 Support cloud upgrade  
 1x HDD, up to 10TB

150,00 125,00

**NVR501-08B-IQ****NOVO****PRIME**

I1118

**8-ch NVR**

Decoding Capability: Smart Off: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30  
 Smart On: 2 x 12MP@30, 2 x 4K@30,  
 6 x 4MP@30, 8 x 3MP@30  
 Smart On: 2 x 12MP@30, 2 x 4K@30,  
 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30  
 Support Ultra H.265/H.265/H.264 video formats  
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T ) and RTSP protocols  
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution  
 Support HDMI and VGA simultaneous output  
 Up to 16 Megapixels resolution recording  
 ANR technology to enhance the storage reliability  
 When the network is disconnected  
 Support cloud upgrade  
 1 SATA Interface, up to 16 TB

168,00 140,00

**NVR301-16S3****NOVO****EASY**

1116

**16-ch NVR**

Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Ulazno/izlazni saobraćaj: 64/48Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),

Smart Funkcije:Face detection, Intrusion detection,

Cross line detection, Audio detection

ONVIF conformance: Profile S, Profile G, Profile T

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

138,00

115,00

**NVR301-16B-IQ****NOVO****EASY**

1151

**16-ch NVR**

Decoding Capability - Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 10 x 1080P@30, 16 x 720P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30, 16 x 720P@30

Support Ultra 265/H.265/H.264 video formats

Support mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T ) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

210,00

175,00

**NVR501-16B****PRIME**

11047

**16-ch NVR**

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/izlazni saobraćaj: 80/64 Mbps

Video kompresija: Ultra 265/H.265/H.264

Video/audio izlazi: HDMI (4K) / HD, VGA

Smart Funkcije: Intrusion Detection, Cross Line Detection,Enter Area, Leave Area, Defocus

Detection,Scene Change Detection, Object Left Behind, Object Removed,Auto Tracking, UMD(Ultra Motion Detection)

Statistické analize: People counting

Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP,HTTPS, DNS, DDNS, SNMP, SMTP

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 222mm × 47mm, Težina 0,98Kg

216,00

180,00

Better Security. Better World.

**NVR501-16B-IQ****NOVO****PRIME**

1119

**16-ch NVR**

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30, 12 x

1080P@30, 16 x 720P@30

Support Ultra H.265/H.265/H.264 video formats

Supports mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T ) and RTSP protocols

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability

When the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

228,00

190,00

NVR304-32X

PRIME



32-ch NVR

32-KANALNI MREŽNI SNIMAČ

Rezolucija snimanja:

12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 384/384 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio

detection, Defocus detection, Scene change detection, Auto tracking, Object left

I1154 behind, Object removed, Face search, Behavior search

600,00 500,00

Statisticke analize: People counting

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1 x RS485, 1 x

RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5

Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,

Radna temperatura: -10 °C – +55 °C,

Dimenzije: 442mm x426mmx 89mm, Težina 5,7Kg

DOME IP KAMERE 2MPX

IPC3612LB-SF28-A

EASY

NOVO



2MP Fixed IR Turret Network Camera

High quality image with 1080P, 1/2.8" CMOS sensor

1080P (1920 x 1080)@30/25 fps; 720P (1280 x 720)@30/25 fps

Ultra 265, H.265, H.264

I1144 Smart IR, up to 30 m (98.4 ft) IR distance

66,00 55,00

Day/night functionality

2D/3D DNR (digital noise reduction)

IP67 protection

Supports PoE power supply

3-axis

2MP

IR

Smart IR

Ultra H.265

Smart Search

POE

IP 67

IPC322LB-SF28-A

EASY



2MP Vandal-resistant Network IR Fixed Dome Camera

High quality image with 2MP, 1/2.8" CMOS sensor

2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps

Ultra 265, H.265, H.264

I1174 Smart IR, up to 30m (98ft) IR distance

56,40 47,00

Day/night functionality

2D/3D DNR (Digital Noise Reduction)

IP67 protection

IK10 vandal resistant

Support PoE power supply

2-Axis

2MP

IR

IK10

IP 67

Smart IR

Ultra H.265

POE

IPC322LB-AF28WK-G

EASY



2MP WIFI Fixed Dome Network Camera

High quality image with 2MP, 1/2.9" CMOS sensor

2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps

Ultra 265, H.265, H.264, MJPEG

I1008 Built-in Mic

86,40 72,00

Smart IR, up to 30m (98ft) IR distance

Supports 128 G Micro SD card

IK10 vandal resistant

IP67 protection

3-Axis

2MP

Edge Storage

Built-in Mic

WIFI Connection

Smart IR

Ultra H.265

IR

IP 67

IPC322LB-DSF28K-G



**High quality image with 2MP, 1/2.7" CMOS sensor**

2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 IK10 vandal resistant  
 IP67 protection  
 Support PoE power supply

11177

72,00 60,00

IPC3622LE-ADF28K-WP



**2MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera**

High quality image with 2MP, 1/2.7" CMOS sensor and F1.0 large aperture lens  
 2MP (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, Detail, and smear effects in extremely low-light scenes  
 120 dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 White Light, up to 30 m (98 ft) warm light distance  
 Supports up to 512 GB Micro SD Card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11112

104,40 87,00

IPC3612LE-ADF28KC-WL



**2MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 2MP, 1/2.8" CMOS sensor  
 2MP (1920\*1080) @30/25fps; 720P (1280\*720) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic & Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 White Light, up to 30m (98ft) white light distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11038

110,40 92,00

IPC3532LB-ADZK-G-BLACK



**2MP HD IR VF (2.8 ~ 12mm) Dome Network Camera**

High quality image with 2MP, 1/2.7" CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 40m (131ft) IR distance  
 Supports 128 G Micro SD card  
 IK10 vandal resistant  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11092

156,00 130,00

BULLET IP KAMERA 2MPX

IPC2122LB-SF28-A



**2MP Mini Fixed Bullet Network Camera**

High quality image with 2MP, 1/2.8" CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264  
 Smart IR, up to 30m (98ft) IR distance  
 Day/night functionality  
 2D/3D DNR (Digital Noise Reduction)  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11143

55,20 46,00

IPC2122LB-SF40-A



**2MP Mini Fixed Bullet Network Camera**

High quality image with 2MP, 1/2.8"CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264  
 Smart IR, up to 30m (98ft) IR distance  
 Day/night functionality  
 2D/3D DNR (Digital Noise Reduction)  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11173

55,20 46,00

IPC2122LB-AF28WK-G



**2MP HD WIFI Bullet Network Camera**

High quality image with 2MP, 1/2.9"CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 3-Axis

11009

78,00 65,00

IPC2122LB-AF40WK-G BLACK



**2MP HD WIFI Bullet Network Camera**

High quality image with 2MP, 1/2.9"CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 3-Axis

11093

78,00 65,00

IPC2122LB-ADF40KM-G



**2MP HD WDR Fixed IR Bullet Network Camera**

High quality image with 2MP, 1/2.7"CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 Support PoE power supply  
 3-Axis

11175

72,00 60,00

IPC2122LB-AF28K-WL



**2MP HD ColorHunter Mini Fixed Bullet Network Camera**

High quality image with 2MP, 1/2.9"CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra H.265, H.265, H.264  
 Built-in Mic  
 Warm Light, up to 30m (98ft) warm light distance  
 2D/3D DNR (Digital Noise Reduction)  
 Support 128GB Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11050

99,00 82,50

IPC2312LE-ADF28KM-WP



**2MP ColorHunter with Wise-ISP Fixed Bullet Network Camera**

High quality image with 2MP, 1/2.7"CMOS sensor and F1.0 large aperture lens  
 2MP (1920\*1080) @30/25fps; 720P (1280\*720) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Colorhunter with Wise-ISP technology ensures 24-hour full-color images  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 White Light, up to 30m warm light distance  
 Supports 512 GB Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

I1111 104,40 87,00

IPC2122LE-ADF28KMC-WL



**2MP HD ColorHunter Mini IR Fixed Bullet Network Camera**

High quality image with 2MP, 1/2.8"CMOS sensor  
 2MP (1920\*1080) @30/25fps; 720P (1280\*720) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic & Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 White Light, up to 30m (98ft) white light distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

I1028 110,40 92,00

BULLET IP KAMERE 3MPX

IPC2123LB-AF28KM-G



**3MP HD Fixed IR Bullet Network Camera**

High quality image with 3MP, 1/2.7"CMOS sensor  
 3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

I1037 86,40 72,00

DOME IP KAMERE 4MPX

IPC3614LB-SF28-A



**4MP Fixed Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor  
 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart IR, up to 30m (98ft) IR distance  
 Support PoE power supply  
 3-Axis

I1030 81,60 68,00

IPC324LB-SF28-A

EASY

NOVO



**4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera**

Rezolucija snimanja: ④4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@25/20fps; 2MP (1920\*1080)@30/25fps

Čip: 1/3", progressive scan , 4.0 megapixel, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm @F2.0

Osetljivost: 0.01Lux ( F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP,

DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,Qos,SSL/TLS

Mrežni stadardi: ONVIF (Profile S, Profile T),API,SDK

Kompresija: H.265, H.264,

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR. HLC, BLC, OSD, Privacy mask, ROI, Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V±25%, PoE (IEEE 802.3af), max 5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

11010

81,60

68,00

IPC3614LB-ASF28K-A

EASY

NOVO



**4MP Fixed Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor

4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps

11114

86,40

72,00

Ultra 265, H.265, H.264, MJPEG

Smart IR, up to 30m (98ft) IR distance

Supports 128 G Micro SD card

Support PoE power supply

Built-in Mic

3-Axis

IPC324LB-ASF28K-A

EASY



**4MP Fixed IR Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor

4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps

Ultra 265, H.265, H.264

Built-in Mic

Smart IR, up to 30m (98ft) IR distance

11070

Day/night functionality

2D/3D DNR (Digital Noise Reduction)

Support Micro SD card

IP67 protection

IK10 vandal resistant

DC12V or PoE(IEEE 802.3af) power supply

2-Axis

NEMA NA STANJU

IPC3624LE-ADF28K-WP

EASYSSTAR



**4MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera**

High quality image with 4MP, 1/1.8"CMOS sensor and F1.0 large aperture lens

4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps

Ultra 265, H.265, H.264, MJPEG

Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail,

And smear effects in extremely low-light scenes

120dB true WDR technology enables clear image in strong light scene

11086

128,40

107,00

Support 9:16 Corridor Mode

Built-in Mic

White Light, up to 30m (98ft) warm light distance

Supports 512 GB Micro SD card

IP67 protection

Support PoE power supply

3-Axis

IPC3514LE-ADF28K-WP

EASYSSTAR



**4MP ColorHunter Wise-ISP Fixed Dome Network Camera**

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Supports 512 GB Micro SD card  
 IP67 protection  
 IK10 protection  
 Support PoE power supply  
 3-Axis

11084

128,40 107,00

IPC3614LE-ADF28K-H

EASYSSTAR



**4MP EasyStar Fixed IR Turret Network Camera**

High quality image with 4MP, 1/3" CMOS sensor  
 4MP (2688 × 1520)@25/20 fps; 4MP (2560 × 1440)@25/20 fps; 3MP (2304 × 1296)@30/25 fps; 2MP (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 EasyStar technology ensures high image quality in low illumination environment  
 120 dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 30 m (98 ft) IR distance  
 Supports up to 512 GB Micro SD Card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11137

147,60 123,00

IPC3614LE-ADF28KC-WL

EASYSSTAR



**4MP HD ColorHunter IR Fixed Eyeball Network Camera**

High quality image with 4MP, 1/3" CMOS sensor  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic & Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 White Light, up to 30m (98ft) white light distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11040

150,00 125,00

IPC3614SB-ADF28KMC-10

PRIME



**4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera**

High quality image with 4MP, 1/2.7" CMOS sensor  
 4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Supports sound and light alarm linkage. When Smart intrusion prevention is triggered the camera links sound alarm and light linkage.  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic and Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply

11194

156,00 130,00

IPC3614SB-ADF40KMC-10

PRIME



**4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera**

High quality image with 4MP, 1/2.7"CMOS sensor  
 4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Supports sound and light alarm linkage. When Smart intrusion prevention is triggered, the camera links sound alarm and light linkage.  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic and Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply

i1094

156,00 130,00

IPC354SB-ADNF28K-10

PRIME



**4MP LightHunter Fixed IR Dome Network Camera**

High quality image with 4MP, 1/2.7"CMOS sensor  
 4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and,  
 Motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 30m (98 ft) IR distance  
 Supports 512 G Micro SD card  
 Cable-free  
 Support PoE power supply

i1087

180,00 150,00

IPC3534LB-ADZK-G

EASY

NOVO



**4MP HD IR VF (2.8 ~ 12mm) Dome Network Camera**

High quality image with 4MP, 1/3"CMOS sensor  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296)@ 30/25fps; 2MP (1920\*1080)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 40m (131ft) IR distance  
 Supports 256 G Micro SD card  
 IK10 vandal resistant  
 IP67 protection  
 Support PoE power supply  
 3-Axis

i1166

180,00 150,00

BULLET IP KAMERE 4MPX

IPC2124LB-SF28-A

EASY



**4MP Fixed IR Mini Bullet Network Camera**

High quality image with 4MP, 1/3.0"CMOS sensor  
 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@25/20fps; 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 H.265, H.264  
 Smart IR, up to 30m (98ft) IR distance  
 Day/night functionality  
 2D/3D DNR (Digital Noise Reduction)  
 IP67 protection  
 DC12V or PoE(IEEE 802.3af) power supply  
 3-Axis

i1011

81,60 68,00

IPC2124LB-SF40-A



**4MP Fixed IR Mini Bullet Network Camera**

High quality image with 4MP, 1/3.0" CMOS sensor  
 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@25/20fps; 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 H.265, H.264  
 Smart IR, up to 30m (98ft) IR distance  
 Day/night functionality  
 2D/3D DNR (Digital Noise Reduction)  
 IP67 protection  
 DC12V or PoE(IEEE 802.3af) power supply  
 3-Axis

11081

84,00 70,00

IPC2124LB-AF28K-A2



**4MP Fixed IR Bullet Network Camera**

High quality image with 4 MP, 1/3.0" CMOS sensor  
 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps  
 Supports accurate human body detection 2.0  
 Ultra 265, H.265, H.264  
 Built-in mic  
 Smart IR, up to 30 m (98.4 ft) IR distance  
 Day/night functionality  
 2D/3D DNR (digital noise reduction)  
 MicroSD, up to 512 GB  
 DC 12 V, PoE (IEEE 802.3af) power supply  
 IP67 protection  
 3-axis

11155

86,40 72,00

IPC2124LB-ASF28K-A



**4MP Fixed IR Mini Bullet Network Camera**

High quality image with 4MP, 1/3.0" CMOS sensor  
 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps  
 Ultra H.265, H.265, H.264  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Day/night functionality  
 2D/3D DNR (Digital Noise Reduction)  
 Supports Micro SD card  
 IP67 protection  
 DC12V or PoE(IEEE 802.3af) power supply  
 3-Axis

11071

86,40 72,00

IPC2124LB-ADF28KM-H



**4MP Mini Fixed Bullet Network Camera**

High quality image with 4MP, 1/2.9" CMOS sensor  
 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps;  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 Support PoE power supply  
 120dB WDR  
 3-Axis

11068

114,00 95,00

IPC2124LB-ADF40KM-H



**4MP Mini Fixed Bullet Network Camera**

High quality image with 4MP, 1/2.9" CMOS sensor  
 4MP (2560\*1440)@25/20fps; 3MP (2304\*1296)@30/25fps;  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Built-in Mic  
 Ultra 265, H.265, H.264, MJPEG  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 Support PoE power supply  
 120dB WDR  
 3-Axis

11075

116,40 97,00

IPC2314LE-ADF28KM-WP



11085

**4MP ColorHunter with Wise-ISP Fixed Bullet Network Camera**

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Colorhunter with Wise-ISP technology ensures 24-hour full-color images  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 White Light, up to 30m warm light distance  
 Supports 512 GB Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

128,40 107,00

IPC2124LE-ADF28KMC-WL



11148

**4MP ColorHunter Fixed Dual-light Bullet Network Camera**

High quality image with 4 MP, 1/3.0" CMOS sensor  
 4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps;  
 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 120 dB true WDR technology enables clear image in strong light scene  
 Supports 9:16 corridor mode  
 Built-in mic and speaker  
 Smart IR, up to 30 m (98.4 ft) IR distance  
 White light, up to 30 m (98.4 ft) white light distance  
 MicroSD, up to 512 GB  
 IP67 protection  
 Supports PoE power supply  
 3-axis

132,00 110,00

IPC2124LE-ADF28KM-G



11027

**4MP HD Mini IR Fixed Bullet Network Camera**

High quality image with 4MP, 1/3" CMOS sensor  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Easystar technology ensures high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 50m (164ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

147,60 123,00

IPC2314LE-ADF28KM-WL



11029

**4MP HD ColorHunter Fixed Bullet Network Camera**

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Colorhunter technology ensures 24-hour full-color images  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 White Light, up to 30m white light distance  
 Supports 128 GB Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

159,60 133,00

IPC2124SB-ADF28KM-IO



11088

**4MP HD Intelligent LightHunter IR Fixed Bullet Network Camera**

High quality image with 4MP, 1/3" CMOS sensor  
 4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 40m (131ft) IR distance  
 Supports 512 G Micro SD card  
 IP67 protection  
 Support PoE power supply

162,00 135,00

IPC2324LB-ADZK-G

EASY

NOVO



**4MP HD IR VF (2.8 ~ 12mm) Bullet Network Camera**

High quality image with 4MP, 1/3"CMOS sensor  
 4MP (2688\*1520)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296)@ 30/25fps;2MP (1920\*1080)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 50m (164ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 IK10 vandal resistant  
 Support PoE power supply  
 3-Axis

9999

180,00 150,00

IPC2314SB-ADF60KM-10

PRIME



**4MP HD Intelligent 80m IR Fixed Bullet Network Camera**

High quality image with 4MP, 1/2.7"CMOS sensor  
 4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle  
 And non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in 2 Mic  
 Smart IR, up to 80m (262 ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection

11097

192,00 160,00

IPC2314SB-ADF40KM-10

PRIME



**4MP LightHunter Fixed IR Bullet Network Camera**

High quality image with 4MP, 1/2.7"CMOS sensor  
 4MP (2688\*1520)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in 2 Mic  
 Smart IR, up to 80m (262 ft) IR distance  
 Supports 512 G Micro SD card  
 IP67 protection

11167

192,00 160,00

IPC2124SB-ADF40KMC-10

PRIME

NOVO



**4MP Tri-Guard Fixed Dual-light Bullet Network Camera**

High quality image with 4 MP, 1/2.7" CMOS sensor  
 4 MP (2688 × 1520)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection  
 Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles  
 Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage  
 120 dB true WDR technology enables clear image in strong light scene  
 Supports 9:16 corridor mode  
 Built-in mic and speaker  
 Smart IR, up to 30 m (98.4 ft) IR distance  
 MicroSD, up to 512 GB  
 IP67 protection

11159

215,88 179,90

**4MP Recognition Of Vehicle License Plate Bullet IP Camera (2.8 ~ 12mm)**

**Features**  
**Optics**  
 Built-in lens supports motorized zoom to adapt to different scenes and allows for easy installation. Automatic gain control, white balance, and WDR for various light conditions.  
**Compression**  
 Supports triple streams.  
 Advanced H.265 encoding technology improves compression efficiency.  
 Custom OSD allows various vehicle information to be overlaid on the video image.  
**Functions**  
 Built-in vehicle and license plate recognition algorithm can recognize standard license plates of multiple countries.  
 Supports capturing vehicle head only.  
 Supports plate allowlist and blacklist configuration.  
 Supports vehicle access control when connected to a barrier.  
 Supports Micro SD cards of up to 256GB.  
 Automatic network replenishment (ANR) allows to automatically store video to SD card in case of network disconnection.  
 Supports audio collection and intercom.



<p><b>4MP</b></p> <p>Edge Storage</p> <p>IP 67</p> <p>50 IR distance</p> <p>H.265</p> <p>POE</p>	<p><b>I1120</b></p> <p><b>Network</b>                  Network auto-adaptability ensures smooth live video in relatively bad network conditions such as packet loss.                  Supports SNMP.                  Supports UNP for NAT traversal between public and private networks.                  Supports integration with the third party via SDK or HTTP.  <b>Network Security</b>                  Supports authorized user access by password. Weak password detection and account lock-up when failed login attempts reach the Upper limit enhance password security.                  Supports Web access via HTTPS.                  RTSP authentication prevents unauthorized video stream requests.                  IP address filtering prevents illegal access from untrusted IP addresses.                  Gateway ARP protection prevents MAC address spoofing.  <b>Structure</b>                  Supports DC 12V and PoE (802.3at) power supplies.                  Cast aluminum body offers excellent heat dissipation.                  3-axis mounting bracket for various installation scenarios.                  A junction box on the mounting bracket is convenient for storing tail cables.                  IP67 and IK10 protection.</p>	<p><b>840,00</b></p> <p><b>700,00</b></p>
--	---	---

**DOME IP KAMERE 5MPX**

**IPC3615LB-SF28-A**

**NOVO** **EASY**

**5MP**

IP 67

IR-C

H.265

Smart IR

IP 67

Smart Search

POE

<p><b>5MP Fixed IR Turret Network Camera</b>                  High quality image with 5 MP, 1/3.0" CMOS sensor                  5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;                  3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps                  Ultra 265, H.265, H.264, MJPEG                  Smart IR, up to 30 m (98.4 ft) IR distance                  Day/night functionality                  2D/3D DNR (digital noise reduction)                  IP67 protection                  DC 12 V, PoE (IEEE 802.3af) power supply                  3-axis</p>	<p><b>I1147</b></p>	<p><b>86,40</b></p> <p><b>72,00</b></p>
--	---------------------	---

**IPC3635LB-ADZK-G**

**NOVO** **EASY**

**5MP**

Built-in Mic

Edge Storage

WDR

Caridair Mode

cross line detection

Intrusion detection

IP 67

<p><b>5MP HD IR VF Eyeball Network Camera</b>                  High quality image with 5MP, 1/2.7" CMOS sensor                  5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;                  3MP (2304*1296)@ 30/25fps;2MP (1920*1080)@30/25fps                  Ultra 265, H.265, H.264, MJPEG                  120dB true WDR technology enables clear image in strong light scene                  Support 9:16 Corridor Mode                  Built-in Mic                  Smart IR, up to 40m (131ft) IR distance                  Supports 256 G Micro SD card                  IP67 protection                  Support PoE power supply                  3-Axis</p>	<p><b>I1139</b></p>	<p><b>192,00</b></p> <p><b>160,00</b></p>
--	---------------------	---

**IPC3615SS-ADF28K-I1**

**PRIME**



**5MP HD Intelligent LightHunter IR Fixed Turret Dome Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor  
 5MP (2880\*1620)@ 30/25(default)fps; 4MP (2560\*1440)@ 30/25fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 Auto Scene Match (ASM) (WDR only)  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 130dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 40m (131ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection

11105

192,00 160,00

**IPC3615SE-ADF28KM-WL-I0**

**PRIME**



**5MP HD Intelligent ColorHunter Fixed Eyeball Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor  
 5MP (2880\*1620)@30/25fps; 4MP (2560\*1440)@30/25fps;3MP (2304\*1296)@30/25fps; 2MP (1920\*1080)@30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce False alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 Colorhunter technology ensures 24-hour full-color images  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 corridor Mode  
 Support built-in Mic  
 Support 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply

11161

258,36 215,30

**BULLET IP KAMERE 5MPX**

**IPC2125LB-SF28-A**

**EASY**



**5MP Fixed IR Bullet Network Camera**

High quality image with 5 MP, 1/3.0" CMOS sensor  
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;  
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart IR, up to 30 m (98.4 ft) IR distance  
 Day/night functionality  
 2D/3D DNR (digital noise reduction)  
 IP67 protection  
 DC 12 V, PoE (IEEE 802.3af) power supply  
 3-axis

11145

86,40 72,00

**IPC2125LB-SF40-A**

**EASY**



**5MP Fixed IR Bullet Network Camera**

High quality image with 5 MP, 1/3.0" CMOS sensor  
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;  
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart IR, up to 30 m (98.4 ft) IR distance  
 Day/night functionality  
 2D/3D DNR (digital noise reduction)  
 IP67 protection  
 DC 12 V, PoE (IEEE 802.3af) power supply  
 3-axis

11146

86,40 72,00

IPC2125LE-ADF28KM-G



11041

**5MP HD Mini IR Fixed Bullet Network Camera**

High quality image with 5MP, 1/2.7"CMOS sensor  
 5MP (2880\*1620)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Ultra 265, H.265, H.264, MJPEG  
 IC domet: do 50m  
 Easystar technology ensures high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 50m (164ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

159,60 133,00

IPC2125SB-ADF40KMC-IO



11095

**5MP HD Intelligent Light and Audible Warning Fixed Bullet Network Camera**

High quality image with 5MP, 1/2.7"CMOS sensor  
 5MP (2880\*1620)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Supports sound and light alarm linkage.When Smart intrusion prevention is triggered, The camera links sound alarm and light linkage.  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic and Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KM-IO



11110

**5MP LightHunter Fixed IR Bullet Network Camera**

High quality image with 5MP, 1/2.7"CMOS sensor  
 5MP (2880\*1620)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 40m (131ft) IR distance  
 Supports 512 G Micro SD card  
 IP67 protection  
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KM-IO BLACK



11106

**5MP LightHunter Fixed IR Bullet Network Camera**

High quality image with 5MP, 1/2.7"CMOS sensor  
 5MP (2880\*1620)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps;  
 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 40m (131ft) IR distance  
 Supports 512 G Micro SD card  
 IP67 protection  
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KMC-IO

**NOVO**

**PRIME**











**5MP Tri-Guard Fixed Dual-light Bullet Network Camera**

High quality image with 5 MP, 1/2.7" CMOS sensor  
 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection  
 Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles  
 Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage  
 120 dB true WDR technology enables clear image in strong light scene  
 Supports 9:16 corridor mode  
 Built-in mic and speaker  
 Smart IR, up to 30 m (98.4 ft) IR distance  
 MicroSD, up to 512 GB  
 IP67 protection  
 Supports PoE power supply

11156 168,00 140,00

IPC2325LB-ADZK-H

**NOVO**

**EASY**











**5MP HD IR VF (2.8 – 12mm) Bullet Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor  
 5MP (2880\*1620)@ 25/20fps; 4MP (2560\*1440)@ 25/20fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps;  
 Built-in Mic  
 Ultra 265, H.265, H.264, MJPEG  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Smart IR, up to 50m (164ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

11069 192,00 160,00

IPC2315SB-ADF40KM-IO

**PRIME**











**5MP LightHunter Fixed IR Bullet Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor  
 5MP (2880\*1620)@ 30/25fps; 4MP (2560\*1440)@ 30/25fps; 3MP (2304\*1296) @30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor Vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in 2 Mic  
 Smart IR, up to 80m (262 ft) IR distance  
 Supports 512 G Micro SD card  
 IP67 protection

11096 198,00 165,00

IPC2225SE-DF40K-WL-IO











**5MP ColorHunter Fixed Warm Light Bullet Network Camera**

High quality image with 5 MP, 1/2.7" CMOS sensor  
 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps  
 Ultra 265, H.265, H.264, MJPEG  
 Intelligent perimeter protection, including cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduces false alarm caused by leaves, birds and lights, accurately focusing on human, motor vehicle and non-motor vehicle  
 Intelligent people flow counting and crowd density monitoring  
 ColorHunter technology ensures 24-hour full-color images  
 120 dB true WDR technology enables clear image in strong light scene  
 Supports 9:16 corridor mode  
 Alarm I/O: 1/1, audio I/O: 1/1  
 MicroSD, up to 512 GB  
 IK10 vandal resistant and IP67 protection  
 Supports PoE power supply

11158 261,60 218,00

**DOME IP KAMERE 8MPX**

**IPC328SB-ADF28K-IO**

**PRIME**



11043

**8MP HD Intelligent IR Fixed Dome Network Camera**

High quality image with 8MP, 1/2.7"CMOS sensor  
 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps;  
 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Intelligent perimeter protection, include cross line, intrusion,  
 enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly  
 reduce false alarm caused by leaves, birds and lights etc., accurately  
 focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Alarm:1 in/1 out, Audio: 1 in/1 out  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 256 G Micro SD card  
 IK10 vandal resistant and IP67 protection

229,20 191,00

**IPC3618LE-ADF28K-G**

**NOVO**

**EASYSSTAR**



11162

**4K HD IR Fixed Eyeball Network Camera**

High quality image with 8MP, 1/2.7"CMOS sensor  
 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080)  
 @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Easystar technology ensures high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

215,00 180,00

**BULLET IP KAMERE 8MPX**

**IPC2318LE-ADF28KM-WP**

**NOVO**

**EASYSSTAR**



11113

**8MP ColorHunter Wise-ISP Warm Light Bullet Network Camera**

High quality image with 8MP, 1/1.8"CMOS sensor and F1.0 large aperture lens  
 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080)  
 @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Colorhunter with Wise-ISP technology ensures 24-hour full-color images  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 White Light, up to 30m warm light distance  
 Supports 512 GB Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

210,00 175,00

**IPC2128LE-ADF28KM-G**

**EASYSSTAR**



11012

**4K 8MP Mini Fixed Bullet Network Camera**

High quality image with 8MP, 1/2.7"CMOS sensor  
 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080)  
 @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Easystar technology ensures high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Smart IR, up to 50m (164ft) IR distance  
 Supports 256 G Micro SD card  
 IP67 protection  
 Support PoE power supply  
 3-Axis

211,20 176,00

IPC2128SB-ADF28KMC-10



11090

**8MP Tri-Guard Fixed Dual-light Bullet Network Camera**

High quality image with 8MP, 1/2.7" CMOS sensor  
 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Built-in Mic  
 Built-in Speaker  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 512 G Micro SD card  
 IP67 protection

245,00 205,00

IPC2328SB-DZK-10



11138

**8MP HD Intelligent LighterHunter IR VF (2.8 ~ 12mm) Bullet Network Camera**

High quality image with 8MP, 1/2.8" CMOS sensor  
 8MP (3840\*2160)@20fps; 5MP (3072\*1728)@30/25fps; 4MP (2560\*1440)@30/25fps; 2MP (1920\*1080) @30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection  
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle  
 Intelligent People Flow Counting and Crowd Density Monitoring  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 120dB true WDR technology enables clear image in strong light scene  
 Support 9:16 Corridor Mode  
 Alarm: 1 in/1 out, Audio: 1 in/1 out  
 Smart IR, up to 50m (164ft) IR distance  
 Supports 256 G Micro SD card  
 IK10 vandal resistant  
 IP67 protection  
 Support PoE power supply

264,00 220,00

UNIARCH

Uho-S2



11091

High quality image with 2MP, 1/3" CMOS sensor  
 2MP (1920\*1080)@25/20fps; 720P (1280\*720) @25/20fps  
 Ultra 265, H.265, H.264  
 Built-in Mic & Speaker, support two-way audio, offer better interaction  
 IR night vision, up to 10m (33ft) IR distance  
 Support 256 G Micro SD card  
 Wi-Fi connection and easy installation

36,00 30,00

Uho-S3E-M3



11051

High quality image with 3MP, 1/3" CMOS sensor  
 3MP (2304\*1296)@25/20fps; 2MP (1920\*1080)@30/25fps; 720P (1280\*720) @30/25fps  
 Ultra 265, H.265, H.264  
 Built-in Mic & Speaker, support two-way audio, offer better interaction  
 IR night vision, up to 10m (33ft) IR distance  
 Support 256 G Micro SD card  
 Wi-Fi connection and easy installation

42,00 35,00

IPC-B122-APF28



I1140

High quality image with 1080P, 1/2.9" CMOS sensor  
 1080P (1920 × 1080)@25/20 fps; 720P (1280 × 720)@25/20 fps  
 Ultra 265, H.265, H.264  
 2D/3D DNR (digital noise reduction)  
 ROI (region of interest) ensures image quality in areas of interest  
 With low bandwidth  
 Smart IR, up to 30 m (98.4 ft.) IR distance  
 Built-in mic  
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)  
 DC 12 V, PoE (IEEE 802.3af) power supply

43,20 36,00



IPC-T122-APF28



I1141

High quality image with 1080P, 1/2.8" CMOS sensor  
 1080P (1920 × 1080)@25 fps; 720P (1280 × 720)@25 fps  
 Ultra 265, H.265, H.264  
 2D/3D DNR (digital noise reduction)  
 ROI (region of interest) ensures image quality in areas of interest  
 with low bandwidth  
 Smart IR, up to 30 m (98.4 ft.) IR distance  
 Built-in mic  
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)  
 DC 12 V, PoE (IEEE 802.3af) power supply

43,20 36,00



Uho-B1R-M2F3



I1127

High quality image with 2MP, 1/2.9" CMOS sensor  
 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps  
 Ultra 265, H.265, H.264, MJPEG  
 Built-in Mic  
 Smart IR, up to 30m (98ft) IR distance  
 Supports 128 G Micro SD card  
 IP67 protection  
 3-Axis

51,60 43,00



IPC-B125-APF28



I1142

High quality image with 5 MP, 1/3.0" CMOS sensor  
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps; 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30 fps; 720P (1280 × 720)@30 fps; D1 (720 × 576)@30 fps  
 Ultra 265, H.265, H.264  
 2D/3D DNR (digital noise reduction)  
 ROI (region of interest) ensures image quality in areas of interest with low bandwidth  
 Smart IR, up to 30 m (98.4 ft.) IR distance  
 Built-in mic  
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)  
 DC 12 V, PoE (IEEE 802.3af) power supply

60,00 50,00



**Uho-P1A-M3F4D**



High quality image with 3MP, 1/2.8"CMOS sensor  
 2304\*1296@20fps in the main stream  
 Ultra 265, H.265, H.264  
 Support digital WDR (Wide Dynamic Range)  
 Built-in Mic & Speaker, support two-way audio, offer better interaction  
 Support sound and light warning, makes warning and alarming more noticeable  
 Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes  
 Self-contained bracket, support two kinds of mounting  
 Supports 256 GB Micro SD card  
 Wi-Fi connection and easy installation  
 IP66 ingress protection  
 The front face is made of grapheme, which has better heat dissipation and more Environmental protection

**I1052** Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes

**NEMA NA STANJU**

**Uho-P2S-M33F34**



Fixed camera and PTZ camera integration, dual channels with one IP, Look at overall situation and consider details at the same time  
 Ultra 265, H.265, H.264  
 Support digital WDR (Wide Dynamic Range)  
 Built in Mic Speaker, support two way audio, offer better interaction  
 Support sound and light warning, makes warning and alarming more noticeable  
 Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes  
 IR warm light illumination to deal with different scenes and achieve full color illumination  
 Supports 512 GB Micro SD card  
 Wi Fi connection and easy installation  
 IP66 ingress protection

**I1128** Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes

**NEMA NA STANJU**

**118,80 99,00**

**PTZ IP KAMERE**

**IPC6312LR-AX4W-VG**



**2MP LightHunter WIFI IR Network PTZ Camera**  
 High quality image with 2MP, 1/2.7"CMOS sensor  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion,  
 Enter Area, Leave Area detection  
 People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 Up to 120 dB Optical WDR (Wide Dynamic Range)  
 Wi-Fi connection and easy installation  
 Built-in Mic & Speaker  
 Smart IR, Up to 50 m (164 ft) IR distance  
 Micro SD, up to 256GB  
 IP66 protection

**I1160** LightHunter technology ensures ultra-high image quality in low illumination environment

**NEMA NA STANJU**

**IPC6312LR-AX4-VG**



**2MP LightHunter IR Network PTZ Camera**  
 High quality image with 2MP, 1/2.7"CMOS sensor  
 Ultra 265, H.265, H.264, MJPEG  
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection  
 People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios  
 LightHunter technology ensures ultra-high image quality in Low illumination environment  
 Up to 120 dB Optical WDR (Wide Dynamic Range)  
 Built-in Mic & Speaker  
 Smart IR, Up to 50 m (164 ft) IR distance  
 Micro SD, up to 256GB  
 IP66 protection  
 DC12V or PoE (IEEE 802.3af) power supply

**I1073** LightHunter technology ensures ultra-high image quality in Low illumination environment

**255,00 212,50**

IPC675LFW-AX4DUPKC-VG



**5MP LightHunter Active Deterrence Mini PTZ Camera**  
 High quality image with 5MP, 1/2.7" CMOS sensor  
 Ultra 265, H.265, H.264, MJPEG  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 Up to 120 dB Optical WDR (Wide Dynamic Range)  
 Built-in Mic & Speaker  
 Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance  
 Micro SD, up to 256GB  
 IP66 protection  
 DC12V or PoE (IEEE 802.3af) power supply

1109 270,00 225,00

IPC6412LR-X5UPW-VG



**2MP 5X LightHunter Wi-Fi IR Network Mini PTZ Camera**  
 High quality image with 1080P, 1/2.7" CMOS sensor  
 1920 × 1080@30 fps in the main stream  
 Ultra 265, H.265, H.264, MJPEG  
 5X optical zoom allows for closer viewing of subjects  
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection  
 automatic selection of best snapshots  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 Up to 120 dB optical WDR (wide dynamic range)  
 Wi-Fi connection and easy installation  
 Built-in mic and speaker, supports two-way audio  
 Alarm I/O: 1/1  
 Smart IR, up to 30 m (98.4 ft) IR distance

1157 228,00 190,00

IPC6412LR-X16-VG



**2MP 16x LightHunter Network PTZ Dome Camera**  
 High quality image with 2MP, 1/2.8" CMOS sensor  
 1920\*1080@30fps in the main stream  
 Ultra 265, H.265, H.264, MJPEG  
 16X optical zoom allows for closer viewing of subjects  
 LightHunter technology ensures ultra-high image quality  
 In low illumination environment  
 Smart IR, up to 100m (328ft) IR distance  
 Micro SD, up to 256GB  
 DC 12V±25% or PoE+ (IEEE 802.3at)  
 IP66 ingress protection

11074 396,00 330,00

IPC6424SR-X25--B



**4MP 25x LightHunter IR Network PTZ Camera**  
 High quality image with 4 MP, 1/2.8" CMOS sensor  
 2688 × 1520@30 fps in the main stream  
 Ultra 265, H.265, H.264, MJPEG  
 25X optical zoom  
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection  
 automatic selection of best snapshots, supports face detection masked area  
 People counting, supports people flow counting and crowd density monitoring, suitable for different statistical scenarios  
 LightHunter technology ensures ultra-high image quality in low illumination environment  
 Smart IR, up to 100 m (328 ft) IR distance  
 DC 12 V±25%, PoE+ (IEEE 802.3at)  
 Alarm I/O: 2/1, audio I/O: 1/1  
 IP67 ingress protection  
 IK10 vandal resistant

11152 636,00 530,00

IPC6612SR-X33-VG



**2MP 33x Lighthunter Network PTZ Dome Camera**  
 High quality image with 2MP, 1/2.8" CMOS sensor  
 1920\*1080@30fps in the main stream  
 Ultra 265, H.265, H.264, MJPEG  
 33X optical zoom allows for closer viewing of subjects  
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection  
 LightHunter technology ensures ultra-high image quality in Low illumination environment  
 Up to 120 dB Optical WDR (Wide Dynamic Range)  
 DC12V or PoE+(IEEE 802.3at) power supply  
 Audio 1 in and 1 out, Alarm 2 in and 1 out  
 Micro SD, up to 256GB  
 Smart IR, up to 150m (492 ft) IR distance  
 IP66 ingress protection

11083

NEMA NA STANYU

NOVO

**4MP 33X LightHunter IR Network PTZ Camera**

High quality image with 4 MP, 1/2.8" CMOS sensor

2688 × 1520@30 fps in the main stream

Ultra 265, H.265, H.264, MJPEG

33X optical zoom

Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection

11153	automatic selection of best snapshots, supports face detection masked area People counting, supports people flow counting and crowd density monitoring, Suitable for different statistical scenarios LightHunter technology ensures ultra-high image quality in low illumination environment AC 24 V±25%, DC 24 V±25%, PoE+ (IEEE802.3 at) Alarm I/O: 7/2, audio I/O: 1/1 IP67 ingress protection IK10 vandal resistant	1320,00	1100,00
-------	---	---------	---------

**VIDEO INTERFONI**

## OEU-201B-HMK-W



UNV

11201	Outdoor Station Front panel: Plastic cement Supports batch configuration Supports intercom calls to associated indoor units or APPs Support monitoring function, security alarm, tamper alarm Support Wi-Fi Built-in IC card reader Card Capacity 2000 IP65(Apply silica gel to gaps between the device and the wall)	215,00	180,00
-------	---	--------	--------

## OEU-202S-HMK2



UNV

11202	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)	252,00	210,00
-------	---	--------	--------

## OEU-202S-HMK4



UNV

11204	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)	276,00	230,00
-------	---	--------	--------

## OEU-301S-HMKA




UNV

11301	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 Alarm Output: 2 IP65(Apply silica gel to gaps between the device and the wall)	420,00	350,00
-------	--	--------	--------



I1203	<p>Wall Mount Sunshield</p> <p>Compatible with OEU-201B-HMK-W, OEU-201B-HMK-W-NB, OEU-201S-HMK-W, And OEU-201S-HMK-W-NB villa door stations</p>	18,00	15,00
-------	---	-------	-------



I1372	<p>Indoor Station</p> <p>Rugged ABS casing and glass panel.</p> <p>1024*600 HD touch screen.</p> <p>Batch configuration transfer.</p> <p>Remote opening of linked door stations, one-key opening.</p> <p>Network camera monitoring, security alarm</p>	192,00	160,00
-------	--	--------	--------



I1205	<p>OEU-201S-HMK-W</p> <p>Metal casing.</p> <p>Supports call and intercom with the connected indoor station and app.</p> <p>Supports security protection alarm and tamper alarm triggered by door magnet, infrared, etc.</p> <p>Supports Wi-Fi.</p> <p>Built-in IC card reader.</p> <p>OEI-372S-H-W</p> <p>ABS casing and glass panel, solid and durable.</p> <p>Supports Wi-Fi.</p> <p>Supports touchscreen operation.</p> <p>1024 x 600 HD screen.</p> <p>Supports remote door opening by sending signal to the door station.</p> <p>Allows to view live video of connected door stations and network cameras.</p> <p>NSW2020-6T-POE-IN</p> <p>Allows to switch operating modes, including Default, VLAN, and Extend.</p> <p>Supports VLAN isolation. All PoE ports are isolated from each other and only able to communicate with uplink ports.</p> <p>Supports network extension. With a high-quality network cable and IPC, the network transmission distance can reach up to 250 meters by lowering the network port rate to 10Mbps.</p> <p>Supports port priority. Packets from high-priority ports will be forwarded first.</p> <p>Supports flow control. When there is data congestion in the uplink ports, the switch will actively send flow control frames to PoE ports.</p> <p>Plug-and-play, simple and convenient.</p> <p>All metal casing, secure and reliable.</p>	360,00	300,00
-------	--	--------	--------

## HARD DISKOVI

### WD GREEN 320 GB



Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB	KONTAKT
---	---------

### WD GREEN 500 GB



Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB	KONTAKT
---	---------

### WD GREEN 1 TB



Western Digital, 1 TB GREEN, 7200RPM, SATA III, 32MB	KONTAKT
--	---------

---

**HDD 1TB WD64PURZ-85BWUYO**

I1100 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB 104,40 87,00

---

**HDD 2TB WD64PURZ-85BWUYO**

I1200 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB 144,00 120,00

---

**HDD 4TB WD64PURZ-85BWUYO**

I1400 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB 217,20 181,00

---

**HDD 6TB WD64PURZ-85BWUYO**

I1600 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB 316,80 264,00

---

**HDD 8TB WD64PURZ-85BWUYO**

6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB 388,80 324,00

---

**TF-64G-T-L**

I1021 Uniview memorijska kartica  
Kapacitet: 64GB  
Maksimalna brzina čitanja: 90MB/s  
Maksimalna brzina pisanja: 65MB/s  
Dimenzije: 11mm x 15mm x 1mm  
Težina: 0,33g 14,40 12,00

---

**TF-128G-T-L**

I1022 Uniview memorijska kartica  
Kapacitet: 128GB  
Maksimalna brzina čitanja: 100MB/s  
Maksimalna brzina pisanja: 80MB/s  
Dimenzije: 11mm x 15mm x 1mm  
Težina: 0,33g 22,80 19,00

---

**TF-256G-T-L**

I1123 Uniview memorijska kartica  
Kapacitet: 256GB  
Maksimalna brzina čitanja: 90MB/s  
Maksimalna brzina pisanja: 65MB/s  
Dimenzije: 11mm x 15mm x 1mm  
Težina: 0,33g 43,20 36,00

---

**Uniview SVIČEVI****NSW1010-5T-IN**

I1130 5-Port 100 Megabit Plastic Shell Switch  
Supports IEEE802.3 and IEEE802.3u standards.  
Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.  
Supports auto MDI/MDIX.  
Supports IEEE802.3 flow control for full-duplex mode and backpressure  
For half-duplex mode. 8,40 7,00

**NSW1010-8T-IN****NOVO**

I1131	<p>8-Port 100 Megabit Plastic Shell Switch          Supports IEEE802.3 and IEEE802.3u standards.          Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.          Supports auto MDI/MDIX.          Supports IEEE802.3 flow control for full-duplex mode and backpressure          For half-duplex mode.</p>	12,00	10,00
-------	--	-------	-------

**NSW1010-5GT-IN****NOVO**

I1132	<p>5-Port Gigabit Plastic Shell Switch          Supports IEEE802.3 and IEEE802.3u standards.          Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.          Supports auto MDI/MDIX.          Supports IEEE802.3 flow control for full-duplex mode and backpressure          For half-duplex mode</p>	14,40	12,00
-------	---	-------	-------

**NSW1010-8GT-IN****NOVO**

I1133	<p>8-Port Gigabit Plastic Shell Switch          Supports IEEE802.3 and IEEE802.3u standards.          Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.          Supports auto MDI/MDIX.          Supports IEEE802.3 flow control for full-duplex mode and backpressure          For half-duplex mode.</p>	24,00	20,00
-------	--	-------	-------

**Uniview POE SVIČEVI****NSW2020-6T-POE-IN**

I1023	<p>6x100Mbps network parts (RJ45), od toga 4 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm</p>	54,00	45,00
-------	---	-------	-------

**NSW2010-5GT-POE-IN**

I1059	<p>4 Port GigabitPoE Switch          1 Port Gigabit Uplink          PoE Power up to 30W Each Port          Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD)          Auto Detect Power Device          Power Port Supply prioritization, guarantees the continuous power supply of key nodes          IEEE802.3 X full duplex flow control and Backpressure half duplex flow control          Line Speed Forwarding, intelligent identification          Up to 250m transmission distance on surveillance mode</p>	78,00	65,00
-------	--	-------	-------

**NSW2020-10T-POE-IN**

I1024	<p>10x100Mbps network parts (RJ45), od toga 8 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode); 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm</p>	90,00	75,00
-------	--	-------	-------

**NSW2010-10GT-POE-IN**

I1060	<p>8 Port Gigabit PoE Switch          2 Port Gigabit Uplink          PoE Power up to 30W Each Port          Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD)          Auto Detect Power Device          Power Port Supply prioritization, guarantees the continuous power supply of key nodes          IEEE802.3 X full duplex flow control and Backpressure half duplex flow control          Line Speed Forwarding, intelligent identification          Up to 250m transmission distance on surveillance mode</p>		
-------	---	--	--

**NEMA NA STANJU**

**NSW3000-8T2GT-POE-IN**



I1134

**Cloud Managed** Ethernet Switch(PoE)  
 8 x 10/100Mbps PoE port (RJ45) ,2 x Gigabit port (RJ45)  
 Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software.  
 Supports Web login, and device configuration and management on the Web interface; supports visiting the cloud by scanning the QR code.  
 Allows to view the device status and network topology in real time on the app, and remotely restart the PoE power supply.  
 Allows up to 250m power supply using a standard network cable.  
 Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.  
 Allows to report port abnormal alarms to the software for realtime monitoring.  
 Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full.  
 All metal casing, secure and reliable.  
 Maximum total power: 120W  
 Maximum PoE power for single port: 30W

96,00 80,00

**NSW2020-16T2GC-POE-IN**



I1067

16x100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta  
 Podržava: IEEE802.3,IEEE802.3u,IEEE802.3az, IEEE802.3x,IEEE802.3af,IEEE802.3at  
 Modovi rada: Default(Normal mode):  
 Svi portovi komuniciraju normalno međusobno  
 EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s.  
 VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima.  
 6kV zaštita od prenapona PoE Budžet: 370W  
 Maksimalna snaga: 250W  
 Maksimalna PoE snaga porta: 30W  
 Dimenzije: 440mm x 207mm x 45mm  
 Moguća rek montaža 19" , dolazi uz switch

216,00 180,00

**NSW3000-16T16T16C-LPOE-IN**



I1135

**Cloud Management Switch**  
 16 x 10/100Mbps PoE port (RJ45) + 1 x Gigabit port (RJ45)+ 1 x Gigabit Combo  
 Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software.  
 Supports Web login, and device configuration and management on the Web interface  
 in real time on the app, and remotely restart the PoE power supply.  
 Supports PoE power supply and allows to view the power; allows to enable or disable PoE power supply for the powered device;  
 Allows up to 250m power supply using a standard network cable.  
 Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.  
 Allows to report port abnormal alarms to the software for realtime monitoring.  
 Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full.  
 All metal casing, secure and reliable.  
 Maximum total power: 150W  
 Maximum PoE power for single port: 30W

150,00 125,00

**NSW2020-24T16T16C-POE-IN**



I1163

Unmanaged Ethernet Switch(PoE)  
 24x100Mbps PoE ports (RJ45) + 1x1000Mbps Gigaethernet ports +1x1000Mbps Combo ports  
 Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)  
 Support port traffic control  
 Support for secure mode, all downlink ports can communicate only with uplink ports  
 Up to 250m transmission distance on surveillance mode  
 Support buffer optimization  
 All metal housing, safe and reliable  
 Max capacity:370W  
 Max capacity for single port: 30W

232,20 193,50

NSW2010-24T2GC-PoE-IN



I1136	<p>Ethernet Switch(PoE)                  24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports                  Multiple working modes to address your business needs:                  Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)                  Support port traffic control                  Support for secure mode, all downlink ports can communicate                  Only with uplink ports                  Up to 250m transmission distance on surveillance mode                  Support buffer optimization                  All metal housing, safe and reliable                  Max power: 390W</p>	288,00	240,00
-------	---	--------	--------

MONITORI

MW3224-V



I1164	<p>UNV 24" LED Monitor                  Resolution 1920 × 1080                  Color Support: 16.7 M                  Refresh Rate: 60 Hz                  Operation Hour: 24/7</p>	120,00	100,00
-------	--	--------	--------

DODATNA OPREMA

GCB01-B7



I1101	<p>UNV-Link Pro Connect Box                  Network: 4 x RJ45 10M/100M Base-TX EthernetNetwork                  Port 1 Support POE (IEEE802.3af) OutputNetwork Port 4                  Support PSE Voltage Test                  Wi-Fi 2.4G Wi-Fi                  Battery: 7500mAH                  Power Input: 1 x DC 5V/2A max, type-c                  Power Output: 1 x DC 12V/1A output; 1 x DC 5V/1A output, type-A</p>	78,00	65,00
-------	--	-------	-------

PoE Extender



9995	<p>Model: LN-POEPL03S                  PoE In: 44-57V/30W                  PoE Out (1-3) : 44-57V/25W                  Support: 10/100 Mbps IEEE802.3af/at</p>	NEMA NA STANJU
------	--	----------------


3 Ports POE Injector



2255	<p>PoE extender, repeater, switch 1 na 2                  Usklađenost sa IEEE 802. af/at                  Power over Ethernet(10/100M podržano)                  Proširite domet Porta za dodatnih 100 metara</p>	25,00	20,83
------	---	-------	-------


KABLOVI

UNV Cat6 (UTP), CCA




i1044	<p>CAB-LC3100B-CCA-IN                  Conductor material: CCA(Copper content: 27%)                  Insulation material: HDPE                  Packing length: 305±1 m                  Sheath material: PVC</p>	NEMA NA STANJU
-------	---	----------------

UNV Cat5e (UTP), BC



11045	CAB-LC2100A-E2-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,54	0,450
-------	---	------	-------

UNV Cat6 (UTP), BC



11046	CAB-LC3100A-EC-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,78	0,650
-------	---	------	-------

KUĆIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633	Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00
------	--	------	------

DOZNA ZA KAMERE G153



8644	Razvodna kutija za spoljašnu montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,20	2,67
------	--	------	------

DOZNA ZA KAMERE BA-02



8645	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,00	2,50
------	--	------	------

TR-JB05-B-IN



11062	Nosač za Dome kamere serije IPC21XX Dimenzije: $\Phi 104,4\text{mm} \times 54,5\text{mm}$ Težina: 0.36kg Materijal: Aluminijum	19,20	16,00
-------	---	-------	-------

TR-JB05-A-IN



11061	Nosač za kamere Dimenzije: $\Phi 93 \times 93 \times 39\text{mm}$ Težina: 0.2kg Materijal: Aluminijum	15,60	13,00
-------	--	-------	-------

TR-JB03-G-IN



11064	Nosač za Dome kamere serije IPC32x i IPC31x Dimenzije: $\phi 106,6\text{mm} \times 36\text{mm}$ Težina: 0.2kg Materijal: Aluminijum	13,20	11,00
-------	--	-------	-------

## TR-JB03-I-IN



Nosač za Dome kamere serije IPC36XXL i IPCT1XX  
Dimenzije: Ø117.8 × 36mm  
Težina: 0.2kg  
Materijal: Aluminijum

15,60 13,00

## TR-JB03-H-IN



Nosač za Dome kamere serije IPC363X, IPC36XXS/E i 4MP fisheye  
Dimenzije: Ø126mm\*36mm (4.96" x1.42")  
Težina: 0.24kg  
Materijal: Aluminijum legura

14,40 12,00

## TR-JB04-C-IN



Nosač za Dome kamere serije 323  
Dimenzije: Ø144.8 mm × 42.5 mm (5.7" × 1.7")  
Težina: 0.3kg  
Materijal: Aluminijum legura

15,60 13,00

## TR-JB07-D-IN



11170 Bullet Junction Box(Support wiring from behind)

30,00 25,00

## TR-JB07/WM03-G-IN



11165 Wall Mounting Assembling Bracket For 32 Fix-dome  
&Mini Fix-dome&Plastic Turret Camera

36,00 30,00

## UNV TR-UP06-C-IN



11169 Pole Mounting Bracket for Bullet Junction Box Only  
Application: Outdoor, pole or rail installation for bullet camera of IPC23XX OEM IPC23XX/22X、IPC74X  
and IPC252/25X series  
Bracket Dimensions: 136.0 mm × 127.0 mm × 63.6 mm (5.4" × 5.0" × 2.5")  
Bracket Weight: 0.34kg  
Bracket Material: Aluminum alloy

NEMA NA STANJU

## KONEKTORI

BNC NA LEMLJENJE  
SA ŠRAFOM

3299 BNC konektor muški sa šrafom.  
Pakovanje 100 kom.

0,54 0,45

## BNC NA LEMLJENJE



2560 BNC konektor muški na lemljenje.  
Pakovanje 100 kom.

0,54 0,45

## BNC KONEKTOR



30020 BNC konektor muški na šraf.

0,50 0,42

---

**BNC NA KRIMP RG59**

2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,60	0,50
------	---	------	------

---

**BNC MUŠKI- F ŽENSKI**

1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,70	0,58
------	--	------	------

---

**BNC NASTAVAK**

4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

---

**F KONEKTOR na krimp  
RG6**

2559	F konektor za RG6 kabl. Pakovanje 100 kom.	0,14	0,12
------	---	------	------

---

**F KONEKTOR na krimp RG59**

1796	F konektor za RG59 kabl. Pakovanje 100 kom.	0,14	0,12
------	--	------	------

---

**RF METALNI G MUŠKI**

4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,35	0,29
------	--	------	------

---

**RCA MUŠKI-F ŽENSKI**

4446	RCA muški - F ženski konektor Pakovanje 100 kom.	0,53	0,44
------	---	------	------

---

**F NASTAVAK**

3300	F nastavak ženski - ženski Pakovanje 100 kom	0,22	0,18
------	---	------	------

---

**F KONEKTOR  
KOMPRESIONI RG6 XL**

1625	Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.	0,44	0,37
------	--	------	------

---

**F KONEKTOR  
KOMPRESIONI RG11 XL**

1627	Profesionalni PPC F konektor za RG11 kabl.	2,96	2,47
------	--	------	------

---

**F KONEKTOR  
KOMPRESIONI RG59 XL**

1624	Profesionalni PPC F konektor za RG59 kabl. Pakovanje 50 kom.	0,47	0,39
------	---	------	------

---

**DC KABL-MUŠKI**

1387	DC utikač-muški	0,47	0,39
------	-----------------	------	------

---

**DC KABL-ŽENSKI**

1391	DC utikač-ženski	0,47	0,39
------	------------------	------	------

---

---

**DC KONEKTOR MUŠKI**

3425 DC konektor Muški

0,37 0,31

---

**DC KONEKTOR ŽENSKI**

4197 DC konektor ženski.

0,38 0,32

---

**DC RAZDELNIK 1-4**

1388 1 DC utičnica - 4 DC utikača

1,99 1,66

---

**DC RAZDELNIK 1-8**

1389 1 DC utičnica - 8 DC utikača

3,97 3,31

---

**CAT7 RJ45**

Mrežni konektor RJ45 kategorija 7

0,50 0,42

---

**CAT5 RJ45**

0067 Mrežni konektor RJ45

0,05 0,04

---

**Telefonski konektor RJ11**

0066 Telefonski konektor RJ11

0,02 0,02

---

**DODATNA OPREMA****ŠTAMPAČ P-TOUCH E100**

Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija \*dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu

4663 106,56 88,80

---

**MIKROFON LY-501C**2584 Audio modul sa izvedenim konektorima.  
Napajanje 12 V DC

3,97 3,31

---

**MIKROFON LY-502B**2583 Audio modul plastični sa trimerom.  
Napajanje 12 V DC

6,00 5,00

---

**MIKROFON LY-506**1937 Audio modul metalni sa trimerom.  
Napajanje 12 V DC

10,00 8,33

DS-2FP2020		5222	Viisoko osetljivi omnidirekcionni mikrofon. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).	36,00	30,00
DH-PFM800-4K (par)		3632	One (1) Channel Balun Real-time Transmission over UTP CAT5E/6 Cable Compatible with HDCVI, TVI, AHD, and CVBS Video Formats Transmission Distance at 4K: 200 m (656 ft) External Power Supply not Required	6,90	5,75
OG razvodna kutija 100x100		00091	Razvodna kutija 100x100	1,80	1,50
OG razvodna kutija 80x80		00092	Razvodna kutija 80x80	1,10	0,92
OG razvodna kutija 160x100x74		00093	Razvodna kutija 160x100x74	3,00	2,50
OG razvodna kutija 160x100x48		00094	Razvodna kutija 160x100x48	2,64	2,20
ALAT ZA KRIMP RG6, RG11,RG59		3302	Alat za krimpovanje RG6, RG11,RG59 konektora	48,00	40,00
STRIPER ZA KABLOVE RG59,RG6		3301	Alat za stripovanje RG59,RG6 kablova	20,40	17,00
ALAT KOMPRESIONI ZA RG59, RG6		1629	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake.	37,92	31,60
ALAT KOMPRESIONI, ZA RG6,RG11,RG59		3796	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6,RG11,RG59 XL oznake.	54,34	45,28
KLEŠTA ZA KRIMPOVANJE KOMPLET		5790	Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sećicom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)	28,68	23,90

**NAPAJANJA**

XED-1212S		1633	Ulaz: 90V-264V Izlaz: 12V , 1A Snaga: 12W Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	6,00	5,00
XED-2012S		1382	Ulaz: 90V-264V Izlaz: 12V , 2A Snaga: 24W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	8,04	6,70
XED-3013S		1383	Ulaz: 90V-264V Izlaz: 12V , 3A Snaga: 36W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	12,60	10,50
XED-5013S		1384	Ulaz: 100V-240V Izlaz: 12V , 5A Snaga: 60W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	16,20	13,50
XED-6013B		3509	Ulaz: 100V-240V Izlaz: 12V , 6A Snaga: 72W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	20,40	17,00
9-KANALNO NAPAJANJE XED-10A12VX-9L		5435	Snaga: 120W Ulaz: 100-240V 50-60Hz Izlaz: 12V 10A 9 kanala Dimenzije: 237*213*70mm Neto težina: 1800g Napomena: Sadrži AC kabl	82,80	69,00
18-KANALNO NAPAJANJE XED-15A12VX-18L		5114	Snaga: 180W Ulaz: 100-240V 50-60Hz Izlaz: 12V 15A 18 kanala Dimenzije: 240*218*70mm Neto težina: 2300g Napomena: Sadrži AC kabl	94,80	79,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite [www.isec.rs](http://www.isec.rs)