

CENOVNIK UNIVIEW VIDEO NADZORA – 24.11.2025.



NAZIV	ŠIFRA	OPIS	CENA	
-------	-------	------	------	--

DVR UREDJAJI			sa PDV	bez PDV
--------------	--	--	--------	---------

4 KANALNI

XVR301-04G3



4-CH Hybrid DVR

Podrzan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal)

4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podrzan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6)

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulazno/Izlazni saobraćaj: 16/48 Mbps

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 226mm × 47mm (10.2" × 8.9" × 1.8"), 1.1kg

11031

69,60

58,00



XVR301-04Q3

4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6)

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

Ulazno/Izlazni saobraćaj: 48/60 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 226mm × 47mm

11032

96,00

80,00

XVR301-04U3



4-ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
Support 1-ch CVBS output, 1-ch VGA output,
1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols
1HDD Up to 16 TB

I1129

144,00 120,00

8 KANALNI

XVR301-08G3



8-CH Hybrid DVR

Podrška: TVI,AHD, CVI, CVBS
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF
Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)
Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)
Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio
Ulazno/Izlazni saobraćaj: 32/64 Mbps
Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 sata HDD do 8TB
Napajanje 12V DC, Potrošnja 8W bez HDD
Radna temperatura: -10 °C ~ +55 °C
Dimenzije: 260mm × 226mm × 47mm

I1025

91,20 76,00

XVR301-08Q3



8-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
Podrška: TVI,AHD, CVI,CVBS
Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)
Video kompresija: H.265, H.264
Video/audio ulazi: 8ch BNC, 1ch audio
Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio
Ulazno/Izlazni saobraćaj: 40/64 Mbps
Smart funkcije: Motion detection, video loss detection, audio detection,
Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 sata HDD do 8TB kapaciteta
Napajanje 12V DC,
Potrošnja 10W bez HDD,
Radna temperatura: -10 °C ~ +55 °C,
Dimenzije: 260mm × 226mm × 47mm

I1033

138,00 115,00

XVR301-08U3



8-Ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
8-channel BNC input
Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols

I1080

222,00 185,00

16 KANALNI

XVR301-16G3



16-CH Hybrid DVR

Podrška: TVI, AHD, CVI, CVBS, IP cameras
 Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF
 IP kamere: do 8 IP kamere ili svih 16
 Video/audio ulazi: 16-ch BNC / 1-ch RCA
 Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio
 Ulazno/Izlazni saobraćaj: 40/64 Mbps
 Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485
 Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
 Hard disk: 1 SATA HDD do 8TB
 Napajanje 12V DC, Potrošnja 10W bez HDD
 Radna temperatura: -10 °C ~ +55 °C
 Dimenzije: 260mm × 226mm × 47mm

I1026

148,80 124,00

XVR302-16Q3



16-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
 Podrška 8MP@15fps na prva 4 kanala
 Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.
 Ulazno/Izlazni saobraćaj: 72/80 Mbps
 Video kompresija: H.265/H.264 video kompresija,
 Video/audio ulazi: 16ch BNC, 1ch RCA
 Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA
 Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection
 Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
 Hard disk prostor: 2 sata HDD do 6TB kapaciteta
 Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 380mm × 315mm × 53mm, Težina 1.9Kg

I1034

288,00 240,00

KIT/XVR 301-04G3/4*UAC-T112-F28



UNV KIT/XVR 301-04G3/4*UAC-T112-F28

Kompet sadrži:
 1x XVR 04G3
 4x UAC-T112-F28
 1x Napajanje 2A
 4x 20m Koaksijalni kabl + napajanje (sa konektorima)
 1x Razdelnik 1 /4

I1065

180,00 150,00

ANALOGNE DOME KAMERE 2MP

UAC-T112-AF28



2MP HD Fixed IR Turret Analog Camera

2MP high quality image
 TVI/AHD/CVI/CVBS
 IR-cut filter with auto switch (ICR)
 Built-in microphone
 Supports 180° horizontal flip, 180° vertical flip
 OSD configuration menu, easy to operate
 IP67 waterproof and dustproof design, high reliability
 OSD configuration menu in 11 languages

I1066

24,00 20,00

UAC-T112-F28-W



2MP ColourHunter HD Fixed Turret Analog Camera

2MP high quality image
 TVI/AHD/CVI/CVBS
 Supports white light illumination, 24/7 full-color imaging
 Supports 180° horizontal flip, 180° vertical flip
 OSD configuration menu, easy to operate
 IP67 waterproof and dustproof design, high reliability
 OSD configuration menu in 11 languages

I1006

28,80 24,00

UAC-T122-AF28LM 		2MP LightHunter HD IR Fixed Turret Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	11054	36,00	30,00
UAC-T122-AF40LM 		2MP LightHunter HD IR Fixed Turret Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	11099	36,00	30,00
UAC-T122-AF28M-W 		2MP ColorHunter HD Fixed Turret Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing 3-Axis	11016	36,00	30,00
UAC-T142-AF28LM-DL 		2MP ColorHunter Fixed Dual-light Turret Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	11077	43,20	36,00
ANALOGNE BULLET KAMERE 2MP					
UAC-B112-F28 		2MP HD Fixed IR Mini Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	11000	25,20	21,00
UAC-B112-AF28 		2MP Fixed IR Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	11121	26,40	22,00

UAC-B112-F28-W



	2MP ColourHunter HD Fixed Mini Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 full-color imaging Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages		
11001		27,60	23,00

UAC-B122-AF28LM



	2MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog		
11053		36,00	30,00

UAC-B122-AF40LM



	2MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog		
11098		36,00	30,00

UAC-B122-AF28M-W



	2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability SD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing		
11014		36,00	30,00

UAC-B122-AF28M-W-Black



	2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability SD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing		
11214		36,00	30,00

UAC-B122-AF40M-W



	2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing		
11015		37,20	31,00

UAC-B142-AF28LM-DL



	2MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables		
I1076		46,80	39,00

UAC-B142-AF40LM-DL



	2MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables		
I1122		46,80	39,00

ANALOGNE DOME KAMERE 5MP

UAC-T115-AF28



	5MP Fixed IR Turret Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables		
I1126		30,00	25,00

UAC-T125-AF28LM



	5MP LightHunter HD IR Fixed Turret Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables 3-Axis		
I1056		46,80	39,00

UAC-T125-AF28M-W



	5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis		
I1020			

NEMA NA STANJU

UAC-T125-AF28M-W-Black



	5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis		
I1057		48,00	40,00

UAC-T145-AF28LM-DL



5MP ColorHunter Fixed Dual-light Turret Analog Camera
High quality imaging with 5MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
Smart Dual Light (only TVI)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

I1079

NEMA NA STANJU

ANALOGNE BULLET KAMERE 5MP

UAC-B115-F28



5MP HD Fixed IR Mini Bullet Analog Camera
5MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

I1002

30,00 25,00

UAC-B115-AF28



5MP Fixed IR Bullet Analog Camera
5MP high quality image
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

I1125

30,00 25,00

UAC-B125-AF28LM



5MP LightHunter HD IR Fixed Mini Bullet Analog Camera
High quality imaging with 5MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

I1055

44,40 37,00

UAC-B125-AF40LM



5MP LightHunter HD IR Fixed Mini Bullet Analog Camera
High quality imaging with 5MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

I1124

44,40 37,00

UAC-B125-AF28M-W



5MP ColorHunter HD Fixed Mini Bullet Analog Camera
5MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing

I1018

48,00 40,00

UAC-B125-AF40M-W
5MP ColorHunter HD Fixed Mini Bullet Analog Camera

I1019	5MP high quality imaging		
	TVI/AHD/CVI/CVBS		
	Supports white light illumination, 24/7 color images		
	Supports 180° horizontal flip, 180° vertical flip	49,20	41,00
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Metal front face and housing		

UAC-B145-AF28LM-DL
5MP ColorHunter Fixed Dual-light Bullet Analog Camera

I1078	High quality imaging with 5MP resolution		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	Smart Dual Light (only TVI)	54,00	45,00
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		

NVR UREDJAJI**NVR301-04S3**


I1049	4-ch NVR		
	Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p		
	Ulazno/Izlazni saobraćaj: 64/48Mbps		
	Video kompresija: Ultra 265, H.265, H.264 video kompresija,		
	Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),		
	Smart Funkcije:Face detection, Intrusion detection, Cross line detection, Audio detection		
	ONVIF conformance: Profile S, Profile G, Profile T		
	Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search	108,00	90,00
	Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm		
	Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE		
	Hard disk prostor: 1 sata HDD do 6TB kapaciteta		
	Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,		
	Radna temperatura: -10 °C ~ +55 °C,		
	Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg		

NVR301-04B-IQ


I1115	4-ch NVR		
	Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30		
	Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30		
	Support Ultra 265/H.265/H.264 video formats		
	Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols		
	Support HDMI and VGA simultaneous output		
	Up to 12 Megapixels resolution recording		
	ANR technology to enhance the storage reliability when the network is disconnected		
	Support cloud upgrade	132,00	110,00
	1x HDD, up to 10TB		

NVR501-04B-IQ


I1150	4-ch NVR		
	Decoding Capability:		
	Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30		
	Smart On: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30		
	Support Ultra H.265/H.265/H.264 video formats		
	Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution		
	Support HDMI and VGA simultaneous output		
	Up to 16 Megapixels resolution recording		
	ANR technology to enhance the storage reliability when the network is disconnected		
	Support cloud upgrade	150,00	125,00
	1 SATA Interface, up to 16 TB		

NVR301-04LS2-P4	  	4-ch PoE NVR Support Ultra 265/H.265/H.264 video formats 4-channel input Recording Resolution: 6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Capability: 1 x 6MP@20, 1 x 5MP@30, 2 x 4MP@25, 2 x 3MP @30, 4 x 1080p@25, 8 x 960p@25, 8 x 720p@30 Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T Support 1-ch HDMI, 1-ch VGA HDMI and VGA simultaneous output Up to 6MP resolution recording 1 SATA HDD up to 6 TB Support cloud upgrade Power Supply: 48V DC	I1149	120,00	100,00
NVR301-08S3	  	8-ch NVR Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF Ulazno/Izlazni saobraćaj: 64/48 Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search ONVIF conformance: Profile S, Profile G, Profile T Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0., Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg	I1048	120,00	100,00
NVR301-08B-IQ	  	8-ch NVR Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30 Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30 Support Ultra 265/H.265/H.264 video formats 4/8/16 channel input Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols Support HDMI and VGA simultaneous output Up to 12 Megapixels resolution recording ANR technology to enhance the storage reliability when the network is disconnected Support cloud upgrade 1x HDD, up to 10TB	I1117	150,00	125,00
NVR501-08B-IQ	  	8-ch NVR Decoding Capability: Smart Off: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30 Support Ultra H.265/H.265/H.264 video formats Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution Support HDMI and VGA simultaneous output Up to 16 Megapixels resolution recording ANR technology to enhance the storage reliability When the network is disconnected Support cloud upgrade 1 SATA Interface, up to 16 TB	I1118	168,00	140,00
NVR301-16S3	  	16-ch NVR Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p Ulazno/Izlazni saobraćaj: 64/48Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD), Smart Funkcije:Face detection, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg	I1116	138,00	115,00

NVR301-16B-IQ**EASY****I1151****16-ch NVR**

Decoding Capability – Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 10 x 1080P@30, 16 x 720P@30
 Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30, 16 x 720P@30
 Support Ultra 265/H.265/H.264 video formats
 Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support HDMI and VGA simultaneous output
 Up to 12 Megapixels resolution recording
 ANR technology to enhance the storage reliability when the network is disconnected
 Support cloud upgrade

210,00 175,00**NVR501-16B****PRIME****I1047****16-ch NVR**

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Ulazno/Izlazni saobraćaj: 80/64 Mbps
 Video kompresija: Ultra 265/H.265/H.264
 Video/audio izlazi: HDMI (4K) / HD, VGA
 Smart Funkcije: Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, UMD(Ultra Motion Detection)
 Statisticke analize: People counting
 Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP
 Hard disk prostor: 1 sata HDD do 8TB kapaciteta
 Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 260mm × 222mm × 47mm, Težina 0,98Kg

216,00 180,00**NVR501-16B-IQ****PRIME****I1119****16-ch NVR**

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30
 Support Ultra H.265/H.265/H.264 video formats
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
 Support HDMI and VGA simultaneous output
 Up to 16 Megapixels resolution recording
 ANR technology to enhance the storage reliability
 When the network is disconnected
 Support cloud upgrade
 1 SATA Interface, up to 16 TB

228,00 190,00**NVR304-32X****PRIME****I1154****32-ch NVR**

32-KANALNI MREŽNI SNIMAČ
 Rezolucija snimanja: 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Ulazno/Izlazni saobraćaj: 384/384 Mbps
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,
 Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA
 Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed, Face search, Behavior search
 Statisticke analize: People counting
 ONVIF conformance: Profile S, Profile G, Profile T
 Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1 x RS485, 1 x RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza
 Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE
 Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5
 Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 442mm × 426mm × 89mm, Težina 5,7Kg

600,00 500,00

DOME IP KAMERE 2MPX

IPC3612LB-SF28-A

NOVO



2MP

Ultra H.265

Smart Search

11144	2MP Fixed IR Turret Network Camera		
	High quality image with 1080P, 1/2.8" CMOS sensor		
	1080P (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps		
	Ultra 265, H.265, H.264		
	Smart IR, up to 30 m (98.4 ft) IR distance	66,00	55,00
	Day/night functionality		
	2D/3D DNR (digital noise reduction)		
	IP67 protection		
	Supports PoE power supply		
	3-axis		

IPC322LB-SF28-A

EASY



2MP

Ultra H.265

7059	2MP Vandal-resistant Network IR Fixed Dome Camera		
	High quality image with 2MP, 1/2.8"CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264		
	Smart IR, up to 30m (98ft) IR distance	68,40	57,00
	Day/night functionality		
	2D/3D DNR (Digital Noise Reduction)		
	IP67 protection		
	IK10 vandal resistant		
	Support PoE power supply		
	2-Axis		

IPC322LB-AF28WK-G

EASY



2MP

WIFI Connection

Ultra H.265

11008	2MP WIFI Fixed Dome Network Camera		
	High quality image with 2MP, 1/2.9"CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264, MJPEG		
	Built-in Mic	86,40	72,00
	Smart IR, up to 30m (98ft) IR distance		
	Supports 128 G Micro SD card		
	IK10 vandal resistant		
	IP67 protection		
	3-Axis		

IPC322LB-DSF28K-G

EASY



2MP

Corridor Mode

Ultra H.265

7581	High quality image with 2MP, 1/2.7"CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264, MJPEG		
	120dB true WDR technology enables clear image in strong light scene		
	Support 9:16 Corridor Mode	72,00	60,00
	Smart IR, up to 30m (98ft) IR distance		
	Supports 128 G Micro SD card		
	IK10 vandal resistant		
	IP67 protection		
	Support PoE power supply		

IPC3622LE-ADF28K-WP

NOVO



EASYSSTAR

2MP

Built-in Mic

Edge Storage

WDR

Wide-ISP

F1.8 Large Aperture

Ultra Motion Detection

IP 67

I1112

2MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera
High quality image with 2MP, 1/2.7" CMOS sensor and F1.0 large aperture lens
2MP (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
Support ColorHunter with Wise-ISP technology, deeply optimizing color, Detail, and smear effects in extremely low-light scenes
120 dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30 m (98 ft) warm light distance
Supports up to 512 GB Micro SD Card
IP67 protection
Support PoE power supply
3-Axis

104,40 87,00

IPC3612LE-ADF28KC-WL



EASYSSTAR

2MP

ColorHunter

Built-in Mic

Edge Storage

WDR

POE

IP 67

Corridor Mode

I1038

2MP HD ColorHunter IR Fixed Eyeball Network Camera
High quality image with 2MP, 1/2.8"CMOS sensor
2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic & Speaker
Smart IR, up to 30m (98ft) IR distance
White Light, up to 30m (98ft) white light distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

110,40 92,00

IPC3532LB-ADZK-G-BLACK



EASY

2MP

Built-in Mic

Edge Storage

WDR

Open Line detection

IP 67

Intrusion detection

IK 10

I1092

2MP HD IR VF (2.8 ~ 12mm) Dome Network Camera
High quality image with 2MP, 1/2.7"CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 40m (131ft) IR distance
Supports 128 G Micro SD card
IK10 vandal resistant
IP67 protection
Support PoE power supply
3-Axis

156,00 130,00

BULLET IP KAMERE 2MPX

IPC2122LB-SF28-A



EASY

2MP

Smart Search

Smart IR

Ultra H.265

POE

IP 67

HLR

I1143

2MP Mini Fixed Bullet Network Camera
High quality image with 2MP, 1/2.8"CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
IP67 protection
Support PoE power supply
3-Axis

66,00 55,00

IPC2122LB-AF28WK-G



EASY

2MP

WiFi Connection

Edge Storage

Built-in Mic

Smart IR

HLR

Ultra H.265

IP 67

I1009

2MP HD WIFI Bullet Network Camera
High quality image with 2MP, 1/2.9"CMOS sensor
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
IP67 protection
3-Axis

78,00 65,00

IPC2122LB-AF40WK-G BLACK



	2MP HD WIFI Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG		
I1093	Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card IP67 protection 3-Axis	78,00	65,00

IPC2122LB-ADF40KM-G



	2MP HD WDR Fixed IR Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene		
7113	Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card Support PoE power supply 3-Axis	72,00	60,00

IPC2122LB-AF28K-WL



	2MP HD ColorHunter Mini Fixed Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra H.265,H.265, H.264 Built-in Mic		
I1050	Warm Light, up to 30m (98ft) warm light distance 2D/3D DNR (Digital Noise Reduction) Support 128GB Micro SD card IP67 protection Support PoE power supply 3-Axis	99,00	82,50

IPC2312LE-ADF28KM-WP



	2MP ColorHunter with Wise-ISP Fixed Bullet Network Camera High quality image with 2MP, 1/2.7"CMOS sensor and F1.0 large aperture lens 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps; Ultra 265, H.265, H.264, MJPEG Colorhunter with Wise-ISP technology ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene		
I1111	Support 9:16 Corridor Mode Built-in Mic White Light, up to 30m warm light distance Supports 512 GB Micro SD card IP67 protection Support PoE power supply 3-Axis	104,40	87,00

IPC2122LE-ADF28KMC-WL



	2MP HD ColorHunter Mini IR Fixed Bullet Network Camera High quality image with 2MP, 1/2.8"CMOS sensor 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps; Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode		
I1028	Built-in Mic & Speaker Smart IR, up to 30m (98ft) IR distance White Light, up to 30m (98ft) white light distance Supports 128 G Micro SD card IP67 protection Support PoE power supply 3-Axis	110,40	92,00

BULLET IP KAMERE 3MPX

IPC2123LB-AF28KM-G





3MP

Built-in Mic

Edge Storage

HLC

Smart IR

IP 67

Ultra H.265

Corridor Mode

I1037

3MP HD Fixed IR Bullet Network Camera

High quality image with 3MP, 1/2.7"CMOS sensor
3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
Ultra 265, H.265, H.264, MJPEG
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

86,40 72,00

DOME IP KAMERE 4MPX

IPC3614LB-SF28-A





4MP

H.265

Smart IR

IP 67

POE

HLC

Smart Search

I1030

4MP Fixed Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Support PoE power supply
3-Axis

81,60 68,00

IPC324LB-SF28-A





4MP

Smart IR

IP 67

POE

HLC

H.265

Smart Search

IK 10

I1010

4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera

Rezolucija snimanja: ③4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps
Čip: 1/3", progressive scan , 4.0 megapixel, CMOS
Šater: Auto/Manual, 1 ~ 1/100000s
Optika: 2.8mm @F2.0
Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter
IC domet: do 30m
Interfejsi: 10/100M Base-TX Ethernet
Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP,
DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,Qos,SSL/TLS
Mrežni standardi: ONVIF (Profile S, Profile T),API,SDK
Kompresija: H.265, H.264,
Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI,
Corridor mod
Zaštita: IP67, IK10
Napajanje i potrošnja: DC 12V±25%, PoE (IEEE 802.3af), max 5W
Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlačnost: ≤95% RH (ne kondenzujuće)
Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg
Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

81,60 68,00

IPC3614LB-ASF28K-A





4MP

Built-in Mic

Edge Storage

IP 67

POE

HLC

Smart Search

Smart IR

I1114

4MP Fixed Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
Support PoE power supply
Built-in Mic
3-Axis

86,40 72,00

IPC324LB-ASF28K-A



I1070

4MP Fixed IR Dome Network Camera
High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
Ultra 265, H.265, H.264
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
Support Micro SD card
IP67 protection
IK10 vandal resistant
DC12V or PoE(IEEE 802.3af) power supply
2-Axis

NEMA NA STANJU

IPC3624LE-ADF28K-WP



I1086

4MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera
High quality image with 4MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m (98ft) warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

128,40 107,00

IPC3514LE-ADF28K-WP



I1084

4MP ColorHunter Wise-ISP Fixed Dome Network Camera
High quality image with 4MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Supports 512 GB Micro SD card
IP67 protection
IK10 protection
Support PoE power supply
3-Axis

128,40 107,00

IPC3614LE-ADF28K-H



I1137

4MP EasyStar Fixed IR Turret Network Camera
High quality image with 4MP, 1/3" CMOS sensor
4MP (2688 × 1520)@25/20 fps; 4MP (2560 × 1440)@25/20 fps; 3MP (2304 × 1296)@30/25 fps; 2MP (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
Easystar technology ensures high image quality in low illumination environment
120 dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30 m (98 ft) IR distance
Supports up to 512 GB Micro SD Card
IP67 protection
Support PoE power supply
3-Axis

147,60 123,00

IPC3614LE-ADF28KC-WL



I1040

4MP HD ColorHunter IR Fixed Eyeball Network Camera
High quality image with 4MP, 1/3"CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic & Speaker
Smart IR, up to 30m (98ft) IR distance
White Light, up to 30m (98ft) white light distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

150,00 125,00

IPC3614SB-ADF28KMC-10 PRIME  4MP Active deterrence Built-in Mic Edge Storage Corridor Mode WDR IP 67	4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera High quality image with 4MP, 1/2.7"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps; Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle Supports sound and light alarm linkage.When Smart intrusion prevention is triggered The camera links sound alarm and light linkage. Intelligent People Flow Counting and Crowd Density Monitoring 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic and Speaker Smart IR, up to 30m (98ft) IR distance Supports 256 G Micro SD card IP67 protection Support PoE power supply 11194 156,00 130,00
IPC3614SB-ADF40KMC-10 PRIME  4MP Active deterrence Built-in Mic Edge Storage Corridor Mode WDR IP 67	4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera High quality image with 4MP, 1/2.7"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps; Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle Supports sound and light alarm linkage.When Smart intrusion prevention is triggered , the camera links sound alarm and light linkage. Intelligent People Flow Counting and Crowd Density Monitoring 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic and Speaker Smart IR, up to 30m (98ft) IR distance Supports 256 G Micro SD card IP67 protection Support PoE power supply 11094 156,00 130,00
IPC354SB-ADNF28K-10 PRIME  4MP LightHunter WDR Built-in Mic Ultra motion Detection People Counting Intrusion detection Edge Storage	4MP LightHunter Fixed IR Dome Network Camera High quality image with 4MP, 1/2.7"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, Motor vehicle and non-motor vehicle Intelligent People Flow Counting and Crowd Density Monitoring 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 30m (98 ft) IR distance Supports 512 G Micro SD card Cable-free Support PoE power supply 11087 180,00 150,00
IPC3534LB-ADZK-G NOVO EASY  4MP Built-in Mic Edge Storage Intrusion detection WDR IP 67 cross line detection Corridor Mode	4MP HD IR VF (2.8 ~ 12mm) Dome Network Camera High quality image with 4MP, 1/3"CMOS sensor 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps;2MP (1920*1080)@30/25fps Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 40m (131ft) IR distance Supports 256 G Micro SD card IK10 vandal resistant IP67 protection Support PoE power supply 3-Axis 2295 180,00 150,00

BULLET IP KAMERE 4MPX

IPC2124LB-SF28-A



I1011

4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
H.265, H.264
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
IP67 protection
DC12V or PoE(IEEE 802.3af) power supply
3-Axis

81,60 68,00

IPC2124LB-SF40-A



I1081

4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
H.265, H.264
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
IP67 protection
DC12V or PoE(IEEE 802.3af) power supply
3-Axis

84,00 70,00

IPC2124LB-ASF28K-A



I1071

4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
Ultra H.265,H.265, H.264
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
Supports Micro SD card
IP67 protection
DC12V or PoE(IEEE 802.3af) power supply
3-Axis

86,40 72,00

IPC2124LB-ADF28KM-H



I1068

4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/2.9"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps;
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
Support PoE power supply
120dB WDR
3-Axis

114,00 95,00

IPC2124LB-ADF40KM-H



I1075

4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/2.9"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps;
2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Built-in Mic
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
Support PoE power supply
120dB WDR
3-Axis

116,40 97,00

IPC2314LE-ADF28KM-WP

EASYSSTAR



I1085

4MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Colorhunter with Wise-ISP technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

128,40 107,00

IPC2124LE-ADF28KMC-WL



I1148

4MP ColorHunter Fixed Dual-light Bullet Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps;
3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
120 dB true WDR technology enables clear image in strong light scene
Supports 9:16 corridor mode
Built-in mic and speaker
Smart IR, up to 30 m (98.4 ft) IR distance
White light, up to 30 m (98.4 ft) white light distance
MicroSD, up to 512 GB
IP67 protection
Supports PoE power supply
3-axis

132,00 110,00

IPC2124LE-ADF28KM-G

EASYSSTAR



I1027

4MP HD Mini IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Easystar technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

147,60 123,00

IPC2314LE-ADF28KM-WL

EASYSSTAR



I1029

4MP HD ColorHunter Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Colorhunter technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m white light distance
Supports 128 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

159,60 133,00

IPC2124SB-ADF28KM-IO

PRIME



I1088

4MP HD Intelligent LightHunter IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
LightHunter technology ensures ultra-high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 40m (131ft) IR distance
Supports 512 G Micro SD card
IP67 protection
Support PoE power supply

162,00 135,00

IPC2324LB-ADZK-G

NOVO

EASY



4MP

Edge Storage

Built-in Mic

Cross Line detection

Corridor Mode

Intrusion detection

WDR

IP 67

4MP HD IR VF (2.8 ~ 12mm) Bullet Network Camera

High quality image with 4MP, 1/3"CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps;2MP (1920*1080)@30/25fps
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
IK10 vandal resistant
Support PoE power supply
3-Axis

9999180,00150,00

IPC2314SB-ADF60KM-10

PRIME



4MP

Built-in Mic

80 IR distance

IP 67

WDR

Group's Intrusion Prevention

Light Hunter

4MP HD Intelligent 80m IR Fixed Bullet Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle
And non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in 2 Mic
Smart IR, up to 80m (262 ft) IR distance
Supports 256 G Micro SD card
IP67 protection

11097192,00160,00

IPC2314SB-ADF40KM-10

NOVO

PRIME



4MP

Built-in Mic

Light Hunter

POE

WDR

Ultra Motion Detection

Intrusion Detection

IP 67

4MP LightHunter Fixed IR Bullet Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in 2 Mic
Smart IR, up to 80m (262 ft) IR distance
Supports 512 G Micro SD card
IP67 protection

2297192,00160,00

**4MP Recognition Of Vehicle License Plate Bullet IP Camera (2.8 ~ 12mm)****Features****Optics**

Built-in lens supports motorized zoom to adapt to different scenes and allows for easy installation.

Automatic gain control, white balance, and WDR for various light conditions.

Compression

Supports triple streams.

Advanced H.265 encoding technology improves compression efficiency.

Custom OSD allows various vehicle information to be overlaid on the video image.

Functions

Built-in vehicle and license plate recognition algorithm can recognize

standard license plates of multiple countries.

Supports capturing vehicle head only.

Supports plate allowlist and blacklist configuration.

Supports vehicle access control when connected to a barrier.

Supports Micro SD cards of up to 256GB.

Automatic network replenishment (ANR) allows to automatically

store video to SD card in case of network disconnection.

Supports audio collection and intercom.

I1120

Network

Network auto-adaptability ensures smooth live video in relatively bad network conditions such as packet loss.

Supports SNMP.

Supports UNP for NAT traversal between public and private networks.

Supports integration with the third party via SDK or HTTP.

Network Security

Supports authorized user access by password. Weak password detection and account lock-up when failed login attempts reach the Upper limit enhance password security.

Supports Web access via HTTPS.

RTSP authentication prevents unauthorized video stream requests.

IP address filtering prevents illegal access from untrusted IP addresses.

Gateway ARP protection prevents MAC address spoofing.

Structure

Supports DC 12V and PoE (802.3at) power supplies.


Cast aluminum body offers excellent heat dissipation.

3-axis mounting bracket for various installation scenarios.

A junction box on the mounting bracket is convenient for storing tail cables.

IP67 and IK10 protection.

840,00 700,00

DOME IP KAMERE 5MPX**IPC3615LB-SF28-A****5MP Fixed IR Turret Network Camera**

High quality image with 5 MP, 1/3.0" CMOS sensor

5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;

3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps

Ultra 265, H.265, H.264, MJPEG

I1147

Smart IR, up to 30 m (98.4 ft) IR distance

86,40 72,00

Day/night functionality

2D/3D DNR (digital noise reduction)

IP67 protection

DC 12 V, PoE (IEEE 802.3af) power supply

3-axis

IPC3635LB-ADZK-G**5MP HD IR VF Eyeball Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor

5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;

3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@30/25fps

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in strong light scene

I1139

Support 9:16 Corridor Mode

192,00 160,00

Built-in Mic

Smart IR, up to 40m (131ft) IR distance

Supports 256 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

IPC3615SS-ADF28K-I1





5MP

Edge Storage

Built-in Mic

LightHunter

WDR

Smart Intrusion Prevention

Corridor Mode

IP 67

11105

5MP HD Intelligent LightHunter IR Fixed Turret Dome Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@ 30/25(default)fps; 4MP (2560*1440)@ 30/25fps;
3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
Auto Scene Match (ASM) (WDR only)
LightHunter technology ensures ultra-high image quality in low illumination environment
130dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 40m (131ft) IR distance
Supports 256 G Micro SD card
IP67 protection

192,00 160,00

IPC3615SE-ADF28KM-WL-I0





5MP

ColorHunter

Edge Storage

Built-in Mic

Smart Intrusion Prevention

WDR

IP 67

7058

5MP HD Intelligent ColorHunter Fixed Eyeball Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@30/25fps; 4MP (2560*1440)@30/25fps;3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
Ultra 265, H.265, H.264, MJPEG
Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce False alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
Colorhunter technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 corridor Mode
Support built-in Mic
Support 256 G Micro SD card
IP67 protection
Support PoE power supply

232,00 197,50

BULLET IP KAMERA 5MPX

IPC2125LB-SF28-A







5MP

POE

H.265

RLC

Smart IR

Smart Search

IP 67

11145

5MP Fixed IR Bullet Network Camera

High quality image with 5 MP, 1/3.0" CMOS sensor
5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30 m (98.4 ft) IR distance
Day/night functionality
2D/3D DNR (digital noise reduction)
IP67 protection
DC 12 V, PoE (IEEE 802.3af) power supply
3-axis

86,40 72,00

IPC2125LB-SF40-A







5MP

POE

H.265

RLC

Smart IR

Smart Search

IP 67

11146

5MP Fixed IR Bullet Network Camera

High quality image with 5 MP, 1/3.0" CMOS sensor
5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30 m (98.4 ft) IR distance
Day/night functionality
2D/3D DNR (digital noise reduction)
IP67 protection
DC 12 V, PoE (IEEE 802.3af) power supply
3-axis

86,40 72,00

IPC2125LE-ADF28KM-G

EASYSSTAR



11041

5MP HD Mini IR Fixed Bullet Network Camera


High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 IC domet: do 50m
 Easystar technology ensures high image quality in low
 illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

159,60 133,00

IPC2125SB-ADF40KMC-IO



PRIME



11095

5MP HD Intelligent Light and Audible Warning Fixed Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296)
 @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area
 detection
 Based on target classification, smart intrusion prevention significantly reduce
 false alarm caused by leaves, birds and lights etc., accurately focus on human and,
 motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage.When Smart intrusion prevention
 is triggered, The camera links sound alarm and light linkage.
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KM-IO



PRIME



11110

5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area,
 leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low
 Illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KM-IO BLACK

PRIME



11106

5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area,
 leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low
 Illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply


168,00 140,00

IPC2325LB-ADZK-H



5MP HD IR VF (2.8 ~ 12mm) Bullet Network Camera
High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Built-in Mic
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

IPC2315SB-ADF40KM-IO



5MP LightHunter Fixed IR Bullet Network Camera
High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor Vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in 2 Mic
Smart IR, up to 80m (262 ft) IR distance
Supports 512 G Micro SD card
IP67 protection

DOME IP KAMERE 8MPX

IPC328SB-ADF28K-IO



8MP HD Intelligent IR Fixed Dome Network Camera
High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Alarm:1 in/1 out, Audio: 1 in/1 out
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 256 G Micro SD card
IK10 vandal resistant and IP67 protection

BULLET IP KAMERE 8MPX

IPC2318LE-ADF28KM-WP



8MP ColorHunter Wise-ISP Warm Light Bullet Network Camera
High quality image with 8MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Colorhunter with Wise-ISP technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

IPC2128LE-ADF28KM-G





4K

Built-in Mic

Edge Storage

Intrusion detection

WDR

IP 67

Cross line detection

Encoder

11012

4K 8MP Mini Fixed Bullet Network Camera
High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Easystar technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

211,20176,00

IPC2128SB-ADF28KMC-IO





4K

Edge Storage

Active disturbance

120dB WDR

Smart Face Capture

Group Portraits

Ultra Motion Detection

IP 67

11090

8MP Tri-Guard Fixed Dual-light Bullet Network Camera
High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Built-in Speaker
Smart IR, up to 30m (98ft) IR distance
Supports 512 G Micro SD card
IP67 protection

246,00205,00

IPC2328SB-DZK-IO

NOVO





4K

LightHunter

50 IR distance

IK 10

Smart Intrusion Prevention

WDR

IP 67

11138

8MP HD Intelligent LighterHunter IR VF (2.8 ~ 12mm) Bullet Network Camera
High quality image with 8MP, 1/2.8"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
LightHunter technology ensures ultra-high image
Quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Alarm:1 in/1 out, Audio: 1 in/1 out
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IK10 vandal resistant
IP67 protection
Support PoE power supply

264,00220,00

UNIARCH

Uho-S2



2MP

Edge Storage

Built-in Mic

IR

U-code

Human Body Detection

H.265


Auto tracking

11091

High quality image with 2MP, 1/3"CMOS sensor
2MP (1920*1080)@25/20fps; 720P (1280*720) @25/20fps
Ultra 265, H.265, H.264
Built-in Mic & Speaker, support two-way audio, offer better interaction
IR night vision, up to 10m (33ft) IR distance
Support 256 G Micro SD card
Wi-Fi connection and easy installation

36,0030,00

Uho-S3E-M3




I1051	High quality image with 3MP, 1/3" CMOS sensor		
	3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps;720P (1280*720) @30/25/fps		
	Ultra 265, H.265, H.264		
	Built-in Mic & Speaker, support two-way audio,offer better interaction	42,00	35,00
	IR night vision, up to 10m (33ft) IR distance		
	Support 256 G Micro SD card		
	Wi-Fi connection and easy installation		

IPC-B122-APF28



I1140	High quality image with 1080P, 1/2.9" CMOS sensor		
	1080P (1920 × 1080)@25/20 fps; 720P (1280 × 720)@25/20 fps		
	Ultra 265, H.265, H.264		
	2D/3D DNR (digital noise reduction)		
	ROI (region of interest) ensures image quality in areas of interest	43,20	36,00
	With low bandwidth		
	Smart IR, up to 30 m (98.4 ft.) IR distance		
	Built-in mic		
	Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)		
	DC 12 V, PoE (IEEE 802.3af) power supply		

IPC-T122-APF28



I1141	High quality image with 1080P, 1/2.8" CMOS sensor		
	1080P (1920 × 1080)@25 fps; 720P (1280 × 720)@25 fps		
	Ultra 265, H.265, H.264		
	2D/3D DNR (digital noise reduction)		
	ROI (region of interest) ensures image quality in areas of Interest with low bandwidth	43,20	36,00
	Smart IR, up to 30 m (98.4 ft.) IR distance		
	Built-in mic		
	Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)		
	DC 12 V, PoE (IEEE 802.3af) power supply		

Uho-B1R-M2F3



I1127	High quality image with 2MP, 1/2.9" CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264, MJPEG		
	Built-in Mic	51,60	43,00
	Smart IR, up to 30m (98ft) IR distance		
	Supports 128 G Micro SD card		
	IP67 protection		
	3-Axis		

IPC-B125-APF2B

NOVO



5 MP

Built-in Mic

MIC

ONVIF

PoE

IP67

Smart IR

Ultra H.265

I1142

High quality image with 5 MP, 1/3.0" CMOS sensor
5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps; 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30 fps; 720P (1280 × 720)@30 fps; D1 (720 × 576)@30 fps
Ultra 265, H.265, H.264
2D/3D DNR (digital noise reduction)
ROI (region of interest) ensures image quality in areas Of interest with low bandwidth
Smart IR, up to 30 m (98.4 ft.) IR distance
Built-in mic
Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
DC 12 V, PoE (IEEE 802.3af) power supply

60,00

50,00

Uho-P1A-M3F4D



3MP

Human Body Detection

Built-in Mic

Edge Storage

Smart IR

Intrusion detection

Video Size Adjustment

IP66

I1052

High quality image with 3MP, 1/2.8" CMOS sensor
2304*1296@20fps in the main stream
Ultra 265, H.265, H.264
Support digital WDR (Wide Dynamic Range)
Built-in Mic & Speaker, support two-way audio, offer better interaction
Support sound and light warning, makes warning and alarming more noticeable
Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes
Self-contained bracket, support two kinds of mounting
Supports 256 GB Micro SD card
Wi-Fi connection and easy installation
IP66 ingress protection
The front face is made of grapheme, which has better heat dissipation and more Environmental protection

NEMA NA STANJU

Uho-P2S-M33F34

NOVO



3MP

Built-in Mic

Edge Storage

IP66

Smart IR

Ultra H.265

Wifi

I1128

Fixed camera and PTZ camera integration, dual channels with one IP, Look at overall situation and consider details at the same time
Ultra 265, H.265, H.264
Support digital WDR (Wide Dynamic Range)
Built in Mic Speaker, support two way audio, offer better interaction
Support sound and light warning, makes warning and alarming more noticeable
Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes
IR warm light illumination to deal with different scenes and achieve full color illumination
Supports 512 GB Micro SD card
Wi Fi connection and easy installation
IP66 ingress protection

118,80

99,00

PTZ IP KAMERE

IPC6312LR-AX4W-VG



LightHunter

Auto Tracking

Deep Penetration

WDR

Ultra H.265

Built-in Mic

Edge Storage

WiFi Connection

2219

2MP LightHunter WIFI IR Network PTZ Camera
High quality image with 2MP, 1/2.7" CMOS sensor
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios
LightHunter technology ensures ultra-high image quality in low illumination environment
Up to 120 dB Optical WDR (Wide Dynamic Range)
Wi-Fi connection and easy installation
Built-in Mic & Speaker
Smart IR, Up to 50 m (164 ft) IR distance
Micro SD, up to 256GB
IP66 protection

255,00

212,50

IPC6312LR-AX4-VG

        	2MP LightHunter IR Network PTZ Camera High quality image with 2MP, 1/2.7" CMOS sensor Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios LightHunter technology ensures ultra-high image quality in Low illumination environment Up to 120 dB Optical WDR (Wide Dynamic Range) Built-in Mic & Speaker Smart IR, Up to 50 m (164 ft) IR distance Micro SD, up to 256GB IP66 protection DC12V or PoE (IEEE 802.3af) power supply	255,00	212,50

IPC675LFW-AX4DUPKC-VG

       	5MP LightHunter Active Deterrence Mini PTZ Camera High quality image with 5MP, 1/2.7" CMOS sensor Ultra 265, H.265, H.264, MJPEG LightHunter technology ensures ultra-high image quality in low illumination environment Up to 120 dB Optical WDR (Wide Dynamic Range) Built-in Mic & Speaker Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance Micro SD, up to 256GB IP66 protection DC12V or PoE (IEEE 802.3af) power supply	270,00	225,00

IPC5412LR-X16-VG

     	2MP 16x LightHunter Network PTZ Dome Camera High quality image with 2MP, 1/2.8" CMOS sensor 1920*1080@30fps in the main stream Ultra 265, H.265, H.264, MJPEG 16X optical zoom allows for closer viewing of subjects LightHunter technology ensures ultra-high image quality in low illumination environment Smart IR, up to 100m (328ft) IR distance Micro SD, up to 256GB DC 12V±25% or PoE+ (IEEE 802.3at) IP66 ingress protection	396,00	330,00

IPC6424SR-X25--B

       	4MP 25x LightHunter IR Network PTZ Camera High quality image with 4 MP, 1/2.8" CMOS sensor 2688 × 1520@30 fps in the main stream Ultra 265, H.265, H.264, MJPEG 25X optical zoom Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection automatic selection of best snapshots, supports face detection masked area People counting, supports people flow counting and crowd density monitoring, suitable for different statistical scenarios LightHunter technology ensures ultra-high image quality in low illumination environment Smart IR, up to 100 m (328 ft) IR distance DC 12 V±25%, PoE+ (IEEE 802.3at) Alarm I/O: 2/1, audio I/O: 1/1 IP67 ingress protection IK10 vandal resistant	636,00	530,00

IPC6612SR-X33-VG

       	2MP 33x Lighthunter Network PTZ Dome Camera High quality image with 2MP, 1/2.8" CMOS sensor 1920*1080@30fps in the main stream Ultra 265, H.265, H.264, MJPEG 33X optical zoom allows for closer viewing of subjects Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection LightHunter technology ensures ultra-high image quality in Low illumination environment Up to 120 dB Optical WDR (Wide Dynamic Range) DC12V or PoE+(IEEE 802.3at) power supply Audio 1 in and 1 out, Alarm 2 in and 1 out Micro SD, up to 256GB Smart IR, up to 150m (492 ft) IR distance IP66 ingress protection	NEMA NA STANJU	



4MP 33X LightHunter IR Network PTZ Camera

High quality image with 4 MP, 1/2.8" CMOS sensor
2688 × 1520@30 fps in the main stream
Ultra 265, H.265, H.264, MJPEG
33X optical zoom
Smart intrusion prevention, supports false alarm filtering,
including cross line, intrusion, enter area, leave area detection
automatic selection of best snapshots, supports face detection masked area
People counting, supports people flow counting and crowd density monitoring,
Suitable for different statistical scenarios
LightHunter technology ensures ultra-high image quality in low illumination environment
AC 24 V±25%, DC 24 V±25%, PoE+ (IEEE802.3 at)
Alarm I/O: 7/2, audio I/O: 1/1
IP67 ingress protection
IK10 vandal resistant

I1153 1320,00 1100,00

VIDEO INTERFONI

OEU-201B-HMK-W



Outdoor Station
Front panel: Plastic cement
Supports batch configuration
Supports intercom calls to associated indoor units or APPs
Support monitoring function, security alarm, tamper alarm
Support Wi-Fi
Built-in IC card reader
Card Capacity 2000
IP65(Apply silica gel to gaps between the device and the wall)

I1201 216,00 180,00

OEU-202S-HMK2



Outdoor Station
Front panel: Metal
Vandal-resistant: IK08
Supports batch configuration
WDR: Digital
Built-in IC card reader
Card Capacity 10000
IP65(Apply silica gel to gaps between the device and the wall)

I1202 252,00 210,00

OEU-202S-HMK4



Outdoor Station
Front panel: Metal
Vandal-resistant: IK08
Supports batch configuration
WDR: Digital
Built-in IC card reader
Card Capacity 10000
IP65(Apply silica gel to gaps between the device and the wall)

I1204 276,00 230,00

OEU-301S-HMKA



Outdoor Station
Front panel: Metal
Vandal-resistant: IK08
Supports batch configuration
WDR: Digital
Built-in IC card reader
Card Capacity 10000
Alarm Output: 2
IP65(Apply silica gel to gaps between the device and the wall)

I1301 420,00 350,00



I1203	Wall Mount Sunshield Compatible with OEU-201B-HMK-W, OEU-201B-HMK-W-NB, OEU-201S-HMK-W, And OEU-201S-HMK-W-NB villa door stations	18,00	15,00
-------	---	-------	-------

OEI-372S-H-W



I1372	Indoor Station Rugged ABS casing and glass panel. 1024*600 HD touch screen. Batch configuration transfer. Remote opening of linked door stations, one-key opening. Network camera monitoring, security alarm	192,00	160,00
-------	---	--------	--------

KIT/201S/372S/NSW2020



I1205	OEU-201S-HMK-W Metal casing. Supports call and intercom with the connected indoor station and app. Supports security protection alarm and tamper alarm triggered by door magnet, infrared, etc. Supports Wi-Fi. Built-in IC card reader. OEI-372S-H-W ABS casing and glass panel, solid and durable. Supports Wi-Fi. Supports touchscreen operation. 1024 x 600 HD screen. Supports remote door opening by sending signal to the door station. Allows to view live video of connected door stations and network cameras. NSW2020-6T-POE-IN Allows to switch operating modes, including Default, VLAN, and Extend. Supports VLAN isolation. All PoE ports are isolated from each other and only able to communicate with uplink ports. Supports network extension. With a high-quality network cable and IPC, the network transmission distance can reach up to 250 meters by lowering the network port rate to 10Mbps. Supports port priority. Packets from high-priority ports will be forwarded first. Supports flow control. When there is data congestion in the uplink ports, the switch will actively send flow control frames to PoE ports. Plug-and-play, simple and convenient. All metal casing, secure and reliable.	360,00	300,00
-------	--	--------	--------

HARD DISKOVI

WD GREEN 320 GB



Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB	KONTAKT
---	---------

WD GREEN 500 GB



Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB	KONTAKT
---	---------

WD GREEN 1 TB



Western Digital, 1 TB GREEN, 7200RPM, SATA III, 32MB	KONTAKT
--	---------

HDD 1TB WD64PURZ-85BWUY0



I1100 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB 102,00 85,00

HDD 2TB WD64PURZ-85BWUY0



I1200 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB 120,00 100,00

HDD 4TB WD64PURZ-85BWUY0



I1400 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB 181,20 151,00

HDD 6TB WD64PURZ-85BWUY0



I1600 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB 264,00 220,00

HDD 8TB WD64PURZ-85BWUY0



6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB 360,00 300,00

TF-64G-T-L



I1021 Uniview memorijska kartica
Kapacitet: 64GB
Maksimalna brzina čitanja: 90MB/s
Maksimalna brzina pisanja: 65MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g 14,40 12,00

TF-128G-T-L



I1022 Uniview memorijska kartica
Kapacitet: 128GB
Maksimalna brzina čitanja: 100MB/s
Maksimalna brzina pisanja: 80MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g 22,80 19,00

TF-256G-T-L



I1123 Uniview memorijska kartica
Kapacitet: 256GB
Maksimalna brzina čitanja: 90MB/s
Maksimalna brzina pisanja: 65MB/s
Dimenzije: 11mm x 15mm x 1mm
Težina: 0,33g 43,20 36,00

Uniview SVIČEVI

NSW1010-5T-IN



I1130 5-Port 100 Megabit Plastic Shell Switch
Supports IEEE802.3 and IEEE802.3u standards.
Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
Supports auto MDI/MDIX.
Supports IEEE802.3 flow control for full-duplex mode and backpressure
For half-duplex mode. 8,40 7,00

NSW1010-8T-IN



I1131	8-Port 100 Megabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.	12,00	10,00
-------	---	-------	-------

NSW1010-5GT-IN



I1132	5-Port Gigabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode	14,40	12,00
-------	--	-------	-------

NSW1010-8GT-IN



I1133	8-Port Gigabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.	24,00	20,00
-------	---	-------	-------

Uniview POE SVIČEVI

NSW2020-6T-POE-IN



I1023	6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm	54,00	45,00
-------	---	-------	-------

NSW2010-5GT-POE-IN



I1059	4 Port GigabitPoE Switch 1 Port Gigabit Uplink PoE Power up to 30W Each Port Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD) Auto Detect Power Device Power Port Supply prioritization, guarantees the continuous power supply of key nodes IEEE802.3 X full duplex flow control and Backpressure half duplex flow control Line Speed Forwarding, intelligent identification Up to 250m transmission distance on surveillance mode	78,00	65,00
-------	--	-------	-------

NSW2020-10T-POE-IN



I1024	10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode); 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm	90,00	75,00
-------	--	-------	-------

NSW2010-10GT-POE-IN



I1060	8 Port Gigabit PoE Switch 2 Port Gigabit Uplink PoE Power up to 30W Each Port Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD) Auto Detect Power Device Power Port Supply prioritization, guarantees the continuous power Supply of key nodes IEEE802.3 X full duplex flow control and Backpressure half duplex flow control Line Speed Forwarding, intelligent identification Up to 250m transmission distance on surveillance mode	NEMA NA STANJU	
-------	---	----------------	--

NSW3000-8T2GT-POE-IN



I1134

Cloud Managed Ethernet Switch(PoE)
8 x 10/100Mbps POE port (RJ45) ,2 x Gigabit port (RJ45)
Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software.
Supports Web login, and device configuration and management on the Web interface; supports visiting the cloud by scanning the QR code.
Allows to view the device status and network topology in real time on the app, and remotely restart the PoE power supply.
Allows up to 250m power supply using a standard network cable.
Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.
Allows to report port abnormal alarms to the software for realtime monitoring.
Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full.
All metal casing, secure and reliable.
Maximum total power: 120W
Maximum PoE power for single port: 30W

96,00 80,00

NSW2020-16T2GC-POE-IN



I1067

16×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta
Podrška: IEEE802.3,IEEE802.3u,IEEE802.3az, IEEE802.3x,IEEE802.3af,IEEE802.3at
Modovi rada: Default(Normal mode):
Svi portovi komuniciraju normalno međusobno
EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s.
VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima.
6kV zaštita od prenapona PoE Budžet: 370W
Maksimalna snaga: 250W
Maksimalna PoE snaga porta: 30W
Dimenzije: 440mm x 207mm x 45mm
Moguća rek montaža 19" , dolazi uz switch

216,00 180,00

NSW3000-16T1GT1GC-LPOE-IN



I1135

Cloud Management Switch
16 x 10/100Mbps POE port (RJ45) + 1 x Gigabit port (RJ45)+ 1 x Gigabit Combo
Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software.
Supports Web login, and device configuration and management on the Web interface
in real time on the app, and remotely restart the PoE power supply.
Supports PoE power supply and allows to view the power; allows to enable or disable PoE power supply for the powered device;
Allows up to 250m power supply using a standard network cable.
Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.
Allows to report port abnormal alarms to the software for realtime monitoring.
Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full.
All metal casing, secure and reliable.
Maximum total power: 150W
Maximum PoE power for single port: 30W

150,00 125,00




NSW2010-24T2GC-PoE-IN




I1136

Ethernet Switch(PoE)
24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports
Multiple working modes to address your business needs:
Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
Support port traffic control
Support for secure mode, all downlink ports can communicate
Only with uplink ports
Up to 250m transmission distance on surveillance mode
Support buffer optimization
All metal housing, safe and reliable
Max power: 390W

288,00 240,00

DODATNA OPREMA				
GCB01-B7				
NOVO 	i1101	UNV-Link Pro Connect Box Network: 4 x RJ45 10M/100M Base-TX EthernetNetwork Port 1 Support POE (IEEE802.3af) OutputNetwork Port 4 Support PSE Voltage Test Wi-Fi 2.4G Wi-Fi Battery: 7500mAh Power Input: 1 x DC 5V/2A max, type-c Power Output: 1 x DC 12V/1A output; 1 x DC 5V/1A output, type-A	78,00	65,00
PoE Extender				
	9995	Model: LN-POEPL03S PoE In: 44-57V/30W PoE Out (1-3) : 44-57V/25W Support: 10/100 Mbps IEEE802.3af/at	NEMA NA STANJU	
3 Ports POE Injector				
	2255	PoE extender, repeater, switch 1 na 2 Usklađenost sa IEEE 802. af/at Power over Ethernet(10/100M podržano) Proširite domet Porta za dodatnih 100 metara	25,00	20,83
KABLOVI				
UNV Cat6 (UTP), CCA				
	i1044	CAB-LC3100B-CCA-IN Conductor material: CCA(Copper content: 27%) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC	0,30	0,250
UNV Cat5e (UTP), BC				
	i1045	CAB-LC2100A-E2-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material:HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,54	0,450
UNV Cat6 (UTP), BC				
	i1046	CAB-LC3100A-EC-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,78	0,650
KUĆIŠTA I NOSAČI				
DOZNA ZA KAMERE BA-01				
	5633	Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00

DOZNA ZA KAMERE G153

	8644	Razvodna kutija za spoljašnju montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,20	2,67
---	------	---	------	------

DOZNA ZA KAMERE BA-02

	8645	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,00	2,50
---	------	--	------	------

TR-JB05-B-IN

	I1062	Nosač za Dome kamere serije IPC21XX Dimenzije: Ø104.4mm*54.5mm Težina: 0.36kg Materijal: Aluminijum	19,20	16,00
---	-------	--	-------	-------

TR-JB05-A-IN

	I1061	Nosač za kamere Dimenzije: Ø93 × 93 × 39mm Težina: 0.2kg Materijal: Aluminijum	15,60	13,00
--	-------	---	-------	-------

TR-JB03-G-IN

	I1064	Nosač za Dome kamere serije IPC32x i IPC31x Dimenzije: ø106.6mm*36mm Težina: 0.2kg Materijal: Aluminijum	13,20	11,00
---	-------	---	-------	-------

TR-JB03-I-IN

	I1063	Nosač za Dome kamere serije IPC36XXL i IPCT1XX Dimenzije: Ø117.8 × 36mm Težina: 0.2kg Materijal: Aluminijum	15,60	13,00
---	-------	--	-------	-------

TR-JB03-H-IN

	5878	Nosač za Dome kamere serije IPC363X, IPC36XXS/E i 4MP fisheye Dimenzije: Ø126mm*36mm (4.96" x1.42") Težina: 0.24kg Materijal: Aluminijum legura	14,40	12,00
--	------	--	-------	-------

TR-JB04-C-IN

	5880	Nosač za Dome kamere serije 323 Dimenzije: Ø144.8 mm × 42.5 mm (5.7" × 1.7") Težina: 0.3kg Materijal: Aluminijum legura	15,60	13,00
--	------	--	-------	-------

NOVO



2298	Pole Mounting Bracket for Bullet Junction Box Only Application: Outdoor, pole or rail installation for bullet camera of IPC23XX OEM IPC23XX/22X、IPC74X and IPC252/26X series Bracket Dimensions: 136.0 mm × 127.0 mm × 63.6 mm (5.4" × 5.0" × 2.5") Bracket Weight: 0.34kg Bracket Material: Aluminum alloy	14,40	12,00
------	---	-------	-------

KONEKTORI

BNC NA LEMLJENJE
SA ŠRAFOM

3299	BNC konektor muški sa šrafom. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

BNC NA LEMLJENJE



2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,54	0,45
------	--	------	------

BNC KONEKTOR



30020	BNC konektor muški na šraf.	0,50	0,42
-------	-----------------------------	------	------

BNC NA KRIMP RG59



2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,60	0,50
------	---	------	------

BNC MUŠKI- F ŽENSKI



1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,70	0,58
------	--	------	------

BNC NASTAVAK



4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,54	0,45
------	---	------	------

F KONEKTOR na krimp
RG6

2559	F konektor za RG6 kabl. Pakovanje 100 kom.	0,14	0,12
------	---	------	------

F KONEKTOR na krimp RG59



1796	F konektor za RG59 kabl. Pakovanje 100 kom.	0,14	0,12
------	--	------	------

RF METALNI G MUŠKI



4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,35	0,29
------	--	------	------

RCA MUŠKI-F ŽENSKI



4446	RCA muški - F ženski konektor Pakovanje 100 kom.	0,53	0,44
------	---	------	------

F NASTAVAK					
	3300	F nastavak Ženski - Ženski Pakovanje 100 kom		0,22	0,18
F KONEKTOR KOMPRESIONI RG6 XL					
	1625	Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.		0,44	0,37
F KONEKTOR KOMPRESIONI RG11 XL					
	1627	Profesionalni PPC F konektor za RG11 kabl.		2,96	2,47
F KONEKTOR KOMPRESIONI RG59 XL					
	1624	Profesionalni PPC F konektor za RG59 kabl. Pakovanje 50 kom.		0,47	0,39
DC KABL-MUŠKI					
	1387	DC utikač-muški		0,47	0,39
DC KABL-ŽENSKI					
	1391	DC utikač-ženski		0,47	0,39
DC KONEKTOR MUŠKI					
	3425	DC konektor Muški		0,37	0,31
DC KONEKTOR ŽENSKI					
	4197	DC konektor ženski.		0,38	0,32
DC RAZDELNIK 1-4					
	1388	1 DC utičnica - 4 DC utikača		1,99	1,66
DC RAZDELNIK 1-8					
	1389	1 DC utičnica - 8 DC utikača		3,97	3,31
CAT7 RJ45					
		Mrežni konektor RJ45 kategorija 7		0,50	0,42
CAT5 RJ45					
	0067	Mrežni konektor RJ45		0,05	0,04

Telefonski konektor RJ11



0066 Telefonski konektor RJ11

0,02 0,02

DODATNA OPREMA

ŠTAMPAČ P-TOUCH E100



Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu

4663 106,56 88,80

MIKROFON LY-501C



2584 Audio modul sa izvedenim konektorima.
Napajanje 12 V DC

3,97 3,31

MIKROFON LY-502B



2583 Audio modul plastični sa trimerom.
Napajanje 12 V DC

6,00 5,00

MIKROFON LY-506



1937 Audio modul metalni sa trimerom.
Napajanje 12 V DC

10,00 8,33

DS-2FP2020



Viisoko osetljivi omnidirekcionni mikrofoni. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).

5222 36,00 30,00

DH-PFM800-4K (par)



One (1) Channel Balun
Real-time Transmission over UTP CAT5E/6 Cable
Compatible with HDCVI, TVI, AHD, and CVBS Video Formats
Transmission Distance at 4K: 200 m (656 ft)
External Power Supply not Required

3632 6,90 5,75

OG razvodna kutija 100x100



00091 Razvodna kutija 100x100

1,80 1,50

OG razvodna kutija 80x80



00092 Razvodna kutija 80x80

1,10 0,92

OG razvodna kutija 160x100x74



00093 Razvodna kutija 160x100x74

3,00 2,50

OG razvodna kutija 160x100x48



00094 Razvodna kutija 160x100x48

2,64 2,20

ALAT ZA KRIMP RG6, RG11,RG59					
	3302	Alat za krimpovanje RG6, RG11,RG59 konektora	48,00	40,00	
STRIPER ZA KABLOVE RG59,RG6					
	3301	Alat za stripovanje RG59,RG6 kablova	20,40	17,00	
ALAT KOMPRESIONI ZA RG59, RG6					
	1629	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake.	37,92	31,60	
ALAT KOMPRESIONI, ZA RG6,RG11,RG59					
	3796	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6,RG11,RG59 XL oznake.	54,34	45,28	
KLEŠTA ZA KRIMPOVANJE KOMPLET					
	5790	Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečicom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)	28,68	23,90	
NAPAJANJA					
XED-1212S					
	1633	Ulaz: 90V-264V Izlaz: 12V , 1A Snaga: 12W Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm Dužina izlaznog kabl: 110cm, 10.5x5,5x2mm konektor	6,00	5,00	
XED-2012S					
	1382	Ulaz: 90V-264V Izlaz: 12V , 2A Snaga: 24W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kabl: 110cm, 10.5x5,5x2mm konektor	8,04	6,70	
XED-3013S					
	1383	Ulaz: 90V-264V Izlaz: 12V , 3A Snaga: 36W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kabl: 110cm, 10.5x5,5x2mm konektor	12,60	10,50	
XED-5013S					
	1384	Ulaz: 100V-240V Izlaz: 12V , 5A Snaga: 60W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabl: 110cm, 10.5x5,5x2mm konektor	16,20	13,50	
XED-6013B					
	3509	Ulaz: 100V-240V Izlaz: 12V , 6A Snaga: 72W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabl: 110cm, 10.5x5,5x2mm konektor	20,40	17,00	
9-KANALNO NAPAJANJE XED-10A12VX-9L					
	5435	Snaga: 120W Ulaz: 100~240V 50~60Hz Izlaz: 12V 10A 9 kanala Dimenzije: 237*213*70mm Neto težina: 1800g Napomena: Sadrži AC kabl	82,80	69,00	
18-KANALNO NAPAJANJE XED-15A12VX-18L					
	5114	Snaga: 180W Ulaz: 100~240V 50~60Hz Izlaz: 12V 15A 18 kanala Dimenzije: 240*218*70mm Neto težina: 2300g Napomena: Sadrži AC kabl	94,80	79,00	

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs