

CENOVNIK UNIVIEW VIDEO NADZORA - 04.08.2026.



NAZIV	ŠIFRA	OPIS	CENA	
DVR UREDJAJI			sa PDV	bez PDV
4 KANALNI				

XVR301-04G3



4-CH Hybrid DVR

Podrzan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal)

4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podrzan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6)

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulazno/Izlazni saobraćaj: 16/48 Mbps

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 226mm × 47mm (10.2" × 8.9" × 1.8"), 1.1kg

11031

69,60

58,00



XVR301-04Q3



4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6)

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

Ulazno/Izlazni saobraćaj: 48/60 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 226mm × 47mm

11032

96,00

80,00

XVR301-04U3



4-ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
Support 1-ch CVBS output, 1-ch VGA output,
1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols
1HDD Up to 16 TB

11129

144,00 120,00

8 KANALNI

XVR301-08G



8-Ch Digital Video Recorder

Support H.265/H.264 video formats
Recording Resolution: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF
Support audio over coaxial cable (only for TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
4/8/16-channel BNC input
Support 1-ch HDMI output, 1-ch VGA output at up to 1920*1080
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols
1 SATA interface up to 6 TB

11176

84,00 70,00



XVR301-08G3



8-CH Hybrid DVR

Podrška: TVI,AHD, CVI, CVBS
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF
Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)
Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)
Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio
Ulazno/Izlazni saobraćaj: 32/64 Mbps
Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 sata HDD do 8TB
Napajanje 12V DC, Potrošnja 8W bez HDD
Radna temperatura: -10 °C ~ +55 °C
Dimenzije: 260mm × 226mm × 47mm

11025

91,20 75,00



XVR301-08Q3



8-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
Podrška: TVI,AHD, CVI,CVBS
Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)
Video kompresija: H.265, H.264
Video/audio ulazi: 8ch BNC, 1ch audio
Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio
Ulazno/Izlazni saobraćaj: 40/64 Mbps
Smart funkcije: Motion detection, video loss detection, audio detection,
Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 sata HDD do 8TB kapaciteta
Napajanje 12V DC,
Potrošnja 10W bez HDD,
Radna temperatura: -10 °C ~ +55 °C,
Dimenzije: 260mm × 226mm × 47mm

11033

138,00 115,00



XVR301-08U3



uniview
Better Security. Better World.

8-Ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
8-channel BNC input
Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols

I1080

222,00 185,00

16 KANALNI

XVR301-16G3



uniview
Better Security. Better World.

16-CH Hybrid DVR

Podržava: TVI, AHD, CVI, CVBS, IP cameras
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF
IP kamere: do 8 IP kamere ili svih 16
Video/audio ulazi: 16-ch BNC / 1-ch RCA
Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio
Ulazno/Izlazni saobraćaj: 40/64 Mbps
Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 SATA HDD do 8TB
Napajanje 12V DC, Potrošnja 10W bez HDD
Radna temperatura: -10 °C ~ +55 °C
Dimenzije: 260mm x 226mm x 47mm

I1026

148,80 124,00

XVR302-16Q3



uniview
Better Security. Better World.

16-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
Podržava 8MP@15fps na prva 4 kanala
Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.
Ulazno/Izlazni saobraćaj: 72/80 Mbps
Video kompresija: H.265/H.264 video kompresija,
Video/audio ulazi: 16ch BNC, 1ch RCA
Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA
Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection
Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485
Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
Hard disk prostor: 2 sata HDD do 6TB kapaciteta
Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,
Radna temperatura: -10 °C ~ +55 °C,
Dimenzije: 380mm x 315mm x 53mm, Težina 1.9Kg

I1034

288,00 240,00

KIT/XVR 301-04G3/4*UAC-T112-F28



UNV KIT/XVR 301-04G3/4*UAC-T112-F28

Kompet sadrži:
1x XVR 04G3
4x UAC-T112-F28
1x Napajanje 2A
4x 20m Koaksijalni kabl + napajanje (sa konektorima)
1x Razdelnik 1 / 4

I1065

180,00 150,00

ANALOGNE DOME KAMERE 2MP

UAC-T112-AF28



2MP HD Fixed IR Turret Analog Camera

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Built-in microphone
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

I1066

24,00 20,00

UAC-T112-F28-W



11005	2MP ColourHunter HD Fixed Turret Analog Camera	28,80	24,00
	2MP high quality image		
	TVI/AHD/CVI/CVBS		
	Supports white light illumination, 24/7 full-color imaging		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		

UAC-T122-AF28LM



11054	2MP LightHunter HD IR Fixed Turret Analog Camera	36,00	30,00
	High quality imaging with 2MP resolution		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	LightHunter monitoring with high-sensitivity sensor		
	3D noise reduction technology delivers clean and sharp images		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Supports digital defog		
	3-Axis		

UAC-T122-AF40LM



11099	2MP LightHunter HD IR Fixed Turret Analog Camera	36,00	30,00
	High quality imaging with 2MP resolution		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	LightHunter monitoring with high-sensitivity sensor		
	3D noise reduction technology delivers clean and sharp images		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Supports digital defog		
	3-Axis		

UAC-T122-AF28M-W



11016	2MP ColorHunter HD Fixed Turret Analog Camera	36,00	30,00
	2MP high quality imaging		
	TVI/AHD/CVI/CVBS		
	Supports white light illumination, 24/7 color images		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Supports digital defog		
	Metal front face and housing		
	3-Axis		

UAC-T142-AF28LM-DL



11077	2MP ColorHunter Fixed Dual-light Turret Analog Camera	43,20	36,00
	High quality imaging with 2MP resolution		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	Smart Dual Light (only TVI)		
	3D noise reduction technology delivers clean and sharp images		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		

ANALOGNE BULLET KAMERE 2MP

UAC-B112-F28



11000	2MP HD Fixed IR Mini Bullet Analog Camera	25,20	21,00
	2MP high quality image		
	TVI/AHD/CVI/CVBS		
	IR-cut filter with auto switch (ICR)		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		

UAC-B112-AF28



I1121	2MP Fixed IR Bullet Analog Camera		
	2MP high quality image		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	3D noise reduction technology delivers clean and sharp images		
	Supports 180° horizontal flip, 180° vertical flip	26,40	22,00
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		

UAC-B112-F28-W



I1001	2MP ColourHunter HD Fixed Mini Bullet Analog Camera		
	2MP high quality image		
	TVI/AHD/CVI/CVBS		
	Supports white light illumination, 24/7 full-color imaging		
	Supports 180° horizontal flip, 180° vertical flip	27,60	23,00
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		

UAC-B122-AF28LM



I1053	2MP LightHunter HD IR Fixed Mini Bullet Analog Camera		
	High quality imaging with 2MP resolution		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	LightHunter monitoring with high-sensitivity sensor		
	3D noise reduction technology delivers clean and sharp images		
	Supports 180° horizontal flip, 180° vertical flip	36,00	30,00
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
Supports digital defog			

UAC-B122-AF40LM



I1098	2MP LightHunter HD IR Fixed Mini Bullet Analog Camera		
	High quality imaging with 2MP resolution		
	TVI/AHD/CVI/CVBS		
	Supports IR-cut filter with auto-switch (ICR)		
	LightHunter monitoring with high-sensitivity sensor		
	3D noise reduction technology delivers clean and sharp images		
	Supports 180° horizontal flip, 180° vertical flip	36,00	30,00
	OSD configuration menu, easy to operate		
	IP67 waterproof and dustproof design, high reliability		
	OSD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Supports digital defog		

UAC-B122-AF28M-W



I1014	2MP ColorHunter HD Fixed Mini Bullet Analog Camera		
	2MP high quality imaging		
	TVI/AHD/CVI/CVBS		
	Supports white light illumination, 24/7 color images		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate	36,00	30,00
	IP67 waterproof and dustproof design, high reliability		
	SD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Supports digital defog		
	Metal front face and housing		

UAC-B122-AF28M-W-Black



I1214	2MP ColorHunter HD Fixed Mini Bullet Analog Camera		
	2MP high quality imaging		
	TVI/AHD/CVI/CVBS		
	Supports white light illumination, 24/7 color images		
	Supports 180° horizontal flip, 180° vertical flip		
	OSD configuration menu, easy to operate	36,00	30,00
	IP67 waterproof and dustproof design, high reliability		
	SD configuration menu in 11 languages		
	Built-in microphone for high quality audio transmission via coaxial cables		
	Supports digital defog		
	Metal front face and housing		

UAC-B122-AF40M-W



11015

2MP ColorHunter HD Fixed Mini Bullet Analog Camera

2MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Supports digital defog
Metal front face and housing

37,20

31,00

UAC-B142-AF28LM-DL



11076

2MP ColorHunter Fixed Dual-light Bullet Analog Camera

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
Smart Dual Light (only TVI)
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

46,80

39,00

UAC-B142-AF40LM-DL



11122

2MP ColorHunter Fixed Dual-light Bullet Analog Camera

High quality imaging with 2MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
Smart Dual Light (only TVI)
3D noise reduction technology delivers clean and sharp images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

46,80

39,00

ANALOGNE DOME KAMERE 5MP

UAC-T115-AF28



11126

5MP Fixed IR Turret Analog Camera

5MP high quality image
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables

30,00

25,00

UAC-T125-AF28LM



11056

5MP LightHunter HD IR Fixed Turret Analog Camera

High quality imaging with 5MP resolution
TVI/AHD/CVI/CVBS
Supports IR-cut filter with auto-switch (ICR)
LightHunter monitoring with high-sensitivity sensor
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
3-Axis

46,80

39,00

UAC-T125-AF28M-W



11020

5MP ColorHunter HD Fixed Turret Analog Camera

5MP high quality imaging
TVI/AHD/CVI/CVBS
Supports white light illumination, 24/7 color images
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages
Built-in microphone for high quality audio transmission via coaxial cables
Metal front face and housing
3-Axis

48,00

40,00

UAC-T125-AF28M-W-Black



	5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis	48,00	40,00
--	--	-------	-------

UAC-T145-AF28LM-DL



	5MP ColorHunter Fixed Dual-light Turret Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	50,40	42,00
--	--	-------	-------

ANALOGNE BULLET KAMERE 5MP

UAC-B115-F28



	5MP HD Fixed IR Mini Bullet Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	30,00	25,00
--	--	-------	-------

UAC-B115-AF28



	5MP Fixed IR Bullet Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	30,00	25,00
--	---	-------	-------

UAC-B125-AF28LM



	5MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	44,40	37,00
--	--	-------	-------

UAC-B125-AF40LM



	5MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	44,40	37,00
--	--	-------	-------

UAC-B125-AF28M-W



11018	5MP ColorHunter HD Fixed Mini Bullet Analog Camera		
	5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing	48,00	40,00

UAC-B125-AF40M-W



11019	5MP ColorHunter HD Fixed Mini Bullet Analog Camera		
	5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing	49,20	41,00

UAC-B145-AF28LM-DL



11078	5MP ColorHunter Fixed Dual-Light Bullet Analog Camera		
	High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	54,00	45,00

UAC-B315-ADZLM



11185	5MP LightHunter VARIFOCAL IR Bullet Analog Camera		
	High quality imaging with 5MP resolution 2.8mm-12mm motorized lens TVI/AHD/CVI/CVBS Illumination Distance: 50m Supports IR cut filter with auto switch (ICR) LightHunter monitoring with high sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built in microphone for high quality audio transmission via coaxial cables	90,00	75,00

NVR UREDJAJI

NVR301-04S3



11049	4-ch NVR		
	Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p Ulazno/Izlazni saobraćaj: 64/48Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD), Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg	108,00	90,00

NVR301-04B-IQ**EASY**

1115

4-ch NVR

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Support Ultra 265/H.265/H.264 video formats

Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1x HDD, up to 10TB

132,00 110,00

NVR501-04B-IQ**PRIME**

1150

4-ch NVR

Decoding Capability:

Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30

Smart On: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30

Support Ultra H.265/H.265/H.264 video formats

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

150,00 125,00

NVR301-08S3**EASY**

11048

8-ch NVR

Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 64/48 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

120,00 100,00

NVR301-08B-IQ**EASY**

1117

8-ch NVR

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Support Ultra 265/H.265/H.264 video formats

4/8/16 channel input

Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1x HDD, up to 10TB

150,00 125,00

NVR501-08B-IQ**PRIME**

1118

8-ch NVR

Decoding Capability: Smart Off: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30, 12 x

1080P@30, 16 x 720P@30

Support Ultra H.265/H.265/H.264 video formats

Supports mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T) and RTSP protocols

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability

When the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

168,00 140,00

NVR301-16S3**NOVO****EASY**

11116

16-ch NVR

Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p
 Ulazno/Izlazni saobraćaj: 64/48Mbps
 Video kompresija: Ultra 265, H.265, H.264 video kompresija,
 Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),
 Smart Funkcije: Face detection, Intrusion detection,
 Cross line detection, Audio detection
 ONVIF conformance: Profile S, Profile G, Profile T
 Pretraga snimka po smart funkcijama: Face search, Behavior search,
 Human Body search
 Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
 Hard disk prostor: 1 sata HDD do 6TB kapaciteta
 Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

138,00 115,00

NVR301-16B-IQ**NOVO****EASY**

11151

16-ch NVR

Decoding Capability - Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 10 x 1080P@30, 16 x 720P@30
 Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30, 16 x 720P@30
 Support Ultra 265/H.265/H.264 video formats
 Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support HDMI and VGA simultaneous output
 Up to 12 Megapixels resolution recording
 ANR technology to enhance the storage reliability when the network is disconnected
 Support cloud upgrade

210,00 175,00

NVR501-16B**PRIME**

11047

16-ch NVR

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 Ulazno/Izlazni saobraćaj: 80/64 Mbps
 Video kompresija: Ultra 265/H.265/H.264
 Video/audio izlazi: HDMI (4K) / HD, VGA
 Smart Funkcije: Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, UMD (Ultra Motion Detection)
 Statisticke analize: People counting
 Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0
 Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP
 Hard disk prostor: 1 sata HDD do 8TB kapaciteta
 Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,
 Radna temperatura: -10 °C ~ +55 °C,
 Dimenzije: 260mm × 222mm × 47mm, Težina 0,98Kg

216,00 180,00

NVR501-16B-IQ**NOVO****PRIME**

11119

16-ch NVR

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30
 Support Ultra H.265/H.265/H.264 video formats
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
 Support HDMI and VGA simultaneous output
 Up to 16 Megapixels resolution recording
 ANR technology to enhance the storage reliability
 When the network is disconnected
 Support cloud upgrade
 1 SATA Interface, up to 16 TB

228,00 190,00

NVR502-16B-IQ**NOVO****PRIME**

11180

16-ch NVR

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30
 Smart On: 2 x 12MP@30, 2 x 4K@30, 6 x 4MP@30, 8 x 3MP@30, 12 x 1080P@30, 16 x 720P@30
 Support Ultra H.265/H.265/H.264 video formats
 Supports mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
 Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
 Support HDMI and VGA simultaneous output
 Up to 16 Megapixels resolution recording
 ANR technology to enhance the storage reliability
 When the network is disconnected
 Support cloud upgrade
 2 SATA Interface, up to 16 TB per HDD

264,00 220,00

NVR304-32X

PRIME



32-ch NVR

32-KANALNI MREŽNI SNIMAČ

Rezolucija snimanja:

12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 384/384 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left

11154 behind, Object removed, Face search, Behavior search

600,00 500,00

Statisticke analize: People counting

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1x RS485, 1x

RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5

Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 442mm x426mmx 89mm, Težina 5,7Kg

NVR502-32E-IX-G

NOVO



2 HDDs 32-Ch Network Video Recorder

Support Ultra H.265/H.265/H.264 video formats

Support 32-channel input

Support 2-ch HDMI, 2-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA independent output

Support up to 16 Megapixels resolution recording

Support ANR technology to enhance the storage reliability when the network is disconnected

1140,00 950,00

Support SeekFree function: up to 16-ch with 3rd party IPC, up to 32-ch

With UNV SIP/UMD IPC

Support external USB keyboards

Support Video Metadata, Diverse Algorithms by NVR

Support cloud upgrade

DOME IP KAMERE 2MPX

IPC3612LB-SF28-A

NOVO

EASY



2MP



Ultra H.265



11144

2MP Fixed IR Turret Network Camera

High quality image with 1080P, 1/2.8" CMOS sensor

1080P (1920 x 1080)@30/25 fps; 720P (1280 x 720)@30/25 fps

Ultra 265, H.265, H.264

Smart IR, up to 30 m (98.4 ft) IR distance

66,00 55,00

Day/night functionality

2D/3D DNR (digital noise reduction)

IP67 protection

Supports PoE power supply

3-axis

IPC322LB-SF28-A

EASY



2MP



11174

2MP Vandal-resistant Network IR Fixed Dome Camera

High quality image with 2MP, 1/2.8" CMOS sensor

2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps

Ultra 265, H.265, H.264

Smart IR, up to 30m (98ft) IR distance

56,40 47,00

Day/night functionality

2D/3D DNR (Digital Noise Reduction)

IP67 protection

IK10 vandal resistant

Support PoE power supply

2-Axis

IPC322LB-AF28WK-G



I1008	2MP WIFI Fixed Dome Network Camera		
	High quality image with 2MP, 1/2.9" CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264, MJPEG		
	Built-in Mic	86,40	72,00
	Smart IR, up to 30m (98ft) IR distance		

IPC322LB-DSF28K-G



I1177	High quality Image with 2MP, 1/2.7" CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264, MJPEG		
	120dB true WDR technology enables clear image in strong light scene		
	Support 9:16 Corridor Mode	72,00	60,00
	Smart IR, up to 30m (98ft) IR distance		

IPC3622LE-ADF28K-WP




I1112	2MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera		
	High quality image with 2MP, 1/2.7" CMOS sensor and F1.0 large aperture lens		
	2MP (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps		
	Ultra 265, H.265, H.264, MJPEG		
	Support ColorHunter with Wise-ISP technology, deeply optimizing color, Detail, and smear effects in extremely low-light scenes	104,40	87,00
	120 dB true WDR technology enables clear image in strong light scene		

IPC3612LE-ADF28KC-WL



I1038	2MP HD ColorHunter IR Fixed Eyeball Network Camera		
	High quality image with 2MP, 1/2.8" CMOS sensor		
	2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;		
	Ultra 265, H.265, H.264, MJPEG		
	120dB true WDR technology enables clear image in strong light scene	110,40	92,00
	Support 9:16 Corridor Mode		

IPC3532LB-ADZK-G-BLACK



I1092	2MP HD IR VF (2.8 ~ 12mm) Dome Network Camera		
	High quality image with 2MP, 1/2.7" CMOS sensor		
	2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps		
	Ultra 265, H.265, H.264, MJPEG		
	120dB true WDR technology enables clear image in strong light scene	156,00	130,00
	Support 9:16 Corridor Mode		

BULLET IP KAMERE 2MPX

IPC2122LB-SF28-A

					
      					
		2MP Mini Fixed Bullet Network Camera High quality image with 2MP, 1/2.8"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264 Smart IR, up to 30m (98ft) IR distance Day/night functionality 2D/3D DNR (Digital Noise Reduction) IP67 protection Support PoE power supply 3-Axis		55,20 46,00	
		I1143			

IPC2122LB-SF40-A

					
      					
		2MP Mini Fixed Bullet Network Camera High quality image with 2MP, 1/2.8"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264 Smart IR, up to 30m (98ft) IR distance Day/night functionality 2D/3D DNR (Digital Noise Reduction) IP67 protection Support PoE power supply 3-Axis		55,20 46,00	
		I1173			

IPC2122LB-AF28WK-G

					
       					
		2MP HD WIFI Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card IP67 protection 3-Axis		78,00 65,00	
		I1009			

IPC2122LB-AF40WK-G BLACK

					
       					
		2MP HD WIFI Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card IP67 protection 3-Axis		78,00 65,00	
		I1093			

IPC2122LB-ADF40KM-G



	2MP HD WDR Fixed IR Bullet Network Camera High quality image with 2MP, 1/2.7"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card Support PoE power supply 3-Axis	72,00	60,00
I1175			

IPC2122LB-AF28K-WL



	2MP HD ColorHunter Mini Fixed Bullet Network Camera High quality image with 2MP, 1/2.9"CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra H.265, H.265, H.264 Built-in Mic Warm Light, up to 30m (98ft) warm light distance 2D/3D DNR (Digital Noise Reduction) Support 128GB Micro SD card IP67 protection Support PoE power supply 3-Axis	99,00	82,50
I1050			

IPC2312LE-ADF28KM-WP



	2MP ColorHunter with Wise-ISP Fixed Bullet Network Camera High quality image with 2MP, 1/2.7"CMOS sensor and F1.0 large aperture lens 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps; Ultra 265, H.265, H.264, MJPEG Colorhunter with Wise-ISP technology ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic White Light, up to 30m warm light distance Supports 512 GB Micro SD card IP67 protection Support PoE power supply 3-Axis	104,40	87,00
I1111			

IPC2122LE-ADF28KMC-WL



	2MP HD ColorHunter Mini IR Fixed Bullet Network Camera High quality image with 2MP, 1/2.8"CMOS sensor 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps; Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic & Speaker Smart IR, up to 30m (98ft) IR distance White Light, up to 30m (98ft) white light distance Supports 128 G Micro SD card IP67 protection Support PoE power supply 3-Axis	110,40	92,00
I1028			

BULLET IP KAMERE 3MPX

IPC2123LB-AF28KM-G



	3MP HD Fixed IR Bullet Network Camera High quality image with 3MP, 1/2.7"CMOS sensor 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; Ultra 265, H.265, H.264, MJPEG Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card IP67 protection Support PoE power supply 3-Axis	86,40	72,00
I1037			

DOME IP KAMERE 4MPX

IPC3614LB-SF28-A

NOVO



4 MP

H.265

Smart IR

IP 67

POE

MLC

Smart Search

4MP Fixed Dome Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart IR, up to 30m (98ft) IR distance
 Support PoE power supply
 3-Axis

11030

81,60

68,00

IPC3614LB-AF28K-A2

NOVO



4 MP

Built-in Mic

Edge Storage

IP 67

POE

MLC

Human body detection 2.0

Smart IR

4MP IR Eyeball Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Supports accurate human body detection 2.0
 Ultra 265, H.265, H.264
 Built-in mic
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 MicroSD, up to 512 GB
 DC 12 V, PoE (IEEE 802.3af) power supply
 IP67 protection
 3-axis

11178

86,40

72,00

IPC324LB-AF28K-A2

NOVO



4 MP

Built-in Mic

Edge Storage

IP 67

POE

IK 10

Human body detection 2.0

Smart IR

4MP Fixed IR Dome Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Supports accurate human body detection 2.0
 Ultra 265, H.265, H.264
 Built-in mic
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 MicroSD, up to 512 GB
 DC 12 V, PoE (IEEE 802.3af) power supply
 IP67 protection
 IK10 vandal resistant
 2-axis

11010

86,40

72,00

IPC324LB-ASF28K-A

EASY



4 MP

Smart IR

Built-in Mic

Edge Storage

POE

MLC

IP 67

IK 10

4MP Fixed IR Dome Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 Support Micro SD card
 IP67 protection
 IK10 vandal resistant
 DC12V or PoE(IEEE 802.3af) power supply
 2-Axis

11070

NEMA NA STANJU

IPC3624LE-ADF28K-WP

EASYSTAR



4 MP

Wise-ISP

Ultra Motion Detection

Built-in Mic

Edge Storage

IP 67

F1.0 Large Aperture

1/1.8" Large Sensor

4MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, And smear effects in extremely low-light scenes
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m (98ft) warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11086

128,40

107,00

IPC3514LE-ADF28K-WP   4 MP       	4MP ColorHunter Wise-ISP Fixed Dome Network Camera High quality image with 4MP, 1/1.8"CMOS sensor and F1.0 large aperture lens 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps Ultra 265, H.265, H.264, MJPEG Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic Supports 512 GB Micro SD card IP67 protection IK10 protection Support PoE power supply 3-Axis
IPC3614LE-ADF28K-H   4 MP       	4MP EasyStar Fixed IR Turret Network Camera High quality image with 4MP, 1/3" CMOS sensor 4MP (2688 × 1520)@25/20 fps; 4MP (2560 × 1440)@25/20 fps; 3MP (2304 × 1296)@30/25 fps; 2MP (1920 × 1080)@30/25 fps Ultra 265, H.265, H.264, MJPEG Easystar technology ensures high image quality in low illumination environment 120 dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 30 m (98 ft) IR distance Supports up to 512 GB Micro SD Card IP67 protection Support PoE power supply 3-Axis
IPC3614LE-ADF28KC-WL   4 MP      	4MP HD ColorHunter IR Fixed Eyeball Network Camera High quality image with 4MP, 1/3"CMOS sensor 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps; Ultra 265, H.265, H.264, MJPEG 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic & Speaker Smart IR, up to 30m (98ft) IR distance White Light, up to 30m (98ft) white light distance Supports 128 G Micro SD card IP67 protection Support PoE power supply 3-Axis
IPC3614SB-ADF28KMC-IO   4 MP      	4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera High quality image with 4MP, 1/2.7"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps; Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle Supports sound and light alarm linkage.When Smart intrusion prevention is triggered The camera links sound alarm and light linkage. Intelligent People Flow Counting and Crowd Density Monitoring 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic and Speaker Smart IR, up to 30m (98ft) IR distance Supports 256 G Micro SD card IP67 protection Support PoE power supply


NEMA NA STANJU

147,60123,00

150,00125,00

156,00130,00

IPC3614SB-ADF40KMC-IO



i1094

4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera
High quality image with 4MP, 1/2.7"CMOS sensor
4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Supports sound and light alarm linkage.When Smart intrusion prevention is triggered , the camera links sound alarm and light linkage.
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic and Speaker
Smart IR, up to 30m (98ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply

156,00 130,00

IPC354SB-ADNF28K-IO



i1087

4MP LightHunter Fixed IR Dome Network Camera
High quality image with 4MP, 1/2.7"CMOS sensor
4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30m (98 ft) IR distance
Supports 512 G Micro SD card
Cable-free
Support PoE power supply

180,00 150,00

IPC3534LB-ADZK-G



i1166

4MP HD IR VF (2.8 ~ 12mm) Dome Network Camera
High quality image with 4MP, 1/3"CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps;2MP (1920*1080)@30/25fps
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 40m (131ft) IR distance
Supports 256 G Micro SD card
IK10 vandal resistant
IP67 protection
Support PoE power supply
3-Axis

180,00 150,00

BULLET IP KAMERE 4MPX

IPC2124LB-SF28-A



i1011

4MP Fixed IR Mini Bullet Network Camera
High quality image with 4MP, 1/3.0"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
H.265, H.264
Smart IR, up to 30m (98ft) IR distance
Day/night functionality
2D/3D DNR (Digital Noise Reduction)
IP67 protection
DC12V or PoE(IEEE 802.3af) power supply
3-Axis

81,60 68,00

IPC2124LB-SF40-A

 		4MP Fixed IR Mini Bullet Network Camera High quality image with 4MP, 1/3.0"CMOS sensor 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps H.265, H.264 Smart IR, up to 30m (98ft) IR distance Day/night functionality 2D/3D DNR (Digital Noise Reduction) IP67 protection DC12V or PoE(IEEE 802.3af) power supply 3-Axis			
      		11081		84,00	70,00

IPC2124LB-AF28K-A2

  		4MP Fixed IR Bullet Network Camera High quality image with 4 MP, 1/3.0" CMOS sensor 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps Supports accurate human body detection 2.0 Ultra 265, H.265, H.264 Built-in mic Smart IR, up to 30 m (98.4 ft) IR distance Day/night functionality 2D/3D DNR (digital noise reduction) MicroSD, up to 512 GB DC 12 V, PoE (IEEE 802.3af) power supply IP67 protection 3-axis			
       		11155		86,40	72,00

IPC2124LB-ASF28K-A

 		4MP Fixed IR Mini Bullet Network Camera High quality image with 4MP, 1/3.0"CMOS sensor 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps Ultra H.265,H.265, H.264 Built-in Mic Smart IR, up to 30m (98ft) IR distance Day/night functionality 2D/3D DNR (Digital Noise Reduction) Supports Micro SD card IP67 protection DC12V or PoE(IEEE 802.3af) power supply 3-Axis			
       		11071		86,40	72,00

IPC2124LB-ADF28KM-H

 		4MP Mini Fixed Bullet Network Camera High quality image with 4MP, 1/2.9"CMOS sensor 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card Support PoE power supply 120dB WDR 3-Axis			
       		11068		114,00	95,00

IPC2124LB-ADF40KM-H

 		4MP Mini Fixed Bullet Network Camera High quality image with 4MP, 1/2.9"CMOS sensor 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Built-in Mic Ultra 265, H.265, H.264, MJPEG Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card Support PoE power supply 120dB WDR 3-Axis			
       		11075		116,40	97,00

IPC2314LE-ADF28KM-WP

EASYSSTAR



11085

4MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Colorhunter with Wise-ISP technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

128,40 107,00

IPC2314LE-ADF40KM-WP

EASYSSTAR



11184

4MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Colorhunter with Wise-ISP technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

128,40 107,00

IPC2124LE-ADF28KMC-WL

EASYSSTAR



11148

4MP ColorHunter Fixed Dual-light Bullet Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps;
3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
120 dB true WDR technology enables clear image in strong light scene
Supports 9:16 corridor mode
Built-in mic and speaker
Smart IR, up to 30 m (98.4 ft) IR distance
White light, up to 30 m (98.4 ft) white light distance
MicroSD, up to 512 GB
IP67 protection
Supports PoE power supply
3-axis

132,00 110,00

IPC2124LE-ADF28KM-G

EASYSSTAR



11027

4MP HD Mini IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Easystar technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

147,60 123,00

IPC2314LE-ADF28KM-WL

EASYSSTAR



11029

4MP HD ColorHunter Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Colorhunter technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m white light distance
Supports 128 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

159,60 133,00

IPC2124SB-ADF28KM-IO




4MP HD Intelligent LightHunter IR Fixed Bullet Network Camera High quality image with 4MP, 1/3"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle Intelligent People Flow Counting and Crowd Density Monitoring LightHunter technology ensures ultra-high image quality in low illumination environment 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in Mic Smart IR, up to 40m (131ft) IR distance Supports 512 G Micro SD card IP67 protection Support PoE power supply			162,00	135,00
11088				

IPC2314SB-ADF60KM-IO



4MP HD Intelligent 80m IR Fixed Bullet Network Camera High quality image with 4MP, 1/2.7"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps; Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle And non-motor vehicle Intelligent People Flow Counting and Crowd Density Monitoring 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in 2 Mic Smart IR, up to 80m (262 ft) IR distance Supports 256 G Micro SD card IP67 protection			192,00	160,00
11097				

IPC2314SB-ADF40KM-IO



4MP LightHunter Fixed IR Bullet Network Camera High quality image with 4MP, 1/2.7"CMOS sensor 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle Intelligent People Flow Counting and Crowd Density Monitoring 120dB true WDR technology enables clear image in strong light scene Support 9:16 Corridor Mode Built-in 2 Mic Smart IR, up to 80m (262 ft) IR distance Supports 512 G Micro SD card IP67 protection			192,00	160,00
11167				

IPC2124SB-ADF40KMC-IO



4MP Tri-Guard Fixed Dual-light Bullet Network Camera High quality image with 4 MP, 1/2.7" CMOS sensor 4 MP (2688 × 1520)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps Ultra 265, H.265, H.264, MJPEG Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage 120 dB true WDR technology enables clear image in strong light scene Supports 9:16 corridor mode Built-in mic and speaker Smart IR, up to 30 m (98.4 ft) IR distance MicroSD, up to 512 GB IP67 protection			168,00	140,00
11159				

4MP Recognition Of Vehicle License Plate Bullet IP Camera (2.8 ~ 12mm)

Features

Optics

Built-in lens supports motorized zoom to adapt to different scenes and allows for easy installation.

Automatic gain control, white balance, and WDR for various light conditions.

Compression

Supports triple streams.

Advanced H.265 encoding technology improves compression efficiency.

Custom OSD allows various vehicle information to be overlaid on the video image.

Functions

Built-in vehicle and license plate recognition algorithm can recognize

standard license plates of multiple countries.

Supports capturing vehicle head only.

Supports plate allowlist and blacklist configuration.

Supports vehicle access control when connected to a barrier.

Supports Micro SD cards of up to 256GB.

Automatic network replenishment (ANR) allows to automatically

store video to SD card in case of network disconnection.

Supports audio collection and intercom.

I1120

Network

Network auto-adaptability ensures smooth live video in relatively bad

network conditions such as packet loss.

Supports SNMP.

Supports UNP for NAT traversal between public and private networks.

Supports integration with the third party via SDK or HTTP.

Network Security

Supports authorized user access by password. Weak password detection and account lock-up when failed login attempts reach the Upper limit enhance password security.

Supports Web access via HTTPS.

RTSP authentication prevents unauthorized video stream requests.

IP address filtering prevents illegal access from untrusted IP addresses.

Gateway ARP protection prevents MAC address spoofing.

Structure

Supports DC 12V and PoE (802.3at) power supplies.


Cast aluminum body offers excellent heat dissipation.

3-axis mounting bracket for various installation scenarios.


A junction box on the mounting bracket is convenient for storing tail cables.

IP67 and IK10 protection.

840,00 700,00

**DOME IP KAMERE 5MPX****IPC3615LB-SF28-A**

EASY

**5MP Fixed IR Turret Network Camera**

High quality image with 5 MP, 1/3.0" CMOS sensor

5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;

3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps

Ultra 265, H.265, H.264, MJPEG

I1147

Smart IR, up to 30 m (98.4 ft) IR distance

Day/night functionality

2D/3D DNR (digital noise reduction)

IP67 protection

DC 12 V, PoE (IEEE 802.3af) power supply

3-axis

86,40 72,00

IPC3635LB-ADZK-G

EASY

**5MP HD IR VF Eyeball Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor

5MP (2880 × 1620)@ 25/20fps; 4MP (2560 × 1440)@ 25/20fps;

3MP (2304 × 1296)@ 30/25fps; 2MP (1920 × 1080)@30/25fps

Ultra 265, H.265, H.264, MJPEG

120dB true WDR technology enables clear image in strong light scene

I1139

Support 9:16 Corridor Mode

Built-in Mic

Smart IR, up to 40m (131ft) IR distance

Supports 256 G Micro SD card

IP67 protection

Support PoE power supply

3-Axis

192,00 160,00

IPC3615SS-ADF28K-I1





5MP

Edge Storage

Built-in Mic

LightHunter

WDR

Smart Intrusion Prevention

Corridor Mode

IP 67

I1105

5MP HD Intelligent LightHunter IR Fixed Turret Dome Network Camera
High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@ 30/25(default)fps; 4MP (2560*1440)@ 30/25fps;
3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
Auto Scene Match (ASM) (WDR only)
LightHunter technology ensures ultra-high image quality in low illumination environment
130dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 40m (131ft) IR distance
Supports 256 G Micro SD card
IP67 protection

192,00 160,00

IPC3615SE-ADF28KM-WL-I0





5MP

ColorHunter

Edge Storage

Built-in Mic

Smart Intrusion Prevention

WDR

IP 67

I1161

5MP HD Intelligent ColorHunter Fixed Eyeball Network Camera
High quality image with 5MP, 1/2.7"CMOS sensor
5MP (2880*1620)@30/25fps; 4MP (2560*1440)@30/25fps;3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
Ultra 265, H.265, H.264, MJPEG
Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce False alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
Colorhunter technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 corridor Mode
Support built-in Mic
Support 256 G Micro SD card
IP67 protection
Support PoE power supply

232,00 197,50

BULLET IP KAMERA 5MPX

IPC2125LB-SF28-A







5MP

POE

H.265

RLC

Smart IR

Smart Search

IP 67

I1145

5MP Fixed IR Bullet Network Camera
High quality image with 5 MP, 1/3.0" CMOS sensor
5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30 m (98.4 ft) IR distance
Day/night functionality
2D/3D DNR (digital noise reduction)
IP67 protection
DC 12 V, PoE (IEEE 802.3af) power supply
3-axis

86,40 72,00

IPC2125LB-SF40-A







5MP

POE

H.265

RLC

Smart IR

Smart Search

IP 67

I1146

5MP Fixed IR Bullet Network Camera
High quality image with 5 MP, 1/3.0" CMOS sensor
5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30 m (98.4 ft) IR distance
Day/night functionality
2D/3D DNR (digital noise reduction)
IP67 protection
DC 12 V, PoE (IEEE 802.3af) power supply
3-axis

86,40 72,00

IPC2125LE-ADF28KM-G

EASYSSTAR



11041

5MP HD Mini IR Fixed Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 IC domet: do 50m
 Easystar technology ensures high image quality in low
 illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

159,60 133,00

IPC2125SB-ADF40KMC-IO



PRIME



11095

5MP HD Intelligent Light and Audible Warning Fixed Bullet Network Camera


High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296)
 @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area
 detection
 Based on target classification, smart intrusion prevention significantly reduce
 false alarm caused by leaves, birds and lights etc., accurately focus on human and,
 motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage.When Smart intrusion prevention
 is triggered, The camera links sound alarm and light linkage.
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KM-IO



PRIME



11110


5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area,
 leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low
 Illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KM-IO BLACK

PRIME



11106

5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area,
 leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low
 Illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00

IPC2125SB-ADF28KMC-IO



PRIME

**5MP Tri-Guard Fixed Dual-light Bullet Network Camera**

High quality image with 5 MP, 1/2.7" CMOS sensor

5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps

Ultra 265, H.265, H.264, MJPEG

Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection

Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles

11156 Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage

168,00 140,00

120 dB true WDR technology enables clear image in strong light scene

Supports 9:16 corridor mode

Built-in mic and speaker

Smart IR, up to 30 m (98.4 ft) IR distance

MicroSD, up to 512 GB

IP67 protection

Supports PoE power supply

IPC2325LB-ADZK-H

EASY

**5MP HD IR VF (2.8 ~ 12mm) Bullet Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor

5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080) @30/25fps;

Built-in Mic

Ultra 265, H.265, H.264, MJPEG

11069 120dB true WDR technology enables clear image in strong light scene

192,00 160,00

Support 9:16 Corridor Mode

Smart IR, up to 50m (164ft) IR distance

Supports 256 G Micro SD card


IP67 protection

Support PoE power supply

3-Axis

IPC2315SB-ADF40KM-IO

PRIME

**5MP LightHunter Fixed IR Bullet Network Camera**

High quality image with 5MP, 1/2.7" CMOS sensor

5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080) @30/25fps

Ultra 265, H.265, H.264, MJPEG

Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection

Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor

11096 Vehicle and non-motor vehicle

198,00 165,00

Intelligent People Flow Counting and Crowd Density Monitoring

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode


Built-in 2 Mic

Smart IR, up to 80m (262 ft) IR distance

Supports 512 G Micro SD card

IP67 protection

IPC2225SE-DF40K-WL-IO

**5MP ColorHunter Fixed Warm Light Bullet Network Camera**

High quality image with 5 MP, 1/2.7" CMOS sensor

5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps

Ultra 265, H.265, H.264, MJPEG

Intelligent perimeter protection, including cross line, intrusion, enter area, leave area detection

Based on target classification, smart intrusion prevention significantly reduces false alarm caused by leaves, birds and lights, accurately focusing on human, motor vehicle and non-motor vehicle

11158 Intelligent people flow counting and crowd density monitoring

261,60 218,00

ColorHunter technology ensures 24-hour full-color images

120 dB true WDR technology enables clear image in strong light scene

Supports 9:16 corridor mode

Alarm I/O: 1/1, audio I/O: 1/1

MicroSD, up to 512 GB

IK10 vandal resistant and IP67 protection

Supports PoE power supply

DOME IP KAMERE 8MPX

IPC328SB-ADF28K-10

PRIME



4K

Built-in Mic

Edge Storage

Light Hunter

Deep Face Capture

Deep Perimeter

Ultra Motion Detection

IK 10

11043

8MP HD Intelligent IR Fixed Dome Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Alarm:1 in/1 out, Audio: 1 in/1 out
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 256 G Micro SD card
IK10 vandal resistant and IP67 protection

229,20191,00

IPC3618LE-ADF28K-G

NOVO

EASYSSTAR



4K

Intrusion detection

Cross Line detection

Anti-star

Built-in Mic

Edge Storage

WDR

IP 67

11162

4K HD IR Fixed Eyeball Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Easystar technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

216,00180,00

BULLET IP KAMERE 8MPX

IPC2318LE-ADF28KM-WP

NOVO

EASYSSTAR



4K

Built-in Mic

Edge Storage

Ultra Motion Detection

Wise-ISP

1/1.8" Large Sensor

F1.0 Large Aperture

IP 67

11113

8MP ColorHunter Wise-ISP Warm Light Bullet Network Camera

High quality image with 8MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Colorhunter with Wise-ISP technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

210,00175,00

IPC2128LE-ADF28KM-G

EASYSSTAR



4K

Built-in Mic

Edge Storage

Intrusion detection

WDR

IP 67

Cross Line detection

Anti-star

11012

4K 8MP Mini Fixed Bullet Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Easystar technology ensures high image quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

211,20176,00

IPC2128SB-ADF28KMC-10





4K

Edge Storage

Active Deterrence

120dB WDR

Deep Face Capture

Safe Perimeter

Ultra Motion Detection

IP 67

11090

8MP Tri-Guard Fixed Dual-light Bullet Network Camera
High quality image with 8MP, 1/2.7"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
Built-in Speaker
Smart IR, up to 30m (98ft) IR distance
Supports 512 G Micro SD card
IP67 protection

246,00205,00

IPC2328SB-DZK-10







4K

LightHunter

50 IR distance

IK 10

Smart Intrusion Prevention

WDR

IP 67

11138

8MP HD Intelligent LighterHunter IR VF (2.8 ~ 12mm) Bullet Network Camera
High quality image with 8MP, 1/2.8"CMOS sensor
8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
Intelligent People Flow Counting and Crowd Density Monitoring
LightHunter technology ensures ultra-high image
Quality in low illumination environment
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Alarm:1 in/1 out, Audio: 1 in/1 out
Smart IR, up to 50m (164ft) IR distance
Supports 256 G Micro SD card
IK10 vandal resistant
IP67 protection
Support PoE power supply

264,00220,00

UNIARCH

Uho-S2



2MP

Edge Storage

Build-in Mic

IR

U-code

Human Body Detection

H.265

Auto Tracking

11091

High quality image with 2MP, 1/3"CMOS sensor
2MP (1920*1080)@25/20fps; 720P (1280*720) @25/20fps
Ultra 265, H.265, H.264
Built-in Mic & Speaker, support two-way audio, offer better interaction
IR night vision, up to 10m (33ft) IR distance
Support 256 G Micro SD card
Wi-Fi connection and easy installation

36,0030,00

Uho-S3E-M3



3MP

Edge Storage

Build-in Mic

IR

U-code

Human Body Detection

H.265

Auto Tracking

11051

High quality image with 3MP, 1/3"CMOS sensor
3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps;720P (1280*720) @30/25/fps
Ultra 265, H.265, H.264
Built-in Mic & Speaker, support two-way audio,offer better interaction
IR night vision, up to 10m (33ft) IR distance
Support 256 G Micro SD card
Wi-Fi connection and easy installation

42,0035,00

IPC-B122-APF28

NOVO



2MP

Built-In Mic

Smart IR

Ultra H.265

IR LED

PoE

IP67

	High quality image with 1080P, 1/2.9" CMOS sensor 1080P (1920 × 1080)@25/20 fps; 720P (1280 × 720)@25/20 fps Ultra 265, H.265, H.264 2D/3D DNR (digital noise reduction) ROI (region of interest) ensures image quality in areas of interest With low bandwidth Smart IR, up to 30 m (98.4 ft.) IR distance Built-in mic Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F) DC 12 V, PoE (IEEE 802.3af) power supply		
I1140		43,20	36,00

IPC-T122-APF28

NOVO



2MP

Built-In Mic

Smart IR

PoE

IP67

IR LED

Onvif

	High quality image with 1080P, 1/2.8" CMOS sensor 1080P (1920 × 1080)@25 fps; 720P (1280 × 720)@25 fps Ultra 265, H.265, H.264 2D/3D DNR (digital noise reduction) ROI (region of interest) ensures image quality in areas of interest With low bandwidth Smart IR, up to 30 m (98.4 ft.) IR distance Built-in mic Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F) DC 12 V, PoE (IEEE 802.3af) power supply		
I1141		43,20	36,00

Uho-B1R-M2F3

NOVO



2MP

Built-In Mic

Edge Storage

Smart IR

Human Body Detection

Wifi

Ultra H.265

IP67

	High quality image with 2MP, 1/2.9" CMOS sensor 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps Ultra 265, H.265, H.264, MJPEG Built-in Mic Smart IR, up to 30m (98ft) IR distance Supports 128 G Micro SD card IP67 protection 3-Axis		
I1127		51,60	43,00

IPC-B125-APF28

NOVO



5 MP

Built-In Mic

IR LED

Onvif

PoE

IP67

Smart IR

Ultra H.265

	High quality image with 5 MP, 1/3.0" CMOS sensor 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps; 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30 fps; 720P (1280 × 720)@30 fps; D1 (720 × 576)@30 fps Ultra 265, H.265, H.264 2D/3D DNR (digital noise reduction) ROI (region of interest) ensures image quality in areas of interest With low bandwidth Smart IR, up to 30 m (98.4 ft.) IR distance Built-in mic Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F) DC 12 V, PoE (IEEE 802.3af) power supply		
I1142		60,00	50,00

Uho-P1A-M3F4D



High quality image with 3MP, 1/2.8"CMOS sensor
2304*1296@20fps in the main stream
Ultra 265, H.265, H.264
Support digital WDR (Wide Dynamic Range)
Built-in Mic & Speaker, support two-way audio, offer better interaction
Support sound and light warning, makes warning and alarming more noticeable

I1052 Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes
Self-contained bracket, support two kinds of mounting
Supports 256 GB Micro SD card
Wi-Fi connection and easy installation
IP66 ingress protection
The front face is made of grapheme, which has better heat dissipation and more Environmental protection

68,40 57,00

Uho-P2S-M33F34



Fixed camera and PTZ camera integration, dual channels with one IP, Look at overall situation and consider details at the same time
Ultra 265, H.265, H.264
Support digital WDR (Wide Dynamic Range)
Built in Mic Speaker, support two way audio, offer better interaction
Support sound and light warning, makes warning and alarming more noticeable

I1128 Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes
IR warm light illumination to deal with different scenes and achieve full color illumination
Supports 512 GB Micro SD card
Wi Fi connection and easy installation
IP66 ingress protection

NEMA NA STANJU

PTZ IP KAMERE

IPC6312LR-AX4-VG



2MP LightHunter IR Network PTZ Camera
High quality image with 2MP, 1/2.7"CMOS sensor
Ultra 265, H.265, H.264, MJPEG
Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios

I1073 LightHunter technology ensures ultra-high image quality in Low illumination environment
Up to 120 dB Optical WDR (Wide Dynamic Range)
Built-in Mic & Speaker
Smart IR, Up to 50 m (164 ft) IR distance
Micro SD, up to 256GB
IP66 protection
DC12V or PoE (IEEE 802.3af) power supply

255,00 212,50

IPC675LFW-AX4DUPKC-VG



5MP LightHunter Active Deterrence Mini PTZ Camera
High quality image with 5MP, 1/2.7"CMOS sensor
Ultra 265, H.265, H.264, MJPEG
LightHunter technology ensures ultra-high image quality in low illumination environment
Up to 120 dB Optical WDR (Wide Dynamic Range)

I1109 Built-in Mic & Speaker
Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance
Micro SD, up to 256GB
IP66 protection
DC12V or PoE (IEEE 802.3af) power supply

270,00 225,00

IPC6412LR-X5UPW-VG



2MP 5X LightHunter Wi-Fi IR Network Mini PTZ Camera

High quality image with 1080P, 1/2.7" CMOS sensor
1920 × 1080@30 fps in the main stream
Ultra 265, H.265, H.264, MJPEG
5X optical zoom allows for closer viewing of subjects
Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
automatic selection of best snapshots
LightHunter technology ensures ultra-high image quality in low illumination environment
Up to 120 dB optical WDR (wide dynamic range)
Wi-Fi connection and easy installation
Built-in mic and speaker, supports two-way audio
Alarm I/O: 1/1
Smart IR, up to 30 m (98.4 ft) IR distance

I1157

228,00 190,00

IPC6412LR-X16-VG



2MP 16x LightHunter Network PTZ Dome Camera

High quality image with 2MP,1/2.8" CMOS sensor
1920*1080@30fps in the main stream
Ultra 265, H.265, H.264, MJPEG
16X optical zoom allows for closer viewing of subjects
LightHunter technology ensures ultra-high image quality
In low illumination environment
Smart IR, up to 100m (328ft) IR distance
Micro SD, up to 256GB
DC 12V±25% or PoE+ (IEEE 802.3at)
IP66 ingress protection

I1074

396,00 330,00

IPC6424SR-X25--B



4MP 25x LightHunter IR Network PTZ Camera

High quality image with 4 MP, 1/2.8" CMOS sensor
2688 × 1520@30 fps in the main stream
Ultra 265, H.265, H.264, MJPEG
25X optical zoom
Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
automatic selection of best snapshots, supports face detection masked area
People counting, supports people flow counting and crowd density monitoring, suitable for different statistical scenarios
LightHunter technology ensures ultra-high image quality in low illumination environment
Smart IR, up to 100 m (328 ft) IR distance
DC 12 V±25%, PoE+ (IEEE 802.3at)
Alarm I/O: 2/1, audio I/O: 1/1
IP67 ingress protection
IK10 vandal resistant

I1152

636,00 530,00

IPC6634S-X33-VF



4MP 33X LightHunter IR Network PTZ Camera

High quality image with 4 MP, 1/2.8" CMOS sensor
2688 × 1520@30 fps in the main stream
Ultra 265, H.265, H.264, MJPEG
33X optical zoom
Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
automatic selection of best snapshots, supports face detection masked area
People counting, supports people flow counting and crowd density monitoring, Suitable for different statistical scenarios
LightHunter technology ensures ultra-high image quality in low illumination environment
AC 24 V±25%, DC 24 V±25%, PoE+ (IEEE802.3 at)
Alarm I/O: 7/2, audio I/O: 1/1
IP67 ingress protection
IK10 vandal resistant

I1153

1320,00 1100,00

VIDEO INTERFONI

OEU-201B-HMK-W			
	I1201	Outdoor Station Front panel: Plastic cement Supports batch configuration Supports intercom calls to associated indoor units or APPs Support monitoring function, security alarm, tamper alarm Support Wi-Fi Built-in IC card reader Card Capacity 2000 IP65(Apply silica gel to gaps between the device and the wall)	216,00 180,00
			

OEU-202S-HMK2			
	I1202	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)	252,00 210,00
			

OEU-202S-HMK4			
	I1204	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)	276,00 230,00
			

OEU-301S-HMKA			
	I1301	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration WDR: Digital Built-in IC card reader Card Capacity 10000 Alarm Output: 2 IP65(Apply silica gel to gaps between the device and the wall)	420,00 350,00
			

EP-CS201			
	I1203	Wall Mount Sunshield Compatible with OEU-201B-HMK-W, OEU-201B-HMK-W-NB, OEU-201S-HMK-W, And OEU-201S-HMK-W-NB villa door stations	18,00 15,00
			

OEI-372S-H-W			
	I1372	Indoor Station Rugged ABS casing and glass panel. 1024*600 HD touch screen. Batch configuration transfer. Remote opening of linked door stations, one-key opening. Network camera monitoring, security alarm	192,00 160,00
			



OEI-201S-HMK-W
Metal casing.
Supports call and intercom with the connected indoor station and app.
Supports security protection alarm and tamper alarm triggered by door magnet, infrared, etc.
Supports Wi-Fi.
Built-in IC card reader.

OEI-372S-H-W
ABS casing and glass panel, solid and durable.
Supports Wi-Fi.
Supports touchscreen operation.
1024 x 600 HD screen.
Supports remote door opening by sending signal to the door station.
Allows to view live video of connected door stations and network cameras.

I1205

360,00 300,00

NSW2020-6T-POE-IN
Allows to switch operating modes, including Default, VLAN, and Extend.
Supports VLAN isolation. All PoE ports are isolated from each other and only able to communicate with uplink ports.
Supports network extension. With a high-quality network cable and IPC, the network transmission distance can reach up to 250 meters by lowering the network port rate to 10Mbps.
Supports port priority. Packets from high-priority ports will be forwarded first.
Supports flow control. When there is data congestion in the uplink ports, the switch will actively send flow control frames to PoE ports.
Plug-and-play, simple and convenient.
All metal casing, secure and reliable.



HARD DISKOVI

WD GREEN 320 GB



Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 500 GB



Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 1 TB



Western Digital, 1 TB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

HDD 1TB WD11PURZ-85C5HY0



I1100 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

144,00 120,00

HDD 2TB WD23PURZ-85C5HY0



I1200 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

174,00 145,00

HDD 4TB WD44PURZ-85CPDY0



I1400 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB

216,00 180,00

HDD 6TB WD64PURZ-74BWUY0



I1600 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB

270,60 225,50

HDD 8TB WD64PURZ-85BWUJ0



6250	Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB	469,92	391,60
------	---	--------	--------

TF-64G-T-L



I1021	Uniview memorijska kartica Kapacitet: 64GB Maksimalna brzina čitanja: 90MB/s Maksimalna brzina pisanja: 65MB/s Dimenzije: 11mm x 15mm x 1mm Težina: 0,33g	27,60	23,00
-------	--	-------	-------

TF-128G-T-L



I1022	Uniview memorijska kartica Kapacitet: 128GB Maksimalna brzina čitanja: 100MB/s Maksimalna brzina pisanja: 80MB/s Dimenzije: 11mm x 15mm x 1mm Težina: 0,33g	45,60	38,00
-------	--	-------	-------

TF-256G-T-L



I1123	Uniview memorijska kartica Kapacitet: 256GB Maksimalna brzina čitanja: 90MB/s Maksimalna brzina pisanja: 65MB/s Dimenzije: 11mm x 15mm x 1mm Težina: 0,33g	108,00	90,00
-------	---	--------	-------

Uniview SVIČEVI

NSW1010-5T-IN



I1130	5-Port 100 Megabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.	8,40	7,00
-------	---	------	------

NSW1010-8T-IN



I1131	8-Port 100 Megabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.	12,00	10,00
-------	---	-------	-------

NSW1010-5GT-IN



I1132	5-Port Gigabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode	14,40	12,00
-------	--	-------	-------

NSW1010-8GT-IN



I1133	8-Port Gigabit Plastic Shell Switch Supports IEEE802.3 and IEEE802.3u standards. Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port. Supports auto MDI/MDIX. Supports IEEE802.3 flow control for full-duplex mode and backpressure For half-duplex mode.	24,00	20,00
-------	---	-------	-------

Uniview POE SVIČEVI

NSW2020-6T-POE-IN



I1023

6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava:
IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Modovi rada: Default(Normal mode):
Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode):
Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona
PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm

54,00

45,00

NSW2010-5GT-POE-IN



I1059

4 Port GigabitPoE Switch
1 Port Gigabit Uplink
PoE Power up to 30W Each Port
Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD)
Auto Detect Power Device
Power Port Supply prioritization, guarantees the continuous power supply of key nodes
IEEE802.3 X full duplex flow control and Backpressure half duplex flow control
Line Speed Forwarding, intelligent identification
Up to 250m transmission distance on surveillance mode

78,00

65,00

NSW2020-10T-POE-IN



I1024

10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava: IEEE802.3,IEEE802.3u,
IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode):
Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode):
Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode):
8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona
PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm

90,00

75,00

NSW2010-10GT-POE-IN



I1060

8 Port Gigabit PoE Switch
2 Port Gigabit Uplink
PoE Power up to 30W Each Port
Supports IEEE802.3 at Standard, compatible with IEEE802.3af by
electrical equipment (PD)
Auto Detect Power Device
Power Port Supply prioritization, guarantees the continuous power
Supply of key nodes
IEEE802.3 X full duplex flow control and Backpressure half duplex flow control
Line Speed Forwarding, intelligent identification
Up to 250m transmission distance on surveillance mode

NEMA NA STANJU

NSW2100-9GT16P-LPOE-IN



I1179

8 Port Gigabits PoE Switch
Ports Type:
8x 10/100/1000Mbps PoE port (RJ45)
1 x 10/100/1000Mbps port (RJ45)
1 x Gigabit SFP
Supports Web login, and device configuration and management on the Web interface.
Supports visiting the cloud by scanning the QR code.
Allows to view the device status in real time on the app,
and remotely restart the PoE power supply.
Supports PoE power supply ; allows to enable or disable
PoE power supply for the powered device; allows up to
250m power supply using a standard network cable.
Supports the extend mode for up to 250m
communication range and 10Mbps auto-negotiation rate.
Supports port priority. The priority port will be powered first when the
PoE power supply is full.
All metal casing, secure and reliable.

96,00

80,00

NSW3000-8T2GT-POE-IN



I1134

Cloud Managed Ethernet Switch(PoE)
8 x 10/100Mbps POE port (RJ45) ,2 x Gigabit port (RJ45)
Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software.
Supports Web login, and device configuration and management on the Web interface; supports visiting the cloud by scanning the QR code.
Allows to view the device status and network topology in real time on the app, and remotely restart the PoE power supply.
Allows up to 250m power supply using a standard network cable.
Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.
Allows to report port abnormal alarms to the software for realtime monitoring.
Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full.
All metal casing, secure and reliable.
Maximum total power: 120W
Maximum PoE power for single port: 30W

96,00 80,00

NSW2020-16T2GC-POE-IN



I1057

16x100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta
Podrška: IEEE802.3,IEEE802.3u,IEEE802.3az, IEEE802.3x,IEEE802.3af,IEEE802.3at
Modovi rada: Default(Normal mode):
Svi portovi komuniciraju normalno međusobno
EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s.
VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima.
6kV zaštita od prenapona PoE Budžet: 370W
Maksimalna snaga: 250W
Maksimalna PoE snaga porta: 30W
Dimenzije: 440mm x 207mm x 45mm
Moguća rek montaža 19" , dolazi uz switch

216,00 180,00

NSW3000-16T1GT1GC-LPOE-IN



I1135

Cloud Management Switch
16 x 10/100Mbps POE port (RJ45) + 1 x Gigabit port (RJ45)+ 1 x Gigabit Combo
Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software.
Supports Web login, and device configuration and management on the Web interface
in real time on the app, and remotely restart the PoE power supply.
Supports PoE power supply and allows to view the power; allows to enable or disable PoE power supply for the powered device;
Allows up to 250m power supply using a standard network cable.
Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.
Allows to report port abnormal alarms to the software for realtime monitoring.
Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full.
All metal casing, secure and reliable.
Maximum total power: 150W
Maximum PoE power for single port: 30W

NEMA NA STANJU

NSW2020-24T1GT1GC-POE-IN



I1163

Unmanaged Ethernet Switch(PoE)
24x100Mbps PoE ports (RJ45) + 1x1000Mbps Gigaethernet ports +1x1000Mbps Combo ports
Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
Support port traffic control
Support for secure mode, all downlink ports can communicate only with uplink ports
Up to 250m transmission distance on surveillance mode
Support buffer optimization
All metal housing, safe and reliable
Max capacity:370W
Max capacity for single port: 30W

232,20 193,50

NSW2010-24T2GC-PoE-IN



	Ethernet Switch(PoE) 24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode) Support port traffic control Support for secure mode, all downlink ports can communicate Only with uplink ports Up to 250m transmission distance on surveillance mode Support buffer optimization All metal housing, safe and reliable Max power: 390W		
I1136		288,00	240,00

MONITORI

MW3224-V



	UNV 24" LED Monitor Resolution 1920 × 1080 Color Support: 16.7 M Refresh Rate: 60 Hz Operation Hour: 24/7		
I1164		120,00	100,00

DODATNA OPREMA

GCB01-B7



	UNV-Link Pro Connect Box Network: 4 x RJ45 10M/100M Base-TX EthernetNetwork Port 1 Support POE (IEEE802.3af) OutputNetwork Port 4 Support PSE Voltage Test Wi-Fi 2.4G Wi-Fi Battery: 7500mAH Power Input: 1 x DC 5V/2A max, type-c Power Output: 1 x DC 12V/1A output; 1 x DC 5V/1A output, type-A		
I1101		78,00	65,00

PoE Extender



	Model: LN-POEPL03S PoE In: 44-57V/30W PoE Out (1-3) : 44-57V/25W Support: 10/100 Mbps IEEE802.3af/at		
9995			NEMA NA STANJU


3 Ports POE Injector



	PoE extender, repeater, switch 1 na 2 Usklađenost sa IEEE 802. af/at Power over Ethernet(10/100M podržano) Proširite domet Porta za dodatnih 100 metara		
2255		25,00	20,83


KABLOVI

UNV Cat6 (UTP), CCA




	CAB-LC3100B-CCA-IN Conductor material: CCA(Copper content: 27%) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC		
i1044		0,30	0,250

UNV Cat5e (UTP), BC



i1045	CAB-LC2100A-E2-ECA-IN		
	Conductor material: OFC (Oxygen free copper)		
	Insulation material:HDPE	0,54	0,45
	Packing length: 305±1 m		
	Sheath material: PVC (complies RoHS/REACH)		

UNV Cat6 (UTP), BC



i1046	CAB-LC3100A-EC-ECA-IN		
	Conductor material: OFC (Oxygen free copper)		
	Insulation material: HDPE	0,78	0,65
	Packing length: 305±1 m		
	Sheath material: PVC (complies RoHS/REACH)		

CAB-LC3110B-E-IN



i1186	Cat6 305m Outdoor UTP Network Cable (OFC 0.5mm Black)		
	Packing length: 305±1m		
	Material: Solid-Bare Copper		
	Insulation material: HDPE	0,84	0,70
	Sheath material(IN Jacket): PVC(complies RoHS/REACH)		
	Sheath material (OUT Jacket): LDPE		
	Color: Black		

KUĆIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633	Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00
------	--	------	------

DOZNA ZA KAMERE G153



8644	Razvodna kutija za spoljašnu montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,20	2,67
------	--	------	------

DOZNA ZA KAMERE BA-02



8645	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,00	2,50
------	--	------	------

TR-JB05-B-IN



i1062	Nosač za Dome kamere serije IPC21XX		
	Dimenzije: Φ104.4mm*54.5mm	19,20	16,00
	Težina: 0.36kg		
	Materijal: Aluminijum		

TR-JB05-A-IN



I1061

Nosač za kamere
Dimenzije: Φ93 × 93 × 39mm
Težina: 0.2kg
Materijal: Aluminijum

15,60

13,00

TR-JB03-G-IN



I1064

Nosač za Dome kamere serije IPC32x i IPC31x
Dimenzije: φ106.6mm*36mm
Težina: 0.2kg
Materijal: Aluminijum

13,20

11,00

TR-JB03-I-IN



I1063

Nosač za Dome kamere serije IPC36XXL i IPT1XX
Dimenzije: Ø117.8 × 36mm
Težina: 0.2kg
Materijal: Aluminijum

15,60

13,00

TR-JB03-H-IN



I1171

Nosač za Dome kamere serije IPC363X, IPC36XXS/E i 4MP fisheye
Dimenzije: Φ126mm*36mm (4.96" x1.42")
Težina: 0.24kg
Materijal: Aluminijum legura

14,40

12,00

TR-JB04-C-IN



I1172

Nosač za Dome kamere serije 323
Dimenzije: Φ144.8 mm × 42.5 mm (5.7" × 1.7")
Težina: 0.3kg
Materijal: Aluminijum legura

15,60

13,00

TR-JB07-D-IN



I1170

Bullet Junction Box(Support wiring from behind)

30,00

25,00

TR-JB07/WM03-G-IN



I1165

Wall Mounting Assembling Bracket For 32 Fix-dome
&Mini Fix-dome&Plastic Turret Camera

36,00

30,00

TR-WM07P-B



I1181

Dome Wall Mounting Plastic Bracket
Application: IPC32X Series, IPC361XX Series (Plastic)
Bracket Weight: 0,10kg

7,20

6,00

		Pole Mounting Bracket for Bullet Junction Box Only Application: Outdoor, pole or rail installation for Bullet camera of IPC23XX OEM IPC23XX/22X、IPC74X and IPC252/26X series Bracket Dimensions: 136.0 mm × 127.0 mm × 63.6 mm (5.4" × 5.0" × 2.5") Bracket Weight: 0.34kg Bracket Material: Aluminum alloy				
		11169		14,40	12,00	

KONEKTORI

BNC NA LEMLJENJE
SA ŠRAFOM

	3299	BNC konektor muški sa šrafom. Pakovanje 100 kom.	0,54	0,45
---	------	---	------	------

BNC NA LEMLJENJE

	2560	BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,54	0,45
---	------	--	------	------

BNC KONEKTOR

	30020	BNC konektor muški na šraf.	0,50	0,42
---	-------	-----------------------------	------	------

BNC NA KRIMP RG59

	2534	BNC konektor za RG59 kabl na krimp. Pakovanje 100 kom.	0,60	0,50
---	------	---	------	------

BNC MUŠKI- F ŽENSKI

	1795	BNC konektor muški F ženski. Pakovanje 100 kom.	0,70	0,58
---	------	--	------	------

BNC NASTAVAK

	4447	BNC konektor. Nastavak ženski-ženski. Pakovanje 100 kom.	0,54	0,45
---	------	---	------	------

F KONEKTOR na krimp
RG6

	2559	F konektor za RG6 kabl. Pakovanje 100 kom.	0,14	0,12
---	------	---	------	------

F KONEKTOR na krimp RG59

	1796	F konektor za RG59 kabl. Pakovanje 100 kom.	0,14	0,12
---	------	--	------	------

RF METALNI G MUŠKI

	4448	RF metalni G muški (UGAONI) konektor Pakovanje 100 kom.	0,35	0,29
---	------	--	------	------

RCA MUŠKI-F ŽENSKI

	4446	RCA muški - F ženski konektor Pakovanje 100 kom.	0,53	0,44
---	------	---	------	------

F NASTAVAK					
	3300	F nastavak Ženski - Ženski Pakovanje 100 kom		0,22	0,18
F KONEKTOR KOMPRESIONI RG6 XL					
	1625	Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.		0,44	0,37
F KONEKTOR KOMPRESIONI RG11 XL					
	1627	Profesionalni PPC F konektor za RG11 kabl.		2,96	2,47
F KONEKTOR KOMPRESIONI RG59 XL					
	1624	Profesionalni PPC F konektor za RG59 kabl. Pakovanje 50 kom.		0,47	0,39
DC KABL-MUŠKI					
	1387	DC utikač-muški		0,47	0,39
DC KABL-ŽENSKI					
	1391	DC utikač-ženski		0,47	0,39
DC KONEKTOR MUŠKI					
	3425	DC konektor Muški		0,37	0,31
DC KONEKTOR ŽENSKI					
	4197	DC konektor ženski.		0,38	0,32
DC RAZDELNIK 1-4					
	1388	1 DC utičnica - 4 DC utikača		1,99	1,66
DC RAZDELNIK 1-8					
	1389	1 DC utičnica - 8 DC utikača		3,97	3,31
CAT7 RJ45					
		Mrežni konektor RJ45 kategorija 7		0,50	0,42
CAT6 UNV RJ45 GC-RJ6-IN					
	1182	Cat6 Unshielded Crystal Head 3μ inches gold-plated for excellent contact performance Stable data transmission with up to 750 plugs and unplugs Highly transparent PC material support RoHS standards, Wear-resistant and durable 8 pins × 8 conductors, support 1000Bas-T Ethernet		0,12	0,10

CAT5 UNV GC-RJ5e-IN					
			Cat5e Unshielded Crystal Head 3μ inches gold-plated for excellent contact performance Stable data transmission with up to 750 plugs and unplugs Highly transparent PC material support RoHS standards, wear-resistant and durable 8 pins × 8 conductors, support 1000Base-T Ethernet	0,10	0,08
CAT5 RJ45					
		0067	Mrežni konektor RJ45	0,05	0,04
Telefonski konektor RJ11					
		0066	Telefonski konektor RJ11	0,02	0,02
DODATNA OPREMA					
ŠTAMPAČ P-TOUCH E100					
		4663	Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu	106,56	88,80
MIKROFON LY-501C					
		2584	Audio modul sa izvedenim konektorima. Napajanje 12 V DC	3,97	3,31
MIKROFON LY-502B					
		2583	Audio modul plastični sa trimerom. Napajanje 12 V DC	6,00	5,00
MIKROFON LY-506					
		1937	Audio modul metalni sa trimerom. Napajanje 12 V DC	10,00	8,33
DS-2FP2020					
		5222	Viisoko osetljivi omnidirekcionni mikrofoni. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).	36,00	30,00
DH-PFM800-4K (par)					
		3632	One (1) Channel Balun Real-time Transmission over UTP CAT5E/6 Cable Compatible with HDCVI, TVI, AHD, and CVBS Video Formats Transmission Distance at 4K: 200 m (656 ft) External Power Supply not Required	7,80	6,50
OG razvodna kutija 100x100					
		00091	Razvodna kutija 100x100	1,80	1,50

OG razvodna kutija 80x80					
	00092	Razvodna kutija 80x80		1,10	0,92
OG razvodna kutija 160x100x74					
	00093	Razvodna kutija 160x100x74		3,00	2,50
OG razvodna kutija 160x100x48					
	00094	Razvodna kutija 160x100x48		2,64	2,20
ALAT ZA KRIMP RG6, RG11,RG59					
	3302	Alat za krimpovanje RG6, RG11,RG59 konektora		48,00	40,00
STRIPER ZA KABLOVE RG59,RG6					
	3301	Alat za stripovanje RG59,RG6 kablova		20,40	17,00
ALAT KOMPRESIONI ZA RG59, RG6					
	1629	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59,RG6 XL oznake.		37,92	31,60
ALAT KOMPRESIONI, ZA RG6,RG11,RG59					
	3796	Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6,RG11,RG59 XL oznake.		54,34	45,28
KLEŠTA ZA KRIMPOVANJE KOMPLET					
	5790	Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečićom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)		28,68	23,90
NAPAJANJA					
XED-1212S					
	1633	Ulaz: 90V-264V Izlaz: 12V , 1A Snaga: 12W Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm Dužina izlaznog kablo: 110cm, 10.5x5,5x2mm konektor		6,00	5,00
XED-2012S					
	1382	Ulaz: 90V-264V Izlaz: 12V , 2A Snaga: 24W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kablo: 110cm, 10.5x5,5x2mm konektor		8,04	6,70
XED-3013S					
	1383	Ulaz: 90V-264V Izlaz: 12V , 3A Snaga: 36W Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm Dužina izlaznog kablo: 110cm, 10.5x5,5x2mm konektor		12,60	10,50
XED-5013S					
	1384	Ulaz: 100V-240V Izlaz: 12V , 5A Snaga: 60W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kablo: 110cm, 10.5x5,5x2mm konektor		16,20	13,50

XED-6013B			3509	Ulaz: 100V-240V Izlaz: 12V , 6A Snaga: 72W Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor	20,40	17,00
9-KANALNO NAPAJANJE XED-10A12VX-9L			5435	Snaga: 120W Ulaz: 100~240V 50~60Hz Izlaz: 12V 10A 9 kanala Dimenzije: 237*213*70mm Neto težina: 1800g Napomena: Sadrži AC kabl	82,80	69,00
18-KANALNO NAPAJANJE XED-15A12VX-18L			5114	Snaga: 180W Ulaz: 100~240V 50~60Hz Izlaz: 12V 15A 18 kanala Dimenzije: 240*218*70mm Neto težina: 2300g Napomena: Sadrži AC kabl	94,80	79,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs