

CENOVNIK UNIVIEW VIDEO NADZORA - 04.06.2026.



NAZIV	ŠIFRA	OPIS	CENA	
-------	-------	------	------	--

DVR UREDJAJI

sa PDV bez PDV

4 KANALNI

XVR301-04G3



4-CH Hybrid DVR

Podrzan video ulaz: 5MP @ 20fps (Prvi kanal 20fps, ostali 12fps) 5MP @ 12fps, 4MP @ 30fps (Prvi kanal)

4MP @ 15fps, 1080P @ 30fps, 720P @ 60fps

Podrzan video ulaz IP kamere: do 4MP (2 IP kamere ili svih 6)

Rezolucija snimanja encoding: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio, RCA

Video/audio izlazi: HDMI/VGA (FULL HD), 1ch audio

Ulazno/Izlazni saobraćaj: 16/48 Mbps

Smart funkcije: Detekcija pokreta, video loss detection

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 8W bez HDD, Podržava audio over coaxial cable

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x226mmx 47mm (10.2" x 8.9"x1.8"), 1.1kg

11031

69,60 58,00



XVR301-04Q3



4-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF

Podržava TVI,AHD, CVI,CVBS

Rezolucija snimanja IP kamera: do 8mp (2 IP kamere ili svih 6)

Video kompresija: H.265, H.264

Video/audio ulazi: 4ch BNC, 1ch audio

Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio

Ulazno/Izlazni saobraćaj: 48/60 Mbps

Smart funkcije: Motion detection, video loss detection, audio detection,

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485

Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Hard disk: 1 sata HDD do 8TB kapaciteta

Napajanje 12V DC, Potrošnja 10W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm x226mmx 47mm

11032

96,00 80,00

XVR301-04U3



4-ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
Support 1-ch CVBS output, 1-ch VGA output,
1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols
1HDD Up to 16 TB

I1129

144,00 120,00

8 KANALNI

XVR301-08G



8-Ch Digital Video Recorder

Support H.265/H.264 video formats
Recording Resolution: 5MP Lite/4MP Lite /1080P/720P/960H/D1/CIF
Support audio over coaxial cable (only for TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
4/8/16-channel BNC input
Support 1-ch HDMI output, 1-ch VGA output at up to 1920*1080
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols
1 SATA interface up to 6 TB

I1176

84,00 70,00



XVR301-08G3



8-CH Hybrid DVR

Podrška: TVI,AHD, CVI, CVBS
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/CIF
Rezolucija snimanja IP kamera: do 4mp (4 IP kamere ili svih 8)
Video/audio ulazi: 8-ch (BNC) / 1-ch (RCA)
Video/audio izlazi: HDMI/VGA (FULL HD), CVBS, 1ch audio
Ulazno/izlazni saobraćaj: 32/64 Mbps
Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 sata HDD do 8TB
Napajanje 12V DC, Potrošnja 8W bez HDD
Radna temperatura: -10 °C ~ +55 °C
Dimenzije: 260mm x226mmx 47mm

I1025

91,20 75,00



XVR301-08Q3



8-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP/ 5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
Podrška TVI,AHD, CVI,CVBS
Rezolucija snimanja IP kamera: do 8mp (4 IP kamere ili svih 12)
Video kompresija: H.265, H.264
Video/audio ulazi: 8ch BNC, 1ch audio
Video/audio izlazi: HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio
Ulazno/izlazni saobraćaj: 40/64 Mbps
Smart funkcije: Motion detection, video loss detection, audio detection,
Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 sata HDD do 8TB kapaciteta
Napajanje 12V DC,
Potrošnja 10W bez HDD,
Radna temperatura: -10 °C ~ +55 °C,
Dimenzije: 260mm x226mmx 47mm

I1033

138,00 115,00



XVR301-08U3

uniview
Better Security. Better World.

8-Ch 1U Digital Video Recorder

Recording Resolution: 8MP/5MP/4MP/1080P/720P/D1
Support Ultra 265/H.265/H.264 video formats
Support audio over coaxial cable (TVI cameras)
Control the dual-light of UNV analog cameras under TVI
Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
8-channel BNC input
Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K (3840 x 2160)
HDMI and VGA simultaneous output
Long transmission distance over coaxial cable
Support mainstream cameras of ONVIF and RTSP protocols

11080 222,00 185,00

16 KANALNI**XVR301-16G3**

uniview
Better Security. Better World.

16-CH Hybrid DVR

Podržava: TVI, AHD, CVI, CVBS, IP cameras
Rezolucija snimanja: 5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF
IP kamere: do 8 IP kamere ili svih 16
Video/audio ulazi: 16-ch BNC / 1-ch RCA
Video/audio izlazi: VGA, HDMI, CVBS, 1ch audio
Ulazno/izlazni saobraćaj: 40/64 Mbps
Dodatni ulazi: RJ45 mrežni ulaz, 2x USB, 1x RS485
Mrežni protokoli: TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Hard disk: 1 SATA HDD do 8TB
Napajanje 12V DC, Potrošnja 10W bez HDD
Radna temperatura: -10 °C ~ +55 °C
Dimenzije: 260mm x226mmx 47mm

11026 148,80 124,00

XVR302-16Q3

uniview
Better Security. Better World.

16-CH Hybrid DVR

Rezolucija snimanja: 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF
Podržava 8MP@15fps na prva 4 kanala
Rezolucija snimanja IP kamera: 8IP kamera (isključivanjem analognih kanala 24IP), svaki kanal do 8mpx.
Ulazno/izlazni saobraćaj: 72/80 Mbps
Video kompresija: H.265/H.264 video kompresija,
Video/audio ulazi: 16ch BNC, 1ch RCA
Video/audio izlazi: HDMI/VGA (FULL HD), 1ch RCA
Smart funkcije: Motion detection, tampering, video loss detection, face detection, intrusion detection, cross line detection, audio detection, defocus detection, scene change detection
Dodatni ulazi: RJ45 mrežni ulaz, 1xUSB 3.0 interfejs (pozadi) 1xUSB 2.0 (napred), 1x RS485
Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
Hard disk prostor: 2 sata HDD do 6TB kapaciteta
Opšte: Napajanje 12V DC, Potrošnja 12W bez HDD,
Radna temperatura: -10 °C ~ +55 °C,
Dimenzije: 380mm x315mmx 53mm, Težina 1.9Kg

11034 288,00 240,00

KIT/XVR 301-04G3/4*UAC-T112-F28**UNV KIT/XVR 301-04G3/4*UAC-T112-F28**

Kompet sadrži:
1x XVR 04G3
4x UAC-T112-F28
1x Napajanje 2A
4x 20m Koaksijalni kabl + napajanje (sa konektorima)
1x Razdelnik 1 / 4

11065 180,00 150,00

ANALOGNE DOME KAMERE 2MP**UAC-T112-AF28****2MP HD Fixed IR Turret Analog Camera**

2MP high quality image
TVI/AHD/CVI/CVBS
IR-cut filter with auto switch (ICR)
Built-in microphone
Supports 180° horizontal flip, 180° vertical flip
OSD configuration menu, easy to operate
IP67 waterproof and dustproof design, high reliability
OSD configuration menu in 11 languages

11066 24,00 20,00

UAC-T112-F28-W

	2MP ColourHunter HD Fixed Turret Analog Camera		
	2MP high quality image TVI/AHD/CVI/CVBS		
11006	Supports white light illumination, 24/7 full-color imaging Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	28,80	24,00

UAC-T122-AF28LM

	2MP LightHunter HD IR Fixed Turret Analog Camera		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11054	Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	36,00	30,00

UAC-T122-AF40LM

	2MP LightHunter HD IR Fixed Turret Analog Camera		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11099	Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog 3-Axis	36,00	30,00

UAC-T122-AF28M-W

	2MP ColorHunter HD Fixed Turret Analog Camera		
	2MP high quality imaging TVI/AHD/CVI/CVBS		
11016	Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing 3-Axis	36,00	30,00

UAC-T142-AF28LM-DL

	2MP ColorHunter Fixed Dual-light Turret Analog Camera		
	High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS		
11077	Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	43,20	36,00

ANALOGNE BULLET KAMERE 2MP**UAC-B112-F28**

	2MP HD Fixed IR Mini Bullet Analog Camera		
	2MP high quality image TVI/AHD/CVI/CVBS		
11000	IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages	25,20	21,00

UAC-B112-AF28



1121	<p>2MP Fixed IR Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	26,40	22,00
------	---	-------	-------

UAC-B112-F28-W



11001	<p>2MP ColourHunter HD Fixed Mini Bullet Analog Camera 2MP high quality image TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 full-color imaging Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages</p>	27,60	23,00
-------	---	-------	-------

UAC-B122-AF28LM



11053	<p>2MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog</p>	36,00	30,00
-------	--	-------	-------

UAC-B122-AF40LM



11098	<p>2MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog</p>		<i>NEMA NA STANJU</i>
-------	--	--	-----------------------

UAC-B122-AF28M-W



11014	<p>2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability SD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing</p>		<i>NEMA NA STANJU</i>
-------	---	--	-----------------------

UAC-B122-AF28M-W-Black



11214	<p>2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability SD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing</p>	36,00	30,00
-------	---	-------	-------

UAC-B122-AF40M-W



11015	2MP ColorHunter HD Fixed Mini Bullet Analog Camera 2MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Supports digital defog Metal front face and housing	37,20	31,00
-------	---	-------	-------

UAC-B142-AF28LM-DL



11076	2MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	46,80	39,00
-------	---	-------	-------

UAC-B142-AF40LM-DL



11122	2MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 2MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	46,80	39,00
-------	---	-------	-------

ANALOGNE DOME KAMERE 5MP

UAC-T115-AF28



11126	5MP Fixed IR Turret Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables	30,00	25,00
-------	---	-------	-------

UAC-T125-AF28LM



11056	5MP LightHunter HD IR Fixed Turret Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables 3-Axis	46,80	39,00
-------	---	-------	-------

UAC-T125-AF28M-W



11020	5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis	48,00	40,00
-------	--	-------	-------

UAC-T125-AF28M-W-Black

	<p>5MP ColorHunter HD Fixed Turret Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing 3-Axis</p>			
11057			48,00	40,00

UAC-T145-AF28LM-DL

	<p>5MP ColorHunter Fixed Dual-light Turret Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11079			50,40	42,00

ANALOGNE BULLET KAMERE 5MP**UAC-B115-F28**

	<p>5MP HD Fixed IR Mini Bullet Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS IR-cut filter with auto switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages</p>			
11002			30,00	25,00

UAC-B115-AF28

	<p>5MP Fixed IR Bullet Analog Camera 5MP high quality image TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11125			30,00	25,00

UAC-B125-AF28LM

	<p>5MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11055			44,40	37,00

UAC-B125-AF40LM

	<p>5MP LightHunter HD IR Fixed Mini Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) LightHunter monitoring with high-sensitivity sensor Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>			
11124			44,40	37,00

UAC-B125-AF28M-W

11018	<p>5MP ColorHunter HD Fixed Mini Bullet Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing</p>	48,00	40,00
-------	--	-------	-------

UAC-B125-AF40M-W

11019	<p>5MP ColorHunter HD Fixed Mini Bullet Analog Camera 5MP high quality imaging TVI/AHD/CVI/CVBS Supports white light illumination, 24/7 color images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables Metal front face and housing</p>	49,20	41,00
-------	--	-------	-------

UAC-B145-AF28LM-DL

11078	<p>5MP ColorHunter Fixed Dual-light Bullet Analog Camera High quality imaging with 5MP resolution TVI/AHD/CVI/CVBS Supports IR-cut filter with auto-switch (ICR) Smart Dual Light (only TVI) Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built-in microphone for high quality audio transmission via coaxial cables</p>	54,00	45,00
-------	---	-------	-------

UAC-B315-ADZLM

11185	<p>5MP LightHunter VARIFOCAI IR Bullet Analog Camera High quality imaging with 5MP resolution 2.8mm-12mm motorized lens TVI/AHD/CVI/CVBS Illumination Distance: 50m Supports IR cut filter with auto switch (ICR) LightHunter monitoring with high sensitivity sensor 3D noise reduction technology delivers clean and sharp images Supports 180° horizontal flip, 180° vertical flip OSD configuration menu, easy to operate IP67 waterproof and dustproof design, high reliability OSD configuration menu in 11 languages Built in microphone for high quality audio transmission via coaxial cables</p>	90,00	75,00
-------	---	-------	-------

NVR UREDJAJI**NVR301-04S3**

11049	<p>4-ch NVR Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p Ulazno/izlazni saobraćaj: 64/48Mbps Video kompresija: Ultra 265, H.265, H.264 video kompresija, Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD), Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection ONVIF conformance: Profile S, Profile G, Profile T Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0, Audio out 3.5mm Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE Hard disk prostor: 1 sata HDD do 6TB kapaciteta Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD, Radna temperatura: -10 °C ~ +55 °C, Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg</p>	108,00	90,00
-------	--	--------	-------

NVR301-04B-IQ**NOVO****EASY**

1115

4-ch NVR

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Support Ultra 265/H.265/H.264 video formats

Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1x HDD, up to 10TB

132,00

110,00

NVR501-04B-IQ**NOVO****PRIME**

11150

4-ch NVR

Decoding Capability:

Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30

Smart On: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30

Support Ultra H.265/H.265/H.264 video formats

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

150,00

125,00

NVR301-08S3**EASY**

11048

8-ch NVR

Rezolucija snimanja: 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 64/48 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio detection

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: RJ45 mrežni ulaz, 2xUSB 2.0.,

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm, Težina 1Kg

120,00

100,00

NVR301-08B-IQ**NOVO****EASY**

11117

8-ch NVR

Decoding Capability: Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30

Support Ultra 265/H.265/H.264 video formats

4/8/16 channel input

Support mainstream cameras of ONVIF conformance(Profile S,

Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

1x HDD, up to 10TB

150,00

125,00

NVR501-08B-IQ**NOVO****PRIME**

11118

8-ch NVR

Decoding Capability: Smart Off: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30, 12 x

1080P@30, 16 x 720P@30

Support Ultra H.265/H.265/H.264 video formats

Supports mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T) and RTSP protocols

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability

When the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

168,00

140,00

NVR301-16S3**NOVO****EASY**

1116

16-ch NVR

Rezolucija snimanja: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p

Ulazno/Izlazni saobraćaj: 64/48Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI 4K resolution /VGA (FULL HD),

Smart Funkcije:Face detection, Intrusion detection,

Cross line detection, Audio detection

ONVIF conformance: Profile S, Profile G, Profile T

Pretraga snimka po smart funkcijama: Face search, Behavior search, Human Body search

Dodatni ulazi: RJ45 mrežni ulaz, 2 x USB2.0,Audio out 3.5mm

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 1 sata HDD do 6TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 5W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 240mm × 46mm (10.2"×9.4"×1.8 "), 1kg

138,00

115,00

NVR301-16B-IQ**NOVO****EASY**

11151

16-ch NVR

Decoding Capability - Smart Off: 2 x 12MP@30, 2 x 4K@30, 4 x 4MP@30, 10 x 1080P@30, 16 x 720P@30

Smart On: 2 x 4K@30, 4 x 4MP@30, 8 x 1080P@30, 16 x 720P@30

Support Ultra 265/H.265/H.264 video formats

Support mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T) and RTSP protocols

Support HDMI and VGA simultaneous output

Up to 12 Megapixels resolution recording

ANR technology to enhance the storage reliability when the network is disconnected

Support cloud upgrade

210,00

175,00

NVR501-16B**PRIME**

11047

16-ch NVR

Rezolucija snimanja: 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 80/64 Mbps

Video kompresija: Ultra 265/H.265/H.264

Video/audio izlazi: HDMI (4K) / HD, VGA

Smart Funkcije: Intrusion Detection, Cross Line Detection,Enter Area, Leave Area, Defocus

Detection,Scene Change Detection, Object Left Behind, Object Removed,Auto Tracking, UMD(Ultra Motion Detection)

Statistické analize: People counting

Dodatni ulazi: 1xRJ45 mrežni ulaz, 1xUSB 2.0, 1x USB 3.0

Mrežni protokoli: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP,HTTPS, DNS, DDNS, SNMP, SMTP

Hard disk prostor: 1 sata HDD do 8TB kapaciteta

Opšte: Napajanje 12V DC, Potrošnja 15W bez HDD,

Radna temperatura: -10 °C ~ +55 °C,

Dimenzije: 260mm × 222mm × 47mm, Težina 0,98Kg

216,00

180,00

Better Security. Better World.
NVR501-16B-IQ**NOVO****PRIME**

11119

16-ch NVR

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30, 12 x

1080P@30, 16 x 720P@30

Support Ultra H.265/H.265/H.264 video formats

Supports mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T) and RTSP protocols

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability

When the network is disconnected

Support cloud upgrade

1 SATA Interface, up to 16 TB

228,00

190,00

NVR502-16B-IQ**NOVO****PRIME**

11180

16-ch NVR

Decoding Capability: Smart Off: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30

Smart On: 2 x 12MP@30, 2 x 4K@30,

6 x 4MP@30, 8 x 3MP@30, 12 x

1080P@30, 16 x 720P@30

Support Ultra H.265/H.265/H.264 video formats

Supports mainstream cameras of ONVIF conformance

(Profile S, Profile G, Profile T) and RTSP protocols

Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution

Support HDMI and VGA simultaneous output

Up to 16 Megapixels resolution recording

ANR technology to enhance the storage reliability

When the network is disconnected

Support cloud upgrade

2 SATA Interface, up to 16 TB per HDD

264,00

220,00

NVR304-32X

PRIME



32-ch NVR

32-KANALNI MREŽNI SNIMAČ

Rezolucija snimanja:

12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Ulazno/Izlazni saobraćaj: 384/384 Mbps

Video kompresija: Ultra 265, H.265, H.264 video kompresija,

Video/audio izlazi: HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA

Smart Funkcije: Face detection, Intrusion detection, Cross line detection, Audio

detection, Defocus detection, Scene change detection, Auto tracking, Object left

I1154 behind, Object removed, Face search, Behavior search

600,00 500,00

Statisticke analize: People counting

ONVIF conformance: Profile S, Profile G, Profile T

Dodatni ulazi: 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1x RS485, 1 x

RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza

Mrežni protokoli: P2P, UPnP, NTP, DHCP, PPPoE

Hard disk prostor: 4 sata HDD do 10TB kapaciteta, RAID 1, 5

Opšte: Napajanje 12V DC, Potrošnja 25W bez HDD,

Radna temperatura: -10 °C – +55 °C,

Dimenzije: 442mm x426mmx 89mm, Težina 5,7Kg

DOME IP KAMERE 2MPX

IPC3612LB-SF28-A

EASY

NOVO



2MP Fixed IR Turret Network Camera

High quality image with 1080P, 1/2.8" CMOS sensor

1080P (1920 x 1080)@30/25 fps; 720P (1280 x 720)@30/25 fps

Ultra 265, H.265, H.264

I1144 Smart IR, up to 30 m (98.4 ft) IR distance

66,00 55,00

Day/night functionality

2D/3D DNR (digital noise reduction)

IP67 protection

Supports PoE power supply

3-axis

2MP

IRLC

Smart IR

Ultra H.265

Smart Search

POE

IP 67

IPC322LB-SF28-A

EASY



2MP Vandal-resistant Network IR Fixed Dome Camera

High quality image with 2MP, 1/2.8" CMOS sensor

2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps

Ultra 265, H.265, H.264

I1174 Smart IR, up to 30m (98ft) IR distance

56,40 47,00

Day/night functionality

2D/3D DNR (Digital Noise Reduction)

IP67 protection

IK10 vandal resistant

Support PoE power supply

2-Axis

2MP

IRLC

IK 10

IP 67

Smart IR

Ultra H.265

POE

IPC322LB-AF28WK-G

EASY



2MP WIFI Fixed Dome Network Camera

High quality image with 2MP, 1/2.9" CMOS sensor

2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps

Ultra 265, H.265, H.264, MJPEG

I1008 Built-in Mic

86,40 72,00

Smart IR, up to 30m (98ft) IR distance

Supports 128 G Micro SD card

IK10 vandal resistant

IP67 protection

3-Axis

2MP

Edge Storage

Built-in Mic

WIFI Connection

Smart IR

Ultra H.265

IRLC

IP 67

IPC322LB-DSF28K-G



High quality image with 2MP, 1/2.7" CMOS sensor

2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply

11177

72,00 60,00

IPC3622LE-ADF28K-WP



2MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera

High quality image with 2MP, 1/2.7" CMOS sensor and F1.0 large aperture lens
 2MP (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, Detail, and smear effects in extremely low-light scenes
 120 dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30 m (98 ft) warm light distance
 Supports up to 512 GB Micro SD Card
 IP67 protection
 Support PoE power supply
 3-Axis

11112

104,40 87,00

IPC3612LE-ADF28KC-WL




2MP HD ColorHunter IR Fixed Eyeball Network Camera

High quality image with 2MP, 1/2.8" CMOS sensor
 2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic & Speaker
 Smart IR, up to 30m (98ft) IR distance
 White Light, up to 30m (98ft) white light distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11038

110,40 92,00

IPC3532LB-ADZK-G-BLACK



2MP HD IR VF (2.8 ~ 12mm) Dome Network Camera


High quality image with 2MP, 1/2.7" CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 128 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply
 3-Axis

11092

156,00 130,00

BULLET IP KAMERA 2MPX

IPC2122LB-SF28-A



2MP Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8" CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 Support PoE power supply
 3-Axis

11143

55,20 46,00

IPC2122LB-SF40-A



2MP Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 Support PoE power supply
 3-Axis

11173

55,20 46,00

IPC2122LB-AF28WK-G



2MP HD WIFI Bullet Network Camera

High quality image with 2MP, 1/2.9"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IP67 protection
 3-Axis

11009

78,00 65,00

IPC2122LB-AF40WK-G BLACK



2MP HD WIFI Bullet Network Camera

High quality image with 2MP, 1/2.9"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IP67 protection
 3-Axis

11093

78,00 65,00

IPC2122LB-ADF40KM-G



2MP HD WDR Fixed IR Bullet Network Camera

High quality image with 2MP, 1/2.7"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 3-Axis

11175

72,00 60,00

IPC2122LB-AF28K-WL



2MP HD ColorHunter Mini Fixed Bullet Network Camera

High quality image with 2MP, 1/2.9"CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra H.265, H.265, H.264
 Built-in Mic
 Warm Light, up to 30m (98ft) warm light distance
 2D/3D DNR (Digital Noise Reduction)
 Support 128GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11050

99,00 82,50

IPC2312LE-ADF28KM-WP



2MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 2MP, 1/2.7"CMOS sensor and F1.0 large aperture lens
2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
Colorhunter with Wise-ISP technology ensures 24-hour full-color images
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic
White Light, up to 30m warm light distance
Supports 512 GB Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1111

104,40 87,00

IPC2122LE-ADF28KMC-WL



2MP HD ColorHunter Mini IR Fixed Bullet Network Camera

High quality image with 2MP, 1/2.8"CMOS sensor
2MP (1920*1080) @30/25fps; 720P (1280*720) @30/25fps;
Ultra 265, H.265, H.264, MJPEG
120dB true WDR technology enables clear image in strong light scene
Support 9:16 Corridor Mode
Built-in Mic & Speaker
Smart IR, up to 30m (98ft) IR distance
White Light, up to 30m (98ft) white light distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1028

110,40 92,00

BULLET IP KAMERE 3MPX

IPC2123LB-AF28KM-G



3MP HD Fixed IR Bullet Network Camera

High quality image with 3MP, 1/2.7"CMOS sensor
3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
Ultra 265, H.265, H.264, MJPEG
Support 9:16 Corridor Mode
Built-in Mic
Smart IR, up to 30m (98ft) IR distance
Supports 128 G Micro SD card
IP67 protection
Support PoE power supply
3-Axis

I1037

86,40 72,00

DOME IP KAMERE 4MPX

IPC3614LB-SF28-A



4MP Fixed Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
Ultra 265, H.265, H.264, MJPEG
Smart IR, up to 30m (98ft) IR distance
Support PoE power supply
3-Axis

I1030

81,60 68,00

IPC324LB-SF28-A

EASY

NOVO



4 MP IR Fiksna Anti Vandal Dome Mrežna Kamera

Rezolucija snimanja: ④4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps

Čip: 1/3", progressive scan , 4.0 megapixel, CMOS

Šater: Auto/Manual, 1 ~ 1/100000s

Optika: 2.8mm @F2.0

Osetljivost: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter

IC domet: do 30m

Interfejsi: 10/100M Base-TX Ethernet

Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP,

11010 DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP,Qos,SSL/TLS

Mrežni stadardi: ONVIF (Profile S, Profile T),API,SDK

Kompresija: H.265, H.264,

Ostale Karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod

Zaštita: IP67, IK10

Napajanje i potrošnja: **DC 12V+25%, PoE (IEEE 802.3af), max 5W**

Radna Temperatura: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)

Dimenzije (ΦxV): Φ109 x 81mm težina: 0,32kg

Kompatibilni nosači i pribor: TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TRJB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN

81,60 68,00

IPC3614LB-AF28K-A2

EASY

NOVO



4MP IR Eyeball Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor

4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P

(1920 × 1080)@30/25 fps

Supports accurate human body detection 2.0

Ultra 265, H.265, H.264

11178

Built-in mic

Smart IR, up to 30 m (98.4 ft) IR distance

Day/night functionality

2D/3D DNR (digital noise reduction)

MicroSD, up to 512 GB

DC 12 V, PoE (IEEE 802.3af) power supply

IP67 protection

3-axis

86,40 72,00

IPC324LB-ASF28K-A

EASY



4MP Fixed IR Dome Network Camera

High quality image with 4MP, 1/3" CMOS sensor

4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps

Ultra 265, H.265, H.264

Built-in Mic

Smart IR, up to 30m (98ft) IR distance

11070

Day/night functionality

2D/3D DNR (Digital Noise Reduction)

Support Micro SD card

IP67 protection

IK10 vandal resistant


DC12V or PoE(IEEE 802.3af) power supply

2-Axis

NEMA NA STANJU

IPC3624LE-ADF28K-WP

EASYSSTAR



4MP ColorHunter Wise-ISP Fixed Warm Light Turret Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens

4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP

(1920*1080) @30/25fps

Ultra 265, H.265, H.264, MJPEG

Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail,

And smear effects in extremely low-light scenes

11086

120dB true WDR technology enables clear image in strong light scene

Support 9:16 Corridor Mode

Built-in Mic

White Light, up to 30m (98ft) warm light distance

Supports 512 GB Micro SD card

IP67 protection

Support PoE power supply

3-Axis

128,40 107,00

IPC3514LE-ADF28K-WP

EASYSSTAR



4MP ColorHunter Wise-ISP Fixed Dome Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Support ColorHunter with Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Supports 512 GB Micro SD card
 IP67 protection
 IK10 protection
 Support PoE power supply
 3-Axis

11084

NEMA NA STARJU

IPC3614LE-ADF28K-H

EASYSSTAR



4MP EasyStar Fixed IR Turret Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688 × 1520)@25/20 fps; 4MP (2560 × 1440)@25/20 fps; 3MP (2304 × 1296)@30/25 fps; 2MP (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 EasyStar technology ensures high image quality in low illumination environment
 120 dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30 m (98 ft) IR distance
 Supports up to 512 GB Micro SD Card
 IP67 protection
 Support PoE power supply
 3-Axis

11137

147,60 123,00

IPC3614LE-ADF28KC-WL

EASYSSTAR



4MP HD ColorHunter IR Fixed Eyeball Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic & Speaker
 Smart IR, up to 30m (98ft) IR distance
 White Light, up to 30m (98ft) white light distance
 Supports 128 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11040

150,00 125,00

IPC3614SB-ADF28KMC-10

PRIME



4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera

High quality image with 4MP, 1/2.7" CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage. When Smart intrusion prevention is triggered the camera links sound alarm and light linkage.
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

11194

156,00 130,00

IPC3614SB-ADF40KMC-10

PRIME



4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage.When Smart intrusion prevention is triggered , the camera links sound alarm and light linkage.
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

i1094

156,00 130,00

IPC354SB-ADNF28K-10

PRIME



4MP LightHunter Fixed IR Dome Network Camera

High quality image with 4MP, 1/2.7"CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and,
 Motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30m (98 ft) IR distance
 Supports 512 G Micro SD card
 Cable-free
 Support PoE power supply

i1087

180,00 150,00

IPC3534LB-ADZK-G

EASY

NOVO



4MP HD IR VF (2.8 ~ 12mm) Dome Network Camera

High quality image with 4MP, 1/3"CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296)@ 30/25fps;2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 256 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply
 3-Axis

i1166

180,00 150,00

BULLET IP KAMERE 4MPX

IPC2124LB-SF28-A

EASY



4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0"CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

i1011

81,60 68,00

IPC2124LB-SF40-A



4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 H.265, H.264
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

11081

84,00 70,00

IPC2124LB-AF28K-A2



4MP Fixed IR Bullet Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Supports accurate human body detection 2.0
 Ultra 265, H.265, H.264
 Built-in mic
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 MicroSD, up to 512 GB
 DC 12 V, PoE (IEEE 802.3af) power supply
 IP67 protection
 3-axis

11155

86,40 72,00

IPC2124LB-ASF28K-A



4MP Fixed IR Mini Bullet Network Camera

High quality image with 4MP, 1/3.0" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra H.265, H.265, H.264
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Day/night functionality
 2D/3D DNR (Digital Noise Reduction)
 Supports Micro SD card
 IP67 protection
 DC12V or PoE(IEEE 802.3af) power supply
 3-Axis

11071

86,40 72,00

IPC2124LB-ADF28KM-H



4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/2.9" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps;
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 120dB WDR
 3-Axis

11068

114,00 95,00

IPC2124LB-ADF40KM-H



4MP Mini Fixed Bullet Network Camera

High quality image with 4MP, 1/2.9" CMOS sensor
 4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps;
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Built-in Mic
 Ultra 265, H.265, H.264, MJPEG
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 Support PoE power supply
 120dB WDR
 3-Axis

11075

116,40 97,00

IPC21314LE-ADF28KM-WP



11085

4MP ColorHunter with Wise-ISP Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Colorhunter with Wise-ISP technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

128,40 107,00

IPC2124LE-ADF28KMC-WL



11148

4MP ColorHunter Fixed Dual-light Bullet Network Camera

High quality image with 4 MP, 1/3.0" CMOS sensor
 4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps;
 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 120 dB true WDR technology enables clear image in strong light scene
 Supports 9:16 corridor mode
 Built-in mic and speaker
 Smart IR, up to 30 m (98.4 ft) IR distance
 White light, up to 30 m (98.4 ft) white light distance
 MicroSD, up to 512 GB
 IP67 protection
 Supports PoE power supply
 3-axis

132,00 110,00

IPC2124LE-ADF28KM-G



11027

4MP HD Mini IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Easystar technology ensures high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

147,60 123,00

IPC21314LE-ADF28KM-WL



11029

4MP HD ColorHunter Fixed Bullet Network Camera

High quality image with 4MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Colorhunter technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m white light distance
 Supports 128 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

159,60 133,00

IPC2124SB-ADF28KM-IO




11088

4MP HD Intelligent LightHunter IR Fixed Bullet Network Camera

High quality image with 4MP, 1/3" CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

162,00 135,00

IPC2314SB-ADF60KM-IO



4MP HD Intelligent 80m IR Fixed Bullet Network Camera

High quality image with 4MP, 1/2.7" CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle And non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in 2 Mic
 Smart IR, up to 80m (262 ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection

I1097

192,00 160,00

IPC2314SB-ADF40KM-IO



4MP LightHunter Fixed IR Bullet Network Camera

High quality image with 4MP, 1/2.7" CMOS sensor
 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in 2 Mic
 Smart IR, up to 80m (262 ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection

I1167

192,00 160,00

IPC2124SB-ADF40KMC-IO



4MP Tri-Guard Fixed Dual-light Bullet Network Camera

High quality image with 4 MP, 1/2.7" CMOS sensor
 4 MP (2688 × 1520)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection
 Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles
 Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage
 120 dB true WDR technology enables clear image in strong light scene
 Supports 9:16 corridor mode
 Built-in mic and speaker
 Smart IR, up to 30 m (98.4 ft) IR distance
 MicroSD, up to 512 GB
 IP67 protection

I1159

168,00 140,00

4MP Recognition Of Vehicle License Plate Bullet IP Camera (2.8 ~ 12mm)

Features
Optics
 Built-in lens supports motorized zoom to adapt to different scenes and allows for easy installation. Automatic gain control, white balance, and WDR for various light conditions.
Compression
 Supports triple streams.
 Advanced H.265 encoding technology improves compression efficiency.
 Custom OSD allows various vehicle information to be overlaid on the video image.
Functions
 Built-in vehicle and license plate recognition algorithm can recognize standard license plates of multiple countries.
 Supports capturing vehicle head only.
 Supports plate allowlist and blacklist configuration.
 Supports vehicle access control when connected to a barrier.
 Supports Micro SD cards of up to 256GB.
 Automatic network replenishment (ANR) allows to automatically store video to SD card in case of network disconnection.
 Supports audio collection and intercom.



<p>11120</p> <p>Network Network auto-adaptability ensures smooth live video in relatively bad network conditions such as packet loss. Supports SNMP. Supports UNP for NAT traversal between public and private networks. Supports integration with the third party via SDK or HTTP. Network Security Supports authorized user access by password. Weak password detection and account lock-up when failed login attempts reach the Upper limit enhance password security. Supports Web access via HTTPS. RTSP authentication prevents unauthorized video stream requests. IP address filtering prevents illegal access from untrusted IP addresses. Gateway ARP protection prevents MAC address spoofing. Structure Supports DC 12V and PoE (802.3at) power supplies. Cast aluminum body offers excellent heat dissipation. 3-axis mounting bracket for various installation scenarios. A junction box on the mounting bracket is convenient for storing tail cables. IP67 and IK10 protection.</p>	<p>840,00 700,00</p>
---	---------------------------------------



DOME IP KAMERA 5MPX

IPC3615LB-SF28-A

NOVO **EASY**

5MP Fixed IR Turret Network Camera
 High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
11147 Smart IR, up to 30 m (98.4 ft) IR distance **86,40** **72,00**
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 DC 12 V, PoE (IEEE 802.3af) power supply
 3-axis


IPC3635LB-ADZK-G

NOVO **EASY**

5MP HD IR VF Eyeball Network Camera
 High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
11139 Support 9:16 Corridor Mode **192,00** **160,00**
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

IPC3615SS-ADF28K-I1

PRIME



5MP HD Intelligent LightHunter IR Fixed Turret Dome Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25(default)fps; 4MP (2560*1440)@30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 Auto Scene Match (ASM) (WDR only)
 LightHunter technology ensures ultra-high image quality in low illumination environment
 130dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection

11105

192,00 160,00

IPC3615SE-ADF28KM-WL-I0

PRIME



5MP HD Intelligent ColorHunter Fixed Eyeball Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@30/25fps; 4MP (2560*1440)@30/25fps;3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce False alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 Colorhunter technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 corridor Mode
 Support built-in Mic
 Support 256 G Micro SD card
 IP67 protection
 Support PoE power supply

11161

237,00 197,50

BULLET IP KAMERE 5MPX

IPC2125LB-SF28-A

EASY



5MP Fixed IR Bullet Network Camera

High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 DC 12 V, PoE (IEEE 802.3af) power supply
 3-axis

11145

86,40 72,00

IPC2125LB-SF40-A

EASY



5MP Fixed IR Bullet Network Camera

High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps;
 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Smart IR, up to 30 m (98.4 ft) IR distance
 Day/night functionality
 2D/3D DNR (digital noise reduction)
 IP67 protection
 DC 12 V, PoE (IEEE 802.3af) power supply
 3-axis

11146

86,40 72,00

IPC2125LE-ADF28KM-G



11041

5MP HD Mini IR Fixed Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Ultra 265, H.265, H.264, MJPEG
 IC domet: do 50m
 Easystar technology ensures high image quality in low
 illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

159,60 133,00



IPC2125SB-ADF40KMC-IO



11095

5MP HD Intelligent Light and Audible Warning Fixed Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296)
 @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area
 detection
 Based on target classification, smart intrusion prevention significantly reduce
 false alarm caused by leaves, birds and lights etc., accurately focus on human and,
 motor vehicle and non-motor vehicle
 Supports sound and light alarm linkage.When Smart intrusion prevention
 is triggered, The camera links sound alarm and light linkage.
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic and Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00



IPC2125SB-ADF28KM-IO




11110

5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area,
 leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low
 illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00



IPC2125SB-ADF28KM-IO BLACK



11106

5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7"CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps;
 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area,
 leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low
 illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 40m (131ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection
 Support PoE power supply

168,00 140,00



IPC2125SB-ADF28KMC-IO



5MP Tri-Guard Fixed Dual-light Bullet Network Camera

High quality image with 5 MP, 1/2.7" CMOS sensor
 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, including cross line, intrusion, enter area, leave area detection
 Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles
 Supports sound and light alarm linkage. When smart intrusion prevention is triggered, the camera links sound alarm and light linkage
 120 dB true WDR technology enables clear image in strong light scene
 Supports 9:16 corridor mode
 Built-in mic and speaker
 Smart IR, up to 30 m (98.4 ft) IR distance
 MicroSD, up to 512 GB
 IP67 protection
 Supports PoE power supply

11156 168,00 140,00

IPC2325LB-ADZK-H




5MP HD IR VF (2.8 - 12mm) Bullet Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 25/20fps; 4MP (2560*1440)@ 25/20fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps;
 Built-in Mic
 Ultra 265, H.265, H.264, MJPEG
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

11069 192,00 160,00

IPC2315SB-ADF40KM-IO




5MP LightHunter Fixed IR Bullet Network Camera

High quality image with 5MP, 1/2.7" CMOS sensor
 5MP (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor Vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in 2 Mic
 Smart IR, up to 80m (262 ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection

11096 198,00 165,00

IPC2225SE-DF40K-WL-IO



5MP ColorHunter Fixed Warm Light Bullet Network Camera

High quality image with 5 MP, 1/2.7" CMOS sensor
 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, including cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduces false alarm caused by leaves, birds and lights, accurately focusing on human, motor vehicle and non-motor vehicle
 Intelligent people flow counting and crowd density monitoring
 ColorHunter technology ensures 24-hour full-color images
 120 dB true WDR technology enables clear image in strong light scene
 Supports 9:16 corridor mode
 Alarm I/O: 1/1, audio I/O: 1/1
 MicroSD, up to 512 GB
 IK10 vandal resistant and IP67 protection
 Supports PoE power supply

11158 261,60 218,00

DOME IP KAMERE 8MPX

IPC328SB-ADF28K-IO



11043

8MP HD Intelligent IR Fixed Dome Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps;
 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Intelligent perimeter protection, include cross line, intrusion,
 enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly
 reduce false alarm caused by leaves, birds and lights etc., accurately
 focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Alarm:1 in/1 out, Audio: 1 in/1 out
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IK10 vandal resistant and IP67 protection

229,20 191,00

IPC3618LE-ADF28K-G



11162


4K HD IR Fixed Eyeball Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080)
 @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Easystar technology ensures high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

215,00 180,00

BULLET IP KAMERE 8MPX

IPC2318LE-ADF28KM-WP



11113

8MP ColorHunter Wise-ISP Warm Light Bullet Network Camera

High quality image with 8MP, 1/1.8"CMOS sensor and F1.0 large aperture lens
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080)
 @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Colorhunter with Wise-ISP technology ensures 24-hour full-color images
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 White Light, up to 30m warm light distance
 Supports 512 GB Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

210,00 175,00

IPC2128LE-ADF28KM-G



11012

4K 8MP Mini Fixed Bullet Network Camera

High quality image with 8MP, 1/2.7"CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080)
 @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Easystar technology ensures high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IP67 protection
 Support PoE power supply
 3-Axis

211,20 176,00

IPC2128SB-ADF28KMC-10



11090

8MP Tri-Guard Fixed Dual-light Bullet Network Camera

High quality image with 8MP, 1/2.7" CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Built-in Mic
 Built-in Speaker
 Smart IR, up to 30m (98ft) IR distance
 Supports 512 G Micro SD card
 IP67 protection

245,00 205,00

IPC2328SB-DZK-10



11138


8MP HD Intelligent LighterHunter IR VF (2.8 ~ 12mm) Bullet Network Camera

High quality image with 8MP, 1/2.8" CMOS sensor
 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
 Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, Birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
 Intelligent People Flow Counting and Crowd Density Monitoring
 LightHunter technology ensures ultra-high image quality in low illumination environment
 120dB true WDR technology enables clear image in strong light scene
 Support 9:16 Corridor Mode
 Alarm: 1 in/1 out, Audio: 1 in/1 out
 Smart IR, up to 50m (164ft) IR distance
 Supports 256 G Micro SD card
 IK10 vandal resistant
 IP67 protection
 Support PoE power supply

264,00 220,00

UNIARCH

Uho-S2




11091

High quality image with 2MP, 1/3" CMOS sensor
 2MP (1920*1080)@25/20fps; 720P (1280*720) @25/20fps
 Ultra 265, H.265, H.264
 Built-in Mic & Speaker, support two-way audio, offer better interaction
 IR night vision, up to 10m (33ft) IR distance
 Support 256 G Micro SD card
 Wi-Fi connection and easy installation

36,00 30,00

Uho-S3E-M3



11051

High quality image with 3MP, 1/3" CMOS sensor
 3MP (2304*1296)@25/20fps; 2MP (1920*1080)@30/25fps; 720P (1280*720) @30/25fps
 Ultra 265, H.265, H.264
 Built-in Mic & Speaker, support two-way audio, offer better interaction
 IR night vision, up to 10m (33ft) IR distance
 Support 256 G Micro SD card
 Wi-Fi connection and easy installation

42,00 35,00

IPC-B122-APF28



I1140

High quality image with 1080P, 1/2.9" CMOS sensor
 1080P (1920 × 1080)@25/20 fps; 720P (1280 × 720)@25/20 fps
 Ultra 265, H.265, H.264
 2D/3D DNR (digital noise reduction)
 ROI (region of interest) ensures image quality in areas of interest
 With low bandwidth
 Smart IR, up to 30 m (98.4 ft.) IR distance
 Built-in mic
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
 DC 12 V, PoE (IEEE 802.3af) power supply

43,20 36,00



IPC-T122-APF28



I1141

High quality image with 1080P, 1/2.8" CMOS sensor
 1080P (1920 × 1080)@25 fps; 720P (1280 × 720)@25 fps
 Ultra 265, H.265, H.264
 2D/3D DNR (digital noise reduction)
 ROI (region of interest) ensures image quality in areas of interest
 with low bandwidth
 Smart IR, up to 30 m (98.4 ft.) IR distance
 Built-in mic
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
 DC 12 V, PoE (IEEE 802.3af) power supply

43,20 36,00



Uho-B1R-M2F3



I1127

High quality image with 2MP, 1/2.9" CMOS sensor
 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
 Ultra 265, H.265, H.264, MJPEG
 Built-in Mic
 Smart IR, up to 30m (98ft) IR distance
 Supports 128 G Micro SD card
 IP67 protection
 3-Axis

51,60 43,00



IPC-B125-APF28




I1142

High quality image with 5 MP, 1/3.0" CMOS sensor
 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps; 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30 fps; 720P (1280 × 720)@30 fps; D1 (720 × 576)@30 fps
 Ultra 265, H.265, H.264
 2D/3D DNR (digital noise reduction)
 ROI (region of interest) ensures image quality in areas of interest with low bandwidth
 Smart IR, up to 30 m (98.4 ft.) IR distance
 Built-in mic
 Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
 DC 12 V, PoE (IEEE 802.3af) power supply

60,00 50,00



Uho-P1A-M3F4D



High quality image with 3MP, 1/2.8"CMOS sensor
 2304*1296@20fps in the main stream
 Ultra 265, H.265, H.264
 Support digital WDR (Wide Dynamic Range)
 Built-in Mic & Speaker, support two-way audio, offer better interaction
 Support sound and light warning, makes warning and alarming more noticeable
 Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes
 Self-contained bracket, support two kinds of mounting
 Supports 256 GB Micro SD card
 Wi-Fi connection and easy installation
 IP66 ingress protection
 The front face is made of grapheme, which has better heat dissipation and more Environmental protection

I1052 Smart IR, up to 30 m (98 ft) IR and 10m (33 ft) warm light distance, Suitable for more scenes

NEMA NA STANJU

Uho-P2S-M33F34




Fixed camera and PTZ camera integration, dual channels with one IP, Look at overall situation and consider details at the same time
 Ultra 265, H.265, H.264
 Support digital WDR (Wide Dynamic Range)
 Built in Mic Speaker, support two way audio, offer better interaction
 Support sound and light warning, makes warning and alarming more noticeable
 Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes
 IR warm light illumination to deal with different scenes and achieve full color illumination
 Supports 512 GB Micro SD card
 Wi Fi connection and easy installation
 IP66 ingress protection

I1128 Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes

NEMA NA STANJU

PTZ IP KAMERE

IPC6312LR-AX4-VG



2MP LightHunter IR Network PTZ Camera
 High quality image with 2MP, 1/2.7"CMOS sensor
 Ultra 265, H.265, H.264, MJPEG
 Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
 People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in Low illumination environment
 Up to 120 dB Optical WDR (Wide Dynamic Range)
 Built-in Mic & Speaker
 Smart IR, Up to 50 m (164 ft) IR distance
 Micro SD, up to 256GB
 IP66 protection
 DC12V or PoE (IEEE 802.3af) power supply

I1073 LightHunter technology ensures ultra-high image quality in Low illumination environment

255,00 212,50

IPC675LFW-AX4DUPKC-VG



5MP LightHunter Active Deterrence Mini PTZ Camera
 High quality image with 5MP, 1/2.7"CMOS sensor
 Ultra 265, H.265, H.264, MJPEG
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Up to 120 dB Optical WDR (Wide Dynamic Range)
 Built-in Mic & Speaker
 Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance
 Micro SD, up to 256GB
 IP66 protection
 DC12V or PoE (IEEE 802.3af) power supply

I1109 Smart IR, Up to 50 m (164 ft) IR distance and 10m (33 ft) warm light distance

270,00 225,00

IPC6412LR-X5UPW-VG



2MP 5X LightHunter Wi-Fi IR Network Mini PTZ Camera

High quality image with 1080P, 1/2.7" CMOS sensor
 1920 × 1080@30 fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 5X optical zoom allows for closer viewing of subjects
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
 automatic selection of best snapshots
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Up to 120 dB optical WDR (wide dynamic range)
 Wi-Fi connection and easy installation
 Built-in mic and speaker, supports two-way audio
 Alarm I/O: 1/1
 Smart IR, up to 30 m (98.4 ft) IR distance

11157

228,00 190,00

IPC6412LR-X16-VG




2MP 16x LightHunter Network PTZ Dome Camera

High quality image with 2MP, 1/2.8" CMOS sensor
 1920*1080@30fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 16X optical zoom allows for closer viewing of subjects
 LightHunter technology ensures ultra-high image quality
 In low illumination environment
 Smart IR, up to 100m (328ft) IR distance
 Micro SD, up to 256GB
 DC 12V±25% or PoE+ (IEEE 802.3at)
 IP66 ingress protection

11074

396,00 330,00

IPC6424SR-X25--B




4MP 25x LightHunter IR Network PTZ Camera

High quality image with 4 MP, 1/2.8" CMOS sensor
 2688 × 1520@30 fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 25X optical zoom
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
 automatic selection of best snapshots, supports face detection masked area
 People counting, supports people flow counting and crowd density monitoring, suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in low illumination environment
 Smart IR, up to 100 m (328 ft) IR distance
 DC 12 V±25%, PoE+ (IEEE 802.3at)
 Alarm I/O: 2/1, audio I/O: 1/1
 IP67 ingress protection
 IK10 vandal resistant

11152

636,00 530,00

IPC6634S-X33-VF



4MP 33X LightHunter IR Network PTZ Camera

High quality image with 4 MP, 1/2.8" CMOS sensor
 2688 × 1520@30 fps in the main stream
 Ultra 265, H.265, H.264, MJPEG
 33X optical zoom
 Smart intrusion prevention, supports false alarm filtering, including cross line, intrusion, enter area, leave area detection
 automatic selection of best snapshots, supports face detection masked area
 People counting, supports people flow counting and crowd density monitoring, Suitable for different statistical scenarios
 LightHunter technology ensures ultra-high image quality in low illumination environment
 AC 24 V±25%, DC 24 V±25%, PoE+ (IEEE802.3 at)
 Alarm I/O: 7/2, audio I/O: 1/1
 IP67 ingress protection
 IK10 vandal resistant

11153

1320,00 1100,00

VIDEO INTERFONI

OEU-201B-HMK-W



	Outdoor Station Front panel: Plastic cement Supports batch configuration Supports intercom calls to associated indoor units or APPs			
11201	Support monitoring function, security alarm, tamper alarm Support Wi-Fi Built-in IC card reader Card Capacity 2000 IP65(Apply silica gel to gaps between the device and the wall)	216,00	180,00	

OEU-202S-HMK2



	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration			
11202	WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)	252,00	210,00	

OEU-202S-HMK4



	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration			
11204	WDR: Digital Built-in IC card reader Card Capacity 10000 IP65(Apply silica gel to gaps between the device and the wall)	276,00	230,00	

OEU-301S-HMKA



	Outdoor Station Front panel: Metal Vandal-resistant: IK08 Supports batch configuration			
11301	WDR: Digital Built-in IC card reader Card Capacity 10000 Alarm Output: 2 IP65(Apply silica gel to gaps between the device and the wall)	420,00	350,00	

EP-CS201



	Wall Mount Sunshield			
11203	Compatible with OEU-201B-HMK-W, OEU-201B-HMK-W-NB, OEU-201S-HMK-W, And OEU-201S-HMK-W-NB villa door stations	18,00	15,00	

OEI-372S-H-W



	Indoor Station Rugged ABS casing and glass panel. 1024*600 HD touch screen.			
11372	Batch configuration transfer. Remote opening of linked door stations, one-key opening. Network camera monitoring, security alarm	192,00	160,00	



DEU-201S-HMK-W

Metal casing.

Supports call and intercom with the connected indoor station and app.

Supports security protection alarm and tamper alarm triggered by door magnet, infrared, etc.

Supports Wi-Fi.

Built-in IC card reader.

DEI-372S-H-W

ABS casing and glass panel, solid and durable.

Supports Wi-Fi.

Supports touchscreen operation.

1024 x 600 HD screen.

I1205

Supports remote door opening by sending signal to the door station.

Allows to view live video of connected door stations and network cameras.

360,00 300,00

NSW2020-6T-POE-IN

Allows to switch operating modes, including Default, VLAN, and Extend.

Supports VLAN isolation. All PoE ports are isolated from each other and only able to communicate with uplink ports.

Supports network extension. With a high-quality network cable and IPC, the network transmission distance can reach up to 250 meters by lowering the network port rate to 10Mbps.

Supports port priority. Packets from high-priority ports will be forwarded first.

Supports flow control. When there is data congestion in the uplink ports, the switch will actively send flow control frames to PoE ports.

Plug-and-play, simple and convenient.

All metal casing, secure and reliable.

HARD DISKOVI

WD GREEN 320 GB



Western Digital, 320GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 500 GB



Western Digital, 500GB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

WD GREEN 1 TB



Western Digital, 1 TB GREEN, 7200RPM, SATA III, 32MB

KONTAKT

HDD 1TB WD11PURZ-85C5HYO



I1100 Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB

104,40 87,00

HDD 2TB WD23PURZ-85C5HYO



I1200 Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB

144,00 120,00

HDD 4TB WD44PURZ-85CPDYO



I1400 Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB

192,00 160,00

HDD 6TB WD64PURZ-74BWUYO



I1600 Western Digital, 6TB Purple, IntelliPower, SATA III, 64MB

276,00 230,00

HDD 8TB WD64PURZ-85BWUJ0

6250 Western Digital, 8TB Purple, IntelliPower, SATA III, 5400RPM, 256MB

372,00 310,00

TF-64G-T-L

Uniview memorijska kartica
 Kapacitet: 64GB
 Maksimalna brzina čitanja: 90MB/s
 Maksimalna brzina pisanja: 65MB/s
 Dimenzije: 11mm x 15mm x 1mm
 Težina: 0,33g

11021 14,40 12,00

TF-128G-T-L

Uniview memorijska kartica
 Kapacitet: 128GB
 Maksimalna brzina čitanja: 100MB/s
 Maksimalna brzina pisanja: 80MB/s
 Dimenzije: 11mm x 15mm x 1mm
 Težina: 0,33g

11022 22,80 19,00

TF-256G-T-L

Uniview memorijska kartica
 Kapacitet: 256GB
 Maksimalna brzina čitanja: 90MB/s
 Maksimalna brzina pisanja: 65MB/s
 Dimenzije: 11mm x 15mm x 1mm
 Težina: 0,33g

11123 43,20 36,00

Uniview SVIČEVI**NSW1010-5T-IN**

5-Port 100 Megabit Plastic Shell Switch
 Supports IEEE802.3 and IEEE802.3u standards.
 Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
 Supports auto MDI/MDIX.
 Supports IEEE802.3 flow control for full-duplex mode and backpressure
 For half-duplex mode.

11130 8,40 7,00

NSW1010-8T-IN

8-Port 100 Megabit Plastic Shell Switch
 Supports IEEE802.3 and IEEE802.3u standards.
 Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
 Supports auto MDI/MDIX.
 Supports IEEE802.3 flow control for full-duplex mode and backpressure
 For half-duplex mode.

11131 12,00 10,00

NSW1010-5GT-IN

5-Port Gigabit Plastic Shell Switch
 Supports IEEE802.3 and IEEE802.3u standards.
 Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
 Supports auto MDI/MDIX.
 Supports IEEE802.3 flow control for full-duplex mode and backpressure
 For half-duplex mode

11132 14,40 12,00

NSW1010-8GT-IN

8-Port Gigabit Plastic Shell Switch
 Supports IEEE802.3 and IEEE802.3u standards.
 Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
 Supports auto MDI/MDIX.
 Supports IEEE802.3 flow control for full-duplex mode and backpressure
 For half-duplex mode.

11133 24,00 20,00

Uniview POE SVIČEVI

NSW2020-6T-POE-IN



I1023

6×100Mbps network ports (RJ45), od toga 4 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. 6kV zaštita od prenapona PoE Budžet: 60W Maksimalna snaga porta: 30W Dimenzije: 108mm x 100mm x 25.5mm

54,00 45,00

NSW2010-5GT-POE-IN



I1059

4 Port GigabitPoE Switch
1 Port Gigabit Uplink
PoE Power up to 30W Each Port
Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD)
Auto Detect Power Device
Power Port Supply prioritization, guarantees the continuous power supply of key nodes
IEEE802.3 X full duplex flow control and Backpressure half duplex flow control
Line Speed Forwarding, intelligent identification
Up to 250m transmission distance on surveillance mode

78,00 65,00

NSW2020-10T-POE-IN



I1024

10×100Mbps network ports (RJ45), od toga 8 PoE porta Podržava: IEEE802.3,IEEE802.3u, IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode); Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode); Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode); 8 Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 88W Maksimalna snaga porta: 30W Dimenzije: 171mm x 101mm x 25.5mm

90,00 75,00

NSW2010-10GT-POE-IN



I1060

8 Port Gigabit PoE Switch
2 Port Gigabit Uplink
PoE Power up to 30W Each Port
Supports IEEE802.3 at Standard, compatible with IEEE802.3af by electrical equipment (PD)
Auto Detect Power Device
Power Port Supply prioritization, guarantees the continuous power supply of key nodes
IEEE802.3 X full duplex flow control and Backpressure half duplex flow control
Line Speed Forwarding, intelligent identification
Up to 250m transmission distance on surveillance mode

NEMA NA STANJU

NSW2100-9GT16P-LPOE-IN



I1179

8 Port Gigabits PoE Switch
Ports Type:
8x 10/100/1000Mbps PoE port (RJ45)
1 x 10/100/1000Mbps port (RJ45)
1 x Gigabit SFP
Supports Web login, and device configuration and management on the Web interface.
Supports visiting the cloud by scanning the QR code.
Allows to view the device status in real time on the app, and remotely restart the PoE power supply.
Supports PoE power supply ; allows to enable or disable PoE power supply for the powered device; allows up to 250m power supply using a standard network cable.
Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate.
Supports port priority. The priority port will be powered first when the PoE power supply is full.
All metal casing, secure and reliable.

96,00 80,00

NSW3000-8T2GT-POE-IN



I1134	<p>Cloud Managed Ethernet Switch(PoE) 8 x 10/100Mbps POE port (RJ45) ,2 x Gigabit port (RJ45) Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software. Supports Web login, and device configuration and management on the Web interface; supports visiting the cloud by scanning the QR code. Allows to view the device status and network topology in real time on the app, and remotely restart the PoE power supply. Allows up to 250m power supply using a standard network cable. Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate. Allows to report port abnormal alarms to the software for realtime monitoring. Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full. All metal casing, secure and reliable. Maximum total power: 120W Maximum PoE power for single port: 30W</p>	96,00	80,00
-------	---	-------	-------

NSW2020-16T2GC-POE-IN



I1067	<p>16x100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta Podrška: IEEE802.3,IEEE802.3u,IEEE802.3az, IEEE802.3x,IEEE802.3af,IEEE802.3at Modovi rada: Default(Normal mode): Svi portovi komuniciraju normalno međusobno EXTEND(Surveillance mode): Distanca prenosa do 250 metara uz brzinu 10Mb/s. VLAN(Secure mode): 16 x Downlink portova mogu komunicirati samo sa uplink portovima. 6kV zaštita od prenapona PoE Budžet: 370W Maksimalna snaga: 250W Maksimalna PoE snaga porta: 30W Dimenzije: 440mm x 207mm x 45mm Moguća rek montaža 19" , dolazi uz switch</p>	216,00	180,00
-------	--	--------	--------

NSW3000-16T1GT1GC-LPOE-IN



I1135	<p>Cloud Management Switch 16 x 10/100Mbps POE port (RJ45) + 1 x Gigabit port (RJ45)+ 1 x Gigabit Combo Supports unified configuration, management, and search on the software, convenient for rapid operation and maintenance of multiple devices; supports automatically discovering the connected video devices and generating a network topology on the software. Supports Web login, and device configuration and management on the Web interface in real time on the app, and remotely restart the PoE power supply. Supports PoE power supply and allows to view the power; allows to enable or disable PoE power supply for the powered device; Allows up to 250m power supply using a standard network cable. Supports the extend mode for up to 250m communication range and 10Mbps auto-negotiation rate. Allows to report port abnormal alarms to the software for realtime monitoring. Supports port priority. The packets received by the priority port will be forwarded first when the switch is fully loaded and the priority port will be powered first when the PoE power supply is full. All metal casing, secure and reliable. Maximum total power: 150W Maximum PoE power for single port: 30W</p>	150,00	125,00
-------	---	--------	--------

NSW2020-24T1GT1GC-POE-IN



I1163	<p>Unmanaged Ethernet Switch(PoE) 24x100Mbps PoE ports (RJ45) + 1x1000Mbps Gigaethernet ports +1x1000Mbps Combo ports Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode) Support port traffic control Support for secure mode, all downlink ports can communicate only with uplink ports Up to 250m transmission distance on surveillance mode Support buffer optimization All metal housing, safe and reliable Max capacity:370W Max capacity for single port: 30W</p>	232,20	193,50
-------	---	--------	--------

NSW2010-24T2GC-PoE-IN



I1136	<p>Ethernet Switch(PoE) 24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode) Support port traffic control Support for secure mode, all downlink ports can communicate Only with uplink ports Up to 250m transmission distance on surveillance mode Support buffer optimization All metal housing, safe and reliable Max power: 390W</p>	288,00	240,00
-------	---	--------	--------

MONITORI

MW3224-V



I1154	<p>UNV 24" LED Monitor Resolution 1920 × 1080 Color Support: 16.7 M Refresh Rate: 60 Hz Operation Hour: 24/7</p>	120,00	100,00
-------	--	--------	--------

DODATNA OPREMA

GCB01-B7



I1101	<p>UNV-Link Pro Connect Box Network: 4 x RJ45 10M/100M Base-TX EthernetNetwork Port 1 Support POE (IEEE802.3af) OutputNetwork Port 4 Support PSE Voltage Test Wi-Fi 2.4G Wi-Fi Battery: 7500mAH Power Input: 1 x DC 5V/2A max, type-c Power Output: 1 x DC 12V/1A output; 1 x DC 5V/1A output, type-A</p>	78,00	65,00
-------	--	-------	-------

PoE Extender



9995	<p>Model: LN-POEPL03S PoE In: 44-57V/30W PoE Out (1-3) : 44-57V/25W Support: 10/100 Mbps IEEE802.3af/at</p>	NEMA NA STANJU
------	--	----------------


3 Ports POE Injector



2255	<p>PoE extender, repeater, switch 1 na 2 Usklađenost sa IEEE 802. af/at Power over Ethernet(10/100M podržano) Proširite domet Porta za dodatnih 100 metara</p>	25,00	20,83
------	---	-------	-------


KABLOVI

UNV Cat6 (UTP), CCA




i1044	<p>CAB-LC3100B-CCA-IN Conductor material: CCA(Copper content: 27%) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC</p>	0,30	0,250
-------	---	------	-------

UNV Cat5e (UTP), BC



i1045	CAB-LC2100A-E2-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,54	0,45
-------	---	------	------

UNV Cat6 (UTP), BC



i1046	CAB-LC3100A-EC-ECA-IN Conductor material: OFC (Oxygen free copper) Insulation material: HDPE Packing length: 305±1 m Sheath material: PVC (complies RoHS/REACH)	0,78	0,65
-------	---	------	------

CAB-LC3110B-E-IN



11186	Cat6 305m Outdoor UTP Network Cable (OFC 0.5mm Black) Packing length: 305±1m Material: Solid-Bare Copper Insulation material: HDPE Sheath material (IN Jacket): PVC (complies RoHS/REACH) Sheath material (OUT Jacket): LDPE Color: Black	0,84	0,70
-------	---	------	------


KUČIŠTA I NOSAČI

DOZNA ZA KAMERE BA-01



5633	Razvodna kutija za spoljašnu montažu kamere, 131x131x51 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,60	3,00
------	--	------	------

DOZNA ZA KAMERE G153



8644	Razvodna kutija za spoljašnu montažu kamere, 115x115x55 mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,20	2,67
------	--	------	------

DOZNA ZA KAMERE BA-02



8645	Razvodna kutija za unutrašnju montažu kamere, 120/50mm; Pogodna za direktnu montažu kamere na kutiju i smeštanje konektora za povezivanje.	3,00	2,50
------	--	------	------

TR-JB05-B-IN



i1062	Nosač za Dome kamere serije IPC21XX Dimenzije: $\Phi 104,4\text{mm} \times 54,5\text{mm}$ Težina: 0.36kg Materijal: Aluminijum	19,20	16,00
-------	---	-------	-------

TR-JB05-A-IN



11061	Nosač za kamere Dimenzije: $\Phi 93 \times 93 \times 39\text{mm}$ Težina: 0.2kg Materijal: Aluminijum	15,60	13,00
-------	--	-------	-------

TR-JB03-G-IN



11064	Nosač za Dome kamere serije IPC32x i IPC31x Dimenzije: $\phi 106.6\text{mm} \times 36\text{mm}$ Težina: 0.2kg Materijal: Aluminijum	13,20	11,00
-------	--	-------	-------

TR-JB03-I-IN



11063	Nosač za Dome kamere serije IPC36XXL i IPCT1XX Dimenzije: $\emptyset 117.8 \times 36\text{mm}$ Težina: 0.2kg Materijal: Aluminijum	15,60	13,00
-------	---	-------	-------

TR-JB03-H-IN



11171	Nosač za Dome kamere serije IPC363X, IPC36XXS/E i 4MP fisheye Dimenzije: $\Phi 126\text{mm} \times 36\text{mm}$ (4.96" x 1.42") Težina: 0.24kg Materijal: Aluminijum legura	14,40	12,00
-------	--	-------	-------

TR-JB04-C-IN



11172	Nosač za Dome kamere serije 323 Dimenzije: $\Phi 144.8 \text{ mm} \times 42.5 \text{ mm}$ (5.7" x 1.7") Težina: 0.3kg Materijal: Aluminijum legura	15,60	13,00
-------	---	-------	-------

TR-JB07-D-IN



11170	Bullet Junction Box(Support wiring from behind)	30,00	25,00
-------	---	-------	-------

TR-JB07/WM03-G-IN



11165	Wall Mounting Assembling Bracket For 32 Fix-dome & Mini Fix-dome & Plastic Turret Camera	36,00	30,00
-------	--	-------	-------

TR-WM07P-B



11181	Dome Wall Mounting Plastic Bracket Application: IPC32X Series, IPC361XX Series (Plastic) Bracket Weight: 0,10kg	7,20	6,00
-------	---	------	------



11169 Pole Mounting Bracket for Bullet Junction Box Only
 Application: Outdoor, pole or rail installation for
 Bullet camera of IPC23XX OEM IPC23XX/22X、IPC74X and IPC252/26X series
 Bracket Dimensions: 136.0 mm × 127.0 mm × 63.6 mm (5.4" × 5.0" × 2.5")
 Bracket Weight: 0.34kg
 Bracket Material: Aluminum alloy

NEMA NA STANJU

KONEKTORI

BNC NA LEMLJENJE SA ŠRAFOM



3299 BNC konektor muški sa šrafom.
 Pakovanje 100 kom.

0,54 0,45

BNC NA LEMLJENJE



2560 BNC konektor muški na lemljenje.
 Pakovanje 100 kom.

0,54 0,45

BNC KONEKTOR



30020 BNC konektor muški na šraf.

0,50 0,42

BNC NA KRIMP RG59



2534 BNC konektor za RG59 kabl na krimp.
 Pakovanje 100 kom.

0,60 0,50

BNC MUŠKI- F ŽENSKI



1795 BNC konektor muški F ženski.
 Pakovanje 100 kom.

0,70 0,58

BNC NASTAVAK



4447 BNC konektor. Nastavak ženski-ženski.
 Pakovanje 100 kom.

0,54 0,45

F KONEKTOR na krimp RG6



2559 F konektor za RG6 kabl.
 Pakovanje 100 kom.

0,14 0,12

F KONEKTOR na krimp RG59



1796 F konektor za RG59 kabl.
 Pakovanje 100 kom.

0,14 0,12

RF METALNI G MUŠKI



4448 RF metalni G muški (UGAONI) konektor
 Pakovanje 100 kom.

0,35 0,29

RCA MUŠKI-F ŽENSKI



4446 RCA muški - F ženski konektor
 Pakovanje 100 kom.

0,53 0,44

F NASTAVAK



3300 F nastavak ženski - ženski
Pakovanje 100 kom

0,22 0,18

F KONEKTOR
KOMPRESIONI RG6 XL



1625 Profesionalni PPC F konektor za RG6 kabl.
Pakovanje 50 kom.

0,44 0,37

F KONEKTOR
KOMPRESIONI RG11 XL



1627 Profesionalni PPC F konektor za RG11 kabl.

2,96 2,47

F KONEKTOR
KOMPRESIONI RG59 XL



1624 Profesionalni PPC F konektor za RG59 kabl.
Pakovanje 50 kom.

0,47 0,39

DC KABL-MUŠKI



1387 DC utikač-muški

0,47 0,39

DC KABL-ŽENSKI



1391 DC utikač-ženski

0,47 0,39

DC KONEKTOR MUŠKI



3425 DC konektor Muški

0,37 0,31

DC KONEKTOR ŽENSKI



4197 DC konektor ženski.

0,38 0,32

DC RAZDELNIK 1-4



1388 1 DC utičnica - 4 DC utikača

1,99 1,66

DC RAZDELNIK 1-8



1389 1 DC utičnica - 8 DC utikača

3,97 3,31

CAT7 RJ45



Mrežni konektor RJ45 kategorija 7












0,50 0,42

CAT6 UNV RJ45 GC-RJ6-IN



11182 Cat6 Unshielded Crystal Head
3μ inches gold-plated for excellent contact performance
Stable data transmission with up to 750 plugs and unplugs
Highly transparent PC material support RoHS standards,
Wear-resistant and durable
8 pins × 8 conductors, support 1000Bas-T Ethernet

0,12 0,10

CAT5 RJ45				
	0067	Mrežni konektor RJ45	0,05	0,04
Telefonski konektor RJ11				
	0066	Telefonski konektor RJ11	0,02	0,02
DODATNA OPREMA				
ŠTAMPAČ P-TOUCH E100				
	4663	Širina TZ trake: 6, 9 i 12mm ABC Tastatura LCD displej sa 16 karaktera u jednoj liniji Ispis u najviše 2 linije Najveća visina slova za štampanje: 9mm Brzina štampe: 20mm/s Rezolucija štampe: 180 dpi Serijsko numerisanje 1-9 Podešavanje dužine etikete 30-300mm 9 različitih vrsta fontova, veličine 15 Horizontalni ili vertikalni ispis Manuali sekač Napajanje: 6 AAA baterija *dolazi u kompletu sa praktičnim koferom, trakom za ruku, jednom TZe trakom kao uzorkom i uputstvom za upotrebu	106,56	88,80
MIKROFON LY-501C				
	2584	Audio modul sa izvedenim konektorima. Napajanje 12 V DC	3,97	3,31
MIKROFON LY-502B				
	2583	Audio modul plastični sa trimerom. Napajanje 12 V DC	6,00	5,00
MIKROFON LY-506				
	1937	Audio modul metalni sa trimerom. Napajanje 12 V DC	10,00	8,33
DS-2FP2020				
	5222	Viisoko osetljivi omnidirekcionni mikrofoni. Osetljivost -34 dB. Prenos zvuka do 3.000 metara. SNR: 60dB. Nivo signala 2Vpp, 12Vdc. Dimenzije 78 x 28mm. Napajanje 12 VDC (9 V to 15 V).	36,00	30,00
DH-PFM800-4K (par)				
	3632	One (1) Channel Balun Real-time Transmission over UTP CAT5E/6 Cable Compatible with HDCVI, TVI, AHD, and CVBS Video Formats Transmission Distance at 4K: 200 m (656 ft) External Power Supply not Required	7,80	6,50
06 razvodna kutija 100x100				
	00091	Razvodna kutija 100x100	1,80	1,50
06 razvodna kutija 80x80				
	00092	Razvodna kutija 80x80	1,10	0,92
06 razvodna kutija 160x100x74				
	00093	Razvodna kutija 160x100x74	3,00	2,50

06 razvodna kutija 160x100x48



00094 Razvodna kutija 160x100x48

2,64 2,20

ALAT ZA KRIMP
RG6, RG11, RG59



3302 Alat za krimpovanje RG6, RG11, RG59 konektora

48,00 40,00

STRIPER ZA KABLOVE RG59, RG6



3301 Alat za stripovanje RG59, RG6 kablova

20,40 17,00

ALAT KOMPRESIONI
ZA RG59, RG6



1629 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG59, RG6 XL oznake.

37,92 31,60

ALAT KOMPRESIONI, ZA
RG6, RG11, RG59



3796 Profesionalni PPC alat za kompresovanje kompresionih F konektora RG6, RG11, RG59 XL oznake.

54,34 45,28

KLEŠTA ZA KRIMPOVANJE
KOMPLET



5790 Komplet sadrži: - LAN Tester RJ11, 12 i 45 - LSA Punch Down Tool sa sečićom za kabl - Alat za krimpovanje RJ11, 12 i 45 - Alat za sečenje i skidanje izolacije - Torbica Ne sadrži bateriju za Network Tester (9V block cell)

28,68 23,90

NAPAJANJA

XED-1212S



1633 Ulaz: 90V-264V
Izlaz: 12V , 1A
Snaga: 12W
Dimenzije: 74 (D) x 46 (Š) x 30 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

6,00 5,00

XED-2012S



1382 Ulaz: 90V-264V
Izlaz: 12V , 2A
Snaga: 24W
Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

8,04 6,70

XED-3013S



1383 Ulaz: 90V-264V
Izlaz: 12V , 3A
Snaga: 36W
Dimenzije: 98 (D) x 52 (Š) x 35 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

12,60 10,50

XED-5013S



1384 Ulaz: 100V-240V
Izlaz: 12V , 5A
Snaga: 60W
Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

16,20 13,50

XED-6013B



3509 Ulaz: 100V-240V
Izlaz: 12V , 6A
Snaga: 72W
Dimenzije: 126 (D) x 57 (Š) x 32 (V) mm
Dužina izlaznog kabla: 110cm, 10.5x5,5x2mm konektor

20,40 17,00

9-KANALNO NAPAJANJE
XED-10A12VX-9L



5435 Snaga: 120W
Ulaz: 100-240V 50-60Hz
Izlaz: 12V 10A 9 kanala
Dimenzije: 237*213*70mm
Neto težina: 1800g
Napomena: Sadrži AC kabl

82,80 69,00

18-KANALNO NAPAJSANJE
XED-15A12VX-18L



5114 Snaga: 180W
Ulaz: 100~240V 50~60Hz
Izlaz: 12V 15A 18 kanala
Dimenzije: 240*218*70mm
Neto težina: 2300g
Napomena: Sadrži AC kabl

94,80 79,00

Sve cene su iskazane u EUR sa obračunatim PDV-om, podložne su promenama i zavisne od odnosa DIN/EUR/USD. Plaćanje se vrši u dinarima po važećem prodajnom kursu poslovne banke. ISEC zadržava pravo izmene cena bez prethodne najave. Dostupna i oprema koje nema u cenovniku! Za detaljnije informacije, molimo kontaktirajte nas na gore navedene brojeve telefona ili posetite www.isec.rs